



* PLACE TO SIGNS 100' FROM THE INTERSECTION

PLACE THE WARNING SINGS AT 150' +/- FROM EACH OTHER. THE SINGS SHALL NOT BLOCK ANY DRIVEWAY.

(1) CONTRACTOR SHALL COORDINATE AND NOTIFY MUNI TO TEMPORARY RELOCATE BUS STOP, (SEE PROJECT SPECIFICATIONS SECTION OI 55 26 3.3) INSTALL TEMP. BUS STOP AS NEEDED.



DELINEATOR OR CONE WITH W1-6 - BOTH SIDES



W1-6 - ONE SIDE

TRAFFIC CONTROL SIGN CONES OR DELINEATORS (24" OR 36" WITH REFLECTIVE BAND) AT 5' (MAX) CONES OR DELINEATORS (24" OR 36" WITH REFLECTIVE BAND) AT 20' (MAX)

FLASHING ARROVBOARDS WORKING AREA

FLAG PERSON

MUNI INSPECTOR

RAILLING WITH BASE BOARD AND CONSTRUCTION GRANGE FENCE OR EQUAL WATER FILLED TRITON BARRIERS OR EQUAL

 TA/NS BOTH SIDES A TA/NS ON SIDE NOTED

TEMP. PAVEMENT MARKER "YELLOW" CLUE TO PAVEMENT AT 10' MAX.

TEMP, RAMP 8 % MAX.

LANDING AREA 2% MAX. DELINEATOR OR COME WITH WI-6 SIGN (BOTH SIDES)

DELINEATOR OR CONE WITH WI-6 SIGN (ONE SIDE)



TRAFFIC CONTROL PLAN FOR

VARIOUS LOCATION PAVEMENT RENOVATION NO. 39 AND SEWER REPLACEMENT CONTRACT NO. 2937J

ESOUIVEL GRADING AND PAVING, INC. 918 INGERSON AVENUE SAN FRANCISCO, CA 94124

DRAWN BY: ABDOL M. DEHGHANI, P.E.

100 SCALE: 1" = 100

REVISION NO.

FEBRUARY 19, 2019 JOB NO. 2019-01 SHEET TC.2