

CS 320L – Applied Discrete Mathematics – Spring 2017
Instructor: Marc Pomplun

Assignment #1

Posted on February 7 – Due by February 14, 5:30pm

Question 1: Hair Splitting with Set Expressions

Let us define the *successor* of the set A to be the set $A \cup \{A\}$. Find the successors of the following sets:

- a) $A = \{x\}$
- b) $B = \{x, y\}$
- c) $C = \emptyset$
- d) $D = \{\emptyset, \{\emptyset\}\}$

Question 2: Tautologies and Contradictions

Find out for each of the following propositions whether it is a tautology, a contradiction, or neither (a contingency). Prove your answer.

- a) $[(p \rightarrow q) \wedge (q \rightarrow r)] \rightarrow (p \rightarrow r)$
- b) $(p \vee q \vee r) \rightarrow [(q \rightarrow r) \vee (p \rightarrow q)]$

Question 3: Set Operations

Let us take a look at the sets $A = \{x, y, z\}$, $B = \{1, 2\}$, $C = \{y, z\}$. List the elements of the following sets D , E , F , G , H , and I :

- a) $D = (B \times A) - (B \times C)$
- b) $E = 2^A - 2^C$
- c) $F = 2^{(2^B)}$

d) $G = (A \times B \times C) \cap (C \times B \times A)$

e) $H = \{(a, b, c) \mid a, b, c \in B \wedge b \neq c \wedge a = b\}.$

f) $I = \{(a, b, c) \mid a \in A \wedge b \in B \wedge c \in C \wedge a = c\}$

Question 4: Cardinality

Are the following statements true for all sets A, B and C? Prove your answers.

a) $|A \cup B \cup C| = |A - B - C|$

b) $|A \cup B \cup C| = |A| + |B| + |C| - |A \cap B| - |A \cap C| - |B \cap C|$

Question 5: Functions

Find out whether the following functions from \mathbf{R} to \mathbf{R} are injective, surjective, and/or Bijective (no proof necessary).

a) $f(z) = -z$

b) $f(z) = 300z^5 + 4$

c) $f(z) = z \cdot \sin z$

d) $f(z) = z^2/(z^2 + 1)$

Question 6: Big-O Estimates

Give as good a big-O estimate as possible for the following complexity functions:

a) $f(n) = (n \cdot \log n) (n^2 + 2n)$

b) $f(n) = (2n! + 4n^3) + (2^n \cdot n^3)$

c) $f(n) = n^4 + 5 \log n + n^3 (n^2 + 2n)$

Question 7: Algorithms and Their Complexity

- a) Write a simple program in pseudocode (or in Python, C, C++, or Java, but only use basic commands so that comparisons can be counted) that receives a sequence of integers a_1, \dots, a_n as its input and determines if the sequence contains two distinct terms x, y such that $x = y^2$. Once it finds such terms, it prints them and terminates; it does not continue searching after the first find. If the program does not find any such terms, it prints a disappointed comment and also terminates.
- b) Describe the kind of input that causes worst-case time complexity for your algorithm (only count comparisons), and explain why this is the case.
- c) Provide an equation for your algorithm that describes the number of required comparisons as a function of input length n in the worst case. For some algorithms, it may be a good idea to first use a sum notation, but at the end you should provide a closed-form equation, i.e., one that no longer uses the sum symbol but only operations such as multiplication or addition of individual numbers or variables.
- d) Use the big-O-notation to describe the worst-case time complexity of your algorithm.

Question 8 (Bonus Question): Venn Diagrams

Draw the Venn diagrams for the following sets:

- a) $A \cup B \cup C$
- b) $A \cup (B - C)$
- c) $(A \cap B) \cup (A \cap C)$
- d) $(A \cap \overline{B}) \cup (A \cap \overline{C})$