

TP02 Correction

Matière : ATELIER DEVELOPPEMENT MOBILE AVANCE

Classe : SEM31

```
package com.suivi.patient
```

```
data class Patient(  
    var id: Int,  
    var nom: String,  
    var prenom: String,  
    var dateNaissance: String,  
    var tension: Int,  
    var rythme: Int  
) {  
    override fun toString(): String {  
        return "$nom-$prenom-$dateNaissance"  
    }  
}
```

```
package com.suivi.patient
```

```
import android.content.Context  
import android.database.sqlite.SQLiteDatabase  
import android.database.sqlite.SQLiteOpenHelper
```

```
class SQLiteSuivi (  
    context: Context?,  
    name: String?,  
    factory: SQLiteDatabase.CursorFactory?,  
    version: Int  
) : SQLiteOpenHelper(context, name, factory, version) {  
  
    override fun onCreate(db: SQLiteDatabase) {  
        val sql = "CREATE TABLE Patient " +  
            "(id INTEGER PRIMARY KEY AUTOINCREMENT, " +  
            "nom TEXT NOT NULL, " +  
            "prenom TEXT NOT NULL, " +  
            "dateNaissance TEXT NOT NULL, " +  
            "tension INTEGER default 13, " +  
            "rythme INTEGER default 90);"  
        db.execSQL(sql)  
    }  
  
    override fun onUpgrade(db: SQLiteDatabase, oldVersion: Int, newVersion: Int) {  
        // Laisser vide ou ajouter la logique de mise à jour de la BDD  
    }  
}
```

```
class MainActivity : AppCompatActivity() {
    private lateinit var amb: ActivityMainBinding
    private lateinit var adpPatient: ArrayAdapter<Patient>
    override fun onCreate(savedInstanceState: Bundle?) {
        super.onCreate(savedInstanceState)
        initGraphique()
    }
    private fun initGraphique() {
        amb = ActivityMainBinding.inflate(layoutInflater)
        setContentView(amb.root)
        adpPatient = ArrayAdapter(this, android.R.layout.simple_spinner_item)
        amb.spPatient.adapter = adpPatient
        remplir()
        ajouterEcouteurs()
    }

    private fun remplir() {
        val b = SQLiteSuivi(this, "Suivi.db", null, 1)
        val db : SQLiteDatabase = b.writableDatabase
        val sql = "Select * From Patient order by nom,prenom asc"
        val c: Cursor = db.rawQuery(sql, null)
        adpPatient.clear()
        while (c.moveToNext()) {
            val id = c.getInt(0)
            val nom = c.getString(1)
            val prenom = c.getString(2)
            val dateNaissance = c.getString(3)
            val tension = c.getInt(4)
            val rythme = c.getInt(5)
            val patient = Patient(id, nom, prenom, dateNaissance, tension, rythme)
            adpPatient.add(patient)
        }
        c.close() // Pensez à fermer le curseur manuellement
        db.close()
    }

    private fun ajouterEcouteurs() {
        amb.btnModifier.setOnClickListener { modifier() }
        amb.btnNouveau.setOnClickListener { nouveau() }
        amb.spPatient.onItemSelectedListener = object : AdapterView.OnItemSelectedListener {
            override fun onItemSelected(
                p0: AdapterView<*>?,
                p1: View?,
                p2: Int,
                p3: Long
            ) {
                actualiser()
            }
        }

        private fun actualiser() {
            val patient = amb.spPatient.selectedItem as Patient
        }
    }
}
```

```

        amb.edTension.setText(patient.tension.toString())
        amb.edRythme.setText(patient.rythme.toString())
    }

    override fun onNothingSelected(p0: AdapterView<*>?) {

    }

}

private val launcher = registerForActivityResult(
    ActivityResultContracts.StartActivityForResult()
) { result ->
    if (result.resultCode == RESULT_OK) {
        remplir()

    }
}

private fun nouveau() {
    val intent = Intent(this, AjoutActivity::class.java)
    launcher.launch(intent)
}

private fun modifier() {
    val patient=amb.spPatient.selectedItem as Patient
    val id = patient.id
    val b = SQLiteSuivi(this, "Suivi.db", null, 1)
    val db: SQLiteDatabase = b.writableDatabase
    val v = ContentValues().apply {
        put("tension", amb.edTension.text.toString())
        put("rythme", amb.edRythme.text.toString())
    }
    db.update("Patient", v, "id=?", arrayOf(id.toString()))
    db.close()
    remplir()
}

}

package com.suivi.patient

class AjoutActivity : AppCompatActivity() {
    private lateinit var amb: ActivityAjoutBinding
    override fun onCreate(savedInstanceState: Bundle?) {
        super.onCreate(savedInstanceState)
        initGraphique()
    }
    private fun initGraphique() {
        amb= ActivityAjoutBinding.inflate(layoutInflater)
        setContentView(amb.root)
        ajouterEcouteurs()
    }
}

```

```

private fun ajouterEcouleurs() {
    amb.btnAjouter.setOnClickListener{ ajouter() }
    amb.btnRetour.setOnClickListener { retour() }

}
private fun retour() {
    setResult(RESULT_CANCELED)
    finish()
}
private fun ajouter() {
    if (amb.edNom.text.isNotBlank() &&
        amb.edPrenom.text.isNotBlank() &&
        amb.edDate.text.isNotBlank()
    ) {
        val b = SQLiteSuivi(this, "Suivi.db", null, 1)
        val db = b.writableDatabase
        val v = ContentValues().apply {
            put("nom", amb.edNom.text.toString())
            put("prenom", amb.edPrenom.text.toString())
            put("dateNaissance", amb.edDate.text.toString())
            put("tension", 13)
            put("rythme", 90)
        }
        db.insert("Patient", null, v)
        db.close()
        setResult(RESULT_OK)
        finish()
    } else
        Toast.makeText(
            this, "Remplir tous les champs SVP!",
            Toast.LENGTH_LONG
        ).show()
}
}

```