

TD01 Correction

Matière : DEVELOPPEMENT MOBILE AVANCE

Classes : SEM31

```
private fun remplirVille() {
    val b = SQLiteContact(this, "contact.db", null, 1)
    val db = b.writableDatabase
    val c = db.rawQuery("Select distinct (ville) from contact order by ville;", null)
    adpV.clear()
    // Boucle while explicite pour le curseur
    while (c.moveToNext()) {
        val v = c.getString(0)
        adpV.add(v)
    }
    c.close()
    db.close()
}

private fun rechercher() {
    // Utilisation du View Binding pour le Spinner (spV)
    if (binding.spV.selectedItemPosition >= 0) {
        val v = binding.spV.selectedItem.toString()
        val b = SQLiteContact(this, "contact.db", null, 1)
        val db = b.writableDatabase
        val c = db.rawQuery("Select * from contact where ville=?;", arrayOf(v))
        adpC.clear()
        // Boucle while explicite pour le curseur
        while (c.moveToNext()) {
            val id = c.getInt(0)
            val n = c.getString(1)
            val p = c.getString(2)
            val t = c.getString(4)
            val contact = Contact(id, n, p, v, t)
            adpC.add(contact)
        }
        c.close()
        db.close()
    }
}

private fun ajouter() {
    val b = SQLiteContact(this, "contact.db", null, 1)
    val db = b.writableDatabase

    val values = ContentValues().apply {
        put("nom", amb.edN.text.toString())
        put("prenom", amb.edP.text.toString())
        put("ville", amb.edV.text.toString())
        put("tel", amb.edT.text.toString())
    }
    db.insert("contact", null, values)
    db.close()
}
```