Class 3 ~ HTML/CSS ~ Girl Develop IT



BEGINNING HTML AND CSS
CLASS 3

WELCOME!

Girl Develop It is here to provide affordable and accessible programs to learn software through mentorship and hands-on instruction.

Some "rules"

- We are here for you!
- Every question is important
- Help each other
- Have fun

REVIEW - HTML

```
<hl>headings</hl>

    paragraphs with <strong>importance</strong>.

    li>lists
    li>lists
    mage with relative src
    a href="http://google.com">a link with absolute href</a>

cp id="footer">
    IDs are used once per page.
```

REVIEW - CSS

```
/* classes start with . */
.background-blue{
   background-color:blue;
}

/* IDs start with # */

#footer{
   font-size:12px;
   color:#888;
}
```


REVIEW - CONNECTING HTML AND CSS

External CSS

<head>
 link rel="stylesheet" type="text/css" href="style.css">
</head>

WHAT WE'LL BE MAKING TODAY

Today we will be making a site from scratch using divs and spans to create a header, footer and a content area.



INLINE VS BLOCK

So far, we have mostly seen "block" elements

They appear on the next line, like paragraphs

There are also "inline" elements

They appear on the same line that they are written on.

BLOCK & INLINE

BLOCK:	
INLINE:	

ELEMENTS,

- CSS divides HTML into two types: inline and block.
- After block elements, browsers render a new line.
- Inline elements: img, a, br, em, strong
- Block elements: p, h1, ul, li, almost everything else

Class 3 ~ HTML/CSS ~ Girl Develop IT 3/30/14 3:05 PM



ELEMENT: DIV

- Block level element. Each new div is rendered on a new line.
- A division, or section of content within an HTML page.
- Used to group elements to format them with CSS.
- Apply IDs and Classes to divs to control their styles with CSS.

GROUPING ELEMENTS WITH DIV

- The div tag is used everywhere to group elements together into sections.
- For example, what if we want the first 2 paragraphs of a section to be rightaligned, green & bold, but we don't want any other paragraphs to be rightaligned?
- We would wrap them in a div element to style them differently.

GROUPING ELEMENTS WITH DIV, CONT.

Lorem ipsum dolor sit amet, consectetur adipisicing

Sed do eiusmod tempor incididunt ut labore et dolore.

Magna aliqua. Ut enim ad minim veniam.

Quis nostrud exercitation ullamco.

LET'S DEVELOP IT

Let's create a site using divs to separate content into different sections on our page.

Create a header, content area, sidebar, and a footer.

ELEMENT: SPAN

- Inline element. Each new span is rendered next to each other & only wraps when it reaches the edge of the containing element.
- Can be used to apply styles to text inline so as not to break the flow of content.

SPAN

Span is used to apply a specific style inline

```
.yellow{
  color:yellow;
}
Paragraph with <span class ="yellow">yellow</span> text.
```

Paragraph with yellow text.

LET'S DEVELOP IT

Let's add some spans to our content to help highlight some text.

PSEUDO-CLASSES, MORE CSS FOR LINKS

Changing the format of a link when you hover over it is accomplished by using pseudoclasses.

Syntax:

```
selector:pseudo-class
{
   property:value;
}
```

Example:

```
a:link
{
  text-decoration: none;
}
```

CSS pseudoclasses are used to add special effects to some selectors.

PSEUDO-CLASSES, MORE CSS FOR LINKS


Note: a:hover MUST come after a:link and a:visited in the CSS definition in order to be effective!

Note: a:active MUST come after a:hover in the CSS definition in order to be effective!

LET'S DEVELOP IT

Add pseudo classes to your links


Class 3 ~ HTML/CSS ~ Girl Develop IT 3/30/14 3:05 PM



Class 3 ~ HTML/CSS ~ Girl Develop IT

PADDING


Space between the border and the content



PADDING

Space between the border and the content

Adds to the total width of the box.



PADDING

15 pixels on all sides

padding: 15px;

10 pixels on top only

padding-top: 10px;

10 on top, 5 on right, 3 on bottom, 5 on left

padding: 10px 5px 3px 5px;

PADDING

Four values

padding: top right bottom left;

Two values

padding: top/bottom right/left;


One value

padding: all;

Class 3 ~ HTML/CSS ~ Girl Develop IT 3/30/14 3:05 PM




padding: 10px 20px 30px 40px;



BORDER

The edge around the box, specified as "thickness, style, color."



BORDER

A solid red border

border: 1px solid #ff0000;

A thick dotted black top border

border-top: 4px dotted #000000;

Two different border styles

border-top: 1px solid #ff0000; border-bottom: 4px dotted #000000;


BORDER - OTHER PROPERTIES

border-width: 10px; border-style: dashed; border-color: #666666;

You can specify each property separately, or all three together.

MARGIN

The transparent area around the box that separates it from other elements.



MARGIN

15 pixels on all sides

margin: 15px;

10 on top, 5 on right, 3 on bottom, 5 on left

margin: 10px 5px 3px 5px;

10 pixels on top

margin-top: 10px;

AUTO MARGIN

If a margin is set to auto on a box that has width, it will take up as much space as possible.

CENTERED

margin: auto;
width: 300px;

FLUSH-RIGHT

margin-left: auto;
margin-right: 5px;
width: 300px;

LET'S DEVELOP IT!

Let's add some padding, borders, and margins to our divs.

Let's center our entire document in the browser.

PROPERTY: WIDTH

Sets the width of an element.

Does not include padding or borders, remember these add to the width.

PROPERTY: HEIGHT

Sets the height of an element.

Does not include padding or borders, remember these add to the width.

LET'S DEVELOP IT!

Add a width & height to our divs.

Use IDs to target each div with CSS





Class 3 ~ HTML/CSS ~ Girl Develop IT 3/30/14 3:05 PM

HTML/CSS ~ Girl Develop It ~ (cc) by-nc