

Statistical Methods for Discrete Response, Time Series, and Panel Data (W271): Lab 3


PKyle Chuang and Sullivan Swift

Question 1: Forecasting using a SARIMA model

Note: Custom function `ts_plots()` [plot time series], `ts_resid()` [plot residuals], `forecast_exp()` [exponentiate all values in forecasts objects] and `arimatable()` [summarizes arima table] are not included in the R pdf but is in the R-markdown file.

In the following report, we analyze and model quarterly data of E-Commerce Retail Sales as the Percent of Total Sales. Our goal is to use the data, ranging from Q4 1999 to Q4 2016, to forecast predictions for each quarter in 2017. First we explore the data and determine what models to further pursue. We select two model to test in depth, including with in- and out-of-model sampling. We use our final model to make a 2017 prediction.


```
df=read.csv('ECOMPCTNSA.csv')
head(df)
# exclude 2015 & 2016
dfts=ts(df$ECOMPCTNSA,start=c(1999,4),end=c(2014,4),freq=4)
ts_plots(dfts)
```



There is clearly a seasonal component based on the plot. Additionally, the plot seems to be potentially heteroskedastic. We will perform a log transformation on the time series to decrease


the heteroskedasticity and re-analyze the time series from the starting point.

```
dfts_log=log(dfts)
ts_plots(dfts_log)
```




From the logged time series plots, there is a trend and seasonal component. The seasonality is likely to be quarterly from the t-plot. We will look at a box plot of the data by season.

```
ggplot(data.frame(cycle=factor(cycle(dfts_log)),data=as.numeric(dfts_log)),aes(x=cycle,y=data,
```




The seasonal boxplot does not show significant differences in each of the quarters. However, this is possibly due to the trend component affecting the cycles. We will detrend the series first and re-examine the quarterly plots.

```
tmp=diff(dfts_log,lag=1)
ggplot(data.frame(cycle=factor(cycle(tmp)),data=as.numeric(tmp)),aes(x=cycle,y=data,group=cycle,
```



The detrended series shows a strong quarterly seasonality. The time series will be deseasonalized using a quarterly cycle.

```
df_ds=diff(diff(dfts_log,lag=1),lag=4)
ggplot(data.frame(cycle=factor(cycle(df_ds)),data=as.numeric(df_ds)),aes(x=cycle,y=data,group=cycle))
```



```
adf.test(df_ds)
```

```
##
## Augmented Dickey-Fuller Test
##
## data: df_ds
## Dickey-Fuller = -7.2107, Lag order = 3, p-value = 0.01
## alternative hypothesis: stationary
```

```
pp.test(df_ds)
```


```
##
## Phillips-Perron Unit Root Test
##
## data: df_ds
## Dickey-Fuller Z(alpha) = -52.65, Truncation lag parameter = 3,
```

```
## p-value = 0.01
## alternative hypothesis: stationary
```

The plot of the detrended and deseasonalized data shows the quarterly mean and variance is now similar across the quarters, indicating a deseasonalized time series. Augmented Dickey-Fuller and Phillips-Perron tests are performed on deseasonalized, detrended time series. Both tests reject the non-stationary hypothesis.

With a stationary time series, we can use an ARMA model to model the detrended, deseasonalized time series. Since there are $I(1)$ and $I(1)_4$ components in the time series, we will use the SARIMA model to model the original logged time series rather than modeling the detrended and deseasonalized logged data, thus combining the steps.

```
ggtsdisplay(df_ds)
```



Reviewing the plots of the data we detrended and deseasonalized, we confirm the the time series to have been detrended and deseasonalized. On the PACF plot, there appears to strong serial correlation quarterly as it oscillates towards zero. The ACF plot has high serial correlation at the 4th lag. The strong ACF at lag 4 and cycling towards 0 in pact suggest there is a SMA(1) component.


Based on our exploration, the intial model will be $SARIMA(0, 1, 0)(0, 1, 1)_4$.

```
m = arima(dfts_log,order=c(0,1,0),seasonal = list(order=c(0,1,1),period=4))
xtable(arimatable(m,dfts_log))
```

	beta	SE	Sigma2	AIC	BIC	LogLik	ME	RMSE	MAE
sma1	-0.52	0.10	0.00	-201.54	-197.49	102.77	-0.01	0.04	0.03

The SMA1 β at -0.5167 with se. at 0.0975 suggesting significance. The β_{sma1} does not cross zero.

```
ts_resid(m$residuals)
```



	PhillipsPerron	AugmentedDickeyFuller	LjungBox
p-Value	0.01	0.01	0.35

The t-plot of the residuals appears to be white noise with heteroskedasticity. We will not further attempt to fit the variance of the residuals with GARCH/ARCH models. The t-plot shows no trend or seasonality. The residuals appear to be a stationary white noise process (though not necessarily Gaussian white noise) from the augmented Dickey Fuller and Phillips-Perron Test. Finally, the Ljung-box test almost shows the residuals to be uncorrelated with a p-Value of 0.35 as confirmed by the visual inspection.

We will examine other $SARIMA(p, 1, q)(P, 1, Q)_4$ up to $p = q = P = Q = 2$ to aid in choosing our final model.

```
results=data.frame(matrix(ncol=9,nrow=0))
for (p in 0:2){ for (q in 0:2) { for (PS in 0:2) { for (QS in 0:2) {
  m.tmp=arima(dfts_log,order=c(p,1,q),seasonal = list(order=c(PS,1,QS),period=4))
  results=rbind(results,c(p=p,d=1, q=q,P=PS,D=1,Q=QS,AIC=AIC(m.tmp),BIC=BIC(m.tmp),Log_L_
colnames(results) = c('p','d','q','P','D','Q','AIC','BIC','Log_Likelihood')
xtable(head(results[order(results$AIC,results$BIC),],5))
}

```

	p	d	q	P	D	Q	AIC	BIC	Log_Likelihood
3	0.00	1.00	0.00	0.00	1.00	2.00	-207.22	-201.14	106.61
7	0.00	1.00	0.00	2.00	1.00	0.00	-206.50	-200.42	106.25
4	0.00	1.00	0.00	1.00	1.00	0.00	-206.22	-202.17	105.11
30	1.00	1.00	0.00	0.00	1.00	2.00	-205.53	-197.42	106.76
5	0.00	1.00	0.00	1.00	1.00	1.00	-205.50	-199.42	105.75

```
beta SE Sigma2 AIC BIC LogLik sar1 -0.8011532 0.1506089 0.001302963 -206.4998 -200.4238
106.2499 sar2 -0.2490731 0.1618362 0.001302963 -206.4998 -200.4238 106.2499 ME RMSE MAE
sar1 -0.01010292 0.03396238 0.02369047 sar2 -0.01010292 0.03396238 0.02369047
```

Auto.arima() selected $SARIMA(0, 1, 0)(2, 1, 0)_4$. From the manual iterations and auto.arima(),


$SARIMA(0,1,0)(0,1,2)_4$ and $SARIMA(0,1,0)(2,1,0)_4$ are chosen as the candidate models as they have the lowest AICs and BICs.

In the $SARIMA(0,1,0)(0,1,2)_4$, β_s appear to be statistically significant and the residuals do appear to be white noise with stationarity and no autocorrelation. The Ljung-Box p-Value is higher than the $SARIMA(0,1,0)(0,1,1)_4$ model. Note that the heteroskedasticity in residuals no longer appear.

```
m.010012=arima(dfts_log,order=c(0,1,0),seasonal = list(order=c(0,1,2),period=4))
xtable(arimatable(m.010012,dfts_log))
```

	beta	SE	Sigma2	AIC	BIC	LogLik	ME	RMSE	MAE
sma1	-0.77	0.16	0.00	-207.22	-201.14	106.61	-0.01	0.03	0.02
sma2	0.40	0.13	0.00	-207.22	-201.14	106.61	-0.01	0.03	0.02

```
ts_resid(m.010012$residuals)
```




	PhillipsPerron	AugmentedDickeyFuller	LjungBox
p-Value	0.01	0.01	0.13

In the $SARIMA(0,1,0)(2,1,0)_4$, the β_s do not include zero up to the 95% confidence interval and the residual appear to be stationary and white noise. The Ljung-Box p-Value is ???? and the heteroskedasticity of the residuals is not evident.

```
m.010210=arima(dfts_log,order=c(0,1,0),seasonal = list(order=c(2,1,0),period=4))
xtable(arimatable(m.010210,dfts_log))
```

	beta	SE	Sigma2	AIC	BIC	LogLik	ME	RMSE	MAE
sar1	-0.80	0.15	0.00	-206.50	-200.42	106.25	-0.01	0.03	0.02
sar2	-0.25	0.16	0.00	-206.50	-200.42	106.25	-0.01	0.03	0.02

```
ts_resid(m.010210$residuals)
```




	PhillipsPerron	AugmentedDickeyFuller	LjungBox
p-Value	0.01	0.01	0.09


We first note that these series seem comparable as a MA model can be inverted to become an AR model. An $SARIMA(0, 1, 0)(0, 1, 2)_4$ is very similar to $SARIMA(0, 1, 0)(2, 1, 0)_4$ from invertibility of MA models.

The 2 models will be chosen as potential candidates. We will examine both in-sample and out-of-sample fits to chose the final model.

```
actual=ts(df$ECOMPCTNSA,start=c(1999,4),freq=4)
forecast_sar=forecast_exp_func(forecast(m.010210))
forecast_sma=forecast_exp_func(forecast(m.010012))
autoplot(forecast_sar) +autolayer(exp(fitted(m.010210)),series='ARIMA(0,1,0)(2,1,0)[4]',position='top')
```



```
autoplot(forecast_sma) + autolayer(exp(fitted(m.010012)), series='ARIMA(0,1,0)(0,1,2)[4]', position='bottom')
```



The in-sample fits for both models are extremely close to the historical fit. The predictions for both models are extremely similar. We will select the models based on accuracy of the time series. The time series is logged to avoid overweighting the larger values on the time series due to the trend.

```
pred_test=window(log(actual),start=c(2015,1))
xtable(accuracy(forecast(m.010210),pred_test),caption='$ARIMA(0,1,0)(2,1,0)_4$')
```

	ME	RMSE	MAE	MPE	MAPE	MASE	ACF1	Theil's U
Training set	-0.01	0.03	0.02	-Inf	Inf	0.16	-0.21	
Test set	0.04	0.05	0.04	2.17	2.17	0.30	0.18	0.37

Table 1: $ARIMA(0,1,0)(2,1,0)_4$


```
xtable(accuracy(forecast(m.010012),pred_test),caption='$ARIMA(0,1,0)(0,1,2)_4$')
```

	ME	RMSE	MAE	MPE	MAPE	MASE	ACF1	Theil's U
Training set	-0.01	0.03	0.02	-Inf	Inf	0.16	-0.19	
Test set	0.05	0.05	0.05	2.44	2.44	0.34	0.20	0.41

Table 2: $ARIMA(0, 1, 0)(0, 1, 2)_4$

Every accuracy measure tested showed a lower error with $SARIMA(0, 1, 0)(2, 1, 0)_4$ model. The final model chosen is # CHECK BELOW

$SARIMA(0, 1, 0)(2, 1, 0)_4$

$$(1 - 0.7851B - 0.23651B^2)_4(1 - B)_4(1 - B)x_t = \epsilon_t$$

$$y_t = y_{t-1} + y_{t-4} + -0.7851y_{t-4} + -0.23651y_{t-5} + \epsilon_t$$

```
df_full_log=ts(log(df$ECOMPCTNSA),start=c(1999,4),freq=4)
m=arima(df_full_log,order=c(0,1,0),seasonal = list(order=c(2,1,0),period=4))
xtable(arimatable(m,df_full_log))
```


	beta	SE	Sigma2	AIC	BIC	LogLik	ME	RMSE	MAE
sar1	-0.79	0.14	0.00	-242.53	-236.05	124.27	-0.01	0.03	0.02
sar2	-0.24	0.16	0.00	-242.53	-236.05	124.27	-0.01	0.03	0.02

The forecast for 2017 using $SARIMA(0, 1, 0)(2, 1, 0)_4$ is

```
forecast_sar=forecast_exp_func(forecast(m,h = 4))
xtable(data.frame(forecast_sar))
```

	Point.Forecast	Lo.80	Hi.80	Lo.95	Hi.95
2017 Q1	8.47	8.11	8.84	7.92	9.05
2017 Q2	8.09	7.60	8.60	7.36	8.89
2017 Q3	8.33	7.73	8.99	7.43	9.36
2017 Q4	10.59	9.70	11.55	9.27	12.10

```
autoplot(forecast_sar, 'Model') +autolayer(exp(fitted(m)),series='ARIMA(0,1,0)(2,1,0)[4]',posit
```




KYLE - OWN TEST


Furthermore, the residuals appear to be heteroskedastic. From the *residuals*² act and pacf plots, There appears to be an AR component in the volatility suggesting a GARCH(1,0) model.

```
#library(fGarch)
#m.garch=garchFit(~garch(1,0),m$residuals,trace=FALSE)
#summary(m.garch)
```


```
ggtsdisplay(m$residuals^2)
```



```
tmp=diff(diff(dfts_log,lag=1),lag=4)
ggtsdisplay(tmp)
```




```
ggplot(data.frame(cycle=factor(cycle(tmp)),data=as.numeric(tmp)),aes(x=cycle,y=data,group=cycle))
```



```
#ggplot(data.frame(r=residuals(m.garch)),aes(sample=r))+geom_qq()+geom_qq_line(col='red')
#hist(residuals(m.garch))
#predict(m.garch)
```

The series appear to be detrended and deseasonalized. From the ACF graph

```
par(mfrow=c(2,2))
plot(dfts_log)
hist(dfts_log)
acf(dfts_log,lag=12)
pacf(dfts_log,lag=12)
```







The initial model proposed is a $SARIMA(1, 1, 0)(0, 0, 1)_4$ model.

```
m=arima(dfts_log,order=c(1,1,0),seasonal=list(order=c(0,0,1),period=4))
```

The AR(1) component is likely to be 0 given the -0.0705 β and s.e. of 0.1347 . The SMA(1) β appears significant. We will examine the residuals to see if the I(1) has removed the trend.


From the t-plot, the I(1) appears to have removed the trend. The seasonality does not seem to be removed but m

```
par(mfrow=c(2,2))
plot(m$residuals)
hist(m$residuals)
acf(m$residuals,lag=12)
pacf(m$residuals,lag=12)
```



```
plot(window(m$residuals,start=c(2008,1),end=c(2014,4)))
```

window(m\$residuals, start = c(2008, 1), end = c(2014, 4



```
library(ggplot2)
```

Question 2: Learning how to use the xts library

Materials covered in Question 2 of this lab

- Primarily the references listed in this document:
 - “xts: Extensible Time Series” by Jeffrey A. Ryan and Joshua M. Ulrich. 2008. (xts.pdf)
 - “xts FAQ” by xts Development Team. 2013 (xts_faq.pdf)
 - xts_cheatsheet.pdf

Task 1:

1. Read A. The **Introduction** section (Section 1), which only has 1 page of reading of xts: Extensible Time Series” by Jeffrey A. Ryan and Joshua M. Ulrich B. The first three questions in “xts FAQ” a. What is xts? b. Why should I use xts rather than zoo or another time-series package? c. How do I install xts? C. The “A quick introduction to xts and zoo objects” section in this document
2. Read the “A quick introduction to xts and zoo objects” of this document

A quick introduction to xts and zoo objects

xts

xts - stands for eXtensible Time Series - is an extended zoo object - is essentially matrix + (time-based) index (aka, observation + time)

- xts is a constructor or a subclass that inherits behavior from parent (zoo); in fact, it extends the popular zoo class. As such, most zoo methods work for xts
- is a matrix objects; subsets always preserve the matrix form
- importantly, xts are indexed by a formal time object. Therefore, the data is time-stamped
- The two most important arguments are **x** for the data and **order.by** for the index. **x** must be a vector or matrix. **order.by** is a vector of the same length or number of rows of **x**; it must be a proper time or date object and be in an increasing order

Task 2:

1. Read A. Section 3.1 of “xts: Extensible Time Series” by Jeffrey A. Ryan and Joshua M. Ulrich B. The following questions in “xts FAQ” a. How do I create an xts index with millisecond precision? b. OK, so now I have my millisecond series but I still can’t see the milliseconds displayed. What went wrong?
2. Follow the following section of this document

Creating an xts object and converting to an xts object from an imported dataset

We will create an xts object from a matrix and a time index. First, let's create a matrix and a time index. The matrix, as it creates, is not associated with the time index yet.

```
# Set working directory
#wd <- "~/Documents/Teach/Cal/w271/_2018.03_Fall/labs/lab3"
#setwd(wd)
```

```
# Create a matrix
x <- matrix(rnorm(200), ncol=2, nrow=100)
colnames(x) <- c("Series01", "Series02")
str(x)
```

```
num [1:100, 1:2] 0.989 -0.511 -0.552 0.773 2.474 ... - attr(*, "dimnames")=List of 2 ..$ : NULL ..$ :
chr [1:2] "Series01" "Series02"
```

```
head(x,10)
```

```
      Series01      Series02
[1,] 0.9885600 -0.77910871 [2,] -0.5106589 -0.67318121 [3,] -0.5516471 1.32892218 [4,] 0.7725972
0.33273776 [5,] 2.4741035 0.31665745 [6,] -0.7663276 -1.39916987 [7,] -1.1676380 -0.02195686 [8,]
0.4621566 -0.36791130 [9,] -0.2017706 1.22527090 [10,] 2.0837309 -1.35179660
```

```
idx <- seq(as.Date("2015/1/1"), by = "day", length.out = 100)
str(idx)
```

```
Date[1:100], format: "2015-01-01" "2015-01-02" "2015-01-03" "2015-01-04" "2015-01-05" ...
```

```
head(idx)
```

```
[1] "2015-01-01" "2015-01-02" "2015-01-03" "2015-01-04" "2015-01-05" [6] "2015-01-06"
```

```
tail(idx)
```

```
[1] "2015-04-05" "2015-04-06" "2015-04-07" "2015-04-08" "2015-04-09" [6] "2015-04-10"
```

In a nutshell, xts is a matrix indexed by a time object. To create an xts object, we “bind” the object with the index. Since we have already created a matrix and a time index (of the same length as the number of rows of the matrix), we are ready to “bind” them together. We will name it X.

```
library(xts)
X <- xts(x, order.by=idx)
str(X)
```

```
An 'xts' object on 2015-01-01/2015-04-10 containing: Data: num [1:100, 1:2] 0.989 -0.511 -0.552
0.773 2.474 ... - attr(*, "dimnames")=List of 2 ..$ : NULL ..$ : chr [1:2] "Series01" "Series02"
Indexed by objects of class: [Date] TZ: UTC xts Attributes:
NULL
```

```
head(X,10)
```

```
      Series01      Series02
```



```
2015-01-01 0.9885600 -0.77910871 2015-01-02 -0.5106589 -0.67318121 2015-01-03 -0.5516471
1.32892218 2015-01-04 0.7725972 0.33273776 2015-01-05 2.4741035 0.31665745 2015-01-06 -
0.7663276 -1.39916987 2015-01-07 -1.1676380 -0.02195686 2015-01-08 0.4621566 -0.36791130
2015-01-09 -0.2017706 1.22527090 2015-01-10 2.0837309 -1.35179660
```

As you can see from the structure of an `xts` object, it contains both a data component and an index, indexed by an object of class `Date`.

xts constructor

```
xts(x=NULL,
    order.by=index(x),
    frequency=NULL,
    unique=NULL,
    tzone=Sys.getenv("TZ"))
```

As mentioned previously, the two most important arguments are `x` and `order.by`. In fact, we only use these two arguments to create a `xts` object before.

With a `xts` object, one can decompose it.

Deconstructing xts

`coredata()` is used to extract the data component

```
head(coredata(X),5)
```

```
      Series01      Series02
[1,] 0.9885600 -0.7791087 [2,] -0.5106589 -0.6731812 [3,] -0.5516471 1.3289222 [4,] 0.7725972
0.3327378 [5,] 2.4741035 0.3166574
```

`index()` is used to extract the index (aka times)

```
head(index(X),5)
```

```
[1] "2015-01-01" "2015-01-02" "2015-01-03" "2015-01-04" "2015-01-05"
```

Conversion to xts from other time-series objects

We will use the same dataset “`bls_unemployment.csv`” that we used in the last live session to illustrate the functions below.

```
df <- read.csv("bls_unemployment.csv", header=TRUE, stringsAsFactors = FALSE)

# Examine the data structure
str(df)
```

```
‘data.frame’: 121 obs. of 4 variables: $ Series.id: chr “LNU04000000” “LNU04000000”
“LNU04000000” “LNU04000000” ... $ Year : int 2007 2007 2007 2007 2007 2007 2007 2007 2007
2007 ... $ Period : chr “M01” “M02” “M03” “M04” ... $ Value : num 5 4.9 4.5 4.3 4.3 4.7 4.9 4.6
4.5 4.4 ...
```

```
names(df)
```

```
[1] "Series.id" "Year" "Period" "Value"
```

```
head(df)
```

```
Series.id Year Period Value
```

```
1 LNU04000000 2007 M01 5.0 2 LNU04000000 2007 M02 4.9 3 LNU04000000 2007 M03 4.5 4
LNU04000000 2007 M04 4.3 5 LNU04000000 2007 M05 4.3 6 LNU04000000 2007 M06 4.7
```

```
tail(df)
```

```
Series.id Year Period Value
```

```
116 LNU04000000 2016 M08 5.0 117 LNU04000000 2016 M09 4.8 118 LNU04000000 2016 M10 4.7
119 LNU04000000 2016 M11 4.4 120 LNU04000000 2016 M12 4.5 121 LNU04000000 2017 M01 5.1
```

```
table(df$Series.id, useNA = "always")
```

```
LNU04000000 121 0
```

```
table(df$Period, useNA = "always")
```

```
M01 M02 M03 M04 M05 M06 M07 M08 M09 M10 M11 M12 11 10 10 10 10 10 10 10 10 10 10 0
```

```
# Convert a column of the data frame into a time-series object
```

```
unemp <- ts(df$Value, start = c(2007,1), end = c(2017,1), frequency = 12)
str(unemp)
```

```
Time-Series [1:121] from 2007 to 2017: 5 4.9 4.5 4.3 4.3 4.7 4.9 4.6 4.5 4.4 ...
```

```
head(cbind(time(unemp), unemp), 5)
```

```
time(unemp) unemp
```

```
Jan 2007 2007.000 5.0 Feb 2007 2007.083 4.9 Mar 2007 2007.167 4.5 Apr 2007 2007.250 4.3 May
2007 2007.333 4.3
```

```
# Now, let's convert it to an xts object
```

```
df_matrix <- as.matrix(df)
head(df_matrix)
```

```
Series.id Year Period Value
```

```
[1,] "LNU04000000" "2007" "M01" " 5.0" [2,] "LNU04000000" "2007" "M02" " 4.9" [3,]
"LNU04000000" "2007" "M03" " 4.5" [4,] "LNU04000000" "2007" "M04" " 4.3" [5,] "LNU04000000"
"2007" "M05" " 4.3" [6,] "LNU04000000" "2007" "M06" " 4.7"
```

```
str(df_matrix)
```

```
chr [1:121, 1:4] "LNU04000000" "LNU04000000" "LNU04000000" ... - attr(*, "dimnames")=List of
2 ..$ : NULL ..$ : chr [1:4] "Series.id" "Year" "Period" "Value"
```

```
rownames(df)
```

```
[1] "1" "2" "3" "4" "5" "6" "7" "8" "9" "10" "11" [12] "12" "13" "14" "15" "16" "17" "18" "19"
"20" "21" "22" [23] "23" "24" "25" "26" "27" "28" "29" "30" "31" "32" "33" [34] "34" "35" "36"
"37" "38" "39" "40" "41" "42" "43" "44" [45] "45" "46" "47" "48" "49" "50" "51" "52" "53" "54"
```

```
"55" [56] "56" "57" "58" "59" "60" "61" "62" "63" "64" "65" "66" [67] "67" "68" "69" "70" "71"
"72" "73" "74" "75" "76" "77" [78] "78" "79" "80" "81" "82" "83" "84" "85" "86" "87" "88" [89]
"89" "90" "91" "92" "93" "94" "95" "96" "97" "98" "99" [100] "100" "101" "102" "103" "104" "105"
"106" "107" "108" "109" "110" [111] "111" "112" "113" "114" "115" "116" "117" "118" "119" "120"
"121"
```

```
unemp_idx <- seq(as.Date("2007/1/1"), by = "month", length.out =
length(df[,1]))
head(unemp_idx)
```

```
[1] "2007-01-01" "2007-02-01" "2007-03-01" "2007-04-01" "2007-05-01" [6] "2007-06-01"
```

```
unemp_xts <- xts(df$Value, order.by = unemp_idx)
str(unemp_xts)
```

An 'xts' object on 2007-01-01/2017-01-01 containing: Data: num [1:121, 1] 5 4.9 4.5 4.3 4.3 4.7 4.9 4.6 4.5 4.4 ... Indexed by objects of class: [Date] TZ: UTC xts Attributes: NULL

```
head(unemp_xts)
```

```
[,1]
```

```
2007-01-01 5.0 2007-02-01 4.9 2007-03-01 4.5 2007-04-01 4.3 2007-05-01 4.3 2007-06-01 4.7
```

Task 3:

1. Read A. Section 3.2 of "xts: Extensible Time Series" by Jeffrey A. Ryan and Joshua M. Ulrich
2. Follow the following section of this document

Merging and modifying time series

One of the key strengths of `xts` is that it is easy to join data by column and row using a only few different functions. It makes creating time series datasets almost effortless.

The important criterion is that the `xts` objects must be of identical type (e.g. integer + integer), or be POSIXct dates vector, or be atomic vectors of the same type (e.g. numeric), or be a single NA. It does not work on data.frames with various column types.

The major functions is `merge`. It works like `cbind` or SQL's join:

Let's look at an example. It assumes that you are familiar with concepts of inner join, outer join, left join, and right join.

```
library(quantmod)
```

```
## Loading required package: TTR
```

```
## Version 0.4-0 included new data defaults. See ?getSymbols.
```

```
getSymbols("TWTR")
```

```
## 'getSymbols' currently uses auto.assign=TRUE by default, but will
## use auto.assign=FALSE in 0.5-0. You will still be able to use
## 'loadSymbols' to automatically load data. getOption("getSymbols.env")
## and getOption("getSymbols.auto.assign") will still be checked for
## alternate defaults.
##
## This message is shown once per session and may be disabled by setting
## options("getSymbols.warning4.0"=FALSE). See ?getSymbols for details.
##
## WARNING: There have been significant changes to Yahoo Finance data.
## Please see the Warning section of '?getSymbols.yahoo' for details.
##
## This message is shown once per session and may be disabled by setting
## options("getSymbols.yahoo.warning"=FALSE).
```

```
[1] "TWTR"
```

```
head(TWTR)
```

```
      TWTR.Open TWTR.High TWTR.Low TWTR.Close TWTR.Volume
2013-11-07 45.10 50.09 44.00 44.90 117701600 2013-11-08 45.93 46.94 40.69 41.65 27925300 2013-11-
11 40.50 43.00 39.40 42.90 16113900 2013-11-12 43.66 43.78 41.83 41.90 6316700 2013-11-13 41.03
42.87 40.76 42.60 8688300 2013-11-14 42.34 45.67 42.24 44.69 11099400 TWTR.Adjusted 2013-11-07
44.90 2013-11-08 41.65 2013-11-11 42.90 2013-11-12 41.90 2013-11-13 42.60 2013-11-14 44.69
```

```
str(TWTR)
```

```
An 'xts' object on 2013-11-07/2018-11-16 containing: Data: num [1:1267, 1:6] 45.1 45.9 40.5 43.7
41 ... - attr(*, "dimnames")=List of 2 ..$ : NULL ..$ : chr [1:6] "TWTR.Open" "TWTR.High"
"TWTR.Low" "TWTR.Close" ... Indexed by objects of class: [Date] TZ: UTC xts Attributes:
List of 2 $ src : chr "yahoo" $ updated: POSIXct[1:1], format: "2018-11-19 12:49:16"
```

Note that the date obtained from the `getSymbols` function of the `quantmod` library is already an `xts` object. As such, we can merge it directly with our unemployment rate `xts` object constructed above. Nevertheless, it is instructive to examine the data using the `View()` function to ensure that you understand the number of observations resulting from the joined series.

```
# 1. Inner join
```

```
TWTR_unemp01 <- merge(unemp_xts, TWTR, join = "inner")
str(TWTR_unemp01)
```

```
An 'xts' object on 2014-04-01/2016-12-01 containing: Data: num [1:22, 1:7] 5.9 6.1 6.5 6.3 5.5 5.4 5.1
5.3 5.5 5.6 ... - attr(*, "dimnames")=List of 2 ..$ : NULL ..$ : chr [1:7] "unemp_xts" "TWTR.Open"
"TWTR.High" "TWTR.Low" ... Indexed by objects of class: [Date] TZ: UTC xts Attributes:
NULL
```

```
head(TWTR_unemp01)
```

```
      unemp_xts TWTR.Open TWTR.High TWTR.Low TWTR.Close TWTR.Volume
2014-04-01 5.9 46.71 47.59 46.18 46.98 6916100 2014-05-01 6.1 39.01 40.77 38.97 39.09 15759800
```

```
2014-07-01 6.5 42.06 42.95 41.91 42.05 36019300 2014-08-01 6.3 45.01 45.54 43.81 44.13 37194800
2014-10-01 5.5 51.08 51.29 49.15 50.06 24733500 2014-12-01 5.4 41.29 41.29 39.00 39.04 22214000
TWTR.Adjusted 2014-04-01 46.98 2014-05-01 39.09 2014-07-01 42.05 2014-08-01 44.13 2014-10-01
50.06 2014-12-01 39.04
```

```
# 2. Outer join (filling the missing observations with 99999)
# Basic argument use
TWTR_unemp02 <- merge(unemp_xts, TWTR, join = "outer", fill = 99999)
str(TWTR_unemp02)
```

An 'xts' object on 2007-01-01/2018-11-16 containing: Data: num [1:1366, 1:7] 5 4.9 4.5 4.3 4.3 4.7 4.9 4.6 4.5 4.4 ... - attr(*, "dimnames")=List of 2 ..\$: NULL ..\$: chr [1:7] "unemp_xts" "TWTR.Open" "TWTR.High" "TWTR.Low" ... Indexed by objects of class: [Date] TZ: UTC xts
Attributes:
NULL

```
head(TWTR_unemp02)
```

```
unemp_xts TWTR.Open TWTR.High TWTR.Low TWTR.Close TWTR.Volume
2007-01-01 5.0 99999 99999 99999 99999 99999 2007-02-01 4.9 99999 99999 99999 99999 99999 2007-
03-01 4.5 99999 99999 99999 99999 99999 2007-04-01 4.3 99999 99999 99999 99999 99999 2007-05-01
4.3 99999 99999 99999 99999 99999 2007-06-01 4.7 99999 99999 99999 99999 99999 TWTR.Adjusted
2007-01-01 99999 2007-02-01 99999 2007-03-01 99999 2007-04-01 99999 2007-05-01 99999 2007-06-01
99999
```

```
#View(TWTR_unemp02)
```

```
# Left join
TWTR_unemp03 <- merge(unemp_xts, TWTR, join = "left", fill = 99999)
str(TWTR_unemp03)
```

An 'xts' object on 2007-01-01/2017-01-01 containing: Data: num [1:121, 1:7] 5 4.9 4.5 4.3 4.3 4.7 4.9 4.6 4.5 4.4 ... - attr(*, "dimnames")=List of 2 ..\$: NULL ..\$: chr [1:7] "unemp_xts" "TWTR.Open" "TWTR.High" "TWTR.Low" ... Indexed by objects of class: [Date] TZ: UTC xts Attributes:
NULL

```
head(TWTR_unemp03)
```

```
unemp_xts TWTR.Open TWTR.High TWTR.Low TWTR.Close TWTR.Volume
2007-01-01 5.0 99999 99999 99999 99999 99999 2007-02-01 4.9 99999 99999 99999 99999 99999 2007-
03-01 4.5 99999 99999 99999 99999 99999 2007-04-01 4.3 99999 99999 99999 99999 99999 2007-05-01
4.3 99999 99999 99999 99999 99999 2007-06-01 4.7 99999 99999 99999 99999 99999 TWTR.Adjusted
2007-01-01 99999 2007-02-01 99999 2007-03-01 99999 2007-04-01 99999 2007-05-01 99999 2007-06-01
99999
```

```
#View(TWTR_unemp03)
```

```
# Right join
TWTR_unemp04 <- merge(unemp_xts, TWTR, join = "right", fill = 99999)
str(TWTR_unemp04)
```

An 'xts' object on 2013-11-07/2018-11-16 containing: Data: num [1:1267, 1:7] 99999 99999 99999 99999 99999 ... - attr(*, "dimnames")=List of 2 ..\$: NULL ..\$: chr [1:7] "unemp_xts" "TWTR.Open" "TWTR.High" "TWTR.Low" ... Indexed by objects of class: [Date] TZ: UTC xts
Attributes:
NULL

```
head(TWTR_unemp04)
```

```
unemp_xts TWTR.Open TWTR.High TWTR.Low TWTR.Close TWTR.Volume
2013-11-07 99999 45.10 50.09 44.00 44.90 117701600 2013-11-08 99999 45.93 46.94 40.69 41.65
27925300 2013-11-11 99999 40.50 43.00 39.40 42.90 16113900 2013-11-12 99999 43.66 43.78 41.83
41.90 6316700 2013-11-13 99999 41.03 42.87 40.76 42.60 8688300 2013-11-14 99999 42.34 45.67 42.24
44.69 11099400 TWTR.Adjusted 2013-11-07 44.90 2013-11-08 41.65 2013-11-11 42.90 2013-11-12
41.90 2013-11-13 42.60 2013-11-14 44.69
```

```
#View(TWTR_unemp04)
```

Missing value imputation

xts also offers methods that allows filling missing values using last or previous observation. Note that I include this simply to point out that this is possible. I by no mean certify that this is the preferred method of imputing missing values in a time series. As I mentioned in live session, the specific method to use in missing value imputation is completely context dependent.

Filling missing values from the last observation

```
# First, let's replace the "99999" values with NA and then examine the series.
```

```
# Let's examine the first few dozen observations with NA
```

```
TWTR_unemp02['2013-10-01/2013-12-15'][,1]
```

```
unemp_xts
```

```
2013-10-01 7.0 2013-11-01 6.6 2013-11-07 99999.0 2013-11-08 99999.0 2013-11-11 99999.0 2013-11-12
99999.0 2013-11-13 99999.0 2013-11-14 99999.0 2013-11-15 99999.0 2013-11-18 99999.0 2013-11-19
99999.0 2013-11-20 99999.0 2013-11-21 99999.0 2013-11-22 99999.0 2013-11-25 99999.0 2013-11-
26 99999.0 2013-11-27 99999.0 2013-11-29 99999.0 2013-12-01 6.5 2013-12-02 99999.0 2013-12-03
99999.0 2013-12-04 99999.0 2013-12-05 99999.0 2013-12-06 99999.0 2013-12-09 99999.0 2013-12-10
99999.0 2013-12-11 99999.0 2013-12-12 99999.0 2013-12-13 99999.0
```

```
# Replace observations with "99999" with NA and store in a new series
```

```
unemp01 <- TWTR_unemp02[, 1]
```

```
unemp01['2013-10-01/2013-12-15']
```

```
unemp_xts
```

```
2013-10-01 7.0 2013-11-01 6.6 2013-11-07 99999.0 2013-11-08 99999.0 2013-11-11 99999.0 2013-11-12
99999.0 2013-11-13 99999.0 2013-11-14 99999.0 2013-11-15 99999.0 2013-11-18 99999.0 2013-11-19
99999.0 2013-11-20 99999.0 2013-11-21 99999.0 2013-11-22 99999.0 2013-11-25 99999.0 2013-11-
26 99999.0 2013-11-27 99999.0 2013-11-29 99999.0 2013-12-01 6.5 2013-12-02 99999.0 2013-12-03
```

```
99999.0 2013-12-04 99999.0 2013-12-05 99999.0 2013-12-06 99999.0 2013-12-09 99999.0 2013-12-10
99999.0 2013-12-11 99999.0 2013-12-12 99999.0 2013-12-13 99999.0
```

```
str(unemp01)
```

An 'xts' object on 2007-01-01/2018-11-16 containing: Data: num [1:1366, 1] 5 4.9 4.5 4.3 4.3 4.7 4.9 4.6 4.5 4.4 ... - attr(*, "dimnames")=List of 2 ..\$: NULL ..\$: chr "unemp_xts" Indexed by objects of class: [Date] TZ: UTC xts Attributes: NULL

```
head(unemp01)
```

```
unemp_xts
```

```
2007-01-01 5.0 2007-02-01 4.9 2007-03-01 4.5 2007-04-01 4.3 2007-05-01 4.3 2007-06-01 4.7
```

```
#TWTR_unemp02[, 1][TWTR_unemp02[, 1] >= 99990] <- NA
```

```
unemp02 <- unemp01
```

```
unemp02[unemp02 >= 99990] <- NA
```

```
cbind(unemp01['2013-10-01/2013-12-15'], unemp02['2013-10-01/2013-12-15'])
```

```
unemp_xts unemp_xts.1
```

```
2013-10-01 7.0 7.0 2013-11-01 6.6 6.6 2013-11-07 99999.0 NA 2013-11-08 99999.0 NA 2013-11-11
99999.0 NA 2013-11-12 99999.0 NA 2013-11-13 99999.0 NA 2013-11-14 99999.0 NA 2013-11-15
99999.0 NA 2013-11-18 99999.0 NA 2013-11-19 99999.0 NA 2013-11-20 99999.0 NA 2013-11-21
99999.0 NA 2013-11-22 99999.0 NA 2013-11-25 99999.0 NA 2013-11-26 99999.0 NA 2013-11-27
99999.0 NA 2013-11-29 99999.0 NA 2013-12-01 6.5 6.5 2013-12-02 99999.0 NA 2013-12-03 99999.0
NA 2013-12-04 99999.0 NA 2013-12-05 99999.0 NA 2013-12-06 99999.0 NA 2013-12-09 99999.0 NA
2013-12-10 99999.0 NA 2013-12-11 99999.0 NA 2013-12-12 99999.0 NA 2013-12-13 99999.0 NA
```

```
# Impute the missing values (stored as NA) with the last observation
```

```
TWTR_unemp02_v2a <- na.locf(TWTR_unemp02[,1],
                             na.rm = TRUE, fromLast = TRUE)
```

```
unemp03 <- unemp02
```

```
unemp03 <- na.locf(unemp03, na.rm = TRUE, fromLast = FALSE);
```

```
# Examine the pre- and post-imputed series
```

```
cbind(TWTR_unemp02['2013-10-01/2013-12-30'][,1], TWTR_unemp02_v2a['2013-10-01/2013-12-15'])
```

```
unemp_xts unemp_xts.1
```

```
2013-10-01 7.0 7.0 2013-11-01 6.6 6.6 2013-11-07 99999.0 99999.0 2013-11-08 99999.0 99999.0 2013-
11-11 99999.0 99999.0 2013-11-12 99999.0 99999.0 2013-11-13 99999.0 99999.0 2013-11-14 99999.0
99999.0 2013-11-15 99999.0 99999.0 2013-11-18 99999.0 99999.0 2013-11-19 99999.0 99999.0 2013-
11-20 99999.0 99999.0 2013-11-21 99999.0 99999.0 2013-11-22 99999.0 99999.0 2013-11-25 99999.0
99999.0 2013-11-26 99999.0 99999.0 2013-11-27 99999.0 99999.0 2013-11-29 99999.0 99999.0 2013-12-
01 6.5 6.5 2013-12-02 99999.0 99999.0 2013-12-03 99999.0 99999.0 2013-12-04 99999.0 99999.0 2013-
12-05 99999.0 99999.0 2013-12-06 99999.0 99999.0 2013-12-09 99999.0 99999.0 2013-12-10 99999.0
99999.0 2013-12-11 99999.0 99999.0 2013-12-12 99999.0 99999.0 2013-12-13 99999.0 99999.0 2013-12-
```

```
16 99999.0 NA 2013-12-17 99999.0 NA 2013-12-18 99999.0 NA 2013-12-19 99999.0 NA 2013-12-20
99999.0 NA 2013-12-23 99999.0 NA 2013-12-24 99999.0 NA 2013-12-26 99999.0 NA 2013-12-27
99999.0 NA 2013-12-30 99999.0 NA
```

```
cbind(unemp01['2013-10-01/2013-12-15'], unemp02['2013-10-01/2013-12-15'],
unemp03['2013-10-01/2013-12-15'])
```

```
unemp_xts unemp_xts.1 unemp_xts.2
```

```
2013-10-01 7.0 7.0 7.0 2013-11-01 6.6 6.6 6.6 2013-11-07 99999.0 NA 6.6 2013-11-08 99999.0 NA
6.6 2013-11-11 99999.0 NA 6.6 2013-11-12 99999.0 NA 6.6 2013-11-13 99999.0 NA 6.6 2013-11-14
99999.0 NA 6.6 2013-11-15 99999.0 NA 6.6 2013-11-18 99999.0 NA 6.6 2013-11-19 99999.0 NA
6.6 2013-11-20 99999.0 NA 6.6 2013-11-21 99999.0 NA 6.6 2013-11-22 99999.0 NA 6.6 2013-11-25
99999.0 NA 6.6 2013-11-26 99999.0 NA 6.6 2013-11-27 99999.0 NA 6.6 2013-11-29 99999.0 NA 6.6
2013-12-01 6.5 6.5 6.5 2013-12-02 99999.0 NA 6.5 2013-12-03 99999.0 NA 6.5 2013-12-04 99999.0 NA
6.5 2013-12-05 99999.0 NA 6.5 2013-12-06 99999.0 NA 6.5 2013-12-09 99999.0 NA 6.5 2013-12-10
99999.0 NA 6.5 2013-12-11 99999.0 NA 6.5 2013-12-12 99999.0 NA 6.5 2013-12-13 99999.0 NA 6.5
```

Another missing value imputation method is linear interpolation, which can also be easily done in xts objects. In the following example, we use linear interpolation to fill in the NA in between months. The result is stored in `unemp04`. Note in the following the different ways of imputing missing values.

```
unemp04 <- unemp02
unemp04['2013-10-01/2014-02-01']
```

```
unemp_xts
```

```
2013-10-01 7.0 2013-11-01 6.6 2013-11-07 NA 2013-11-08 NA 2013-11-11 NA 2013-11-12 NA 2013-
11-13 NA 2013-11-14 NA 2013-11-15 NA 2013-11-18 NA 2013-11-19 NA 2013-11-20 NA 2013-11-21
NA 2013-11-22 NA 2013-11-25 NA 2013-11-26 NA 2013-11-27 NA 2013-11-29 NA 2013-12-01 6.5
2013-12-02 NA 2013-12-03 NA 2013-12-04 NA 2013-12-05 NA 2013-12-06 NA 2013-12-09 NA 2013-
12-10 NA 2013-12-11 NA 2013-12-12 NA 2013-12-13 NA 2013-12-16 NA 2013-12-17 NA 2013-12-18
NA 2013-12-19 NA 2013-12-20 NA 2013-12-23 NA 2013-12-24 NA 2013-12-26 NA 2013-12-27 NA
2013-12-30 NA 2013-12-31 NA 2014-01-01 7.0 2014-01-02 NA 2014-01-03 NA 2014-01-06 NA 2014-
01-07 NA 2014-01-08 NA 2014-01-09 NA 2014-01-10 NA 2014-01-13 NA 2014-01-14 NA 2014-01-15
NA 2014-01-16 NA 2014-01-17 NA 2014-01-21 NA 2014-01-22 NA 2014-01-23 NA 2014-01-24 NA
2014-01-27 NA 2014-01-28 NA 2014-01-29 NA 2014-01-30 NA 2014-01-31 NA 2014-02-01 7.0
```

```
unemp04 <- na.approx(unemp04, maxgap=31)
unemp04['2013-10-01/2014-02-01']
```

```
unemp_xts
```

```
2013-10-01 7.000000 2013-11-01 6.600000 2013-11-07 6.580000 2013-11-08 6.576667 2013-11-11
6.566667 2013-11-12 6.563333 2013-11-13 6.560000 2013-11-14 6.556667 2013-11-15 6.553333
2013-11-18 6.543333 2013-11-19 6.540000 2013-11-20 6.536667 2013-11-21 6.533333 2013-11-22
6.530000 2013-11-25 6.520000 2013-11-26 6.516667 2013-11-27 6.513333 2013-11-29 6.506667
2013-12-01 6.500000 2013-12-02 6.516129 2013-12-03 6.532258 2013-12-04 6.548387 2013-12-05
6.564516 2013-12-06 6.580645 2013-12-09 6.629032 2013-12-10 6.645161 2013-12-11 6.661290
2013-12-12 6.677419 2013-12-13 6.693548 2013-12-16 6.741935 2013-12-17 6.758065 2013-12-18
6.774194 2013-12-19 6.790323 2013-12-20 6.806452 2013-12-23 6.854839 2013-12-24 6.870968
```



```
2013-12-26 6.903226 2013-12-27 6.919355 2013-12-30 6.967742 2013-12-31 6.983871 2014-01-01
7.000000 2014-01-02 7.000000 2014-01-03 7.000000 2014-01-06 7.000000 2014-01-07 7.000000
2014-01-08 7.000000 2014-01-09 7.000000 2014-01-10 7.000000 2014-01-13 7.000000 2014-01-14
7.000000 2014-01-15 7.000000 2014-01-16 7.000000 2014-01-17 7.000000 2014-01-21 7.000000
2014-01-22 7.000000 2014-01-23 7.000000 2014-01-24 7.000000 2014-01-27 7.000000 2014-01-28
7.000000 2014-01-29 7.000000 2014-01-30 7.000000 2014-01-31 7.000000 2014-02-01 7.000000
```

```
round(cbind(unemp01['2013-10-01/2013-12-15'], unemp02['2013-10-01/2013-12-15'],
unemp03['2013-10-01/2013-12-15'],
unemp04['2013-10-01/2013-12-15']),2)
```

```
unemp_xts unemp_xts.1 unemp_xts.2 unemp_xts.3
```

```
2013-10-01 7.0 7.0 7.0 7.00 2013-11-01 6.6 6.6 6.6 6.60 2013-11-07 99999.0 NA 6.6 6.58 2013-11-08
99999.0 NA 6.6 6.58 2013-11-11 99999.0 NA 6.6 6.57 2013-11-12 99999.0 NA 6.6 6.56 2013-11-13
99999.0 NA 6.6 6.56 2013-11-14 99999.0 NA 6.6 6.56 2013-11-15 99999.0 NA 6.6 6.55 2013-11-18
99999.0 NA 6.6 6.54 2013-11-19 99999.0 NA 6.6 6.54 2013-11-20 99999.0 NA 6.6 6.54 2013-11-21
99999.0 NA 6.6 6.53 2013-11-22 99999.0 NA 6.6 6.53 2013-11-25 99999.0 NA 6.6 6.52 2013-11-26
99999.0 NA 6.6 6.52 2013-11-27 99999.0 NA 6.6 6.51 2013-11-29 99999.0 NA 6.6 6.51 2013-12-01
6.5 6.5 6.5 6.50 2013-12-02 99999.0 NA 6.5 6.52 2013-12-03 99999.0 NA 6.5 6.53 2013-12-04 99999.0
NA 6.5 6.55 2013-12-05 99999.0 NA 6.5 6.56 2013-12-06 99999.0 NA 6.5 6.58 2013-12-09 99999.0
NA 6.5 6.63 2013-12-10 99999.0 NA 6.5 6.65 2013-12-11 99999.0 NA 6.5 6.66 2013-12-12 99999.0
NA 6.5 6.68 2013-12-13 99999.0 NA 6.5 6.69
```

Calculate difference in time series

A very common operation on time series is to take a difference of the series to transform a non-stationary series to a stationary series. First order differencing takes the form $x(t) - x(t - k)$ where k denotes the number of time lags. Higher order differences are simply the reapplication of a difference to each prior result (like a second derivative or a difference of the difference).

Let's use the `unemp_xts` series as examples:

```
str(unemp_xts)
```

```
An 'xts' object on 2007-01-01/2017-01-01 containing: Data: num [1:121, 1] 5 4.9 4.5 4.3 4.3 4.7 4.9
4.6 4.5 4.4 ... Indexed by objects of class: [Date] TZ: UTC xts Attributes:
NULL
```

```
unemp_xts
```

```
[,1]
```

```
2007-01-01 5.0 2007-02-01 4.9 2007-03-01 4.5 2007-04-01 4.3 2007-05-01 4.3 2007-06-01 4.7 2007-07-
01 4.9 2007-08-01 4.6 2007-09-01 4.5 2007-10-01 4.4 2007-11-01 4.5 2007-12-01 4.8 2008-01-01 5.4
2008-02-01 5.2 2008-03-01 5.2 2008-04-01 4.8 2008-05-01 5.2 2008-06-01 5.7 2008-07-01 6.0 2008-08-
01 6.1 2008-09-01 6.0 2008-10-01 6.1 2008-11-01 6.5 2008-12-01 7.1 2009-01-01 8.5 2009-02-01 8.9
2009-03-01 9.0 2009-04-01 8.6 2009-05-01 9.1 2009-06-01 9.7 2009-07-01 9.7 2009-08-01 9.6 2009-09-
01 9.5 2009-10-01 9.5 2009-11-01 9.4 2009-12-01 9.7 2010-01-01 10.6 2010-02-01 10.4 2010-03-01 10.2
2010-04-01 9.5 2010-05-01 9.3 2010-06-01 9.6 2010-07-01 9.7 2010-08-01 9.5 2010-09-01 9.2 2010-10-
01 9.0 2010-11-01 9.3 2010-12-01 9.1 2011-01-01 9.8 2011-02-01 9.5 2011-03-01 9.2 2011-04-01 8.7
```

2011-05-01 8.7 2011-06-01 9.3 2011-07-01 9.3 2011-08-01 9.1 2011-09-01 8.8 2011-10-01 8.5 2011-11-01 8.2 2011-12-01 8.3 2012-01-01 8.8 2012-02-01 8.7 2012-03-01 8.4 2012-04-01 7.7 2012-05-01 7.9 2012-06-01 8.4 2012-07-01 8.6 2012-08-01 8.2 2012-09-01 7.6 2012-10-01 7.5 2012-11-01 7.4 2012-12-01 7.6 2013-01-01 8.5 2013-02-01 8.1 2013-03-01 7.6 2013-04-01 7.1 2013-05-01 7.3 2013-06-01 7.8 2013-07-01 7.7 2013-08-01 7.3 2013-09-01 7.0 2013-10-01 7.0 2013-11-01 6.6 2013-12-01 6.5 2014-01-01 7.0 2014-02-01 7.0 2014-03-01 6.8 2014-04-01 5.9 2014-05-01 6.1 2014-06-01 6.3 2014-07-01 6.5 2014-08-01 6.3 2014-09-01 5.7 2014-10-01 5.5 2014-11-01 5.5 2014-12-01 5.4 2015-01-01 6.1 2015-02-01 5.8 2015-03-01 5.6 2015-04-01 5.1 2015-05-01 5.3 2015-06-01 5.5 2015-07-01 5.6 2015-08-01 5.2 2015-09-01 4.9 2015-10-01 4.8 2015-11-01 4.8 2015-12-01 4.8 2016-01-01 5.3 2016-02-01 5.2 2016-03-01 5.1 2016-04-01 4.7 2016-05-01 4.5 2016-06-01 5.1 2016-07-01 5.1 2016-08-01 5.0 2016-09-01 4.8 2016-10-01 4.7 2016-11-01 4.4 2016-12-01 4.5 2017-01-01 5.1

```
diff(unemp_xts, lag = 1, difference = 1, log = FALSE, na.pad = TRUE)
```

[,1]

2007-01-01 NA 2007-02-01 -0.1 2007-03-01 -0.4 2007-04-01 -0.2 2007-05-01 0.0 2007-06-01 0.4 2007-07-01 0.2 2007-08-01 -0.3 2007-09-01 -0.1 2007-10-01 -0.1 2007-11-01 0.1 2007-12-01 0.3 2008-01-01 0.6 2008-02-01 -0.2 2008-03-01 0.0 2008-04-01 -0.4 2008-05-01 0.4 2008-06-01 0.5 2008-07-01 0.3 2008-08-01 0.1 2008-09-01 -0.1 2008-10-01 0.1 2008-11-01 0.4 2008-12-01 0.6 2009-01-01 1.4 2009-02-01 0.4 2009-03-01 0.1 2009-04-01 -0.4 2009-05-01 0.5 2009-06-01 0.6 2009-07-01 0.0 2009-08-01 -0.1 2009-09-01 -0.1 2009-10-01 0.0 2009-11-01 -0.1 2009-12-01 0.3 2010-01-01 0.9 2010-02-01 -0.2 2010-03-01 -0.2 2010-04-01 -0.7 2010-05-01 -0.2 2010-06-01 0.3 2010-07-01 0.1 2010-08-01 -0.2 2010-09-01 -0.3 2010-10-01 -0.2 2010-11-01 0.3 2010-12-01 -0.2 2011-01-01 0.7 2011-02-01 -0.3 2011-03-01 -0.3 2011-04-01 -0.5 2011-05-01 0.0 2011-06-01 0.6 2011-07-01 0.0 2011-08-01 -0.2 2011-09-01 -0.3 2011-10-01 -0.3 2011-11-01 -0.3 2011-12-01 0.1 2012-01-01 0.5 2012-02-01 -0.1 2012-03-01 -0.3 2012-04-01 -0.7 2012-05-01 0.2 2012-06-01 0.5 2012-07-01 0.2 2012-08-01 -0.4 2012-09-01 -0.6 2012-10-01 -0.1 2012-11-01 -0.1 2012-12-01 0.2 2013-01-01 0.9 2013-02-01 -0.4 2013-03-01 -0.5 2013-04-01 -0.5 2013-05-01 0.2 2013-06-01 0.5 2013-07-01 -0.1 2013-08-01 -0.4 2013-09-01 -0.3 2013-10-01 0.0 2013-11-01 -0.4 2013-12-01 -0.1 2014-01-01 0.5 2014-02-01 0.0 2014-03-01 -0.2 2014-04-01 -0.9 2014-05-01 0.2 2014-06-01 0.2 2014-07-01 0.2 2014-08-01 -0.2 2014-09-01 -0.6 2014-10-01 -0.2 2014-11-01 0.0 2014-12-01 -0.1 2015-01-01 0.7 2015-02-01 -0.3 2015-03-01 -0.2 2015-04-01 -0.5 2015-05-01 0.2 2015-06-01 0.2 2015-07-01 0.1 2015-08-01 -0.4 2015-09-01 -0.3 2015-10-01 -0.1 2015-11-01 0.0 2015-12-01 0.0 2016-01-01 0.5 2016-02-01 -0.1 2016-03-01 -0.1 2016-04-01 -0.4 2016-05-01 -0.2 2016-06-01 0.6 2016-07-01 0.0 2016-08-01 -0.1 2016-09-01 -0.2 2016-10-01 -0.1 2016-11-01 -0.3 2016-12-01 0.1 2017-01-01 0.6

```
# calculate the first difference of AirPass using lag and subtraction
#AirPass - lag(AirPass, k = 1)

# calculate the first order 12-month difference if AirPass
diff(unemp_xts, lag = 12, differences = 1)
```

[,1]

2007-01-01 NA 2007-02-01 NA 2007-03-01 NA 2007-04-01 NA 2007-05-01 NA 2007-06-01 NA 2007-07-01 NA 2007-08-01 NA 2007-09-01 NA 2007-10-01 NA 2007-11-01 NA 2007-12-01 NA 2008-01-01 0.4 2008-02-01 0.3 2008-03-01 0.7 2008-04-01 0.5 2008-05-01 0.9 2008-06-01 1.0 2008-07-01 1.1 2008-08-01 1.5 2008-09-01 1.5 2008-10-01 1.7 2008-11-01 2.0 2008-12-01 2.3 2009-01-01 3.1 2009-02-01 3.7 2009-03-01 3.8 2009-04-01 3.8 2009-05-01 3.9 2009-06-01 4.0 2009-07-01 3.7 2009-08-01 3.5 2009-09-

01 3.5 2009-10-01 3.4 2009-11-01 2.9 2009-12-01 2.6 2010-01-01 2.1 2010-02-01 1.5 2010-03-01 1.2 2010-04-01 0.9 2010-05-01 0.2 2010-06-01 -0.1 2010-07-01 0.0 2010-08-01 -0.1 2010-09-01 -0.3 2010-10-01 -0.5 2010-11-01 -0.1 2010-12-01 -0.6 2011-01-01 -0.8 2011-02-01 -0.9 2011-03-01 -1.0 2011-04-01 -0.8 2011-05-01 -0.6 2011-06-01 -0.3 2011-07-01 -0.4 2011-08-01 -0.4 2011-09-01 -0.4 2011-10-01 -0.5 2011-11-01 -1.1 2011-12-01 -0.8 2012-01-01 -1.0 2012-02-01 -0.8 2012-03-01 -0.8 2012-04-01 -1.0 2012-05-01 -0.8 2012-06-01 -0.9 2012-07-01 -0.7 2012-08-01 -0.9 2012-09-01 -1.2 2012-10-01 -1.0 2012-11-01 -0.8 2012-12-01 -0.7 2013-01-01 -0.3 2013-02-01 -0.6 2013-03-01 -0.8 2013-04-01 -0.6 2013-05-01 -0.6 2013-06-01 -0.6 2013-07-01 -0.9 2013-08-01 -0.9 2013-09-01 -0.6 2013-10-01 -0.5 2013-11-01 -0.8 2013-12-01 -1.1 2014-01-01 -1.5 2014-02-01 -1.1 2014-03-01 -0.8 2014-04-01 -1.2 2014-05-01 -1.2 2014-06-01 -1.5 2014-07-01 -1.2 2014-08-01 -1.0 2014-09-01 -1.3 2014-10-01 -1.5 2014-11-01 -1.1 2014-12-01 -1.1 2015-01-01 -0.9 2015-02-01 -1.2 2015-03-01 -1.2 2015-04-01 -0.8 2015-05-01 -0.8 2015-06-01 -0.8 2015-07-01 -0.9 2015-08-01 -1.1 2015-09-01 -0.8 2015-10-01 -0.7 2015-11-01 -0.7 2015-12-01 -0.6 2016-01-01 -0.8 2016-02-01 -0.6 2016-03-01 -0.5 2016-04-01 -0.4 2016-05-01 -0.8 2016-06-01 -0.4 2016-07-01 -0.5 2016-08-01 -0.2 2016-09-01 -0.1 2016-10-01 -0.1 2016-11-01 -0.4 2016-12-01 -0.3 2017-01-01 -0.2

Task 4:

1. Read A. Section 3.4 of “xts: Extensible Time Series” by Jeffrey A. Ryan and Joshua M. Ulrich
B. the following questions in “xts FAQ” a. I am using `apply()` to run a custom function on my xts series. Why the returned matrix has different dimensions than the original one?
2. Follow the following two sections of this document

Apply various functions to time series

The family of `apply` functions perhaps is one of the most powerful R function families. In time series, `xts` provides `period.apply`, which takes (1) a time series, (2) an index of endpoints, and (3) a function to apply. It takes the following general form:

```
period.apply(x, INDEX, FUN, ...)
```

As an example, we use the Twitter stock price series (to be precise, the daily closing price), create an index storing the points corresponding to the weeks of the daily series, and apply functions to calculate the weekly mean.

Step 1: Identify the endpoints; in this case, we use weekly time interval. That is, we extract

```
#View(TWTR)
head(TWTR)
```

```
TWTR.Open TWTR.High TWTR.Low TWTR.Close TWTR.Volume
```

```
2013-11-07 45.10 50.09 44.00 44.90 117701600 2013-11-08 45.93 46.94 40.69 41.65 27925300 2013-11-11 40.50 43.00 39.40 42.90 16113900 2013-11-12 43.66 43.78 41.83 41.90 6316700 2013-11-13 41.03 42.87 40.76 42.60 8688300 2013-11-14 42.34 45.67 42.24 44.69 11099400 TWTR.Adjusted 2013-11-07 44.90 2013-11-08 41.65 2013-11-11 42.90 2013-11-12 41.90 2013-11-13 42.60 2013-11-14 44.69
```

```
TWTR_ep <- endpoints(TWTR[,4], on = "weeks")
#TWTR_ep
```

Step 2: Calculate the weekly mean

```
TWTR.Close_weeklyMean <- period.apply(TWTR[, 4], INDEX = TWTR_ep, FUN = mean)
head(round(TWTR.Close_weeklyMean,2),8)
```

TWTR.Close

```
2013-11-08 43.28 2013-11-15 43.21 2013-11-22 41.40 2013-11-29 40.43 2013-12-06 43.28 2013-12-13
53.56 2013-12-20 57.21 2013-12-27 67.89
```

The power of the apply function really comes with the use of custom-defined function. For instance, we can easily

```
f <- function(x) {
  mean <- mean(x)
  quantile <- quantile(x,c(0.05,0.25,0.50,0.75,0.95))
  sd <- sd(x)

  result <- c(mean, sd, quantile)
  return(result)
}
head(round(period.apply(TWTR[, 4], INDEX = TWTR_ep, FUN = f),2),10)
```

```
          5%    25%    50%    75%    95%
2013-11-08 43.28 2.30 41.81 42.46 43.28 44.09 44.74 2013-11-15 43.21 1.11 42.04 42.60 42.90 43.98
44.55 2013-11-22 41.40 0.48 41.01 41.05 41.14 41.75 42.00 2013-11-29 40.43 1.07 39.23 39.90 40.54
41.07 41.47 2013-12-06 43.28 2.14 40.90 41.37 43.69 44.95 45.49 2013-12-13 53.56 3.75 49.71 51.99
52.34 55.33 58.27 2013-12-20 57.21 1.71 55.70 56.45 56.61 57.49 59.51 2013-12-27 67.89 4.55 63.87
64.34 67.25 70.80 72.81 2014-01-03 65.17 3.84 60.98 62.87 65.58 67.88 68.78 2014-01-10 60.22 3.86
57.01 57.05 59.29 61.46 65.32
```

Calculate basic rolling statistics of series by month

Using rollapply, one can calculate rolling statistics of a series:

```
# Calculate rolling mean over a 10-day period and print it with the original series
head(cbind(TWTR[,4], rollapply(TWTR[, 4], 10, FUN = mean, na.rm = TRUE)),15)
```

TWTR.Close TWTR.Close.1

```
2013-11-07 44.90 NA 2013-11-08 41.65 NA 2013-11-11 42.90 NA 2013-11-12 41.90 NA 2013-11-13
42.60 NA 2013-11-14 44.69 NA 2013-11-15 43.98 NA 2013-11-18 41.14 NA 2013-11-19 41.75 NA
2013-11-20 41.05 42.656 2013-11-21 42.06 42.372 2013-11-22 41.00 42.307 2013-11-25 39.06 41.923
2013-11-26 40.18 41.751 2013-11-27 40.90 41.581
```

Task 5:

1. Read AMAZ.csv and UMCSENT.csv into R as R DataFrames

```
library(xts)
amaz <- read.csv('AMAZ.csv')
```

```
umcsent <- read.csv('UMCSENT.csv')
```

```
head(amaz)
```

```
      Index AMAZ.Open AMAZ.High AMAZ.Low AMAZ.Close AMAZ.Volume
1 2007-01-03 20.0 20.0 16.0 16.0 650 2 2007-01-04 20.0 20.0 20.0 20.0 67 3 2007-01-08 19.2 22.0 19.2
22.0 1801 4 2007-01-09 22.0 22.0 20.8 20.8 356 5 2007-01-10 20.8 20.8 20.8 20.8 438 6 2007-01-11
20.8 21.6 20.8 21.6 2318
```

```
tail(amaz)
```

```
      Index AMAZ.Open AMAZ.High AMAZ.Low AMAZ.Close AMAZ.Volume
1174 2013-01-04 0.88 0.88 0.80 0.80 3850 1175 2013-01-07 0.80 1.00 0.80 1.00 2715 1176 2013-01-08
0.80 0.80 0.68 0.68 4668 1177 2013-01-09 0.88 0.88 0.80 0.80 2750 1178 2013-01-11 0.80 0.80 0.80
0.80 3000 1179 2013-01-15 0.68 0.68 0.68 0.68 1000
```

```
length(amaz[Index])
```

```
[1] 1179
```

```
head(umcsent)
```

```
      Index UMCSENT
1 1978-01-01 83.7 2 1978-02-01 84.3 3 1978-03-01 78.8 4 1978-04-01 81.6 5 1978-05-01 82.9 6 1978-
06-01 80.0
```

```
tail(umcsent)
```

```
      Index UMCSENT
472 2017-04-01 97.0 473 2017-05-01 97.1 474 2017-06-01 95.1 475 2017-07-01 93.4 476 2017-08-01
96.8 477 2017-09-01 95.1
```

```
length(umcsent[Index])
```

```
[1] 477
```

2. Convert them to xts objects

```
amaz.xts <- as.xts(amaz[,2:6],order.by=as.Date(amaz[Index],format="%Y-%m-%d"))
```

```
head(amaz.xts)
```

```
      AMAZ.Open AMAZ.High AMAZ.Low AMAZ.Close AMAZ.Volume
2007-01-03 20.0 20.0 16.0 16.0 650 2007-01-04 20.0 20.0 20.0 20.0 67 2007-01-08 19.2 22.0 19.2 22.0
1801 2007-01-09 22.0 22.0 20.8 20.8 356 2007-01-10 20.8 20.8 20.8 20.8 438 2007-01-11 20.8 21.6
20.8 21.6 2318
```

```
tail(amaz.xts)
```

```
      AMAZ.Open AMAZ.High AMAZ.Low AMAZ.Close AMAZ.Volume
```

```
2013-01-04 0.88 0.88 0.80 0.80 3850 2013-01-07 0.80 1.00 0.80 1.00 2715 2013-01-08 0.80 0.80 0.68
0.68 4668 2013-01-09 0.88 0.88 0.80 0.80 2750 2013-01-11 0.80 0.80 0.80 0.80 3000 2013-01-15 0.68
0.68 0.68 0.68 1000
```

```
umcsent.xts <- as.xts(umcsent[,2], order.by=as.Date(umcsent$Index, format="%Y-%d-%m"))
colnames(umcsent.xts)=c('umcsent')
```

```
head(umcsent.xts)
```

```
umcsent
```

```
1978-01-01 83.7 1978-01-02 84.3 1978-01-03 78.8 1978-01-04 81.6 1978-01-05 82.9 1978-01-06 80.0
```

```
tail(umcsent.xts)
```

```
umcsent
```

```
2017-01-04 97.0 2017-01-05 97.1 2017-01-06 95.1 2017-01-07 93.4 2017-01-08 96.8 2017-01-09 95.1
```

It is important to note here that the `amaz.xts` has a shorter duration and span than the `umcsent.xts` series. However, the `amaz.xts` series has more observations than `umcsent.xts`.

3. Merge the two set of series together, perserving all of the observations in both set of series

```
merged <- merge(amaz.xts, umcsent.xts, join="outer")
head(merged)
```

```
AMAZ.Open AMAZ.High AMAZ.Low AMAZ.Close AMAZ.Volume umcsent
```

```
1978-01-01 NA NA NA NA NA 83.7 1978-01-02 NA NA NA NA NA 84.3 1978-01-03 NA NA NA
NA NA 78.8 1978-01-04 NA NA NA NA NA 81.6 1978-01-05 NA NA NA NA NA 82.9 1978-01-06
NA NA NA NA NA 80.0
```

```
tail(merged)
```

```
AMAZ.Open AMAZ.High AMAZ.Low AMAZ.Close AMAZ.Volume umcsent
```

```
2017-01-04 NA NA NA NA NA 97.0 2017-01-05 NA NA NA NA NA 97.1 2017-01-06 NA NA NA
NA NA 95.1 2017-01-07 NA NA NA NA NA 93.4 2017-01-08 NA NA NA NA NA 96.8 2017-01-09
NA NA NA NA NA 95.1
```

```
dim(merged)
```

```
[1] 1610 6
```

- a. fill all of the missing values of the `UMCSENT` series with `-9999`

```
umcsent01=merged
head(umcsent01)
```

```
AMAZ.Open AMAZ.High AMAZ.Low AMAZ.Close AMAZ.Volume umcsent
```

```
1978-01-01 NA NA NA NA NA 83.7 1978-01-02 NA NA NA NA NA 84.3 1978-01-03 NA NA NA
NA NA 78.8 1978-01-04 NA NA NA NA NA 81.6 1978-01-05 NA NA NA NA NA 82.9 1978-01-06
NA NA NA NA NA 80.0
```

```
umcsent01=na.fill(umcsent01,-9999)
head(umcsent01)
```

```
AMAZ.Open AMAZ.High AMAZ.Low AMAZ.Close AMAZ.Volume umcsent
1978-01-01 -9999 -9999 -9999 -9999 -9999 83.7 1978-01-02 -9999 -9999 -9999 -9999 -9999 84.3 1978-
01-03 -9999 -9999 -9999 -9999 -9999 78.8 1978-01-04 -9999 -9999 -9999 -9999 -9999 81.6 1978-01-05
-9999 -9999 -9999 -9999 -9999 82.9 1978-01-06 -9999 -9999 -9999 -9999 -9999 80.0
```

b. then create a new series, named UMCSSENT02, from the original UMCSSENT series replace all of

```
umcsent02 <- umcsent01
head(umcsent02)
```

```
AMAZ.Open AMAZ.High AMAZ.Low AMAZ.Close AMAZ.Volume umcsent
1978-01-01 -9999 -9999 -9999 -9999 -9999 83.7 1978-01-02 -9999 -9999 -9999 -9999 -9999 84.3 1978-
01-03 -9999 -9999 -9999 -9999 -9999 78.8 1978-01-04 -9999 -9999 -9999 -9999 -9999 81.6 1978-01-05
-9999 -9999 -9999 -9999 -9999 82.9 1978-01-06 -9999 -9999 -9999 -9999 -9999 80.0
```

```
umcsent02[umcsent02 <= -9999 ] <- NA
head(umcsent02)
```

```
AMAZ.Open AMAZ.High AMAZ.Low AMAZ.Close AMAZ.Volume umcsent
1978-01-01 NA NA NA NA NA 83.7 1978-01-02 NA NA NA NA NA 84.3 1978-01-03 NA NA NA
NA NA 78.8 1978-01-04 NA NA NA NA NA 81.6 1978-01-05 NA NA NA NA NA 82.9 1978-01-06
NA NA NA NA NA 80.0
```

c. then create a new series, named UMCSSENT03, and replace the NAs with the last observation

```
umcsent03=umcsent02
head(umcsent03)
```

```
AMAZ.Open AMAZ.High AMAZ.Low AMAZ.Close AMAZ.Volume umcsent
1978-01-01 NA NA NA NA NA 83.7 1978-01-02 NA NA NA NA NA 84.3 1978-01-03 NA NA NA
NA NA 78.8 1978-01-04 NA NA NA NA NA 81.6 1978-01-05 NA NA NA NA NA 82.9 1978-01-06
NA NA NA NA NA 80.0
```

```
umcsent03 <- na.locf(umcsent02, na.rm = TRUE, fromLast = TRUE)
head(umcsent03)
```

```
AMAZ.Open AMAZ.High AMAZ.Low AMAZ.Close AMAZ.Volume umcsent
1978-01-01 20 20 16 16 650 83.7 1978-01-02 20 20 16 16 650 84.3 1978-01-03 20 20 16 16 650 78.8
1978-01-04 20 20 16 16 650 81.6 1978-01-05 20 20 16 16 650 82.9 1978-01-06 20 20 16 16 650 80.0
```

d. then create a new series, named UMCSSENT04, and replace the NAs using linear interpolation.

```
umcsent04=umcsent02
head(umcsent04)
```

```
AMAZ.Open AMAZ.High AMAZ.Low AMAZ.Close AMAZ.Volume umcsent
```

```
1978-01-01 NA NA NA NA NA 83.7 1978-01-02 NA NA NA NA NA 84.3 1978-01-03 NA NA NA
NA NA 78.8 1978-01-04 NA NA NA NA NA 81.6 1978-01-05 NA NA NA NA NA 82.9 1978-01-06
NA NA NA NA NA 80.0
```

```
head(umcsent04['2007-01',],15)
```

```
      AMAZ.Open AMAZ.High AMAZ.Low AMAZ.Close AMAZ.Volume umcsent
2007-01-01 NA NA NA NA NA 96.9 2007-01-02 NA NA NA NA NA 91.3 2007-01-03 20.0 20.0 16.0
16.0 650 88.4 2007-01-04 20.0 20.0 20.0 20.0 67 87.1 2007-01-05 NA NA NA NA NA 88.3 2007-01-06
NA NA NA NA NA 85.3 2007-01-07 NA NA NA NA NA 90.4 2007-01-08 19.2 22.0 19.2 22.0 1801
83.4 2007-01-09 22.0 22.0 20.8 20.8 356 83.4 2007-01-10 20.8 20.8 20.8 20.8 438 80.9 2007-01-11 20.8
21.6 20.8 21.6 2318 76.1 2007-01-12 22.0 22.0 22.0 22.0 306 75.5 2007-01-16 21.6 21.6 21.2 21.2 925
NA 2007-01-17 22.0 22.0 21.6 21.6 2138 NA 2007-01-22 23.2 23.2 22.8 22.8 527 NA
```

```
umcsent04=na.approx(umcsent04,maxgap=10000)
```

Note amazon has N/As in 1/1/17 and 1/2/17 because there is no data before 1/1/03 so there is

```
head(umcsent04['2007-01',],15)
```

```
      AMAZ.Open AMAZ.High AMAZ.Low AMAZ.Close AMAZ.Volume umcsent
2007-01-01 NA NA NA NA NA 96.90000 2007-01-02 NA NA NA NA NA 91.30000 2007-01-03 20.0
20.0 16.0 16.0 650.0 88.40000 2007-01-04 20.0 20.0 20.0 20.0 67.0 87.10000 2007-01-05 19.8 20.5
19.8 20.5 500.5 88.30000 2007-01-06 19.6 21.0 19.6 21.0 934.0 85.30000 2007-01-07 19.4 21.5 19.4
21.5 1367.5 90.40000 2007-01-08 19.2 22.0 19.2 22.0 1801.0 83.40000 2007-01-09 22.0 22.0 20.8 20.8
356.0 83.40000 2007-01-10 20.8 20.8 20.8 20.8 438.0 80.90000 2007-01-11 20.8 21.6 20.8 21.6 2318.0
76.10000 2007-01-12 22.0 22.0 22.0 22.0 306.0 75.50000 2007-01-16 21.6 21.6 21.2 21.2 925.0 75.53277
2007-01-17 22.0 22.0 21.6 21.6 2138.0 75.54096 2007-01-22 23.2 23.2 22.8 22.8 527.0 75.58192
```

e. Print out some observations to ensure that your merge as well as the missing value imputation

Observations to check the merge and imputation are printed in the above sections.

4. Calculate the daily return of the Amazon closing price (AMAZ.close), where daily return is defined as $(x(t) - x(t - 1))/x(t - 1)$. Plot the daily return series.

```
amaz.xts.close=amaz.xts$AMAZ.Close
head(amaz.xts.close)
```

```
      AMAZ.Close
2007-01-03 16.0 2007-01-04 20.0 2007-01-08 22.0 2007-01-09 20.8 2007-01-10 20.8 2007-01-11 21.6
```

```
head(diff(amaz.xts.close,lag=1,differences = 1,log=FALSE,na.pad=FALSE))
```

```
      AMAZ.Close
2007-01-04 4.0 2007-01-08 2.0 2007-01-09 -1.2 2007-01-10 0.0 2007-01-11 0.8 2007-01-12 0.4
head(diff(amaz.xts.close,lag=1,differences = 1,log=FALSE,na.pad=FALSE)/amaz.xts.close)
```

```
      AMAZ.Close
2007-01-04 0.20000000 2007-01-08 0.09090909 2007-01-09 -0.05769231 2007-01-10 0.00000000 2007-
01-11 0.03703704 2007-01-12 0.01818182
```



```
head(cbind(amaz.xts.close,diff(amaz.xts.close,lag=1,differences = 1,log=FALSE,na.pad=TRUE),dif
```

```
    AMAZ.Close AMAZ.Close.1 AMAZ.Close.2
```

```
2007-01-03 16.0 NA NA 2007-01-04 20.0 4.0 0.20000000 2007-01-08 22.0 2.0 0.09090909 2007-01-09
20.8 -1.2 -0.05769231 2007-01-10 20.8 0.0 0.00000000 2007-01-11 21.6 0.8 0.03703704
```

```
# another way to do it in 1 long line...
```

```
#head(diff(amaz.xts$AMAZ.Close,lag=1,differences=1,log=F,na.pad=F)/amaz.xts$AMAZ.Close)
```

5. Create a 20-day and a 50-day rolling mean series from the AMAZ.close series.

```
tail(cbind(amaz.xts.close,rollapply(amaz.xts.close,20,FUN=mean,na.rm=TRUE)),15)
```

```
    AMAZ.Close AMAZ.Close.1
```

```
2012-12-07 1.08 1.088 2012-12-10 1.20 1.092 2012-12-18 1.16 1.090 2012-12-19 0.80 1.078 2012-12-24
0.80 1.061 2012-12-26 0.60 1.031 2012-12-31 0.84 0.993 2013-01-02 1.12 0.989 2013-01-03 1.00 0.979
2013-01-04 0.80 0.969 2013-01-07 1.00 0.969 2013-01-08 0.68 0.955 2013-01-09 0.80 0.947 2013-01-11
0.80 0.939 2013-01-15 0.68 0.919
```

```
tail(cbind(amaz.xts.close,rollapply(amaz.xts.close,50,FUN=mean,na.rm=TRUE)),15)
```

```
    AMAZ.Close AMAZ.Close.1
```

```
2012-12-07 1.08 1.2096 2012-12-10 1.20 1.2056 2012-12-18 1.16 1.2128 2012-12-19 0.80 1.2068 2012-
12-24 0.80 1.2004 2012-12-26 0.60 1.1860 2012-12-31 0.84 1.1756 2013-01-02 1.12 1.1700 2013-01-03
1.00 1.1620 2013-01-04 0.80 1.1512 2013-01-07 1.00 1.1432 2013-01-08 0.68 1.1304 2013-01-09 0.80
1.1200 2013-01-11 0.80 1.1080 2013-01-15 0.68 1.0936
```