Design Rules Verification ReportFilename : C:\Users\Gaming\Documents\TeamPhantom\high_voltage\TSAL\TSAL_REV2\TSA

Warnings 0 Rule Violations 0

| Warnings | |
|----------|---|
| Total | 0 |

| Rule Violations Clearance Constraint (Gap=5mil) (All),(All) Clearance Constraint (Gap=5mil) (IsStitchingVia and InNet("HV_GND")),((IsVia and (Not IsStitchingVia)) Or IsPad) Short-Circuit Constraint (Allowed=No) (All),(All) Un-Routed Net Constraint ((All)) | 0 0 0 |
|---|-------------|
| Clearance Constraint (Gap=5mil) (IsStitchingVia and InNet('HV_GND')),((IsVia and (Not IsStitchingVia)) Or IsPad) Short-Circuit Constraint (Allowed=No) (All),(All) Un-Routed Net Constraint ((All)) | 0 0 0 |
| Short-Circuit Constraint (Allowed=No) (All),(All) Un-Routed Net Constraint ((All)) | 0 0 |
| Un-Routed Net Constraint ((All)) | 0 |
| | 0 |
| | |
| Modified Polygon (Allow modified: No), (Allow shelved: No) | 0 |
| Width Constraint (Min=7.874mil) (Max=1000mil) (Preferred=16mil) (All) | 0 |
| Power Plane Connect Rule(Relief Connect)(Expansion=11.811mil) (Conductor Width=10mil) (Air Gap=5mil) (Entries=4) | 0 |
| Power Plane Connect Rule(Direct Connect)(Expansion=20mil) (Conductor Width=10mil) (Air Gap=10mil) (Entries=4) | 0 |
| Minimum Annular Ring (Minimum=3mil) (All) | 0 |
| Hole Size Constraint (Min=11.811mil) (Max=248.031mil) (All) | 0 |
| Hole To Hole Clearance (Gap=9.842mil) (All),(All) | 0 |
| Minimum Solder Mask Sliver (Gap=0mil) (All),(All) | 0 |
| Silk To Solder Mask (Clearance=5mil) (IsPad),(All) | 0 |
| Silk to Silk (Clearance=0mil) (All),(All) | 0 |
| Net Antennae (Tolerance=0mil) (All) | 0 |
| Board Clearance Constraint (Gap=0mil) (All) | 0 |
| Height Constraint (Min=0mil) (Max=71497.938mil) (Prefered=500mil) (All) | 0 |
| Total | 0 |

Page 1 of 1 Saturday 14 Nov 2020 10:31:30 PN.