



Products

# immutable value is still being moved

[Log in](#) or [Sign up](#)

[Ask Question](#)

Asked 1 year ago

Active 10 months ago

Viewed 109 times



4



I can't get this function to compile:

```
/// Return a String with all characters masked as '#' except the last 4.
fn maskify(cc: &str) -> String {
    let chars = cc.to_string().chars();
    chars
        .enumerate()
        .map(|(i, c)| {
            if i > chars.count() - 4 { '#' } else { c }
        })
        .collect()
}
```

The current errors are:

```
error[E0507]: cannot move out of `chars`, a captured variable in an `FnMut` closure
  -> src/lib.rs:7:21
  |
3 |   let chars = cc.to_string().chars();
  |   ----- captured outer variable
...
7 |       if i > &chars.count() - 4 { '#' } else { c }
  |           ~~~~~ move occurs because `chars` has type `std::str::Chars<_>`, which does not implement the `Copy` trait

error[E0716]: temporary value dropped while borrowed
  -> src/lib.rs:3:17
  |
3 |   let chars = cc.to_string().chars();
  |   ~~~~~~ - temporary value is freed at the end of this statement
  |           |
  |           creates a temporary which is freed while still in use
4 |   chars
  |   ---- borrow later used here
  |
= note: consider using a `let` binding to create a longer lived value

error[E0382]: use of moved value: `chars`
  -> src/lib.rs:6:14
  |
3 |   let chars = cc.to_string().chars();
  |   ----- move occurs because `chars` has type `std::str::Chars<_>`, which does not implement the `Copy` trait
4 |   chars
  |   ---- value moved here
5 |       .enumerate()
6 |       .map(|(i, c)| {
  |           ~~~~~ value used here after move
7 |           if i > &chars.count() - 4 { '#' } else { c }
  |               ---- use occurs due to use in closure
```

I think the source of the error is that `chars` is an iterator, so it mutates, making it impossible to borrow in the closure, but even if I try to declare a local variable (such as `let count = chars.count()`), I still get borrow errors.

I've tried dereferencing it with `&`, but that didn't work either.

[rust](#) [closures](#) [borrow-checker](#) [ownership](#) [borrowing](#)

Share

[Improve this question](#)

[Follow](#)

edited Feb 19 at 12:26



[pretzelhammer](#)

11.7k ● 14 ● 39 ● 88

asked Dec 6 '20 at 22:44



[mzedeler](#)

3,753 ● 3 ● 22 ● 37

[Add a comment](#)

3 Answers

Your privacy [Active](#) [Oldest](#) [Votes](#)

By clicking "Accept all cookies", you agree Sack Exchange can store cookies on your device and disclose information in accordance with our [Cookie Policy](#).

[Accept all cookies](#) [Customize settings](#)

4



The crux of the issue here is that `Char.count()` consumes `self`. Even if you declare a local variable, you cannot use `chars` after you moved ownership to the `count` function:

```
fn maskify(cc: &str) {
  let chars = cc.to_string().chars();
  // ~~~~~ move occurs here
  let count = chars.count();
  // ~~~~~ 'chars' moved because 'count' consumes self
  let _ = chars.enumerate();
  // ~~~~~ value used here after move - *this is not allowed*
}
```

You can fix this issue by creating a new iterator and consuming that to get the `count`:

```
fn maskify(cc: &str) -> String {
  let chars = cc.chars();
  let count = cc.chars().count();
  // ~~~ create and consume a new iterator over cc
  chars
    .enumerate()
    .map(|(i, c)| {
      if i < count - 4 { '#' } else { c }
    })
    .collect()
}

fn main() {
  assert_eq!(maskify("abcd1234"), "####1234");
}
```

Or you can get the length of the string with `.len()`:

```
fn maskify(cc: &str) -> String {
  let chars = cc.chars();
  chars
    .enumerate()
    .map(|(i, c)| {
      if i < cc.len() - 4 { '#' } else { c }
    })
    .collect()
}

fn main() {
  assert_eq!(maskify("abcd1234"), "####1234");
}
```

Note that `str.len()` can *only* handle `ascii` while `.chars().count()` can handle full `utf8`.

[Share](#)

[Improve this answer](#)

[Follow](#)

edited Dec 7 '20 at 14:59

answered Dec 6 '20 at 22:57



[Ibraheem Ahmed](#)

6,841 ● 1 ● 19 ● 30

2

I would use `cc.chars().count()`, not `cc.len()`, to better support Unicode. (That still doesn't handle everything but it's closer.)

– [Lambda Fairy](#)

Dec 6 '20 at 23:14

Great explanation - and yes - I also noticed that `len` isn't right here, but adding another `count()` makes this work.

– [mzedeler](#)

Dec 6 '20 at 23:40

@mzedeler Why isn't `len` right? The assertion passes.

– [Ibraheem Ahmed](#)

Dec 7 '20 at 3:05

@IbraheemAhmed `.len()` is the number of bytes (UTF8 code units), `chars` works in terms of codepoints. UTF8 has 1-4 bytes per codepoint, so the code will misbehave for anything outside of `ascii` (e.g. non-latin script, diacritics, emoji, ...). For instance if you maskify "école" using `cc.len()`, you will only get 3 unmasked characters, and things get worse as you get further away from `ascii`. "■■■■■■■■■■" will have *no characters unmasked* with a bytes-based count, because it has 8 codepoints but encodes as 24 bytes.

– [Masklinn](#)

Dec 7 '20 at 7:36

1

So your final line should really be that `str.len()` *only* handles `ascii`, it's completely broken otherwise (and one could argue that it's plain broken any time you're trying to manipulate characters). If using `str.len`, the function should probably fail on getting a non-`ascii` codepoint, whether panicing entirely or just resulting in an `Err`.

– [Masklinn](#)

Dec 7 '20 at 7:47

[Show 4 more comments](#)



3



Two slightly different approaches you can use to implement this function depending on whether or not `cc` is UTF8 or ASCII. The UTF8 implementation of course works for both cases as UTF8 is a superset of ASCII.

```
fn maskify_utf8(cc: &str) -> String {
    let last_four = cc.chars().count().saturating_sub(4);
    cc.chars()
        .enumerate()
        .map((i, c) if i < last_four { '#' } else { c })
        .collect()
}

fn maskify_ascii(cc: &str) -> String {
    let mask_idx = cc.len().saturating_sub(4);
    format!("{0:#<1$} {2}", "#", mask_idx, &cc[mask_idx..])
}

fn main() {
    assert_eq!(maskify_utf8("□□□□1234"), "###1234");
    assert_eq!(maskify_utf8("abcd1234"), "###1234");
    assert_eq!(maskify_ascii("abcd1234"), "###1234");
}
```

[playground](#)

[Share](#)

[Improve this answer](#)

[Follow](#)

edited Dec 7 '20 at 0:47

answered Dec 6 '20 at 22:53



[pretzelhammer](#)

11.7k ● 14 ● 39 ● 88

[Add a comment](#)



0



Thanks to @ibraheem-ahmed, I wound up with this solution:

```
/// Return a String with all characters masked as '#' except the last 4.
fn maskify(cc: &str) -> String {
    let leading = cc.chars().count().saturating_sub(4);
    cc
        .chars()
        .enumerate()
        .map((i, c) {
            if i >= leading { c } else { '#' }
        })
        .collect()
}
```

[Share](#)

[Improve this answer](#)

[Follow](#)

answered Dec 6 '20 at 23:49



[mzedeler](#)

3,753 ● 3 ● 22 ● 37

[Add a comment](#)



Your Answer

Post Your Answer

By clicking "Post Your Answer", you agree to our [terms of service](#), [privacy policy](#) and [cookie policy](#)



Not the answer you're looking for? Browse other questions tagged [rust](#) [closures](#) [borrow-checker](#) [ownership](#) [borrowing](#) or ask your own question.

The Overflow Blog

-  Sequencing your DNA with a USB dongle and open source code
-  Don't push that button: Exploring the software that flies SpaceX rockets and...

#### Featured on Meta

---

-  Providing a JavaScript API for userscripts
-  Congratulations to the 59 sites that just left Beta

#### Related

Variable binding: moving a &mut or borrowing the referent?

Why can't I store a value and a reference to that value in the same struct?

How to capture mutable reference into move closure contained in iterator returned from a closure

Returning a reference from a HashMap or Vec causes a borrow to last beyond the scope it's in?

2






How does ownership of variables work between iterations?

0

Cannot borrow self twice in one function call

Error: use of moved value: `path`. How to correct this code?

#### Hot Network Questions

-  What's the largest REG\_SZ value that Regedit can edit?
-  What caused this crash landing?
-  Is Elon Musk really exploiting a loophole to avoid taxes?
-  I've got a material setup that blends two shaders decently, but how would I apply it to a circular target?
-  What happened to this character in MCU Spider-Man's life?

[more hot questions](#)

 [Question feed](#)

#### STACK OVERFLOW

Questions  
Jobs  
Developer Jobs Directory  
Salary Calculator  
Help  
Mobile

#### PRODUCTS

Teams  
Talent  
Advertising  
Enterprise

#### COMPANY

About  
Press  
Work Here  
Legal  
Privacy Policy  
Terms of Service  
Contact Us  
Cookie Settings  
Cookie Policy

#### STACK EXCHANGE NETWORK

Technology  
Culture & recreation  
Life & arts  
Science  
Professional  
Business  
API  
Data

Blog  
Facebook  
Twitter  
LinkedIn  
Instagram