

Rust - Lifetime of struct member depends on another struct member [duplicate]

Asked 2 years, 5 months ago Active 2 years, 5 months ago Viewed 1k times



1



This question already has answers here:

Why can't I store a value and a reference to that value in the same struct? (2 answers)

I'm trying to write a Rust struct. The struct owns a Reference counted pointer to a string and also owns a vector of string slices to the same string.

Furthermore I'm trying to write a function to generate this struct. I'm unsure how to proceed.

```
struct MyStruct<a> {
  rc_string: Rc<String>,
   vec: Vec<&'a str>
\label{lem:condition} fin \ build_my_struct<'a>(s: &Rc<String>) -> MyStruct<'a> \{ \\ let \ rc_string = s.clone(); \\ \end{aligned}
  let mut vec = Vec::new();
vec.push(&rc_string[0..2]);
  MyStruct {
     rc_string: rc_string,
      vec: vec
error[E0515]: cannot return value referencing local variable `rc_string' --> src/main.rs:13:5
11 | vec.push(&rc_string[0..2]);
                     --- 'rc_string' is borrowed here
12
13 | / MvStruct {
        rc_string: rc_string,
15 ||
          vec: vec
16|| }
            ^ returns a value referencing data owned by the current function
```

I understand that the vec variable has borrowed the re_string. The compiler doesn't like returning vec because it has the borrow to the local variable re_string.

However re string is being returned as well? The string slices are valid for the duration of the life of MyStruct.re string?



rust lifetime



James Welchman 55 • 6

1 Answer

Active Oldest Votes







You need to borrow Re for life time 'a as well. Compiler needs to know that slice from a String is living in 'a or not. In this case we need to borrow Re for 'a and compiler will know inner of $\,Rc\,$ will also live in 'a .

Your private you clone s and assign it to re_string:

By clicking "Accept all cookies", you agree Sack Exchange can store cookies on your device and disclose information in accordance with our <u>Cookie Policy</u>.

• s will stay in the function's scope as borrowed 'Re for lifetime a

• rc_string will be the owner of the Rc pointer
Accept all cookies Customize settings

and compiler won't be able to know slice of a rc_string is living for 'a or not.

```
Using slice from a s will work:
  fin build_my_struct<'a>(s: &'a Rc<String>) -> MyStruct<'a> {
    let mut vec = Vec::new();
    let rc string = s.clone();
    vec.push(&s[0..2]);
    MyStruct { rc_string, vec }
Playground
Improve this answer
Follow
 edited Jul 4 '19 at 18:30
 answered Jul 4 '19 at 18:09
  Ömer Erden
  5,861 • 5 • 25 • 39
 @JamesWelchman The code in your second question will work with the same way, please check this code. You can't return slice from a moved content unless it lives in static lifetime.
 Jul 4'19 at 18:38 🌶
 In my original code I use the Re pointer because the lifetime of MyStruct extends beyond the lifetime of the Re<br/>String> in the calling function. Just to be clear - I can't move both a String and
 a slice of the string into a return value?
 - James Welchman
 Jul 4'19 at 18:50 🥒
 Basically this is always impossible.
  - James Welchman
 Jul 4 '19 at 19:00
 @James Welchman borrow checker's duty is preventing you from facing with dangling pointers, you can create a struct both String and it's slice but there is a possibility at runtime you can
 move(or even drop) String value from a field of struct without moving or dropping slices from that string. With this you can have dangling pointers
 - Ömer Erden
 Jul 4 '19 at 19:08
 @JamesWelchman this is not possible because according to our definition &s needs to live in my_struct 's lifetime argument. It is a bit confusing because you are not dropping the real string
 but borrow checker is not able to know the string is trapped inside a Rc pointer.
 - Ömer Erden
 Jul 4'19 at 19:15
Not the answer you're looking for? Browse other questions tagged \fbox{nust} \fbox{lifetime} or ask your own question.
  The Overflow Blog
   Sequencing your DNA with a USB dongle and open source code
   Don't push that button: Exploring the software that flies SpaceX rockets and...
  Featured on Meta
   п
   Providing a JavaScript API for userscripts
   Congratulations to the 59 sites that just left Beta
Linked
  Why can't I store a value and a reference to that value in the same struct?
Related
  How do I transform &str to ~str in Rust?
  Rust rustc::middle::graph::Graph with string node indices
  Unable to coerce &String to &str
  Encapsulating sequentially initialized state with self-references in Rust struct
  What is the better way to wrap a FFI struct that owns or borrows data?
```

Problems with Tuple's lifetime in rust.

How to use delayed initialization in rust code and pass compiler "possibly-uninitialized variable" rule?

Hot Network Questions

- ★ Why are nerves blocked even though potassium chanels are not blocked?
- Alternatives to replace tandem single pole MWBC breakers?
- Why is JWST parked in sunlight, rather than using a nuclear battery?
- △ Question on connections in general relativity and particle physics
- What's the largest REG_SZ value that Regedit can edit?

more hot questions

STACK OVERFLOW

Questions Jobs Developer Jobs Directory Salary Calculator Help Mobile

PRODUCTS

Teams Talent Advertising Enterprise

COMPANY

About
Press
Work Here
Legal
Privacy Policy
Terms of Service
Contact Us
Cookie Settings
Cookie Policy

STACK EXCHANGE NEIWORK

Technology Culture & recreation Life & arts Science Professional Business API Data

Blog Facebook Twitter LinkedIn Instagram

site design / logo @2021 Stack Exchange Inc; user contributions licensed under cc by-sa. rev 2021.12.22.41046