

#### Products

# Using a struct to store a reference to a non-Copy value

#### Ask Question

Asked 3 years, 2 months ago Active 3 years, 2 months ago Viewed 152 times



1



I need an object that contains a reference to a process child and enables me to execute functions on it.

```
pub struct Shell {
  child: std::process::Child,
impl Shell {
 | pub fit init() > Shell {
| let mut cmd = std::process::Command::new("Command");
| let process = cmd.spawn();
| let new = Shell {
       child: process.unwrap().
    };
new
   pub \ fn \ fl(mut \ self) \ \{
     //do something with self
  pub fn f2(mut self) {
        let stdin = self.child.stdin.as_mut().unwrap();
     let output = self.child.wait_with_output();
fn main() {
    let mut shell = Shell::init();
   shell.fl();
  shell.f2();
error[E0382]: use of moved value: 'shell
27 | shell.fl();
      ---- value moved here
28 | shell.f2();
      ^^^^ value used here after move
   = note: move occurs because 'shell' has type 'Shell', which does not implement the 'Copy' trait
```

# ≥Try it

The problem is that when I initialize my object, I can call functions on the object only once, because the value is moved on the first call due to standard Rust behaviour.

A simple #[derive(Copy, Clone)] does not work here, because std:process::Child does not seem to implement the Copy trait. Is there a way to circumvent that or wrap it into something copy-able?

### Test Implementations

When using a mutable reference as the function argument, the initial problem appears to be solved, however, it is then not possible to access the self-child more than once.

By clicking "Accept all cookies", you agree Stack Exchange can store cookies on your device and disclose information in accordance with our Cookie Policy.

```
pub struct Shell {
      child: std::process::Child,
   impl Shell {
  pub fininit() >> Shell {
    let mut cmd = std::process::Command::new("Command");
    let process = cmd.spawn();
    let new = Shell {
        child: process.unwrap(),
    }
}
      pub fn fl(&mut self) {
     //do something with self
      pub fin f2(&mut self) {
         {
let stdin = self.child.stdin.as_nut().unwrap();
         let output = self.child.wait_with_output();
   fn main() {
    let mut shell = Shell::init();
    shell.f1();
      shell.f2();
   error[E0507]: cannot move out of borrowed content --> src/main.rs:21:22
              let output = self.child.wait_with_output();

^^^ cannot move out of borrowed content
   21 |
<u>>Try it</u>
Is there a way to solve that?
struct reference rust
Share
Improve this question
Follow
 edited Oct 9 '18 at 19:32
  asked Oct 9'18 at 10:12
    217 • 1 • 9
1 Answer
  Active Oldest Votes
Ð
```

The problem is that  $self.child\ has\ to\ be\ consumed\ by\ wait\_with\_output()$ . This is why  $self\ must\ not\ be\ passed\ to\ f2$  by reference, but by value:

```
pub struct Shell {
    child: std::process::Child,
  impl Shell {
    pub fin init() -> Shell {
      let mut cmd = std::process::Command::new("Command");
let process = cmd.spawn();
       let new = Shell {
        child: process.unwrap(),
    pub fn fl(&mut self) {
   //do something with self
    pub fn f2(mut self) {
        let stdin = self.child.stdin.as_mut().unwrap();
      let output = self.child.wait_with_output();
  fn main() {
    let mut shell = Shell::init();
shell.fl();
    shell.f2();
≥Try it
However this implies that f2 must be the last function that accesses self.child.
Improve this answer
Follow
 answered Oct 9 '18 at 19:20
  217 • 1 • 9
Your Answer
  Post Your Answer
By clicking "Post Your Answer", you agree to our terms of service, privacy policy and cookie policy
Not the answer you're looking for? Browse other questions tagged struct reference rust or ask your own question.
  The Overflow Blog
   Sequencing your DNA with a USB dongle and open source code
  Don't push that button: Exploring the software that flies SpaceX rockets and...
  Featured on Meta
   Q
   Providing a JavaScript API for userscripts
  0
  Congratulations to the 59 sites that just left Beta
Related
 Cannot move out of borrowed content when borrowing a generic type
```

Reference to unwrapped property fails: use of partially moved value: `self  $\,$ 

Why can't I store a value and a reference to that value in the same struct?

Factory method: instance does not live long enough

1 the trait `\_embedded\_hal\_digital\_InputPin` is not implemented for `PE2<Output<OpenDrain>>`

Awaiting a Number of Futures Unknown at Compile Time

0

Cannot call read on std::net::TcpStream due to unsatisfied trait bounds

Error: use of moved value: 'path'. How to correct this code?

### Hot Network Questions

- Cloth shop' and 'Clothes shop'
- What edges are not in a Gabriel graph, yet in a Delauney graph?
- Regular expressions within QGIS expressions: logical operator AND
- Calculating mean follow up from ONLY sample size and range
- Why does making a quantum circuit more noise resilient make it easier to simulate classically?

more hot questions

Question feed

### STACK OVERFLOW

Questions Jobs Developer Jobs Directory Salary Calculator Help Mobile

## PRODUCTS

Teams Talent Advertising Enterprise

### COMPANY

About
Press
Work Here
Legal
Privacy Policy
Terms of Service
Contact Us
Cookie Settings
Cookie Policy

### STACK EXCHANGE NEIWORK

Technology Culture & recreation Life & arts Science Professional Business API Data

Blog Facebook Twitter LinkedIn Instagram

site design / logo @2021 Stack Exchange Inc; user contributions licensed under cc by-sa. rev 2021.12.22.41046