



Products

Rust lifetime in closure environment

Log in Sign up

Ask Question

Asked 3 years, 10 months ago

Active 3 years, 10 months ago

Viewed 553 times



2



I want to implement a graph structure in Rust. For this goal, I wrote simple abstractions:

```
pub struct Graph<a> {
    pub nodes: Vec<Node>,
    pub edges: Vec<Edge<a>>,
}

#[derive(Debug)]
pub struct Node {
    pub id: String,
    pub label: String,
}

pub struct Edge<a> {
    pub source: &a Node,
    pub target: &a Node,
}
```

Graph contains vectors of Nodes and Edges. Every Edge has a ref to a Node in the same Graph.

I don't know it's possible to write something like this.

I tried to write a static method that builds a new Graph instance from a JSON representation:

```
impl<a> Graph<a> {
    pub fn from_json(json: &String) -> Graph {
        if let json::JsonValue::Object(deserialized) = json::parse(json.as_ref()).unwrap() {
            let nodes: Vec<Node> = deserialized
                .get("nodes")
                .unwrap()
                .members()
                .map(|v| {
                    if let json::JsonValue::Object(ref val) = *v {
                        return Node {
                            id: val.get("id").unwrap().to_string(),
                            label: val.get("label").unwrap().to_string(),
                        };
                    }
                    panic!("Invalid structure of json graph body.")
                })
                .collect::<Vec<Node>>();
            let edges: Vec<Edge> = deserialized
                .get("edges")
                .unwrap()
                .members()
                .map(|v| {
                    if let json::JsonValue::Object(ref val) = *v {
                        let source = (*nodes)
                            .iter()
                            .find(&|v| v.id == val.get("source").unwrap().to_string())
                            .unwrap();
                        let target = (*nodes)
                            .iter()
                            .find(&|v| v.id == val.get("target").unwrap().to_string())
                            .unwrap();
                        return Edge { source, target };
                    }
                    panic!("Invalid structure of json graph body.")
                })
        }
    }
}
```

When I compile, I get this error:

```
error[E0373]: closure may outlive the current function, but it borrows `nodes`, which is owned by the current function
--> src/graph.rs:30:22
|
| 30 |         .map(|v| {
|           ^^^ may outlive borrowed value `nodes`
| 31 |         if let json::JsonValue::Object(ref val) = *v {
| 32 |             let source = (*nodes).iter().find(&|v| v.id == val.get("source").unwrap().to_string()).unwrap();
|           ----- `nodes` is borrowed here
|
| help: to force the closure to take ownership of `nodes` (and any other referenced variables), use the `move` keyword
|
| 30 |         .map(move |v| {
|           ~~~~~
```

error: aborting due to previous error

Your privacy

A possible solution to this problem is to add `move` before the closure parameters, but I need the `nodes` vector to build the `Graph` instance. By clicking "Accept all cookies", you agree Stack Exchange can store cookies on your device and disclose information in accordance with our [Cookie Policy](#).

What am I doing wrong?

Accept all cookies Customize settings

[rust](#) [closures](#) [lifetime](#)

Share
Improve this
question

Follow

edited Feb 18 '18 at 14:32



Shepmaster

305k • 59 • 824 • 1083

asked Feb 18 '18 at 10:49



Дмитрий Сулохин

31 • 6

1

Useful question [Why can't I store a value and a reference to that value in the same struct?](#)

– red75prime

Feb 18 '18 at 13:06

1

This question could be helpful too: [Implement graph-like datastructure in Rust](#)

– red75prime

Feb 18 '18 at 13:56

@red75prime Second link is very helpful, thank you for help

– Дмитрий Сулохин

Feb 18 '18 at 14:20

This was [cross-posted to the Rust user's forum](#).

– Shepmaster

Feb 18 '18 at 16:23

[Add a comment](#)

1 Answer

[Active](#) [Oldest](#) [Votes](#)



0



After some research, I found this article's: [Rust doc. Smart pointers](#), [Users Rust Lang](#), and I understood my mistakes. The first one: I remove lifetime parameters from structs definitions.

```
use std::rc::Rc;
#[derive(Debug)]
pub struct Graph {
    pub nodes: Vec<Rc<Node>>,
    pub edges: Vec<Edge>
}
#[derive(Debug)]
pub struct Node {
    pub id: String,
    pub label: String
}
#[derive(Debug)]
pub struct Edge {
    pub source: Rc<Node>,
    pub target: Rc<Node>
}
```

Second thing: I rewrote the code of `from_json` function for using `Rc<T>` instead of raw references.

```

impl Graph {
    pub fn from_json(json: & String) -> Graph {
        if let json::JsonValue::Object(deserialized) = json::parse(json.as_ref()).unwrap() {
            let nodes : Vec<Rc<Node>> = deserialized.get("nodes").unwrap().members()
                .map(|v| {
                    if let json::JsonValue::Object(ref val) = *v {
                        return Rc::new(Node {
                            id: val.get("id").unwrap().to_string(),
                            label: val.get("label").unwrap().to_string()
                        });
                    }
                    panic!("Invalid structure of json graph body.")
                }).collect::<Vec<Rc<Node>>>();
            let edges : Vec<Edge> = deserialized.get("edges").unwrap().members()
                .map(|v| {
                    if let json::JsonValue::Object(ref val) = *v {
                        let source = nodes.iter().find(|&v| v.id == val.get("source").unwrap().to_string()).unwrap();
                        let target = nodes.iter().find(|&v| v.id == val.get("target").unwrap().to_string()).unwrap();
                        return Edge {
                            source: Rc::clone(&source),
                            target: Rc::clone(&target)
                        };
                    }
                    panic!("Invalid structure of json graph body.")
                }).collect::<Vec<Edge>>();
            return Graph {
                nodes,
                edges
            }
        }
        panic!("Incorrect struct of json contains!");
    }
}

```

Now it works. Thanks for sharing useful links. I found a lot of helpful information about building graph structs in Rust such as: [Graph structure in Rust](#)

Share

Improve this answer

Follow

answered Feb 20 '18 at 15:55



Дмитрий Сулохин

31 • 6

This is interesting: why the element type of Vec could change the borrow behavior of the Vec itself?

– [zs1222](#)

Mar 3 at 5:25

[Add a comment](#)

Your Answer

Post Your Answer

By clicking "Post Your Answer", you agree to our [terms of service](#), [privacy policy](#) and [cookie policy](#)

Not the answer you're looking for? Browse other questions tagged [rust](#) [closures](#) [lifetime](#) or ask your own question.

The Overflow Blog

- Sequencing your DNA with a USB dongle and open source code
- Don't push that button: Exploring the software that flies SpaceX rockets and...

Featured on Meta

- Providing a JavaScript API for userscripts
- Congratulations to the 59 sites that just left Beta

Linked

[Why can't I store a value and a reference to that value in the same struct?](#)

[Implement graph-like data structure in Rust](#)

Related

[What is the difference between a 'closure' and a 'lambda'?](#)

[Access to Modified Closure](#)

[What is the lifetime of a static variable in a C++ function?](#)

[JavaScript closure inside loops – simple practical example](#)

[In PHP, what is a closure and why does it use the "use" identifier?](#)

[Why doesn't println! work in Rust unit tests?](#)







[Why are explicit lifetimes needed in Rust?](#)

[lifetime with closure captures in rust](#)

[Confused by Rust closure lifetime](#)

[Specify Rust closures lifetime](#)

Hot Network Questions

-  [Why is 20m band waterfall showing signals every 50 kHz?](#)
 -  [Given many questions as to whether Jesus was born on 25 December or not, I ask if the ambiguity in scripture is meant to teach us something?](#)
 -  [What do I do when my boss is sabotaging interviews?](#)
 -  [Company kept previous personal phone number](#)
 -  [What edges are not in a Gabriel graph, yet in a Delauney graph?](#)
- [more hot questions](#)
-  [Question feed](#)

STACK OVERFLOW

[Questions](#)
[Jobs](#)
[Developer Jobs Directory](#)
[Salary Calculator](#)
[Help](#)
[Mobile](#)

PRODUCTS

[Teams](#)
[Talent](#)
[Advertising](#)
[Enterprise](#)

COMPANY

[About](#)
[Press](#)
[Work Here](#)
[Legal](#)
[Privacy Policy](#)
[Terms of Service](#)
[Contact Us](#)
[Cookie Settings](#)
[Cookie Policy](#)

STACK EXCHANGE NETWORK

[Technology](#)
[Culture & recreation](#)
[Life & arts](#)
[Science](#)
[Professional](#)
[Business](#)
[API](#)
[Data](#)

[Blog](#)
[Facebook](#)
[Twitter](#)
[LinkedIn](#)
[Instagram](#)