



Products

Why does passing tokio_postgres::Transaction as a reference ask to indicate the anonymous lifetime?

[Log in](#) [Sign up](#)

[Ask Question](#)

Asked 1 year, 6 months ago

Active 1 year, 6 months ago

Viewed 247 times



0



I'm using tokio_postgres to connect to a database and trying to start a transaction

```
let trans = client.transaction().await.unwrap();
trans.query("select * from abc", &[]).await.unwrap();
// ...
trans.commit().await.unwrap();
```

Everything works as expected. Now I want to put the code between trans.query and trans.commit into a separate function

```
async fn tx_work(trans: &tokio_postgres::Transaction) {
    trans.query("select * from abc", &[]).await.unwrap();
    // ...
    trans.commit().await.unwrap();
}
```

and call it in main :

```
let trans = client.transaction().await.unwrap();
tx_work(&trans).await.unwrap();
```

The code doesn't compile:

```
error[E0726]: implicit elided lifetime not allowed here
--> src/abc.rs:209:28
   |
209 | async fn tx_work(trans: &tokio_postgres::Transaction) {
   |                        ~~~~~~~~~~~~~~~~~~~~~~ help: indicate the anonymous lifetime: `'_`>`
```

This didn't help:

```
async fn tx_work<a>(trans: &a tokio_postgres::Transaction)
```

What do I do?

[rust](#) [lifetime](#) [rust-tokio](#)

Share

Improve this

question

Follow

edited Jun 18 '20 at 1:59

asked Jun 18 '20 at 1:37



[user3839198](#)

75 • 8

It's hard to answer your question because it doesn't include a [minimal reproducible example](#). We can't tell what crates (and their versions), types, traits, fields, etc. are present in the code. It would make it easier for us to help you if you try to reproduce your error on the [Rust Playground](#) if possible, otherwise in a brand new Cargo project, then [edit](#) your question to include the additional info. There are [Rust-specific MRE tips](#) you can use to reduce your original code for posting here. Thanks!

– [Shepmaster](#)

Jun 18 '20 at 1:50

Please [edit](#) your question and paste the exact and entire error that you're getting — that will help us to understand what the problem is so we can help best. Sometimes trying to interpret an error message is tricky and it's actually a different part of the error message that's important. Please use the message from running the compiler directly, not the message produced by an IDE, which might be trying to interpret the error for you.

– [Shepmaster](#)

Jun 18 '20 at 1:52

I edited the question and included the entire error message.

– [user3839198](#)

Jun 18 '20 at 2:00

Your privacy

By clicking "Accept all cookies", you agree Stack Exchange can store cookies on your device and disclose information in accordance with our [Cookie Policy](#).

[Accept all cookies](#) [Answer](#) [Customize settings](#)

[Active](#) [Oldest](#) [Votes](#)

2

Based on the definition of [Transaction](#) it seems you want the lifetime specifier/parameter on the struct itself, not on the function parameter reference:

```
async fn tx_work(trans: &tokio_postgres::Transaction<'_>)
```

That's using the anonymous lifetime, but you can also explicitly specify the lifetime parameter:

```
async fn tx_work<'a>(trans: &tokio_postgres::Transaction<'a>)
```

It is common to relate these lifetimes to other existing lifetimes, for example, if you already had an explicit lifetime elsewhere and it makes sense to do so, you might pass it as the parameter directly.

This is because `tokio_postgres::Transaction` does not fully specify the type anymore than `Vec` would (compared to `Vec<u8>`), i.e. the lifetime specifiers are part of the type name, so you need `tokio_postgres::Transaction<some_lifetime>`, but apparently you can use the anonymous lifetime `'_` too.

More specifically, here, the lifetime parameter on `Transaction` pertains to the lifetime of the references contained within the `Transaction` struct, whereas a lifetime on the *reference* to the `Transaction` struct (like you initially attempted) pertains to ... well, the lifetime of that very reference.

If this is all still confusing, I encourage you to read the excellent [chapter on lifetimes](#) from the book. It is an integral part of the Rust programming paradigm.

[Share](#)

[Improve this answer](#)

[Follow](#)

edited Jun 18 '20 at 6:13

answered Jun 18 '20 at 2:03



Jorge Israel Peña

33.9k • 15 • 86 • 118

1

This answer would be improved by discussing why the compiler gives this error.

– [Shepmaster](#)

Jun 18 '20 at 2:03

Jorge, thanks, it works, but honestly I don't know why. It will be really helpful if you can explain the answer a bit more, why `&tokio_postgres::Transaction<'_>` is a ref on struct `Transaction` while `&tokio_postgres::Transaction` is a ref on the ref to the struct?

– [user3839198](#)

Jun 18 '20 at 2:22

That's my fault, I just realized I used confusing language. What I meant was, where you needed the lifetime specifier `<'lifetime>` is on the type `Transaction`, i.e. `Transaction<'lifetime>`, you can liken it to how `Vec` on its own isn't a type (yet), but something like `Vec<String>` is, in other words, `Transaction` on its own is incomplete. I meant to say that `Transaction` is where you needed to add the lifetime parameter, not on the reference function parameter like you initially attempted.

– [Jorge Israel Peña](#)

Jun 18 '20 at 6:05

To make things more concrete, you use either `<'_>` (the anonymous lifetime) or you explicitly specify a lifetime parameter, I'll add that to my answer.

– [Jorge Israel Peña](#)

Jun 18 '20 at 6:07

[Add a comment](#)

Your Answer

Post Your Answer



By clicking "Post Your Answer", you agree to our [terms of service](#), [privacy policy](#) and [cookie policy](#)

Not the answer you're looking for? Browse other questions tagged [rust](#) [lifetime](#) [rust-tokio](#) or [ask your own question](#).

The Overflow Blog

- Sequencing your DNA with a USB dongle and open source code
- Don't push that button: Exploring the software that flies SpaceX rockets and...

Featured on Meta

-  Providing a JavaScript API for userscripts
-  Congratulations to the 59 sites that just left Beta

Related

Why does the lifetime name appear as part of the function type?

Why is a lifetime needed when implementing a trait on a reference type if the lifetime is otherwise unused, in Rust < 1.31?

Does `<a, 'b: 'a>` mean that the lifetime `'b` must outlive the lifetime `'a`?

Why can't I store a value and a reference to that value in the same struct?






Why does my trait need a lifetime parameter?

Why does the Rust compiler not optimize code assuming that two mutable references cannot alias?

Does a generic lifetime materialize as the reference's lifetime or the referenced value's lifetime?

How to resolve "indicate anonymous lifetime `<'_>`" error?

Hot Network Questions

-  How to plot molecules with angles and bond lengths
 -  Why is the light source not showing but light is being cast on the object
 -  Is Elon Musk really exploiting a loophole to avoid taxes?
 -  Why does the prophecy imply Macbeth has to murder the king?
 -  I've got a material setup that blends two shaders decently, but how would I apply it to a circular target?
- [more hot questions](#)

 [Question feed](#)

STACK OVERFLOW

[Questions](#)
[Jobs](#)
[Developer Jobs Directory](#)
[Salary Calculator](#)
[Help](#)
[Mobile](#)

PRODUCTS

[Teams](#)
[Talent](#)
[Advertising](#)
[Enterprise](#)

COMPANY

[About](#)
[Press](#)
[Work Here](#)
[Legal](#)
[Privacy Policy](#)
[Terms of Service](#)
[Contact Us](#)
[Cookie Settings](#)
[Cookie Policy](#)

STACK EXCHANGE NETWORK

[Technology](#)
[Culture & recreation](#)
[Life & arts](#)
[Science](#)
[Professional](#)
[Business](#)
[API](#)
[Data](#)

[Blog](#)
[Facebook](#)
[Twitter](#)
[LinkedIn](#)
[Instagram](#)