

#### Products

# Can't use locally created vector because "borrowed" [duplicate]

```
Ask Question
```

```
Asked 2 years, 3 months ago
Active 2 years, 3 months ago
Viewed 93 times
```



0





#### This question already has an answer here:

```
What does "cannot move out of index of" mean? (1 answer)
```

Closed 2 years ago

I can't get first element of the vector because of the error and can't change struct design either. I tried borrowing but struct expects a ExtrudeGeometry.

```
#[wasm_bindgen]
pub fit toCollection(arr: js_sys::Array, r_type: String) -> JsValue {
    let n_arr: Vec<ExtrudeGeometry>= arr.into_serde().unwrap(); if r_type = "GeometryCollection" {
       return Js Value::from_serde(&OutputGeometryCollection { collection: n_arr,
         r#type: r_type,
        .unwrap();
    } else {
let ex: ExtrudeGeometry = n_arr[0];
       return JsValue::from_serde(&OutputObject {
         data: ex,
         r#type: r_type,
       })
       .unwrap();
  error[E0507]; cannot move out of borrowed content
     -> src/lib.rs:308:39
               let ex: ExtrudeGeometry = n_arr[0];
  308
          cannot move out of borrowed content
          help: consider borrowing here: `&n_arr[0]`
json vector rust serde borrowing
Improve this question
Follow
 edited Sep 3 '19 at 7:50
  Boiethios
  28.9k • 10 • 104 • 147
  asked Sep 3 '19 at 7:28
```

2

157 • 7

Hi there! Does this or this answer your question? Summary: you are trying to get an element from a Vec by value, but that is not possible without cloning or removing it entirely from the Vec .

- Lukas Kalbertodt
Sep 3 '19 at 7:34

I am new to rust. I don't understand the error. If cloning helps it will be my answer.

— mertselimb

```
- mertselmb

Sep 3 '19 at 7:37

I

If you throw the vector away, you don't need to clone the item Just consume it: n_arr.into_iter().next().unwrap()

- Boiethios

Sep 3 '19 at 7:37 //
```

I just now also found this Q&A which probably fits your question more closely!

# Your privacy Lukas Kalbertodt

By clicking "Accept all 906kies", you agree Stack Exchange can store cookies on your device and disclose information in accordance with our Cookie Policy.

```
Accept all cookies Customize settings
```

Don't worry! Your question now serves as signpost and will be easier found by people who formulate the problem like you do.

- Lukas Kalbertodt

Sep 3 '19 at 7:57

Show 2 more comments

#### 1 Answer

Active Oldest Votes



2





I assume in this answer that the ownership system of Rust is known. Your vector owns the items, so if you ask for the first one, you can only borrow it because the vector is composed of items contiguous in memory. You cannot randomly remove an item from it with the index notation.

If you want to take the first one, you have 3 choices:

• You don't care about the remaining of the vector: you can transform it into an iterator and take the first item iterated:

```
vector
.into_iter() // consume the vector to get an iterator
.next() // get the first iterated item
.unwran()
```

- You care about the remaining, but you don't care about the ordering, use  $\,\underline{\text{swap\_remove}}$  :

vector.swap\_remove(0)

• You care about the remaining and the ordering: don't use a vector. I you don't have that choice, you can use remove, but that's a O(n) function.

By the way, the return in last position is not idiomatic:

```
#[wasm bindgen]
   pub fin toCollection(arr: js_sys::Array, r_type: String) -> JsValue {
      let \ n\_arr: Vec < Extrude Geometry > = arr.into\_serde().unwrap();
     \label{eq:contryCollection} \begin{split} & \text{if } r\_type = \text{"GeometryCollection"} \; \{ \\ & \text{JsValue::from\_serde(\&OutputGeometryCollection} \; \{ \end{split}
           collection: n_arr,
           r#type: r_type,
        })
.unwrap()
     } else {
        let ex = n_arr.into_iter().next().unwrap();
        JsValue::from_serde(&OutputObject {
           data: ex.
           r#type: r_type,
         .unwrap();
Improve this answer
Follow
 edited Sep 3 '19 at 11:57
```

answered Sep 3 '19 at 7:47



Boiethios

**28.9k** • 10 • 104 • 147

Add a com ment

Not the answer you're looking for? Browse other questions tagged <code>[json] [vector] [rust] [serde] [borrowing]</code> or ask your own question.

#### The Overflow Blog

•

Sequencing your DNA with a USB dongle and open source code

1

Don't push that button: Exploring the software that flies SpaceX rockets and..

#### Featured on Meta

Q

Providing a JavaScript API for userscripts

Q

Congratulations to the 59 sites that just left Beta

Linked

What does "cannot move out of index of" mean?

How can I take an item from a Vec in Rust?

Getting value from a collection without using the Clone trait
Related
403 Why can't I make a vector of references?
Cannot move out of borrowed content / cannot move out of behind a shared reference
Cannot move out of borrowed content when borrowing a generic type
How to implement Iterator for boxed values?
How to clone last element from vector?
Pass self reference to contained object's function
How to capture self consuming variable in a struct?
Reference to unwrapped property fails: use of partially moved value: 'self
1 Rust cannot find module even though the file is present
Hot Network Questions
What's the social meaning of "He was a student of"?
த்து Naruto fighting game with Hulk and Homer Simpson?
On what basis do countries repay international loans?
Why couldn't Smith absorb Neo in The Matrix Reloaded?
Circuit analysis homework - LTspice results are different from calculations
more hot questions
RFLOW
Directory

# STACK OVERFLOW

Questions Jobs Developer Jobs Directory Salary Calculator Help Mobile

### PRODUCTS

Teams Talent Advertising Enterprise

# COMPANY

About
Press
Work Here
Legal
Privacy Policy
Terms of Service
Contact Us
Cookie Settings
Cookie Policy

# STACK EXCHANGE NETWORK

Technology Culture & recreation Life & arts Science Professional Business API Data

Blog Facebook Twitter LinkedIn Instagram

site design / logo © 2021 Stack Exchange Inc; user contributions licensed under cc by-sa. rev 2021.12.22.41046