

Why does Rust not recognize that I re-assign to the moved variable inside a closure?

Asked 4 years ago Active 4 years ago Viewed 349 times







I am having trouble understanding why a particular pattern is not compiling.

Rust recognizes when I move a variable and then reassign to it outside of a closure and I think properly allows the code to compile, but when I try to do the same in a closure that will be run more than once it will not.

```
fn main() {
   let mut v = vec![1, 2, 3, 4];
   v.into_iter().fold(0, |a, b| a + b);
  v = vec![1, 2, 3, 4];
vec![1, 2, 3].into_iter().for_each(|x| {
     v.into_iter().fold(x, |a, b| a + b);
v = vec![1, 2, 3, 4];
  });
}
error[E0507]; cannot move out of captured outer variable in an 'FnMut' closure --> src/main.rs:6:9
2 let mut v = vec![1, 2, 3, 4];
6|
        v.into\_iter().fold(x, |a, b| a + b);
        ^ cannot move out of captured outer variable in an `FnMut` closure
```

It seems to me that the reassignment to v should satisfy the borrow checker that no variable will be accessed after being moved. Am I missing something?

```
rust borrow-checker
```

```
Improve this question
Follow
 edited Dec 7117 at 2:03
  Shepmaster
  305k • 59 • 824 • 1083
  asked Dec 7 '17 at 1:47
           -david-lewis
  21 • 1 • 2
```

My guess: FnMut closures can possibly be called multiple times. In this case a for_each will execute in sequence, but what if that closure were being passed to multiple threads? You could consume v and then other thread try to access it before you can reassign to it. But this is just a wild guess - I'ma Rust newbie myself so I'm not sure. – iulioolyr

```
Dec 7'17 at 2:15
```

@julioolvr I had that thought too, but I believe rust has traits that must be implemented for that to be so. The Send and Sync traits are what tell rust that types can be shared between threads, and for_each does not require either of those types so that should never be possible.

```
Dec 7 '17 at 2:20
```

2 Answers

Active Oldest Votes







As @Shepmaster mentioned, the fix is to use std::mem::replace.

So, what is the difference between:

Your privacy $v_into_iter().fold(x_i|a,b|a+b);$ By clicking "Acceptall ocologis 2youngere Stack Exchange can store cookies on your device and disclose information in accordance with our Cookie Policy.

```
let v_old = std::mem::replace(&mut v, vec![1, 2, 3, 4]);
    v_old.into_iter().fold(x, |a, b| a + b);
In two words: exception safety.
```

 $If, for some \ reason, the \ expression \ v.into_iter().fold(...) \ would \ panic, it \ would \ leave \ v \ moved out \ and \ the \ next \ statement \ would \ never \ be \ executed.$

This is perfectly acceptable in a FnOnce, as you will never call the closure another time, but not acceptable in a FnMut or Fn as on the next call... what would you do with v?

On the other hand, using std::mem:replace, you swap first and then execute the potentially panicking operation. If the operation does panic, then all that is left "moved out" is a temporary variable which disappears at the end of the stack frame anyway. No issue.





2



the reassignment to v should satisfy the borrow checker that no variable will be accessed after being moved

Pay attention to the error message details — there isn't a move to start with:

cannot move out of captured outer variable in an 'FnMut' closure

Since there was no move out, it doesn't make sense to move something back in.

Instead, you can replace the value through the mutable reference and consume the old value:

```
fn main() {
 let mut v = vec![1, 2, 3, 4];
 v_old.into_iter().fold(x, |a, b| a + b);
});
```

Share

Improve this answer

answered Dec 7 '17 at 2:53



305k • 59 • 824 • 1083

Your Answer



Post Your Answer

By clicking "Post Your Answer", you agree to our terms of service, privacy policy and cookie policy

Not the answer you're looking for? Browse other questions tagged nust borrow-checker or ask your own question.

The Overflow Blog

- Sequencing your DNA with a USB dongle and open source code
- Don't push that button: Exploring the software that flies SpaceX rockets and..

Featured on Meta

. 0
Providing a JavaScript API for userscripts
Congratulations to the 59 sites that just left Beta
Related
кемец
336 How do I print the type of a variable in Rust?
now do 1 print the type of a variable in Kust:
Passing a closure to a recursive function
6
cannot move out of borrowed content when unwrapping a member variable in a &mut self method
How to convert C variable-length array code to Rust?
To the control of talling and produce to tall.
Why can't I store a value and a reference to that value in the same struct?
Returning a reference from a HashMap or Vec causes a borrow to last beyond the scope it's in?
Why does the closure take ownership of the vector here?
Why does the Rust compiler not optimize code assuming that two mutable references cannot alias?
How to deal with rust borrow checker
Hot Network Questions
·
Could mass timber construction techniques have been used in the past?
FEM for vector valued problems: reference request
What did John the Baptist say about Jesus that resulted in many Jews in Jesus' time to put faith in him? John 10:41-42
ls there a deterministic guide to landing?
What happened to this character in MCU Spider-Man's life?
more hot questions
Question feed

STACK OVERFLOW

Questions Jobs Developer Jobs Directory Salary Calculator Help Mobile

PRODUCTS

Teams Talent Advertising Enterprise

COMPANY

About
Press
Work Here
Legal
Privacy Policy
Terms of Service
Contact Us
Cookie Settings
Cookie Policy

STACK EXCHANGE NETWORK

STACK EXCHANGE
Technology
Culture & recreation
Life & arts
Science
Professional
Business
API
Data

Blog Facebook Twitter LinkedIn Instagram

site design / logo © 2021 Stack Exchange Inc; user contributions licensed under cc by-sa. rev 2021.12.22.41046