



Products

What does "borrowed data cannot be stored outside of its closure" mean?

Login Sign up

Ask Question

Asked 3 years, 6 months ago

Active 11 months ago

Viewed 2k times



7



When compiling the following code:

```
fn main() {  
    let mut fields = Vec::new();  
    let pusher = &mut |a: &str| {  
        fields.push(a);  
    };  
}
```

The compiler gives me the following error:

```
error: borrowed data cannot be stored outside of its closure  
--> src/main.rs:4:21  
|  
3|   let pusher = &mut |a: &str| {  
|   ----- ...because it cannot outlive this closure  
|   |  
|   borrowed data cannot be stored into here...  
4|     fields.push(a);  
|     ^ cannot be stored outside of its closure
```

And in later versions of Rust:

```
error[E0521]: borrowed data escapes outside of closure  
--> src/main.rs:4:9  
|  
2|   let mut fields = Vec::new();  
|   ----- 'fields' declared here, outside of the closure body  
3|   let pusher = &mut |a: &str| {  
|   - 'a' is a reference that is only valid in the closure body  
4|     fields.push(a);  
|     ~~~~~ 'a' escapes the closure body here
```

What does this error mean, and how can I fix my code?

[rust](#) [closures](#) [borrow-checker](#) [ownership](#)

Share

Improve this question

Follow

edited Jan 5 at 18:36



Shepmaster

305k ● 59 ● 824 ● 1083

asked Jun 30 '18 at 19:48



Valentin Lorentz

9,127 ● 5 ● 45 ● 64

Add a comment

1 Answer

[Active](#) [Oldest](#) [Votes](#)



6



It means exactly what it says: that the data you are borrowing only lives for the duration of the closure. Attempting to store it outside of the closure would expose the code to memory unsafety.

This arises because the inferred lifetime of the closure's argument has no relation to the lifetimes stored in the `Vec`.

Your privacy

By clicking "Accept all cookies", you agree to the storing of cookies on your device to enhance site navigation, analyze site usage, assist in our marketing efforts, and our site's functionality. You can adjust your cookie preferences at any time. [Learn more](#)

[Accept all cookies](#) [Customize settings](#)

```
let mut fields: Vec<&str> = Vec::new();
let pusher = |a| fields.push(a);
```

[Share](#)

[Improve this answer](#)

[Follow](#)

answered Jun 30 '18 at 20:36



[Shepmaster](#)

305k • 59 • 824 • 1083

Oh, thank you! I would have expected an error telling me the borrowchk does not have enough info.

– [Valentin Lorentz](#)

Jun 30 '18 at 22:40

@ValentinLorentz FWIW, I've never seen this particular error before, and this is the first SO question about it. It's possible this is a brand new error. You may wish to [file a bug](#) with your case and the error message and say that it wasn't helpful. The Rust contributors strive to have useful error messages.

– [Shepmaster](#)

Jul 1 '18 at 3:36

I spent a few hours misinterpreting the "and remove it from the closure" part. It's not that you can remove it if you're bored with it, you *have to* remove it to make this compile.

– [Stein](#)

Aug 8 '20 at 19:34

[Add a comment](#)

Your Answer

Post Your Answer

By clicking "Post Your Answer", you agree to our [terms of service](#), [privacy policy](#) and [cookie policy](#)

Not the answer you're looking for? Browse other questions tagged [rust](#) [closures](#) [borrow-checker](#) [ownership](#) or [ask your own question](#).

The Overflow Blog

- Sequencing your DNA with a USB dongle and open source code
- Don't push that button: Exploring the software that flies SpaceX rockets and...

Featured on Meta

- Providing a JavaScript API for userscripts
- Congratulations to the 59 sites that just left Beta

Linked

[Store a vec of references to objects in another data structure](#)

[1 borrowed data cannot be stored outside of its closure](#)

Related

[In PHP, what is a closure and why does it use the "use" identifier?](#)

[How to include and use Rust libraries](#)

[No method parse for String](#)

[Cannot move out of borrowed content when trying to transfer ownership](#)

[Unable to coerce &String to &str](#)

[Factory method: instance does not live long enough](#)







How to convert C variable-length array code to Rust?

0

Pass a Struct<a>::method as a 'for<a> Fn(&Foo<a>)' for use in a closure

How to use delayed initialization in rust code and pass compiler "possibly-uninitialized variable" rule?

Hot Network Questions

-  How much of the English history in this Decameron story has any basis in fact?
 -  which one of these paths has the priority: /usr or /usr/local
 -  Why does the prophecy imply Macbeth has to murder the king?
 -  What does the numbers mean in this guitar tab if they already give the chords to play?
 -  Text overflow in tabularx
- [more hot questions](#)
-  [Question feed](#)

STACK OVERFLOW

[Questions](#)
[Jobs](#)
[Developer Jobs Directory](#)
[Salary Calculator](#)
[Help](#)
[Mobile](#)

PRODUCTS

[Teams](#)
[Talent](#)
[Advertising](#)
[Enterprise](#)

COMPANY

[About](#)
[Press](#)
[Work Here](#)
[Legal](#)
[Privacy Policy](#)
[Terms of Service](#)
[Contact Us](#)
[Cookie Settings](#)
[Cookie Policy](#)

STACK EXCHANGE NETWORK

[Technology](#)
[Culture & recreation](#)
[Life & arts](#)
[Science](#)
[Professional](#)
[Business](#)
[API](#)
[Data](#)

[Blog](#)
[Facebook](#)
[Twitter](#)
[LinkedIn](#)
[Instagram](#)

site design / logo © 2021 Stack Exchange Inc; user contributions licensed under [cc by-sa](#). rev 2021.12.22.41046