



Products

# Temporarily move out of borrowed content

Log in or sign up

Ask Question

Asked 6 years, 8 months ago

Active 6 months ago

Viewed 2k times



8



I'm trying to replace a value in a mutable borrow; moving part of it into the new value:

```
enum Foo<T> {
    Bar(T),
    Baz(T),
}

impl<T> Foo<T> {
    fn switch(&mut self) {
        *self = match self {
            &mut Foo::Bar(val) => Foo::Baz(val),
            &mut Foo::Baz(val) => Foo::Bar(val),
        }
    }
}
```

The code above doesn't work, and understandably so, moving the value out of `self` breaks the integrity of it. But since that value is dropped immediately afterwards, I (if not the compiler) could guarantee it's safety.

Is there some way to achieve this? I feel like this is a job for unsafe code, but I'm not sure how that would work.

[rust](#) [ownership](#) [borrow-checker](#)

Share

Improve this

question

Follow

edited Apr 10 '15 at 21:18

asked Apr 10 '15 at 21:12



464 ● 2 ● 9

1

If you add a `Copy` bound to `T`, your code actually works, although I obviously don't know if you're ok with that restriction.

– fjh

Apr 10 '15 at 21:44

[Add a comment](#)

3 Answers

[Active](#) [Oldest](#) [Votes](#)



5



Okay, I figured out how to do it with a bit of `unsafe`ness and `std::mem`.

I replace `self` with an uninitialized temporary value. Since I now "own" what used to be `self`, I can safely move the value out of it and replace it:

## Your privacy

By clicking "Accept all cookies", you agree Stack Exchange can store cookies on your device and disclose information in accordance with our [Cookie Policy](#).

[Accept all cookies](#)

[Customize settings](#)

```

use std::mem;

enum Foo<T> {
    Bar(T),
    Baz(T),
}

impl<T> Foo<T> {
    fn switch(&mut self) {
        // This is safe since we will overwrite it without ever reading it.
        let tmp = mem::replace(self, unsafe { mem::uninitialized() });
        // We absolutely must **never** panic while the uninitialized value is around!

        let new = match tmp {
            Foo::Bar(val) => Foo::Baz(val),
            Foo::Baz(val) => Foo::Bar(val),
        };

        let uninitialized = mem::replace(self, new);
        mem::forget(uninitialized);
    }
}

fn main() {}

```

Share

Improve this answer

Follow

edited Sep 16 '17 at 20:05



Shepmaster

305k ● 59 ● 824 ● 1083

answered Apr 10 '15 at 22:05



azgult

464 ● 2 ● 9

4

This program will fail horribly if `T` has destructor. When you call `swap` you're replacing whatever is located at `self` with garbage. Then you reassign `*self`, and Rust will insert a call to destructor which would attempt to destroy the "old" value of `*self`, which is now garbage. For some reason [playpen](#) does not fail (but you can see double free there), but for me that program core dumps when I compile and run it locally.

– Vladimir Matveev

Apr 10 '15 at 22:26

1

[This](#) program more clearly demonstrates when and how a destructor is called. If your program was safe, it would be called only once, but it is called twice - the first time being erroneous.

– Vladimir Matveev

Apr 10 '15 at 22:31

Good catch. I believe that the modified version which uses `std::ptr::write` should be safe however.

– azgult

Apr 10 '15 at 22:41

1

no it's not safe, now you are actually dropping uninitialized memory. You need to `mem::forget` the `tmp` variable after the `write` call

– oli\_obk

Nov 6 '15 at 9:23

2

[take](#) shows how to do this in a generic way, and also protects against unwinding (aborts instead).

– Stefan

Nov 25 '17 at 15:30

Show 2 more comments



4



The code above doesn't work, and understandably so, moving the value out of `self` breaks the integrity of it.

This is not exactly what happens here. For example, same thing with `self` would work nicely:

```

impl<T> Foo<T> {
    fn switch(self) {
        self = match self {
            Foo::Bar(val) => Foo::Baz(val),
            Foo::Baz(val) => Foo::Bar(val),
        }
    }
}

```

Rust is absolutely fine with partial and total moves. The problem here is that you do not own the value you're trying to move - you only have a mutable borrowed reference. You cannot move out of any reference, including mutable ones.

This is in fact one of the frequently requested features - a special kind of reference which would allow moving out of it. It would allow several kinds of useful patterns. You can find more [here](#) and [here](#).

In the meantime for some cases you can use [std::mem::replace](#) and [std::mem::swap](#). These functions allow you to "take" a value out of mutable reference, provided you give something in exchange.

Share

Improve this answer

Follow

answered Apr 10 '15 at 22:01



Vladimir Matveev

104k ● 30 ● 254 ● 274

It makes little sense for me to require the caller of the method to own `Foo`, when it is possible to implement it using only a `&mut`. Ownership shouldn't be required in this case, as the integrity of `self` can be guaranteed.

– [azgult](#)

Apr 10 '15 at 22:14

@azgult and that's exactly the reason why a lot of people request `&own`-like pointer (see the links to RFC and issue I provided) - because such thing in fact *do* require ownership (*only* owner can move values around).

– [Vladimir Matveev](#)

Apr 10 '15 at 22:19

Add a comment



3



[memuninitialized](#) has been deprecated since Rust 1.39, replaced by [MaybeUninit](#).

However, uninitialized data is not required here. Instead, you can use `ptr::read` to get the data referred to by `self`.

At this point, `tmp` has ownership of the data in the enum, but if we were to drop `self`, that data would attempt to be read by the destructor, causing memory unsafety.

We then perform our transformation and put the value back, restoring the safety of the type.

```
use std::ptr;

enum Foo<T> {
    Bar(T),
    Baz(T),
}

impl<T> Foo<T> {
    fn switch(&mut self) {
        // I copied this code from Stack Overflow without reading
        // the surrounding text that explains why this is safe.
        unsafe {
            let tmp = ptr::read(self);

            // Must not panic before we get to `ptr::write`

            let new = match tmp {
                Foo::Bar(val) => Foo::Baz(val),
                Foo::Baz(val) => Foo::Bar(val),
            };

            ptr::write(self, new);
        }
    }
}
```

More advanced versions of this code would **prevent** a panic from bubbling out of this code and instead cause the program to abort.

See also:

- [replace\\_with](#), a crate that wraps this logic up.
- [take\\_mut](#), a crate that wraps this logic up.
- [Change enum variant while moving the field to the new variant](#)
- [How can I swap in a new value for a field in a mutable reference to a structure?](#)

Share

Improve this answer

Follow

edited Jun 4 at 20:52

answered Feb 24 '20 at 18:42



Shepmaster

305k ● 59 ● 824 ● 1083

Add a comment



Your Answer

Post Your Answer



By clicking "Post Your Answer", you agree to our [terms of service](#), [privacy policy](#) and [cookie policy](#)

Not the answer you're looking for? Browse other questions tagged [rust](#) [ownership](#) [borrow-checker](#) or ask your own question.

The Overflow Blog

-  Sequencing your DNA with a USB dongle and open source code
-  Don't push that button: Exploring the software that flies SpaceX rockets and...

Featured on Meta

-  Providing a JavaScript API for userscripts
-  Congratulations to the 59 sites that just left Beta

Linked

Is there a safe way to temporarily retrieve an owned value from a mutable reference in Rust?

How can I swap out the value of a mutable reference, temporarily taking ownership?

moving out of borrowed content safely

2

Is there some unsafe way to take ownership of a contained value in order to mutate it?

How can I replace an element in a vector with another element based on the original

0

How to replace a struct in a vector using self consuming / mutator method

0

How can I apply an arbitrary in-place operation to a `&mut` reference?

0

How to reorder the elements of an array in-place?

0

Is there a clean way in Rust to mutate a `'&mut'` by replacing its value?

0

Is it possible to take temporary ownership of a struct field?

[See more linked questions](#)

Related

Can't borrow File from `&mut self` (error msg: cannot move out of borrowed content)

Cannot move out of borrowed content / cannot move out of behind a shared reference

6

cannot move out of borrowed content when unwrapping a member variable in a `&mut self` method

Get an enum field from a struct: cannot move out of borrowed content

"Cannot move out of borrowed content" while summing command line arguments

Cannot move out of borrowed content and Builder pattern

0






`&self` move field containing Box - Move out of borrowed content

How can I replace the value inside a Mutex?

Cannot move out of borrowed content for Box::into\_raw on self.attribute

Hot Network Questions

 What does "Γραεὸς Ἀργῶς" in this sentence mean? (LLpsl)

-  [Split polyline to equal parts using QGIS](#)
  -  [Company kept previous personal phone number](#)
  -  [Bit Rot within LUKS Encryption](#)
  -  [How does a river freeze when the water keeps moving?](#)
- [more hot questions](#)
-  [Question feed](#)

#### STACK OVERFLOW

[Questions](#)  
[Jobs](#)  
[Developer Jobs Directory](#)  
[Salary Calculator](#)  
[Help](#)  
[Mobile](#)

#### PRODUCTS

[Teams](#)  
[Talent](#)  
[Advertising](#)  
[Enterprise](#)

#### COMPANY

[About](#)  
[Press](#)  
[Work Here](#)  
[Legal](#)  
[Privacy Policy](#)  
[Terms of Service](#)  
[Contact Us](#)  
[Cookie Settings](#)  
[Cookie Policy](#)

#### STACK EXCHANGE NETWORK

[Technology](#)  
[Culture & recreation](#)  
[Life & arts](#)  
[Science](#)  
[Professional](#)  
[Business](#)  
[API](#)  
[Data](#)

[Blog](#)  
[Facebook](#)  
[Twitter](#)  
[LinkedIn](#)  
[Instagram](#)