

How to reuse a 'Result'?

Ask Question

Asked 1 year, 6 months ago Active 1 year, 6 months ago Viewed 111 times



0



The following does not compile. What's the canonical way to make this work?

```
let file = File::open(&args.path)?;
let reader = BufReader::new(file);
for line in reader.lines() {
   if line?.contains(&args.pattern) {
     println!(" {}", line?);
```

Here's the error message, for completeness:

```
34 | println!("{}", line?);
             ^^^ value used here after move
```



Improve this question

Follow edited Jun 20 '20 at 19:23 **3,071** • 1 • 11 • 21 asked Jun 20 '20 at 18:46



4,027 • 2 • 28 • 57

1 Answer

Active Oldest Votes



5



In your example line is a Result, which is moved when you use ? (but do we really need the Result after you've unwrapped its contents???). To alleviate your problem, let's shadow the value of the Result in a local variable of the same name.

```
for line in reader.lines() {
  let line = line?;
  if line.contains(&args.pattern) {
     println!("{}", line);
```

Share

Improve this answer edited Jun 20 '20 at 19:14

answered Jun 20 '20 at 18:55



Thanks. This was my initial solution, too. But as a developer coming from numerous other languages without Rust's ownership model, creating an extra local variable just felt wrong somehow.

Your privacy CXJ

By clicking "Actupt 211 2004 623;94 agree Stack Exchange can store cookies on your device and disclose information in accordance with our Cookie Policy.

```
Accept all cookies
                      Customize settings
```

I understand, it seems clunky at first. I believe (but am not positive) that when we shadow a variable by using the same name the previous value is dropped from memory, so it's not even incurring a performance hit; we're just making the borrow checker happy:)

- MeetTitan Jun 21 '20 at 23:43
Add a comment
Your Answer
Post Your Answer
By clicking "Post Your Answer", you agree to our terms of service, privacy policy and cookie policy
Not the answer you're looking for? Browse other questions tagged error-handling ust move ust-result or ask your own question.
The Overflow Blog
Sequencing your DNA with a USB dongle and open source code
Don't push that button: Exploring the software that flies SpaceX rockets and
Featured on Meta
. 0
Providing a JavaScript API for userscripts
Congratulations to the 59 sites that just left Beta
Related
How can I exclude all "permission denied" messages from "find"?
How can I get useful error messages in PHP?
How do I get PHP errors to display?
How to print an exception in Python?
Reference - What does this error mean in PHP?
How do I stop iteration and return an error when Iterator::map returns a Result::Err?
30 How to trace the cause of an error result?
Cannot find the position of a string within a file because the BufReader is used after it's moved
How to run for loop on elements of a vector and change the vector inside the for loop and outside the for loop in rust?
Why a borrowed error appears if I use a non mutable variable in various place of my code?
Hot Network Questions
What did John the Postict on short form that resulted in report form to put first in kind John 1041 42.
What did John the Baptist say about Jesus that resulted in many Jews in Jesus' time to put faith in him? John 10:41-42 What inspired the touch move rule?
What's the largest REG_SZ value that Regedit can edit?
How to force Mathematica to do infinite-precision calculations?
more hot questions
Question feed

STACK OVERFLOW

Questions Jobs Developer Jobs Directory Salary Calculator Help Mobile Teams Talent Advertising Enterprise

COMPANY

About
Press
Work Here
Legal
Privacy Policy
Terms of Service
Contact Us
Cookie Settings
Cookie Policy

STACK EXCHANGE NETWORK

Technology Culture & recreation Life & arts Science Professional Business API Data

Blog Facebook Twitter LinkedIn Instagram

site design / logo @2021 Stack Exchange Inc; user contributions licensed under cc by-sa. rev 2021.12.22.41046