

Products

How to swap two fields of a struct

Ask Question

Asked 5 years, 10 months ago Active 5 years, 10 months ago Viewed 693 times



5



I've started studying Rust and I'm trying to implement a simple 1D cellular automata. I want to represent the automata state (Board) as struct holding the size and two different vectors (of same size). I tried:

```
struct Board {
n: usize,
cur: Vec<u32>,
next: Vec<u32>,
}

impl Board {
fin new(size: usize) -> Board {
Board {
n: size,
cur: vec![0;size],
next: vec![0;size],
}
}
```

So far so good. I'm also able of mutating both vectors. But then I want to be able to swap both vectors (or rather their references), such as:

```
fn swap(&mut self) >> &Board {
    let tmp = self.cur;
    self.cur = self.next;
    self.next = tmp;
    self
}
```

It fails, with an cannot move out of borrowed content [E0507] which I think I can understand. I also tried mem:swap which I found in a similarly title question without success.

How can I make this example work? (Since I'm a total beginner with Rust, don't hesitate to suggest a different data representation).

```
struct reference rust swap
```

```
Improve this question
Follow
edited Feb 26 '16 at 14:39

Shepmaster
305k • 59 • 824 • 1083
asked Feb 26 '16 at 11:00

paradigmatic
39.3k • 18 • 86 • 145
```

2 Answers

Share

Active Oldest Votes





What's the problem?

You are **punching holes** in your data:

```
fin swap(&mut self) >> &Board {
let tmp = self.cur; // 1
self.cur = self.next; // 2
self.next = tmp; // 3
self
}
```

Your privacy

By clicking "Accept all cookies"; Aguagree Sack Exchange can store cookies on your device and disclose information in accordance with our Cookie Policy.

```
Accept all colokieself.cur Ciastom antinitialized
```

- 2. self.next is now uninitialized
- 3. everything is kosher again

If for some reason computation is interrupted before line (3) has a change to tighten up the situation, self is now poisoned and may cause all kinds of nasty things to happen. Notably, its destructor could attempt to free memory twice for example.

In theory, you could have the compiler check for temporary holes and prove, without doubt, that:

- no function accesses self while a hole is punched
- by the end of the scope, whether it is reached normally or by unwinding, the holes are filled up again

and indeed at some point it was considered... but the truth is that it's complicated and there are readily available work-arounds.

So

The answer lies in std::mem which exposes functions to perform such low-level operations in a safe manner. While the functions themselves are implemented using unsafe under the hood, they lean on their understanding of the language and runtime to expose safe interfaces.

The two particular functions that will interest you are:

- replace : replaces the content of dest: &mut T by src: T and returns the what was previously contained behind dest
- swap : exchanges the content of its arguments

With those two simple and safe primitives, you can avoid punching holes in your data.

```
Share
Improve this answer
Follow
edited Feb 26'16 at 14:39

Shepmaster
305k • 59 • 824 • 1083

answered Feb 26'16 at 12:52

Matthieu M.
261k • 40 • 396 • 665
```



As you noticed, mem:swap is the way to go:

```
fn swap(&mut self) >> &Board {
    std::mem::swap(&mut self.cur, &mut self.next);
    self
}
```

This works. Note that when using . you are dereferencing self . So while self has the type &mut Board , self.cur has the type Vec < u32 > . Therefore the compiler complained about "move out of borrowed content" and we need the additional &mut s.

Share Improve this answer Follow answered Feb 26 '16 at 11:08 Lukas Kalbertodt 61.1k • 18 • 189 • 248

Your Answer

Post Your Answer

By clicking "Post Your Answer", you agree to our terms of service, privacy policy and cookie policy

Not the answer you're looking for? Browse other questions tagged struct reference rust swap or ask your own question.

```
The Overflow Blog
```

	Don't push that button: Exploring the software that flies SpaceX rockets and
	Featured on Meta
•	0
	Providing a JavaScript API for userscripts
•	Conceptuations to the States that just left Date
	Congratulations to the 59 sites that just left Beta
	Related
	What's the difference between struct and class in .NET?
	When should you use a class vs a struct in C++? 1523
	When should I use a struct rather than a class in C#?
	Difference between 'struct' and 'typedef struct' in C++?
	How do I pass a variable by reference? 1174
	How to copy a dictionary and only edit the copy
	List changes unexpectedly after assignment. Why is this and how can I prevent it?
	Is there a standardized method to swap two variables in Python?
	How to print struct variables in console?
	Hot Network Questions
	Who (or what) created the atropal?
	What does the numbers mean in this guitar tab if they already gave the chords to play?
	If we can get people to the moon and back, why are we so adamant that it's impossible to service James Webb at 4x that with a one way robotic vehicle?
	[S] Have there been no deaths due to omicron in Africa?
	What's the largest REG_SZ value that Regedit can edit?
	more hot questions
	Question feed
STACK OVERN	
STACK OVERF Questions	LUW .
Jobs Developer Jobs I	Directory
Salary Calculator Help	
Mobile	
PRODUCTS Teams	
Talent Advertising	
Enterprise	
COMPANY	
About Press	
Work Here Legal	
Privacy Policy Terms of Service	
Contact Us Cookie Settings Cookie Policy	
	ANGENETWORK
Technology Culture & recreat	tion
Life & arts Science	
Professional Business	
API Data	
Blog	

Blog Facebook Twitter LinkedIn Instagram site design / logo © 2021 Stack Exchange Inc; user contributions licensed under cc by-sa. rev 2021.12.22.41046