



Products

# How do Rust closures work and how does it execute a closure?

[Log in](#) [Sign up](#)

[Ask Question](#)

Asked 4 years, 4 months ago

Active 4 years, 4 months ago

Viewed 889 times



4



Does it create a new thread and then execute that anonymous function inside the new thread?

I noticed many ownership / borrowing restrictions when I'm working with a closure. For example, if I have `Fn()` , [I cannot pass a mutable variable inside the closure or it needs to be wrapped with a `Mutex`](#) :

```
fn helloworld(f: &Fn(f64)) {  
    f(42f64);  
}  
  
pub fn main() {  
    let mut killer = 2;  
    helloworld(&|n| {  
        println!("{}", n);  
        killer += 1;  
    });  
}
```

If a closure can be unsafe like that then something asynchronous or parallel is going on behind the scene and that's why Rust compiler doesn't let me to compile such code.

I might just be confused because I'm coming from a JavaScript / Python world and things are completely different there.

[multithreading](#) [rust](#) [closures](#)

[Share](#)

[Improve this question](#)

[Follow](#)

edited Aug 29 '17 at 12:54



Shepmaster

305k ● 59 ● 824 ● 1083

asked Aug 29 '17 at 9:14



Afshin Mehrabani

29.6k ● 26 ● 121 ● 191

1

A closure is an anonymous function with variable capture, it is not multithreaded (unless you ask for it). Moreover, could you post the code you refer to, when you say "if I have `Fn()` , I cannot pass a mutable variable inside the closure or it needs to be wrapped with a `Mutex` "?

– Boiethios

Aug 29 '17 at 9:17

@Boiethios sure, just updated the question with a link.

– Afshin Mehrabani

Aug 29 '17 at 9:21

You need to use `FnMut` : [play.rust-lang.org/...](http://play.rust-lang.org/) But I let someone with more knowledge to answer with detailed explanations.

– Boiethios

Aug 29 '17 at 9:25

@Boiethios that is correct, changing to `FnMut` or using a `Mutex` can solve the problem but my question is, why? If it is not a separate thread, why it should be even important to pass a `Mutex`?

– Afshin Mehrabani

Aug 29 '17 at 9:29

[Add a comment](#)

1 Answer

[Active](#) [Oldest](#) [Votes](#)



21



## Your privacy

By clicking "Accept all cookies", you agree Stack Exchange can store cookies on your device and disclose information in accordance with our [Cookie Policy](#).



Accept all cookies. There are two options to this question.

First, a closure in Rust is just an anonymously-defined type that implements one or more "callable" traits. For example, this:

```
fn main() {
    let a = 6;
    let closure = |b| {
        println!("product is: {}", a * b);
    };
    closure(7);
}
```

is de-sugared into something similar to:

```
fn main() {
    let a = 6;
    let closure = {
        struct Closure<a> {
            a: &a i32,
        }
        impl<a> Fn<(i32,> for Closure<a> {
            extern "rust-call" fn call(&self, (b,): (i32,)) {
                println!("product is: {}", (*self.a) * b);
            }
        }
        impl<a> FnMut<(i32,> for Closure<a> {
            extern "rust-call" fn call_mut(&mut self, args: (i32,)) {
                self.call(args)
            }
        }
        impl<a> FnOnce<(i32,> for Closure<a> {
            type Output = ();
            extern "rust-call" fn call_once(self, args: (i32,)) {
                self.call(args)
            }
        }
        Closure {
            a: &a,
        }
    };
    FnOnce::call_once(closure, (7,));
}
```

**Note:** the above code relies on unstable, internal details and will not work on a stable compiler. It is provided for explanation only; you should **not** use this pattern yourself.

There's no threading involved, and nothing magical is happening. They boil down to a regular function call with an extra initial "context" argument.

This brings us to the second layer, which is why your *specific* code doesn't work: *because you told the compiler to forbid it*. One critical concern for callables is how the context is passed to the callable's code. This is represented by the `Fn`, `FnMut` and `FnOnce` traits (which are explained in the answer to the question [When does a closure implement Fn, FnMut and FnOnce?](#)). By taking `&Fn(i64)`, you've restricted yourself to only accepting closures which require immutable access to their context.

If you want a closure to be able to mutate its context, you need to use `FnMut` instead. Or, if you only need to call a closure once, you can use `FnOnce` (although not as a trait object like you're doing in your example).

Share

Improve this answer

Follow

edited Aug 29 '17 at 12:55



Shepmaster

305k • 59 • 824 • 1083

answered Aug 29 '17 at 9:38



DK.

47.4k • 3 • 150 • 142

2

Oh wow, this is a nice and clear explanation. Thank you so much DK.

— Afshin Mehrabani

Aug 29 '17 at 9:59

Add a comment



Your Answer

Post Your Answer

By clicking "Post Your Answer", you agree to our [terms of service](#), [privacy policy](#) and [cookie policy](#)



Not the answer you're looking for? Browse other questions tagged [multithreading](#) [rust](#) [closures](#) or ask your own question.

The Overflow Blog

-  Sequencing your DNA with a USB dongle and open source code
-  Don't push that button: Exploring the software that flies SpaceX rockets and...

#### Featured on Meta

---

-  Providing a JavaScript API for userscripts
-  Congratulations to the 59 sites that just left Beta

#### Linked

[When does a closure implement Fn, FnMut and FnOnce?](#)

[Are Rust closures stack-allocated or heap-allocated by default?](#)

["the ``and\_then`` method cannot be invoked on a trait object" error when type annotations are added to the ``and\_then``](#)

#### Related

[How do JavaScript closures work?](#)

[What is the difference between a 'closure' and a 'lambda'?](#)

[When and how should I use a ThreadLocal variable?](#)

[In PHP, what is a closure and why does it use the "use" identifier?](#)

[How do servlets work? Instantiation, sessions, shared variables and multithreading](#)

[C++11 introduced a standardized memory model. What does it mean? And how is it going to affect C++ programming?](#)






[Why doesn't println! work in Rust unit tests?](#)

[When does a closure implement Fn, FnMut and FnOnce?](#)

[Method not compatible with trait with confusing error message](#)

[Rust cloned closures expected closure, found different closure](#)

#### Hot Network Questions

-  [How to install a package via `'apt-get'` without flagging it as manually installed](#)
-  [Help identify a short story about professor using voodoo doll to prevent the marriage of a much younger woman he loves - by Henry Slesar](#)
-  [Is the science in "Don't Look Up" realistic?](#)
-  [Why couldn't Smith absorb Neo in The Matrix Reloaded?](#)
-  [Using a friend to move cash into my checking account](#)

[more hot questions](#)

 [Question feed](#)

#### STACK OVERFLOW

[Questions](#)  
[Jobs](#)  
[Developer Jobs Directory](#)  
[Salary Calculator](#)  
[Help](#)  
[Mobile](#)

#### PRODUCTS

[Teams](#)  
[Talent](#)  
[Advertising](#)  
[Enterprise](#)

#### COMPANY

[About](#)  
[Press](#)  
[Work Here](#)  
[Legal](#)  
[Privacy Policy](#)  
[Terms of Service](#)  
[Contact Us](#)  
[Cookie Settings](#)  
[Cookie Policy](#)

#### STACK EXCHANGE NETWORK

[Technology](#)  
[Culture & recreation](#)  
[Life & arts](#)  
[Science](#)  
[Professional](#)  
[Business](#)  
[API](#)  
[Data](#)

[Blog](#)  
[Facebook](#)  
[Twitter](#)  
[LinkedIn](#)  
[Instagram](#)

site design / logo © 2021 Stack Exchange Inc; user contributions licensed under [cc by-sa](#). rev 2021.12.22.41046