



Products

Changing a vector inside a closure gives "borrow of moved value" error

Log in or Sign up

Ask Question

Asked 1 year, 11 months ago

Active 1 year, 11 months ago

Viewed 995 times



1



I am trying to change the elements of a vector inside a closure:

```
pub struct Foo<A, T> {
    cb: Box<dyn FnMut(Vec<T>) + 'a>,
}

impl<A, T> Foo<A, T> {
    pub fn new<F: FnMut(Vec<T>) + 'a>(cb: F) -> Self {
        Self { cb: Box::new(cb) }
    }

    pub fn fun(&mut self, v: T) {
        let vector = vec![v];
        (self.cb)(vector);
    }
}

fn main() {
    let mut a = Vec::new();
    let mut foo = Foo::new(move |v| {
        for i in v {
            a.push(i);
        }
    });
    foo.fun(1);
    println!("{}", a);
}
```

[Playground](#)

I'm getting an error:

```
error[E0382]: borrow of moved value: 'a'
  --> src/main.rs:24:22
   |
17 |   let mut a = Vec::new();
   |   ----- move occurs because 'a' has type 'std::vec::Vec<i32>', which does not implement the 'Copy' trait
18 |   let mut foo = Foo::new(move |v| {
   |   ----- value moved into closure here
19 |       for i in v {
20 |           a.push(i);
   |           - variable moved due to use in closure
...
24 |   println!("{}", a);
   |               ^ value borrowed here after move
```

I understand that Rust can't copy the value of `a` in the closure because `Vec` does not implement the trait `Copy`, so it has to move it, and moving `a` as mutable makes it unusable by `println!` later.

Am I storing the closure correctly? Is the use of the lifetime `'a` correct here? Should I wrap the vector in something like `Box` or `Cell`?

[rust](#)

Share

Improve this

question

Follow

edited Jan 21 '20 at 14:58



Shepmaster

305k ● 59 ● 824 ● 1083

asked Jan 21 '20 at 14:56



Alex Covizzi

671 ● 7 ● 8

1

Why have you chosen to require ownership of the `Vec` in the closure argument (`FnMut(Vec<T>)`)?

– Shepmaster

Jan 21 '20 at 15:00

Your privacy

By clicking “Accept all cookies”, you agree Stack Exchange can store cookies on your device and disclose information in accordance with our [Cookie Policy](#).

You can solve your problem by [removing the move](#) and [ensuring that the mutable borrow ends before the immutable borrow](#).

– Shepmaster

Accept all cookies or customize settings

What if i need to use `a` before `foo` is dropped?

– AlexCovizzi

Jan 21 '20 at 15:09

1

Then it's a duplicate of [Can't borrow mutably within two different closures in the same scope](#)

– Shepmaster

Jan 21 '20 at 15:10

[Add a comment](#)

1 Answer

[Active](#) [Oldest](#) [Votes](#)



1



Here's the solution ([playground](#)):

```
pub struct Foo<a, T> {
    cb: Box<dyn FnMut(Vec<T>) + 'a>,
}

impl<a, T> Foo<a, T> {

    pub fn new<F: FnMut(Vec<T>) + 'a>(cb: F) -> Self {
        Self {
            cb: Box::new(cb),
        }
    }

    pub fn fun(&mut self, v: T) {
        let vector = vec![v];
        (self.cb)(vector);
    }
}

fn main() {
    let mut a = Vec::new();

    // new scope to make sure that 'foo' isn't alive when 'a' is borrowed later
    {
        // no 'move' to prevent moving 'a' into the closure
        let mut foo = Foo::new(|v| {
            a = v.clone();
        });
        foo.fun(1);
    }
    println!("{}", a);
}
```

[Share](#)

[Improve this answer](#)

Follow

answered Jan 21 '20 at 19:22



Aloso

4,380 ● 4 ● 21 ● 36

[Add a comment](#)

Your Answer


Post Your Answer

By clicking "Post Your Answer", you agree to our [terms of service](#), [privacy policy](#) and [cookie policy](#)



Not the answer you're looking for? Browse other questions tagged [rust](#) or ask your own question.

The Overflow Blog

- Sequencing your DNA with a USB dongle and open source code

-  Don't push that button: Exploring the software that flies SpaceX rockets and...

Featured on Meta

-  Providing a JavaScript API for userscripts
-  Congratulations to the 59 sites that just left Beta

Linked

[Can't borrow mutably within two different closures in the same scope](#)

Related

[Borrow errors for multiple borrows](#)

[Reference to unwrapped property fails: use of partially moved value: `self`](#)

[Why does the closure take ownership of the vector here?](#)

[How to compute arithmetic operations on a borrowed vector of elements that lack Copy in Rust?](#)

[I the trait `embedded_hal::digital::InputPin` is not implemented for `PE2<Output<OpenDrain>>`](#)

[Awaiting a Number of Futures Unknown at Compile Time](#)

[Declaring Associated Type of Trait Object in Async Function Parameter](#)

Hot Network Questions

 which one of these paths has the priority: `/usr` or `/usr/local`

 What is this large long-legged orange and black insect?

 Are they already planning a successor to the JWST?

 How much of the English history in this Decameron story has any basis in fact?

 Company kept previous personal phone number

[more hot questions](#)

 [Question feed](#)

STACK OVERFLOW

[Questions](#)
[Jobs](#)
[Developer Jobs Directory](#)
[Salary Calculator](#)
[Help](#)
[Mobile](#)

PRODUCTS

[Teams](#)
[Talent](#)
[Advertising](#)
[Enterprise](#)

COMPANY

[About](#)
[Press](#)
[Work Here](#)
[Legal](#)
[Privacy Policy](#)
[Terms of Service](#)
[Contact Us](#)
[Cookie Settings](#)
[Cookie Policy](#)

STACK EXCHANGE NETWORK

[Technology](#)
[Culture & recreation](#)
[Life & arts](#)
[Science](#)
[Professional](#)
[Business](#)
[API](#)
[Data](#)

[Blog](#)
[Facebook](#)
[Twitter](#)
[LinkedIn](#)
[Instagram](#)