



Products

Why is "&&" being used in closure arguments?

Login

Sign up

Ask Question

Asked 4 years, 7 months ago

Active 2 years, 5 months ago

Viewed 2k times



18



5



I have two questions regarding [this example](#):

```
let a = [1, 2, 3];
```

```
assert_eq!(a.iter().find(|&&x| x == 2), Some(&2));
```

```
assert_eq!(a.iter().find(|&&x| x == 5), None);
```

1. Why is `&&x` used in the closure arguments rather than just `x`? I understand that `&` is passing a reference to an object, but what does using it twice mean?

I don't understand what the documentation says:

Because `find()` takes a reference, and many iterators iterate over references, this leads to a possibly confusing situation where the argument is a double reference. You can see this effect in the examples below, with `&&x`.

2. Why is `Some(&2)` used rather than `Some(2)`?

[reference](#) [rust](#) [borrowing](#)

Share

Improve this question

Follow

edited Jul 10 '19 at 14:04



Shepmaster

305k • 59 • 824 • 1083

asked May 7 '17 at 5:03



Sijak

2,001 • 3 • 13 • 31

Add a comment

2 Answers

[Active](#) [Oldest](#) [Votes](#)



24



`a` is of type `[i32; 3]`; an array of three `i32`s. `[i32; 3]` does not implement an `iter` method, but it *does* dereference into `&[i32]`. [&\[i32\] implements an iter method](#) which produces an iterator. [This iterator](#) implements `Iterator::Item=&i32`.

It uses `&i32` rather than `i32` because the iterator has to work on arrays of *any* type, and not all types can be safely copied. So rather than restrict itself to copyable types, it iterates over the elements by reference rather than by value.

[find](#) is a method defined for all `Iterator`s. It lets you look at each element and return the one that matches the predicate. Problem: if the iterator produces non-copyable values, then passing the value into the predicate would make it impossible to return it from `find`. The value cannot be re-generated, since iterators are not (in general) rewindable or restartable. Thus, `find` has to pass the element to the predicate by-reference rather than by-value.

So, if you have an iterator that implements `Iterator::Item=T`, then `Iterator::find` requires a predicate that takes a `&T` and returns a `bool`. `[i32]::iter` produces an iterator that implements `Iterator::Item=&i32`. Thus, `Iterator::find` called on an array iterator requires a predicate that takes a `&&i32`. That is, it passes the predicate a pointer to a pointer to the element in question.

So if you were to write `a.iter().find(|x|..)`, the type of `x` would be `&&i32`. This cannot be directly compared to the literal `i32` value `2`. There are several ways of fixing this. One is to explicitly dereference `x`: `a.iter().find(|x| **x == 2)`. The other is to use pattern matching to destructure the double reference: `a.iter().find(|&&x| x == 2)`. These two approaches are, in this case, doing *exactly* the same thing. [1]

As for why `Some(&2)` is used: because `a.iter()` is an iterator over `&i32`, *not* an iterator of `i32`. If you look at the documentation for `Iterator::find`, you'll see that for `Iterator::Item=T`, it returns an `Option<T>`. Hence, in this case, it returns an `Option<&i32>`, so that's what you need to compare it against.

[1]: The differences only matter when you're talking about non-Copy types. For example, `|&&x|..` wouldn't work on a `&&String`, because you'd have to be able to move the `String` out from behind the reference, and that's not allowed. However, `|x| **x..` *would* work, because that is just reaching inside the reference without moving anything.

By clicking "Accept all cookies", you agree Stack Exchange can store cookies on your device and disclose information in accordance with our [Cookie Policy](#).

Share

Improve this answer

Follow

answered May 7 '17 at 6:05

Your privacy

Accept all cookies

Customize settings



DK

47.4k ● 3 ● 150 ● 142

2

thanks! Additionally, in case if anyone doesn't understand what is "*dereference into* [this](#)", an array `a` can be automatically borrowed as a slice `&a` according to [this](#).

– Sajuuk

May 7 '17 at 7:10

[Add a comment](#)



4



1) I thought the book explanation was good, maybe my example with `.cloned()` below will be useful. But since `.iter()` iterates over references, you have to specify reference additionally because `find` expects a reference.

2) `.iter()` is iterating over references; therefore, you find a reference.

You could use `.cloned()` to see what it would look like if you didn't have to deal with references:

```
assert_eq!(a.iter().cloned().find(|&x| x == 2), Some(2));
```

[Share](#)

[Improve this answer](#)

[Follow](#)

answered May 7 '17 at 5:50



Akavall

72.9k ● 43 ● 190 ● 235

[Add a comment](#)

Your Answer

Post Your Answer

By clicking "Post Your Answer", you agree to our [terms of service](#), [privacy policy](#) and [cookie policy](#)

Not the answer you're looking for? Browse other questions tagged [reference](#) [rust](#) [borrowing](#) or [ask your own question](#).

The Overflow Blog

- [Sequencing your DNA with a USB dongle and open source code](#)
- [Don't push that button: Exploring the software that flies SpaceX rockets and...](#)

Featured on Meta

- [Providing a JavaScript API for userscripts](#)
- [Congratulations to the 59 sites that just left Beta](#)

Linked

1

[Why does 'find' take a parameter by reference and then dereference it?](#)

0

[Reference to reference in rust](#)

[What is an idiomatic way to collect an iterator of &T into a collection of Ts?](#)

[Is Vec<&&str> the same as Vec<&Str>?](#)

[Can't compare '&Thing' with 'Thing'](#)

[How to use a vector of string slices](#)

0

[References to references usage](#)

Related

[Why is 'this' a pointer and not a reference?](#)

[List changes unexpectedly after assignment. Why is this and how can I prevent it?](#)

[When to use references vs. pointers](#)

[Why does the argument for the find closure need two ampersands?](#)

3

[When to use Box instead of reference?](#)

[Why is it discouraged to accept a reference to a String \(&String\), Vec \(&Vec\), or Box \(&Box\) as a function argument?](#)

0

[Return and consume an iterator of mutable references from a closure](#)

[Mutating fields of Rc RefCell depending on its other internal fields](#)

Hot Network Questions

 [Is it possible to convert a taproot address into a native segwit address?](#)

 [How am I able to simulate gears on my single speed?](#)

 [Split polyline to equal parts using QGIS](#)

 [Numbers, Racked Up](#)

 [Company kept previous personal phone number](#)

[more hot questions](#)

 [Question feed](#)

STACK OVERFLOW

[Questions](#)
[Jobs](#)
[Developer Jobs Directory](#)
[Salary Calculator](#)
[Help](#)
[Mobile](#)

PRODUCTS

[Teams](#)
[Talent](#)
[Advertising](#)
[Enterprise](#)

COMPANY

[About](#)
[Press](#)
[Work Here](#)
[Legal](#)
[Privacy Policy](#)
[Terms of Service](#)
[Contact Us](#)
[Cookie Settings](#)
[Cookie Policy](#)

STACK EXCHANGE NETWORK

[Technology](#)
[Culture & recreation](#)
[Life & arts](#)
[Science](#)
[Professional](#)
[Business](#)
[API](#)
[Data](#)

[Blog](#)
[Facebook](#)
[Twitter](#)
[LinkedIn](#)
[Instagram](#)

site design / logo © 2021 Stack Exchange Inc; user contributions licensed under [cc by-sa](#). rev 2021.12.22.41046