

Products

How to have multiple references for a single node in a tree structure using Rust

Ask Question

Asked 2 years, 1 month ago Active 2 years, 1 month ago Viewed 756 times



2



Trying to create a tree in rust with the following struct:

```
pub struct Node{
    pub children: Vec<Box<Node>>,
    pub parent: Option<Box<Node>>,
    pub value: f32,
    //.....
}
```

To build a new node the following function is used:

When trying to add nodes, for example with:

```
let mut root_nd = tree::build_node(None, 5, state);
let mut next_nd = tree::build_node(Some(Box:new(root_nd)), 2);
root_nd.children.push(Box:new(next_nd));
```

There will be errors, because I am borrowing for example <code>root_nd</code> and then trying to add <code>next_nd</code> to the <code>root_children</code> list, and even if there wasnt this error I would still need to have a reference for <code>next_nd</code> after adding it to the children of <code>root_nd</code>. I know that in rust it is not possible to have several mutable references simultaneously for the same element. So the question is how is it possible to make a tree-like data structure, with bi-directional references in rust? In my head this is a conflict since rust does not want multiple references but I need a node in the middle of the tree to be referenced by both his parent node and his children nodes.



1 Answer

Active Oldest Votes









I've been meddling with trees in Rust for quite a bit recently. To work with trees in rust, you will need Re (A single-threaded reference-counting pointer) so that you can have multiple ownership. And you'll also need RefCell to enable interior mutability since multiple mutable references are not allowed by the compiler. With Rc and RefCell, you can define your TreeNode as following:

```
use std::rc::Rc;
use std::rcell::RefCell;
pub struct TreeNode {
    pub children: Vec<Re<RefCell<TreeNode>>>,
    pub parent: Option<Rc<RefCell<TreeNode>>>,
    pub value: f32,
}
```

Your privacy

By clicking "AAUG htts: dkiens, was to state throughoutes that the state all states information in accordance with our Cookie Policy.

```
impl TreeNode {
         #[inline]
        pub fn new(value: f32) > Self {
             TreeNode {
              value,
children: vec![],
              parent: None
     \label{eq:continuous_problem}  \mbox{let mut root\_nd} = Rc::new(RefCell::new(TreeNode::new(5.0))); \\ \mbox{let mut child\_nd} = Rc::new(RefCell::new(TreeNode::new(2.0))); \\ \mbox{let mut child\_nd} = Rc::new(RefCell::new(TreeNode::new(2.0))); \\ \mbox{let mut child\_nd} = Rc::new(RefCell::new(TreeNode::new(5.0))); \\ \mbox{let mut child\_nd} = Rc::new(5.0)); \\ \mbox{let mut child\_nd} = Rc::new(5
     child_nd.borrow_mut().parent = Some(root_nd.clone()); // use Rc::clone to create a new reference to root_nd
     root_nd.borrow_mut().children.push(child_nd.clone());
Since we use Reciclone to create a new reference to the node, root_nd and child_nd are not consumed and can still be accessed in later program.
More examples on Trees in Rust:
       • leetcode 95 Unique Binary Search Trees
       • <u>leetcode 94 Binary Tree Inorder Traversal</u>
       • leetcode 100 Is Same Tree
Share
Improve this answer
Follow
   edited Nov 3 '19 at 19:14
    answered Nov 3 '19 at 18:54
       188k • 24 • 281 • 306
   There are other solutions, like using arenas to store the nodes and use indexes or ids as "pointers" (look for example for id-arena).
    - Denys Séguret
   Nov 3 '19 at 19:29
  So every time I want to use it, I should pass the full re<refcell<...> to the function and then use borrow_mut() to extract and access its elements?
    - Miguel
  Nov 3 '19 at 20:00
  It depends on what you want to do. Normally a node is represented as \\ let node: Option < Rc < RefCell < TreeNode>>> . And when you pass the reference to the function, you probably need to clone \\ let node: Option < Rc < RefCell < TreeNode>>> . And when you pass the reference to the function, you probably need to clone \\ let node: Option < Rc < RefCell < TreeNode>>> . And when you pass the reference to the function, you probably need to clone \\ let node: Option < Rc < RefCell < TreeNode>>> . And when you pass the reference to the function, you probably need to clone \\ let node: Option < Rc < RefCell < TreeNode>>> . And when you pass the reference to the function, you probably need to clone \\ let node: Option < Rc < RefCell < TreeNode>>> . And when you pass the reference to the function, you probably need to clone \\ let node: Option < Rc < RefCell < TreeNode>>> . And when you pass the reference to the function, you probably need to clone \\ let node: Option < Rc < RefCell < TreeNode>>> . And when you pass the reference to the function, you probably need to clone \\ let node: Option < Rc < RefCell < TreeNode>>> . And when you pass the reference to the function, you probably need to clone \\ let node: Option < Rc < RefCell < TreeNode>>> . And when you pass the reference to the function, you probably need to clone \\ let node: Option < Rc < RefCell < TreeNode>>> . And when you pass the reference to the function, you probably need to clone \\ let node: Option < Rc < RefCell < TreeNode>>> . And when you pass the reference to the function of the reference in the reference of the reference in the reference of the reference in the referenc
  it so that the current reference is not moved. i.e. somefun(node.clone()). And to access its elements, use borrow (immutable) or borrow mut (mutable).
    – Psidom
   Nov 3 '19 at 21:18 🥒
  @Psidom I got it working after some grinding! Thank you. Just one more thing, why do you like to use option on the <Rc<RefCell? In your use case it can be passed as None? Because I did not
  need it yet.
   Nov 4 '19 at 0:44
  Use Option here b/c the parent can be None, and btw None by itself is of type Option so if a value can be None, then its type must be Option.
  Nov 4 '19 at 3:29
Your Answer
     Post Your Answer
By clicking "Post Your Answer", you agree to our terms of service, privacy policy and cookie policy
Not the answer you're looking for? Browse other questions tagged reference rust tree or ask your own question.
        The Overflow Blog
         Sequencing your DNA with a USB dongle and open source code
```

Don't push that button: Exploring the software that flies SpaceX rockets and..

Q Providing a JavaScript API for userscripts 0 Congratulations to the 59 sites that just left Beta Related What is the most efficient/elegant way to parse a flat table into a tree? How to implement a tree data-structure in Java? Borrow errors for multiple borrows How can I deserialize a tree of references in Rust? Is there a way to iterate over a mutable tree to get a random node? Why Rust prevents from multiple mutable references? How do I properly insert into a Rust AVL Tree? Hot Network Questions Does saying "Keep it up" put me in an authoritative position? Why doesn't dkim sign the letter? (a) Can a Pyromancer Sorcerer deal fire damage to a creature under the effect of Invulnerability? Why did the JWST solar array deploy early? more hot questions

STACK OVERFLOW

Question feed

Questions Jobs Developer Jobs Directory Salary Calculator Help Mobile

PRODUCTS

Teams Talent Advertising Enterprise

COMPANY

About
Press
Work Here
Legal
Privacy Policy
Terms of Service
Contact Us
Cookie Settings
Cookie Policy

STACK EXCHANGE NETWORK

Technology Culture & recreation Life & arts Science Professional Business API Data

Blog Facebook Twitter LinkedIn Instagram

site design / logo © 2021 Stack Exchange Inc; user contributions licensed under cc by-sa. rev 2021.12.22.41046