

Tracker Meeting: simulation of the first station calibration in a vertical position

Sara Gamba, University of Pisa Pavel Murat, FNAL

April 29th 2024




figures/pdf/cherub

Cosmics simulation and selection criteria

- A simulation has been performed to reconstruct cosmics for the calibration of the station, which is vertically oriented, aiming to understand possible biases in determining longitudinal position caused by the non-uniform illumination of a panel;
- Selection of the first station;
- Vertical and extracted position;
- No magnetic field;
- To reconstruct a straight line in 3D, at least 4 hits at different z are needed: tracks selected with nhits_{facei} ≥ 1;
- To improve the resolution, $nhits_{panel} \le 3$ were selected.


Panel illumination





Reconstruction of Cosmic tracks

- The station is not yet calibrated: whether a straw has been hit or not is the only info we have;
- The reconstruction of the hit position is performed using:
 - the straw direction:
 - the straw midpoints (x, y);
 - the straw z coordinate.
- The intersection of two straw in two different faces, in the same plane, is considered to be the hit point;



Combo, Stereo Hits and Reconstructed line

1. Geometrical Combo Hits

Determination of a unique straw in a panel:

- mean of straws midpoint (x_m, y_m, z_m) ;
- straws direction (D_x, D_y) .

2. Geometrical Stereo Hits

Determination of the hit point in a plane:


- intersection point (x, y) using the two straws directions and midpoints;
- mean of z coordinate between the two faces.


3. Reconstructed Line


Determination of a unique reconstructed track:


- one stereo hit per plane: one line reconstructed geometrically;
- the intersection point of the line with panels is found knowing the z_m coordinate.

Results











6/10

long. pos. [mm]


Results





Conclusions

Backup Slide



Backup Slide

