



Machine Learning

SILVERIO GARCÍA CORTÉS


ASSOCIATE PROF. UNIVERSITY OF OVIEDO

MAY 23, NAPLES

PREPARED FOR UNIV. FEDERICO II

Input Data Structure I: (e.g for classification, clustering, etc)

- X data matrix
- Each row of X is a sample
- Each sample is composed of values for different features.
- A sample is then composed of a set of values for the features that represent it. It is thus possible to represent each sample by a point in a feature space.
- The true classes of each sample are provided in the vector "y".
- (they must be known for training in supervised learning)



Feature space: Iris dataset

Classes: 3 (50 muestras, 50, 50)

+Setosa, versicolor, virginica

Descriptors:

+Sepal Length, Sepal Width, Petal Length and Petal Width

Data Matrix

Rows: samples

muestra x^m

$$X = \begin{bmatrix} x_1^{(1)} & x_2^{(1)} & \dots & x_n^{(1)} \\ x_1^{(2)} & x_2^{(2)} & \dots & x_n^{(2)} \\ \dots & \dots & \dots & \dots \\ x_1^{(m)} & x_2^{(m)} & \dots & x_n^{(m)} \end{bmatrix}$$

True Class Vector


Supervised learning only

$$y = \begin{bmatrix} y^{(1)} \\ y^{(2)} \\ \dots \\ y^{(m)} \end{bmatrix}$$

característica $x_j^{(i)}$
Cols: features

Input data Structure II: Multispectral Imagery

Multi-band imagery can also be reshaped as the previous data matrix:




$$\mathbf{X} = \begin{bmatrix} \text{Band 1} & x_1^{(1)} & x_2^{(1)} & \dots & x_n^{(1)} & \text{Band } m \\ \text{Pixel 2} & x_1^{(2)} & x_2^{(2)} & \dots & x_n^{(2)} & \\ \vdots & \vdots & \vdots & \vdots & \vdots & \\ \text{Pixel } n & x_1^{(m)} & x_2^{(m)} & \dots & x_n^{(m)} & \end{bmatrix}$$

Unsupervised Learning: Clustering



Clustering

- Image clustering is a technique to group an image into clusters (units: groups of pixels) that are homogeneous with respect to one or more characteristics.
- It is applied when the features which define the interest classes are unknown or not well defined.
- In other classes this methods are used to discover groups of data with similar patterns.
- Commonly the algorithms use to start with a tentative number of clusters and each pixel is initially assigned to one of them
- During processing each sample can be reassigned to other clusters depending on some criterio. These criterio use to be given as thresholds, dispersion measurements for each cluster and some other parameters connected with a sort of "total energy" for all the samples grouping.
- In some algorithms the number of classes are fixed during all the processing and this number is set by the user.
- In other algorithms the user set an initial number of desired clusters and additional criteria that allow this number to evolve during the iterations. umbrales decisión para agrupamiento, separación y eliminación de clusters
- Some criteria for number of cluster evolution:
 - Número máximo de clusters. Maximum number of clusters allowed
 - Minimum Cluster center distance for aggregation.
 - Maximum cluster radius for cluster division (Splitting)
 - Minimum number of elements on a cluster (Cluster elimination)
- Different measurements can be also used to measure the "compactness" of a cluster (dispersion around the center). Standard deviation for each spectral band.
- There also exists different implementations of the same basic algorithms with different. Criteria and variants.
- Common algorithms for unsupervised learning in Satellite Remote Sensing are:
 - k-means , Isodata

Morro Bay Comp. 234 Unsup Classif. 15 Clusters



CLUSTERING: K-MEANS (MOBILE MEANS ALG.)



Pro:

- Fully automatic algorithm

Cons:

- Different possible solutions depending on initial values
- Fixed number of clusters must set a priori (before processing)

Global Function:
$$J = \sum_{j=1}^k \sum_{i \in \text{class } j} |x_i^j - m_j|^2$$