Memory-Efficient Speculative Decoding with Quantized Draft KV Cache

Saksham Gupta*
Carnegie Mellon University
sakshamg@andrew.cmu.edu

Michael Li*
Carnegie Mellon University
ml7@andrew.cmu.edu

Abstract

Speculative decoding reduces generation cost, but it stores two KV caches: one for the target model and one for the draft model. We reduce this extra memory by quantizing the draft cache. The target cache and verifier remain in BF16, so that compression cannot change the target model's final correction rule. We first study how to divide precision between keys and values. A naive per-token quantizer makes keys appear much more sensitive: splitting a 12-bit budget, K8V4 beats K4V8 in acceptance by 10.87 pp. However, with grouped per-channel keys, the gap becomes -0.25 pp. A controlled Qwen test confirms that changing only the key quantizer can erase or reverse the preferred bit split. Hence, following KIVI, we propose K4V4 quantization with per-channel keys and per-token values. Across six model pairs, our method reduces draft cache memory by 66.20%, and combined memory across both caches by 23.95%. Mean acceptance drops from 57.93% to 57.14%, only 1.36% relative. Overall, quantized draft caches can make speculative decoding more memory efficient; as a predictive principle for efficient AI design, key and value precision must be co-designed with the quantizer layout.

1 Introduction

Speculative Decoding (SD) improves LLM inference latency by letting a small *draft* model propose tokens that a larger *target* model verifies in parallel [Leviathan et al., 2023, Chen et al., 2023]. Draft tokens are accepted sequentially until the first rejection, at which point a corrected token is sampled from the target model and generation continues from there. This maintains the target output rule while reducing the number of expensive target forward passes.

However, standard SD maintains a KV cache for each model, increasing memory pressure as context length and batch size grow. Let Mem_T and Mem_D be the target and draft cache sizes. Standard SD stores $\text{Mem}_T + \text{Mem}_D$. We instead store $\text{Mem}_T + \widehat{\text{Mem}}_D$, where $\widehat{\text{Mem}}_D$ is the low-precision draft cache size. Note that the target cache remains unchanged. Quantization may reduce draft model acceptance, but it will not affect target model performance.

The main design question is how to quantize keys and values. Attention computes $O = AVW_O$ with $A = \text{softmax}(QK^\top/\sqrt{d_h} + M)$ [Vaswani et al., 2017]. Keys control where we read, while values contain the information returned by reads. Empirically, it is tempting to conclude that keys always need more precision because they are more sensitive to noise. For example, under Gaussian noise with standard deviation 0.03 times the per-layer RMS, key noise reduced top-1 agreement to 61.7%, while value noise retained 99.2%.

We organize our study around three research questions. **(1) Key and value precision.** Is the apparent need for higher key precision intrinsic to attention, or is it caused by quantizer geometry and

*Equal contribution.

40th Conference on Neural Information Processing Systems (NeurIPS 2026). Workshop: AXIOM Foundations of Efficient Deep Learning.

outlier handling? **(2) Memory and acceptance.** How much SD memory can draft-only KV cache quantization save without materially reducing token acceptance? **(3) Generalization and practical savings.** Do these memory-quality tradeoffs hold across model families, long contexts, and retrieval workloads, and do they translate into real packed-storage savings?

2 Related Work

In standard autoregressive inference, KV cache quantization successfully mitigates memory costs, though precision allocation is often heuristically driven. For example, KIVI applies an asymmetric strategy of per-channel quantization for keys and per-token quantization for values [Liu et al., 2024], whereas Quantize What Counts argues for allocating higher precision to keys based on the distinct geometries of key and value representations [Hariri et al., 2026]. Other approaches optimize bit allocation dynamically: KVTuner searches for layer-wise precision pairings [Li et al., 2025], RateQuant distributes bits across attention heads via rate-distortion theory [Zuo et al., 2026], and RoPE-Aware techniques allocate precision across frequency blocks [Liang et al., 2026]. We build on KIVI's geometry and study asymmetric bit splitting (e.g., K8V4 vs. K4V8) in conjunction with it.

While QuantSpec introduces hierarchical KV quantization for self-speculative decoding [Tiwari et al., 2025], our work addresses a different paradigm. We study standard two-model speculative decoding, specifically targeting the quantization of the draft model's cache. By evaluating the trade-off between total memory savings and candidate acceptance rates, we isolate how key-quantizer geometry alters conclusions about the optimal precision balance between keys and values.

3 Draft Cache Quantization

Let KaVb denote a-bit keys and b-bit values. We first compare K8V4 against K4V8 to test whether keys or values need more bits. Our simple baseline uses one symmetric scale for each token and KV head. For a b-bit group G, symmetric scale s_G is computed as follows:

$$s_G = \frac{\max_{x \in G} |x|}{2^{b-1} - 1}, \qquad \widehat{x} = s_G \, \mathrm{clip}(\mathrm{round}(x / s_G)). \tag{1}$$

This baseline lets channel-specific key outliers set the scale for the full vector. Inspired by KIVI, our layout instead uses 32-token per-channel key groups and per-token affine value groups within each head [Liu et al., 2024], as shown in Figure 1. Section 5 tests this choice. Keys also use affine groups, and the 128 most recent keys stay in BF16 (Appendix A). We count payload bits, BF16 scales, zero-points, and the BF16 residual window in every memory result.




Figure 1: **Quantizer geometry.** Draft keys share scales by channel, while draft values share scales by token. K8V4 and K4V8 allocate equal average payload precision. Note that only the draft cache is quantized; the target cache remains in BF16. Our scales are affine, not symmetric as drawn.

The target verifier also remains in BF16. We measure draft-token acceptance, KL from BF16 draft logits, top-1 agreement, and retrieval accuracy.

4 Evaluation

We test six target and draft pairs across Qwen2.5 [Yang et al., 2024], Qwen3 [Yang et al., 2025], Llama 3 [Grattafiori et al., 2024], OLMo 2 [Team OLMo et al., 2025], and SmolLM2 [Allal et al., 2025]. Model sizes range from 360M to 8B parameters. We evaluate 576 FineWeb-Edu prompts (96 per pair) [Penedo et al., 2024] with greedy decoding. The draft proposes up to four tokens per round,

and each run generates 16 tokens. Every prompt is tested with BF16, K8V4, K4V8, and K4V4. The noise test, the RQ1 acceptance comparisons, and the KL and top-1 measurements use WikiText-2 validation text instead [Merity et al., 2016].

With the Qwen2.5 3B/1.5B pair, we keep the models, prompts, value quantizer, and bit budget fixed, and change only the key quantizer. We also run 192 paired passkey examples at 16K context. Finally, we test 256-token continuations and an end-to-end packed prototype with the same pair at 1K and 16K context (Appendix E). Full model details and confidence interval procedures are in Appendix A.

5 Results

5.1 RQ1: Are keys intrinsically more precision-sensitive?

We demonstrate that the apparent need for higher key precision depends strongly on quantizer geometry, and is not necessarily an intrinsic property of attention. When using a naive per-token symmetric quantizer, keys appear highly sensitive: K8V4 outperforms an equal-mean-bit K4V8 by 10.87 pp on average. However, switching to grouped per-channel keys eliminates this advantage, shifting the contrast to -0.25 pp and dropping all within-pair gaps below 1 pp (Figure 2a).

A controlled Qwen intervention, which strictly isolates the key quantizer, confirms this behavior. Changing the key geometry shifts the K8V4 versus K4V8 gap from $+28.70$ to -0.33 pp, and reverses the aggressive K4V2 versus K2V4 contrast from $+15.05$ to -3.66 pp. This interaction extends to 16K retrieval tasks (Figure 2b), where modifying key geometry shrinks the K4V2 versus K2V4 accuracy gap from 81.25 to 16.15 pp. Ultimately, bit width and quantizer geometry must be co-designed; keys do not universally demand more precision. Appendix B contains more details.




Figure 2: **Quantizer geometry changes the K/V conclusion.** (a) Each line follows one model pair while models and bit budgets remain fixed. Positive values favor more key bits. (b) On 192 paired Qwen2.5 passkey examples, grouped per-channel keys recover most of the failure of K2V4 and sharply reduce the apparent key-bit advantage.

5.2 RQ2: How much memory can draft-only quantization save?

Using K4V4 as our balanced operating point, we find it removes about two-thirds of draft cache memory. Across all six evaluated model pairs, K4V4 reduces draft cache bytes by 66.20% and the combined target-plus-draft KV memory by 23.95% (11.30% to 33.17% across pairs).

Importantly, this compression incurs minimal degradation to candidate generation. The mean cross-family acceptance rate falls only from 57.93% to 57.14%, a 1.36% relative drop (Figure 3a). In separate WikiText-2 runs, the K4V4 draft's KL from BF16 is 0.00730 (95% CI $[0.00660, 0.00801]$), with 95.99% top-1 agreement. With 256-token continuations on one Qwen2.5 pair, the acceptance change ranges from -0.59 to $+0.33$ pp, and the outputs match target-only greedy decoding under a sequential verifier (Appendix E).




Figure 3: **Memory and acceptance.** (a) K4V4 total KV saving and paired acceptance change across six target/draft pairs. Error bars are paired 95% CIs; the star is the equal-model macro. (b) Actual bit-packed draft cache storage, including quantizer metadata and the BF16 residual window. The absolute saving grows with retained context.

5.3 RQ3: Does the result generalize and produce real savings?

The memory-quality tradeoffs of K4V4 hold across six model pairs and extended context windows. At 16K and 32K context with the Qwen2.5 3B/1.5B pair, K4V4 reduces combined KV memory by about 31%, with mean acceptance drops of only 0.94 and 0.73 pp, respectively (Appendices B and C).

The analytical byte savings also hold in physical packed storage. At 32K context, a standard Qwen2.5-1.5B BF16 cache requires 896.0 MiB per sequence, whereas our packed K4V4 implementation consumes just 260.2 MiB, saving 635.8 MiB (Figure 3b). However, these savings do not yet translate into a serving benefit. In an end-to-end prototype with the same pair at 1K and 16K context, packed K4V4 stores 67% to 71% fewer draft cache bytes, but it is 18% to 33% slower than BF16 speculative decoding, which is slower than target-only decoding. Peak GPU memory is also unchanged, since the draft cache is packed only after a BF16 prefill. Its batched verifier reproduces target-only outputs on only 2 to 5 prompts per setting (of 12 or 24), even with a BF16 draft, so we treat these timings as preliminary (Appendix E). Appendix F covers policy selection.

6 Discussion

Conclusion. Our results show that draft-only KV cache quantization can substantially reduce the KV cache memory overhead of two-model speculative decoding while largely preserving draft acceptance. K4V4 removes about two-thirds of draft cache memory, while the target verifier and its correction rule remain unchanged. The results also show that key and value precision cannot be evaluated independently of quantizer geometry, providing a predictive principle for the design of future quantization systems.

Limitations. Our longest-context experiments have fewer prompts than the 1K study. The retrieval task is partly synthetic. Fake quantization measures quality but not production speed. Our packed prototype is still slower than BF16 speculative decoding and does not yet lower peak GPU memory, so we do not claim an end-to-end speedup. The 256-token and prototype experiments cover one model pair at batch size one, and the batched verifier, which the RQ1 acceptance comparisons also use, is not yet exact. We do not measure key outliers directly, and keys and values may differ intrinsically in settings we do not test.

Future work. Future work could replace static bit assignments with serving-time adaptive computation, building predictive models for runtime quantization that select key and value precision by layer, context region, or request. Realizing this approach will also require an exact batched verifier, streaming prefill, fused packed-cache attention kernels, and end-to-end evaluation in production inference systems.

References

Loubna Ben Allal, Anton Lozhkov, Elie Bakouch, Gabriel Martín Blázquez, Guilherme Penedo, Lewis Tunstall, Andrés Marafioti, Hynek Kydlíček, Agustín Piqueres Lajarín, Vaibhav Srivastav, Joshua Lochner, Caleb Fahlgren, Xuan-Son Nguyen, Clémentine Fourrier, Ben Burtenshaw, Hugo Larcher, Haojun Zhao, Cyril Zakka, Mathieu Morlon, Colin Raffel, Leandro von Werra, and Thomas Wolf. SmolLM2: When smol goes big – data-centric training of a small language model, 2025. URL https://arxiv.org/abs/2502.02737.

Yushi Bai, Xin Lv, Jiajie Zhang, Hongchang Lyu, Jiankai Tang, Zhidian Huang, Zhengxiao Du, Xiao Liu, Aohan Zeng, Lei Hou, Yuxiao Dong, Jie Tang, and Juanzi Li. LongBench: A bilingual, multitask benchmark for long context understanding. In *Proceedings of the 62nd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*. Association for Computational Linguistics, 2024. URL https://aclanthology.org/2024.acl-long.172/.

Charlie Chen, Sebastian Borgeaud, Geoffrey Irving, Jean-Baptiste Lespiau, Laurent Sifre, and John Jumper. Accelerating large language model decoding with speculative sampling, 2023. URL https://arxiv.org/abs/2302.01318.

Aaron Grattafiori, Abhimanyu Dubey, Abhinav Jauhri, Abhinav Pandey, Abhishek Kadian, Ahmad Al-Dahle, Aiesha Letman, Akhil Mathur, Alan Schelten, Alex Vaughan, et al. The Llama 3 herd of models, 2024. URL https://arxiv.org/abs/2407.21783.

Mohsen Hariri, Alan Luo, Weicong Chen, Tianyi Zhang, Qifan Wang, Xiaotian Han, and Vipin Chaudhary. Quantize what counts: More for keys, less for values. In *Findings of the Association for Computational Linguistics: ACL 2026*, pages 26393–26420. Association for Computational Linguistics, 2026. doi: 10.18653/v1/2026.findings-acl.1314. URL https://aclanthology.org/2026.findings-acl.1314/.

Yaniv Leviathan, Matan Kalman, and Yossi Matias. Fast inference from transformers via speculative decoding. In *Proceedings of the 40th International Conference on Machine Learning*, volume 202 of *Proceedings of Machine Learning Research*, 2023. URL https://proceedings.mlr.press/v202/leviathan23a.html.

Xing Li, Zeyu Xing, Yiming Li, Linping Qu, Hui-Ling Zhen, Yiwu Yao, Wulong Liu, Sinno Jialin Pan, and Mingxuan Yuan. KVTuner: Sensitivity-aware layer-wise mixed-precision KV cache quantization for efficient and nearly lossless LLM inference. In *Proceedings of the 42nd International Conference on Machine Learning*, volume 267 of *Proceedings of Machine Learning Research*, pages 36451–36485, 2025. URL https://proceedings.mlr.press/v267/li25dd.html.

Fengfeng Liang, Yuechen Zhang, and Jiaya Jia. Block-GTQ: RoPE-block rate allocation for KV-cache quantization, 2026. URL https://arxiv.org/abs/2606.24033.

Zirui Liu, Jiayi Yuan, Hongye Jin, Shaochen Zhong, Zhaozhuo Xu, Vladimir Braverman, Beidi Chen, and Xia Hu. KIVI: A tuning-free asymmetric 2bit quantization for KV cache. In *Proceedings of the 41st International Conference on Machine Learning*, volume 235 of *Proceedings of Machine Learning Research*, 2024. URL https://proceedings.mlr.press/v235/liu24bz.html.

Stephen Merity, Caiming Xiong, James Bradbury, and Richard Socher. Pointer sentinel mixture models, 2016. URL https://arxiv.org/abs/1609.07843.

Guilherme Penedo, Hynek Kydlíček, Loubna Ben Allal, Anton Lozhkov, Margaret Mitchell, Colin Raffel, Leandro Von Werra, and Thomas Wolf. The FineWeb datasets: Decanting the web for the finest text data at scale. In *Advances in Neural Information Processing Systems, Datasets and Benchmarks Track*, 2024. URL https://openreview.net/forum?id=n6SCkn2QaG.

Jack W. Rae, Anna Potapenko, Siddhant M. Jayakumar, and Timothy P. Lillicrap. Compressive transformers for long-range sequence modelling, 2019. URL https://arxiv.org/abs/1911.05507.

Team OLMo, Pete Walsh, Luca Soldaini, Dirk Groeneveld, Kyle Lo, Shane Arora, Akshita Bhagia, Yuling Gu, Shengyi Huang, Matt Jordan, et al. 2 OLMo 2 furious, 2025. URL https://arxiv.org/abs/2501.00656.

Rishabh Tiwari, Haocheng Xi, Aditya Tomar, Coleman Hooper, Sehoon Kim, Maxwell Horton, Mahyar Najibi, Michael W. Mahoney, Kurt Keutzer, and Amir Gholami. QuantSpec: Self-speculative decoding with hierarchical quantized KV cache. In *Proceedings of the 42nd International Conference on Machine Learning*, volume 267 of *Proceedings of Machine Learning Research*, pages 59668–59686, 2025. URL https://proceedings.mlr.press/v267/tiwari25b.html.

Ashish Vaswani, Noam Shazeer, Niki Parmar, Jakob Uszkoreit, Llion Jones, Aidan N. Gomez, Łukasz Kaiser, and Illia Polosukhin. Attention is all you need. In I. Guyon, U. Von Luxburg, S. Bengio, H. Wallach, R. Fergus, S. Vishwanathan, and R. Garnett, editors, *Advances in Neural Information Processing Systems*, volume 30. Curran Associates, Inc., 2017. URL https://proceedings.neurips.cc/paper_files/paper/2017/file/3f5ee243547dee91fbd053c1c4a845aa-Paper.pdf.

An Yang, Baosong Yang, Beichen Zhang, Binyuan Hui, Bo Zheng, Bowen Yu, Chengyuan Li, Dayiheng Liu, Fei Huang, Haoran Wei, et al. Qwen2.5 technical report, 2024. URL https://arxiv.org/abs/2412.15115.

An Yang, Anfeng Li, Baosong Yang, Beichen Zhang, Binyuan Hui, Bo Zheng, Bowen Yu, Chang Gao, Chengen Huang, Chenxu Lv, et al. Qwen3 technical report, 2025. URL https://arxiv.org/abs/2505.09388.

Fei Zuo, Zikang Zhou, Hao Cong, Xiaoyan Xi, and Ho Fai Leung. RateQuant: Optimal mixed-precision KV cache quantization via rate-distortion theory, 2026. URL https://arxiv.org/abs/2605.06675.

A Experimental Details

Model pairs and data. Table 1 lists the six model pairs. Only the draft cache is quantized. The target model verifies tokens with its original BF16 cache. Each run prefills a 1,024-token FineWeb-Edu prompt, proposes up to four tokens per round, and generates 16 tokens. Across six model pairs, we evaluate 576 prompts. Every prompt is tested with BF16, K8V4, K4V8, and K4V4. Prompts are consecutive 1,024-token blocks from the streamed `sample-10BT` training split. We tokenize with the target tokenizer without special tokens and place an end-of-sequence token between documents. Each pair uses three disjoint shards of 32 prompts at fixed stream offsets. The noise test, Tables 3 and 4, the KL and top-1 measurements, and the Spearman grid use WikiText-2. The Qwen3 checkpoints are instruction-tuned, and all others are base models. All models read raw text without chat templates.

Table 1: Primary speculative-decoding model pairs (Hugging Face checkpoint identifiers).

Family	Target	Draft
Qwen2.5	`Qwen/Qwen2.5-3B`	`Qwen/Qwen2.5-1.5B`
Qwen2.5	`Qwen/Qwen2.5-7B`	`Qwen/Qwen2.5-3B`
Qwen3	`Qwen/Qwen3-8B`	`Qwen/Qwen3-4B`
Llama 3	`meta-llama/Llama-3.1-8B`	`meta-llama/Llama-3.2-3B`
OLMo 2	`allenai/OLMo-2-1124-7B`	`allenai/OLMo-2-0425-1B`
SmolLM2	`HuggingFaceTB/SmolLM2-1.7B`	`HuggingFaceTB/SmolLM2-360M`

Decoding protocol. All speculative decoding experiments use greedy decoding at batch size one. In each round, the draft proposes up to four argmax tokens. The target accepts the longest proposal prefix that matches its own argmax tokens. The target then emits a correction token at the first disagreement, or a bonus token after a fully accepted proposal. We crop the draft cache to the committed prefix, which discards rejected entries, and append the emitted token to both caches. Generation has a fixed length without early stopping. Acceptance excludes correction and bonus tokens. The sequential verifier advances the target one accepted token at a time and makes one target call per emitted token, so it measures draft quality but not target-call savings. The batched verifier scores a proposal in one target call and rolls the target cache back. Tables 3 and 4, the Spearman grid, and the prototype use the batched verifier; all other speculative results use the sequential verifier.

Quantizer geometries. The simple quantizer (Equation 1) uses one scale for each token and KV head, for keys and values. The stronger quantizer uses KIVI's per-channel key and per-token value geometry [Liu et al., 2024] with affine groups (Equation 2). In our implementation, keys are grouped over 32 tokens, values are grouped within each token and head, and the newest 128 key tokens remain in BF16. In the controlled test, we remove this residual window and change only the key quantizer (per-token symmetric versus per-channel affine). We never update model weights.

Quantizer specification. An affine b-bit group G has zero-point $m_G = \min_{x \in G} x$ and scale s_G:

$$s_G = \frac{\max_{x \in G} x - m_G}{2^b - 1}, \qquad \widehat{x} = m_G + s_G \operatorname{clip}\big(\operatorname{round}((x - m_G)/s_G),\, 0,\, 2^b - 1\big). \tag{2}$$

Consider one layer with keys and values of shape $H \times L \times d$, with H KV heads, L committed tokens, and d channels. We use KaVb with group size $g = 32$ and residual length $R = 128$. For keys, we set $P = g\lfloor \max(0, L - R)/g \rfloor$. A key group covers one head, one channel, and g consecutive tokens. We apply Equation 2 with a bits to each newly completed group below P. Tokens at or beyond P remain in BF16, and we never pad or requantize incomplete groups. For values, we apply Equation 2 with b bits to the d channels of each new token and head. Values have no residual window. During a speculative round, P is frozen, so we only quantize committed keys. We compute statistics in FP32 and floor ranges at 10^{-8}. We round to nearest with ties to even. The symmetric baseline clips to $\pm(2^{b-1} - 1)$. Quality experiments use fake quantization, which writes dequantized tensors back into the BF16 cache and computes bytes analytically. The packed implementation stores two 4-bit payload entries per byte in row-major `uint8` tensors. Metadata and residual keys remain in BF16.

Byte accounting. We count packed payloads, BF16 scales, zero-points, and the BF16 residual window. Let Mem_T be the target cache, Mem_D be the native draft cache, and $\widehat{\mathrm{Mem}}_D$ be the quantized

draft cache. Total memory saving is

$$\text{saved}_{\text{total}} = 1 - \frac{\text{Mem}_T + \widehat{\text{Mem}}_D}{\text{Mem}_T + \text{Mem}_D}. \tag{3}$$

The draft cache shrinks by 66% to 71%, depending on experimental factors. The target cache does not shrink, so the combined saving across both caches is smaller. For each pair, the total saving equals the draft saving times the draft's share of the combined BF16 cache (Table 2). All savings refer to KV cache bytes, not model weights or activations.

Metrics and uncertainty. Acceptance is the fraction of proposed draft tokens accepted by the target. Acceptance differences are absolute, in percentage points (pp), unless marked as relative. We also measure KL from the BF16 draft, top-1 agreement, and exact retrieval accuracy. KL is $\mathrm{KL}(p \,\|\, q)$, where p and q are the draft's next-token distributions with a BF16 and a quantized cache on teacher-forced continuations. We average it over positions and prompts, and then equally over model pairs. Top-1 agreement is the fraction of these positions with the same argmax. Confidence intervals are paired bootstrap intervals over prompts with 5,000 to 30,000 resamples. The macro of Table 2 resamples pairs and then prompts; other cross-model averages resample pairs only.

Verifier audit. The target still checks every proposed token, so draft quantization does not change the mathematical correction rule. We compare every speculative output with an independent tokenwise target path and call a mismatch a near tie when the target's top-1 margin is at most 10^{-3}. All sequential-verifier trajectories match, including 38,400 checks in Appendix F. With the batched verifier, Table 4 and the grouped-key column of Table 3 drop prompts with non-tie mismatches; Table 3's per-token column keeps them (one to three prompts in four of its twelve runs). A BF16 target cache preserves the correction rule, but it does not guarantee bit-identical outputs from a batched verifier.

Reproducibility details. We release the implementation, SLURM launchers, pinned environment, tests, aggregation code, and output schemas at github.com/sgdescent/KV_Reduce under the MIT License. Table 4 and the Spearman grid come from an earlier launcher version that used shuffled prompts and the batched verifier.

B Cross-Family Generalization and Mechanism Ablations

The cross-family study tests whether the K4V4 operating point and the K/V contrast generalize beyond one Qwen pair. The controlled Qwen intervention then isolates mechanism by changing only the key quantizer. Group-size and residual-window sweeps are implementation ablations rather than additional generalization claims.

Cross-family generalization test. Table 2 reports the K4V4 operating point for all six speculative model pairs. Four pair-level confidence intervals include zero; Qwen3 and SmolLM2 show small resolved losses. All six central estimates remain within 2 pp, while combined savings vary with the relative size of the target cache and draft cache, from 33.17% at a 50.0% draft share to 11.30% at a 17.2% draft share.

Table 2: Cross-family K4V4 generalization. Acceptance changes are differences in pp from the BF16 draft cache. BF16 and K4V4 are acceptance rates in %.

Target / draft	BF16	K4V4	Δ acceptance (95% CI)	Draft saved	Draft share	Total saved
Qwen2.5 3B/1.5B	59.78	59.02	-0.76 $[-2.23, +0.66]$	66.33%	43.8%	29.02%
Qwen2.5 7B/3B	61.80	62.08	$+0.28$ $[-0.98, +1.47]$	66.33%	39.1%	25.96%
Qwen3 8B/4B	54.06	52.39	-1.67 $[-3.12, -0.30]$	66.33%	50.0%	33.17%
Llama 3.1/3.2	64.95	65.09	$+0.13$ $[-1.27, +1.60]$	66.33%	46.7%	30.96%
OLMo 2 7B/1B	54.03	53.17	-0.86 $[-1.98, +0.18]$	66.33%	20.0%	13.27%
SmolLM2 1.7B/360M	52.95	51.10	-1.85 $[-3.21, -0.54]$	65.55%	17.2%	11.30%
Equal-model macro	57.93	57.14	-0.79 $[-1.63, +0.04]$	66.20%	36.1%	23.95%

Cross-family quantizer-geometry test. Table 3 gives every equal-bit K8V4 versus K4V8 result. The per-token quantizer makes extra key bits look valuable for Qwen2.5, Qwen3, and SmolLM2. With grouped per-channel keys, every difference is below 1 pp. Only the models, bit budgets, and verifier match: the grouped-key column also uses affine values, a 128-token BF16 residual window, and 64 shuffled instead of 32 consecutive blocks per pair. Table 4 isolates the key quantizer.

Table 3: Acceptance contrasts in pp. "Shift" is grouped per-channel minus per-token. Brackets give paired 95% CIs for each within-pair contrast.

Target / draft	Per-token Δ	Grouped-key Δ	Shift
Qwen2.5 3B/1.5B	$+31.18$ $[23.33, 39.00]$	$+0.20$ $[-1.28, 1.68]$	-30.99
Qwen2.5 7B/3B	$+12.51$ $[7.54, 17.84]$	$+0.18$ $[-1.09, 1.50]$	-12.33
Qwen3 8B/4B	$+10.91$ $[4.61, 17.27]$	-0.58 $[-1.88, 0.64]$	-11.49
Llama 3.1/3.2	$+1.13$ $[-1.91, 4.28]$	-0.44 $[-1.94, 1.06]$	-1.57
OLMo 2 7B/1B	-0.19 $[-2.30, 2.05]$	-0.80 $[-2.22, 0.45]$	-0.61
SmolLM2 1.7B/360M	$+9.69$ $[5.36, 14.31]$	-0.06 $[-0.98, 0.84]$	-9.75
Macro	$+10.87$ $[3.75, 19.68]$	-0.25 $[-0.56, 0.04]$	-11.12 $[-19.71, -4.25]$

Controlled Qwen test. Table 4 keeps the models, prompts, value quantizer, bit budget, and decoding loop fixed. Only the key quantizer changes. The K4V2 versus K2V4 result changes sign, so the preferred bit split also changes.

Table 4: Qwen2.5 3B/1.5B key-axis intervention. Values are acceptance contrasts in pp with paired 95% CIs.

Contrast	Per-token keys	Grouped per-channel keys
K8V4 − K4V8	$+28.70$ $[26.10, 31.38]$	-0.33 $[-1.26, 0.62]$
K4V2 − K2V4	$+15.05$ $[13.58, 16.65]$	-3.66 $[-5.80, -1.56]$

Granularity and residual-window controls. With the Qwen2.5 3B/1.5B pair on FineWeb-Edu, we also test key groups of 16, 32, 64, and 128 tokens. The K4V2 versus K2V4 differences are -5.83, -2.94, -1.57, and -1.87 pp; only the 16-token interval excludes zero. We test BF16 residual windows of 0, 32, 128, and 256 tokens as well. A longer window gives no clear K4V4 acceptance gain. Removing it increases draft cache saving from 66.33% to 70.56%. Our 256-token experiments also show no clear acceptance gain from the window (Appendix E), so we treat 128 tokens as a configuration choice rather than an optimum.

C Long-Context Generalization and Retrieval Stress Tests

16K associative retrieval. Table 5 reports 192 examples per model. Each example is a 16,384-token prompt. The prompt hides 16 records of the form "Archive record [tag]: the access code is [six digits]" at even spacing in filler text and then asks for the code of one tagged record. The 15 distractor codes differ from the correct code in one digit. We query the 3rd, 9th, or 15th record. We count an example as retrieved when the correct code has the highest length-normalized log-likelihood among the 16 candidates. We run each draft model alone on three seeds of 64 examples. Qwen2.5 benefits from giving keys more bits. Llama and Qwen3 do not show the same effect. On Qwen2.5, per-token K4V2 and K2V4 retrieve 166 and 10 examples. Grouped-key K4V2 and K2V4 retrieve 189 and 158. The key quantizer changes the gap by 65.10 pp (95% CI $[56.77, 73.44]$).

Table 5: Associative-passkey accuracy at 16K with grouped per-channel keys.

Draft model	BF16	K4V2	K2V4	Δ (pp)
Qwen2.5-1.5B	186/192	189/192	158/192	$+16.15$
Llama-3.2-3B	n/a	185/192	183/192	$+1.04$
Qwen3-4B	191/192	192/192	192/192	0.00

We also run a natural LongBench passage-retrieval task [Bai et al., 2024] on three 7B to 8B instruction models (Qwen2.5-7B-Instruct, Llama-3.1-8B-Instruct, and Qwen3-8B). The task is `passage_retrieval_en`, which asks for the source paragraph of an abstract among 30 Wikipedia paragraphs. We use the LongBench prompt template without a chat template and truncate prompts in the middle to at most 32,752 tokens. We score the 30 answers by length-normalized log-likelihood on 72 examples per model. K4V2 matches the BF16 average. K2V4 is 3.24 pp lower (95% CI $[-9.72, 0.00]$), and all of this gap comes from Qwen2.5; Llama and Qwen3 saturate.

Long-context speculative decoding. Table 6 uses PG-19 prefixes [Rae et al., 2019] with the Qwen2.5 3B/1.5B pair. Prompts are consecutive token blocks from the streamed PG-19 training split. We use three disjoint shards of 12 prompts at 16K and 8 prompts at 32K. At 16K and 32K, K4V4 saves about 71% of the draft cache and 31% of total KV memory. Acceptance drops by less than 1 pp; only the 16K interval excludes zero.

Table 6: K4V4 at long context. Acceptance changes are differences in pp from BF16 draft KV.

Context	Prompts	Draft saved	Combined saved	Δ acceptance
16K	36	70.83%	30.99%	-0.94 $[-2.06, -0.13]$
32K	24	70.96%	31.04%	-0.73 $[-2.99, 1.28]$

D Memory Implementation

Packed storage. Figure 3b uses a real packed cache with `uint8` payloads, BF16 metadata, and a BF16 residual window. The measured tensors use 28 layers, two KV heads, and head dimension 128. This confirms that the estimated saving we report is present in stored tensors rather than only in theoretical bit counts. At 32,768 tokens, the 896.00 MiB BF16 cache becomes 260.20 MiB. Keys take 111.56 MiB of 4-bit payload, 27.89 MiB of BF16 scales and zero-points, and 1.75 MiB for the BF16 residual window. Values take 112.00 MiB of 4-bit payload and 7.00 MiB of BF16 scales and zero-points. This metadata costs $2 \cdot 16/32 = 1$ bit per quantized key element and $2 \cdot 16/128 = 0.25$ bits per value element, so a 4-bit payload does not give a 75% saving. The packed cache needs no padding or alignment bytes. We exclude temporary kernel workspace.

Kernel diagnostic. A Triton prototype reads the packed cache without first rebuilding a full BF16 cache. At 32K, it takes 0.708 ms per layer. Rebuilding the cache first takes 1.448 ms. Native BF16 SDPA takes only 0.103 ms. The prototype proves that packed attention is possible, but it does not yet provide an end-to-end speedup.

E Longer Continuations and End-to-End Packed Prototype

Protocol. We also test 256-token continuations with the Qwen2.5 3B/1.5B pair, using greedy decoding, a proposal length of four, and batch size one. Prompts come from a seeded shuffle of the streamed FineWeb-Edu `sample-10BT` training split, skipping 100 blocks for the quality study and 200 for the prototype. The quality study covers 1K context with prompt seeds 0 and 1, and 16K context with seed 0, each with residual windows of 0 and 128 tokens. Every setting tests BF16, K8V4, K4V8, and K4V4 on the same 24 prompts with fake quantization and the sequential verifier. The two residual settings share prompts and BF16 baselines, so the six settings are not independent. All use grouped per-channel keys.

Acceptance and residual window. Table 7 reports the mean of per-prompt acceptance. This weights prompts equally, so it can differ from the pooled acceptance of the cross-family study. The K4V4 change ranges from -0.59 to $+0.33$ pp, and every interval includes zero. These exploratory intervals are not adjusted for multiple comparisons, so we do not claim equivalence. The differences between residual windows of 128 and 0 tokens also include zero, so the window gives no clear acceptance gain.

Accepted prefixes and target calls. The accepted prefix is the number of draft tokens accepted before the first rejection in a round, excluding the correction or bonus token. We average it within

Table 7: Acceptance in % for 256-token continuations with 24 prompts per row. Differences are in pp with paired 95% CIs. The last column compares K4V4 at residual windows of 128 and 0.

Context	Residual	Seed	BF16	K8V4	K4V8	K4V4	K4V4 − BF16	K4V4: residual 128 − 0
1K	0	0	76.69	77.25	77.01	76.61	-0.08 $[-1.18, +0.94]$	
1K	0	1	74.01	74.18	73.58	73.45	-0.56 $[-1.30, +0.17]$	
1K	128	0	76.69	77.44	76.61	77.02	$+0.33$ $[-0.43, +1.06]$	$+0.408$ $[-0.379, +1.290]$
1K	128	1	74.01	73.79	73.55	73.42	-0.59 $[-1.34, +0.20]$	-0.033 $[-0.614, +0.629]$
16K	0	0	79.62	79.54	79.64	79.20	-0.42 $[-1.42, +0.52]$	
16K	128	0	79.62	79.92	79.42	79.55	-0.07 $[-1.04, +0.95]$	$+0.351$ $[-0.358, +1.110]$

each prompt and then across prompts. Across the six settings, BF16 accepts 2.95 to 3.17 tokens per round and K4V4 accepts 2.92 to 3.17. The paired differences range from -0.027 to $+0.018$ tokens, and all six 95% CIs include zero. With K4V4, every proposed token is accepted in 62.8% to 71.6% of rounds. The first rejection falls on the first, second, third, and fourth proposed token in 10.8% to 13.5%, 7.6% to 10.3%, 5.7% to 7.6%, and 3.9% to 5.9% of rounds. The sequential verifier makes 257 target calls for 256 tokens, so these runs measure draft quality and correctness rather than target-call savings.

End-to-end packed prototype. The prototype uses the packed cache and Triton kernel of Appendix D with the batched verifier, and packs key groups only after rollback. Table 8 compares target-only decoding, BF16 speculative decoding (SD), and packed K4V4 on 24 prompts at 1K and 12 prompts at 16K. Latency is the mean wall-clock time per continuation, including prefill but excluding warmup and the extra sequential audits. Savings compare stored draft cache bytes with the BF16 draft cache, not with total GPU memory. Peak memory is peak allocated GPU memory. We measure the target-only value before loading the draft.

Table 8: End-to-end prototype with 256-token continuations at batch size one. Δ is the paired latency increase over BF16 SD with a 95% CI. "Exact" counts outputs that equal target-only greedy decoding.

Context	Configuration	Latency (s)	Δ vs. BF16 SD (s)	Draft bytes saved	Peak allocated (GiB)	Exact
1K	Target only	7.10	–	–	5.98	reference
1K	BF16 SD	9.68	–	0.00%	8.87	3/24
1K	Packed K4V4, residual 0	12.77	$+3.09$ $[2.77, 3.42]$	70.45%	8.87	4/24
1K	Packed K4V4, residual 128	12.87	$+3.18$ $[2.73, 3.77]$	67.05%	8.87	5/24
16K	Target only	8.65	–	–	7.69	reference
16K	BF16 SD	14.54	–	0.00%	10.76	2/12
16K	Packed K4V4, residual 0	17.20	$+2.66$ $[2.30, 3.03]$	71.05%	10.76	2/12
16K	Packed K4V4, residual 128	17.46	$+2.92$ $[2.55, 3.22]$	70.78%	10.76	2/12

At 1K, packed K4V4 is 31.9% and 32.9% slower than BF16 SD with residual windows of 0 and 128 tokens. At 16K, it is 18.3% and 20.1% slower. BF16 SD is itself slower than target-only decoding, so the prototype trades runtime for storage and does not give a speedup. Peak allocated memory is the same as for BF16 SD. The prototype first builds the BF16 draft cache during prefill and then packs it, so smaller stored tensors need not lower the peak. We did not profile other contributors.

Correctness. With the sequential verifier, all 576 evaluations of the quality study (six settings, four configurations, and 24 prompts) reproduce target-only greedy decoding exactly. All 94 sequential audits recorded in the packed runs also pass. The batched verifier behaves differently. At 1K, it matches target-only greedy decoding on 3, 4, and 5 of 24 sequences for BF16, residual 0, and residual 128. At 16K, it matches on 2 of 12 sequences for each configuration. A mismatch means that at least one token differs. The BF16 baseline also mismatches, so quantization alone cannot explain the difference. We have not yet found the cause, and we do not assume that the mismatches are harmless near ties, so we treat the timings as preliminary. The timings also come from a shared node and one model pair. We do not measure production throughput, maximum batch size, or concurrent serving.

F Choosing a Precision Policy

We ask whether precision should be chosen using speculative acceptance or ordinary draft quality. Over 20 uniform K/V settings of Qwen2.5 3B/1.5B on WikiText-2, the two have Spearman correlation

0.964 at 1K and 0.878 at 4K. For five pairs on FineWeb-Edu, equal-byte per-layer allocations built from each measure coincide at mild budgets. At a three-bit budget, the acceptance-profiled choice is 0.48 pp worse (95% CI $[-0.98, -0.05]$) and has higher KL. Direct acceptance is still the final serving metric, but we do not find a benefit from an acceptance-only allocator.

G Compute and Asset Disclosure

Compute. GPU jobs used one or two NVIDIA RTX A5000 accelerators with 24 GiB of device memory, 8 CPU cores, and 64 GiB of host memory. At most four GPUs ran concurrently. SLURM accounting gives 229.45 total GPU-hours: 224.77 for completed allocations and 4.68 for failed, cancelled, or timed-out allocations. Table 9 separates the major paper-facing experiment families. The remaining 85.55 GPU-hours cover robustness, verification, proposal-length sweeps, and preliminary experiments. CPU-only aggregation is excluded from GPU-hours. The recorded environment used Python 3.13.7, PyTorch 2.10.0 with CUDA 12.8, Transformers 5.3.0, and Datasets 4.8.2.

Table 9: Measured compute for major experiment families. GPU-hours equal wall time multiplied by allocated GPUs, including model loading. The experiments of Appendix E are not included.

Experiment family	GPU allocations	GPU-hours
Cross-family speculative and quality	107	33.24
Key geometry and residual controls	47	4.60
Passkey retrieval, layers, and policy	95	13.14
LongBench retrieval	18	2.51
Long-context speculative and quality	19	1.90
Objective and precision matrix	710	88.35
Packed-cache storage and kernels	29	0.16

Third-party assets. Table 10 summarizes the upstream terms for every model family and dataset used in reported results. We redistribute no model weights or other dataset records, but the raw outputs released for Appendix E include the token IDs of their FineWeb-Edu prompts.

Table 10: Upstream licenses and terms for reported third-party assets.

Asset	License or access terms
Qwen2.5 1.5B, 7B	Apache License 2.0
Qwen2.5 7B-Instruct; Qwen3 4B, 8B	Apache License 2.0
Qwen2.5 3B	Qwen Research License
Llama 3.1 8B(-Instruct); Llama 3.2 3B	Llama Community License, acceptable-use terms, and gated access
OLMo 2 7B, 1B; SmolLM2 1.7B, 360M	Apache License 2.0
FineWeb-Edu	Open Data Commons Attribution License (ODC-By) v1.0
WikiText-2	Creative Commons Attribution-ShareAlike License 3.0
PG-19	Apache License 2.0 for the upstream benchmark compilation
LongBench	MIT License
Synthetic passkey	Generated by our released evaluator; no external records

H What We Do Not Claim

- We do not claim that one key and value bit split works for every model.
- We do not claim faster kernels or decoding, or lower peak GPU memory.
- We do not claim that the 128-token residual window improves acceptance.
- We do not claim that our results hold under stochastic sampling.
- We do not quantize the target cache in the main method.
- We treat BF16 near ties separately from true target mismatches.
- We reject incomplete runs before computing aggregate results.