Distance-hereditary graphs characterize minimum-fusion synthesis of graph states

Sean Howell*

In fusion-based quantum computation, graph states are assembled from small entangled resource states by destructive two-qubit measurements called fusions. We study the minimum number $\mathrm{F}(G)$ of fusions needed to produce the graph state of a graph G on n vertices from three-qubit Greenberger-Horne-Zeilinger states, with Bell-type fusions on arbitrary pairs of qubits and free single-qubit Clifford operations. We prove that $\mathrm{F}(G) \geq n + 3\,\mathrm{rw}(G) - 6$ for every connected graph on $n \geq 3$ vertices, where $\mathrm{rw}(G)$ is the rank-width. The proof bounds the Schmidt rank of the output across each cut of a tree decomposition by the cycle rank of the network formed by the resources and the fusions. The bound is attained at rank-width one, and $\mathrm{F}(G) = n - 3$ holds if and only if G is distance-hereditary. Both directions of this characterization can be assembled from published results on Schmidt-rank width and split decompositions, but we have not found it stated, and the graph-theoretic core of its constructive direction is verified in Lean 4. An exhaustive search over the 585 connected local-complementation orbits on three to nine vertices, with every construction checked by two independently implemented stabilizer simulators, gives nineteen exact values of F above the minimum. The sixteen orbits with $\mathrm{F} = n$ attain the rank-width bound, whereas three orbits of rank-width two require $n + 3$ fusions, so the fusion cost is not determined by rank-width. For 25 orbits of rank-width three whose minimum is not known, the bound raises the lower bound from n to $n + 3$.

I. INTRODUCTION

Fusion-based quantum computation (FBQC) builds fault-tolerant computation from a supply of small, identical entangled resource states that are joined by fusions, destructive joint measurements of two qubits [1]. The three-qubit Greenberger-Horne-Zeilinger (GHZ) state is a basic resource in several photonic proposals [2, 3], and the number of fusions is a main cost in such architectures, which raises the question of how few fusions suffice to prepare a given entangled state. For graph states, the stabilizer states associated with simple graphs [4, 5], this becomes a combinatorial optimization over graphs. It has been approached with graph-theoretical heuristics for GHZ resources [6], with dynamic programming over local-complementation orbits for caterpillar states produced by a single quantum emitter [7], and through the design of fusion networks built from linear cluster states and other small motifs [8–10].

We take the resource to be the three-qubit GHZ state, whose graph is the path P_3. A fusion is the destructive measurement of a commuting pair of two-qubit Pauli operators that distinguishes the four Bell states, and it may act on any two qubits. Single-qubit Clifford operations are free. We write $\mathrm{F}(G)$ for the least number of fusions in a schedule whose output equals the graph state $|G\rangle$ up to single-qubit Cliffords and a relabeling of the qubits. Counting qubits and connected components shows that $\mathrm{F}(G) \geq n - 3$ for every connected graph on $n \geq 3$ vertices (Proposition 4). We prove a stronger lower bound in terms of the rank-width $\mathrm{rw}(G)$ and characterize the graphs that attain $n - 3$.

Theorem 1 (Rank-width bound)**.** *For every connected graph G on $n \geq 3$ vertices,* $\mathrm{F}(G) \geq n + 3\,\mathrm{rw}(G) - 6$.

Theorem 2 (Characterization)**.** *For a connected graph G on $n \geq 3$ vertices, $\mathrm{F}(G) = n - 3$ if and only if G is distance-hereditary.*

Distance-hereditary graphs [11, 12] are the graphs in which every connected induced subgraph preserves distances. They coincide with the graphs of rank-width at most one [13], with the graphs that have no vertex-minor isomorphic to the five-cycle [14–16], and with the graphs obtained from a single vertex by repeatedly adding pendant vertices and twins [12]. Since rank-width is invariant under local complementation [13] and equals the Schmidt-rank width of the graph state [17, 18], both theorems relate the fusion cost to an entanglement measure of $|G\rangle$ that is invariant under local Clifford operations.

Kumabe, Mori and Yoshimura [19] proved the analogous results for Clifford circuits, where preparing a connected graph state requires at least $n + \mathrm{rw}(G) - 2$ two-qubit gates, and exactly $n - 1$ when the rank-width is one. For caterpillar resources, Löbl *et al.* [7] showed that the number of fusions is at least the linear rank-width minus one. Theorem 1 is the counterpart of these bounds for fusions of GHZ states. Both directions of Theorem 2 can also be

* sean.g.howell@gmail.com

assembled from published results. The implication from $\mathrm{F}(G) = n - 3$ to distance-heredity follows from the equality of Schmidt-rank width and rank-width [18] once one observes that the fusion network of an optimal schedule is a tree. The converse follows from the pendant-and-twin construction of Bandelt and Mulder [12] together with the graph rule for fusion [3, 6], or from the construction of distance-hereditary graph states by fusions along their split decomposition by Connolly *et al.* [20], combined with the preparation of star graph states from GHZ states by Lee and Jeong [6]. We have not found Theorem 2, the bound of Theorem 1, or exact minimum fusion counts for this model in the literature.

Other preparation costs have been studied in related settings. Davies and Jena [21] bound the number of two-qubit gates needed to prepare graph states from classes closed under vertex-minors, unconditionally for circle graphs and for bounded rank-width, and by $O(n \log n)$ for every proper vertex-minor-closed class assuming a structural conjecture of Geelen. Cabello *et al.* [22] and Sharma *et al.* [23] studied the representatives of local-complementation orbits with the fewest gates or edges, and Sharma *et al.* used edge minimization to reduce the GHZ resources and fusions needed for repeater graph states. Adcock *et al.* [24] bounded which graph states can be produced from optical resources with postselected fusions. Whether one graph state can be transformed into another by single-qubit Clifford operations, single-qubit Pauli measurements and classical communication is decidable in time cubic in the size of the source when its rank-width and the size of the target are bounded [25]. In general this problem is NP-complete, even when the target is a tensor product of Bell pairs on specified pairs of qubits, and more efficient algorithms exist for particular targets [26, 27]. Counting the labeled graph states in an orbit under local complementation alone, without identifying isomorphic graphs, is #P-complete [28]. For distance-hereditary graphs, Connolly, Nishio and Nemoto [29] derived the sizes of the local-equivalence classes of several families. The local-equivalence classes of graph states were classified by Hein *et al.* [4] for $n \le 7$ and by Danielsen and Parker [30] for $n \le 12$, and they were mapped by Adcock *et al.* [31].

Theorems 1 and 2 are proved in Secs. II and III. The proofs use the graph rule for a fusion of two disjoint graph states (Lemma 3) and standard facts about rank-width. The graph-theoretic core of the constructive direction of Theorem 2 has been verified with the Lean 4 proof assistant [32] and its mathematical library [33]. The Lean development shows that a graph on $k + 3$ vertices is reachable from P_3 by k pendant and false-twin additions interleaved with local complementations if and only if it belongs to the class generated from the connected three-vertex graphs by pendant and twin additions and local complementation, which is the class of connected distance-hereditary graphs on at least three vertices (Sec. IV). In Sec. V we report an exhaustive search over the 585 connected local-complementation orbits with $3 \le n \le 9$, which agrees with Theorem 2 on every orbit and determines nineteen values of F above the minimum. The characterization was first conjectured by a language model from the labeled orbits with $3 \le n \le 7$, within an automated system that accepts a claim only after machine verification, and the same model wrote the Lean proofs. Given the results cited above, the characterization is within reach of standard techniques, and we describe how it was found in Sec. VI.

II. GRAPH STATES AND FUSIONS

For a simple graph $G = (V, E)$ the graph state

$$|G\rangle = \prod_{\{u,v\}\in E} \mathrm{CZ}_{uv}\, |+\rangle^{\otimes V}$$

is the unique common $+1$ eigenvector of the operators $K_v = X_v \prod_{u\in N(v)} Z_u$, $v \in V$, where $N(v)$ is the neighborhood of v. Local complementation at v replaces the subgraph induced on $N(v)$ by its complement, and we write $\tau_v(G)$ for the result. On graph states it is implemented, up to a global phase, by a product of single-qubit Clifford unitaries [34],

$$|\tau_v(G)\rangle = e^{-i\pi X_v/4} \prod_{u\in N(v)} e^{i\pi Z_u/4}\, |G\rangle, \tag{1}$$

and two graph states on the same qubits are related by a product of single-qubit Clifford unitaries if and only if their graphs are related by a sequence of local complementations [34]. The qubits that survive a schedule carry no fixed labels, so we also identify isomorphic graphs and write $G \sim_{\mathrm{LC}} H$ for the equivalence generated by local complementation and isomorphism. For $A \subseteq V$, the cut-rank $\rho_G(A)$ is the rank over GF(2) of the $A \times (V \setminus A)$ submatrix of the adjacency matrix, and the Schmidt rank of $|G\rangle$ across the bipartition $(A, V \setminus A)$ is $2^{\rho_G(A)}$ [4].

A schedule starts from g copies of the three-qubit GHZ state, whose graph is P_3 and which is LC-equivalent to the triangle K_3. A fusion on two distinct qubits a and b is the destructive measurement of the commuting observables $X_a Z_b$ and $Z_a X_b$, after which both qubits are discarded. This is a Bell measurement preceded by a Hadamard gate on b, the convention of Refs. [6, 35], and other Bell-type conventions differ from it by single-qubit Cliffords on a and b,

which are free in our model. A schedule interleaves fusions, on any pairs of qubits, with arbitrary single-qubit Clifford gates, and it produces G if for every measurement outcome the state of the surviving qubits is LC-equivalent to $|G\rangle$. The outcomes of a fusion on a stabilizer state give post-measurement states that differ by Pauli operators [6, 35], so this condition does not depend on the outcomes. We therefore treat fusions as deterministic and leave the probabilistic success of linear-optical fusion [36] to a layer above the present problem. The cost of a schedule is its number of fusions, and $\mathrm{F}(G)$ is the least cost of a schedule that produces G.

Lemma 3 (Fusion of disjoint graph states)**.** *Let G_1 and G_2 be graphs on disjoint vertex sets, a a vertex of G_1 and b a vertex of G_2. A fusion on (a, b) applied to $|G_1\rangle \otimes |G_2\rangle$ leaves, up to a Pauli operator that depends on the outcomes, the graph state of the graph on $(V_1 \cup V_2) \setminus \{a, b\}$ whose edges are the edges of G_1 and G_2 not incident to a or b, together with every pair $\{u, w\}$ with $u \in N_{G_1}(a)$ and $w \in N_{G_2}(b)$.*

This is the standard graph rule for type-II fusion [36]. It is stated in this form in Refs. [3, 6] and in full generality in Ref. [35], and we sketch the stabilizer calculation for completeness. The observable $X_a Z_b$ anticommutes exactly with K_b and with K_u for $u \in N(a)$, and $Z_a X_b$ anticommutes exactly with K_a and with K_w for $w \in N(b)$. Measuring $X_a Z_b$ and then $Z_a X_b$ replaces K_u by $K_u K_b$ and K_w by $K_w K_a$. Multiplying these by $Z_a X_b$ and $X_a Z_b$, respectively, removes their support on a and b and leaves $X_u Z_{N(u)\setminus\{a\}} Z_{N(b)}$ and $X_w Z_{N(w)\setminus\{b\}} Z_{N(a)}$ up to sign, which are the stabilizers of the graph in the lemma. Both of our stabilizer simulators also reproduce the rule on random inputs (Sec. V).

Fusing a vertex a of a graph with a qubit of a fresh resource therefore adds one vertex, in one of three ways that depend on the graph used to represent the resource. All three are available because single-qubit Cliffords on a fresh resource are free. Fusing with a leaf of P_3 replaces a by the center of P_3 and attaches the other leaf to it, which up to relabeling adds a pendant vertex at a. Fusing with the center of P_3 replaces a by the two leaves, each with the neighborhood of a and not adjacent to each other, which adds a false twin. Fusing with a vertex of K_3 replaces a by the other two vertices, which are adjacent, and adds a true twin. We call these fusions merges.

Proposition 4 (Counting bound)**.** *Let a schedule with g resources and f fusions produce a connected graph on $n \geq 3$ vertices, and let H be the multigraph whose vertices are the resources, with one edge for each fusion joining the resources that hold its two qubits. Then exactly one connected component H_0 of H contains surviving qubits. If H_0 has g_0 resources, f_0 fusions and cycle rank $t = f_0 - g_0 + 1$, then $f \geq f_0 = n - 3 + 3t$. In particular $\mathrm{F}(G) \geq n - 3$, and every schedule has $f \equiv n \pmod 3$.*

Proof. Fusions in different components of H act on different tensor factors. If two components held surviving qubits, the output would be a product state across them, which is impossible because every cut-rank of a connected graph is positive, so that $|G\rangle$ is entangled across every bipartition. Counting the qubits of H_0 gives $3g_0 - 2f_0 = n$, and with $g_0 = f_0 - t + 1$ this becomes $f_0 = n - 3 + 3t$, where $t \geq 0$ because H_0 is connected. The same count over all of H, whose other components have all their qubits fused, gives $3g - 2f = n$ and hence $f \equiv n \pmod 3$. □

A counting form of the bound, in a model of schedules that also tracks fusions which split or consume a component, is the Lean theorem `fusion_cost_lower_bound`.

III. THE RANK-WIDTH BOUND AND THE CHARACTERIZATION

A rank decomposition of a graph G on at least two vertices is a tree T whose internal nodes have degree three and whose leaves are the vertices of G. Each edge e of T splits the leaves into two sets $(A_e, V \setminus A_e)$, and the width of T is $\max_e \rho_G(A_e)$. The rank-width $\mathrm{rw}(G)$ is the least width of a rank decomposition of G [13, 16]. A connected graph on at least two vertices has $\mathrm{rw}(G) \geq 1$, and $\mathrm{rw}(G) \leq 1$ if and only if G is distance-hereditary [13].

Proof of Theorem 1. Take a schedule with $f = \mathrm{F}(G)$ fusions that produces G, and let H_0, g_0, f_0 and t be as in Proposition 4. A single-qubit gate commutes with every operation that does not act on its qubit, so each gate on a fused qubit may be applied to its resource before any fusion, and each gate on a surviving qubit may be applied at the end, where it does not change Schmidt ranks. Fusions act on disjoint pairs of qubits and commute with one another. Conditioned on the outcomes, the state of the surviving qubits is then, up to normalization and single-qubit unitaries,

$$\psi = \Big(\bigotimes_e \langle \beta_e | \Big) \Big(\bigotimes_r |R_r\rangle \Big),$$

where r runs over the resources of H_0, $|R_r\rangle$ is resource r with its gates applied, e runs over the fusions of H_0, and $\langle \beta_e|$ is the two-qubit bra of the outcome of e. The components of H without surviving qubits contribute only a scalar

factor. Choose a spanning tree S of H_0, so that t fusions of H_0 lie outside S, and form a tree T from S by attaching each surviving qubit as a leaf to its resource. Each of the three qubits of a resource either survives, is fused along an edge of S, or is fused along an edge outside S, so every resource has degree at most three in T. Repeatedly deleting resource nodes of degree one and suppressing nodes of degree two turns T into a rank decomposition T' of G, once the surviving qubits are identified with the vertices of G.

Each edge of T' arises from a path in T, and all edges of that path induce the same cut of the surviving qubits. If the path is a single leaf edge, the cut separates one vertex and has cut-rank at most one. Otherwise the path contains an edge e of S. Removing e splits the resources of H_0 into two sets X and Y, and the surviving qubits into A and B, and the fusions joining X and Y are e together with some of the t fusions outside S. After contracting the fusions inside X and inside Y, each remaining bra $\langle\beta|$ is a two-qubit state and hence a sum of two product bras. Expanding them writes ψ as a sum of at most 2^{1+t} products of a state on A and a state on B, so the Schmidt rank of ψ across (A, B) is at most 2^{1+t}. Since ψ is LC-equivalent to $|G\rangle$, it follows that $\rho_G(A) \le 1+t$. Every edge of T' therefore has cut-rank at most $1+t$, so $\mathrm{rw}(G) \le 1+t$, and Proposition 4 gives $\mathrm{F}(G) = f \ge n-3+3t \ge n-3+3(\mathrm{rw}(G)-1)$. □

The argument is the fusion analogue of bounding the Schmidt-rank width of a tensor network by its bond structure [17, 18], and it is close in spirit to the bound $\mathrm{F} \ge \mathrm{lrw}(G) - 1$ in terms of the linear rank-width in Ref. [7] and to the gate bound of Ref. [19]. Since only the cycle rank of the fusion network enters, the bound holds for any destructive two-qubit measurement with pure outcomes, of which Bell-type fusions are a special case.

Proof of Theorem 2. (⇒) If $\mathrm{F}(G) = n-3$, then $\mathrm{rw}(G) \le 1$ by Theorem 1, so G is distance-hereditary [13].

(⇐) A connected distance-hereditary graph on $n \ge 3$ vertices is obtained from a connected graph on three vertices, P_3 or K_3, by $n-3$ additions of pendant vertices, false twins and true twins, with every intermediate graph connected [12]. Start from one resource represented as P_3 or K_3, and realize each addition at a vertex a by a merge with a fresh resource, at a leaf of P_3, at the center of P_3 or at a vertex of K_3. By Lemma 3 this schedule produces G with $n-3$ fusions, and Proposition 4 gives $\mathrm{F}(G) = n-3$. □

At the minimum, the proof of Theorem 1 shows that $t = 0$, so the fusion network is a tree on $n-2$ resources whose $n-3$ fusions each join two components. The constructive direction can also be obtained from the split decomposition. Every node of the split decomposition of a distance-hereditary graph is a star or a complete graph [15, 37, 38], Connolly *et al.* [20] assemble the graph state from the graph states of the nodes by type-II fusions along the split tree, and Lee and Jeong [6] build an m-vertex star from $m-2$ GHZ states with $m-3$ fusions. Together these again use $n-2$ resources and $n-3$ fusions.

IV. FORMAL VERIFICATION

The Lean development is in the directory `lean/EmpiricistLean` of the accompanying repository and uses MATHLIB at release `v4.31.0`. The ancillary files contain the modules behind every declaration cited here as a self-contained Lake project, together with a script that builds it and prints the axioms of each declaration (Table II in Appendix B). All of them depend only on the axioms `propext`, `Classical.choice` and `Quot.sound`. The development covers the combinatorics of the constructive direction of Theorem 2. The steps that involve quantum states, Lemma 3 and the proof of Theorem 1, are not formalized.

Graphs are MATHLIB `SimpleGraph`s on an arbitrary vertex type, and the production predicates are defined on concrete graphs. Let $\mathsf{Prod}_k^+(G)$ state that G is obtained from P_3 by k steps, each of which adds a pendant vertex (the leaf-merge, `ghz3LeafMerge`) or a false twin (the center-merge), interleaved with any number of local complementations and isomorphisms (the inductive `ProducibleByExt`). The lemma `ghz3CenterMerge_iso_addFalseTwin` identifies the center-merge, written as the graph rewrite of Lemma 3, with false-twin addition up to isomorphism. Let DH be the class generated from P_3 and K_3 by pendant, false-twin and true-twin additions, local complementation and isomorphism (the inductive `PendantTwinBuildable`). Without the local-complementation constructor these are the connected distance-hereditary graphs on at least three vertices [12], and the constructor adds no graphs, since that class is closed under local complementation [13]. This identification is not formalized.

Theorem 5 (Model characterization, Lean)**.** *For a finite graph G, $\mathsf{Prod}^+_{|V(G)|-3}(G)$ holds if and only if $G \in \mathsf{DH}$ (`dh_characterization`).*

The forward implication is a structural induction on Prod^+, each of whose constructors is also a constructor of DH. The converse (`dh_forward`) is a structural induction on DH. A pendant addition is a leaf-merge and a false-twin addition is a center-merge, and a true-twin addition is realized by a local complementation, a leaf-merge and a second local complementation, through the identity

$$\tau_u\big(\mathrm{addPendant}(G,u)\big) \;=\; \mathrm{addTrueTwin}\big(\tau_u(G),\,u\big) \tag{2}$$

n	3	4	5	6	7	8	9	total
connected orbits	1	2	4	11	26	101	440	585
$\mathrm{F} = n-3$ (distance-hereditary)	1	2	3	8	15	42	104	175
$\mathrm{F} = n$	0	0	1	2	7	6	0	16
$\mathrm{F} = n+3$	0	0	0	1	2	0	0	3
open, $\mathrm{F} \geq n$	0	0	0	0	0	52	312	364
open, $\mathrm{F} \geq n+3$	0	0	0	0	2	1	24	27

TABLE I. Connected local-complementation orbits by number of vertices. The orbits with $\mathrm{F} = n-3$ are exactly the distance-hereditary ones. All other orbits have rank-width two, except for the 25 open orbits with $n \in \{8, 9\}$ and rank-width three, whose bound $\mathrm{F} \geq n+3$ comes from Theorem 1. The two open orbits with $n = 7$ have $\mathrm{F} \geq n+3$ from the exhaustive Tier 1 search.

(`addPendant_localComplement_center`) and the fact that τ_u is an involution. Combined with `fusion_cost_lower_bound`, the theorem `dh_min_fusions` states the constructive direction of Theorem 2 at the level of the model. A further theorem, `floor_schedule_iff_dh`, extends Theorem 5 to a schedule model with one additional constructor, which may replace the current graph by an arbitrary graph with two fewer vertices at the cost of one fusion. This over-approximates a fusion of two qubits of the same component, and at the minimum a count of vertices excludes it.

Before the general theorem, the development proves constructions at the minimum for several families, each stated together with the general lower bound so that no family theorem can hold vacuously. Paths, stars and all trees are handled by induction on the removal of leaves, K_n is one local complementation away from a star, and $K_{m,n}$ is three local complementations away from a double star. All of these graphs are distance-hereditary.

Remark 6. Although every statement about F is invariant under local complementation, the inductions cannot be carried out on $\sim_{\mathrm{LC}}$ classes, because pendant addition does not descend to them. The graphs P_3 and K_3 are LC-equivalent, yet a pendant at the center of P_3 gives the four-vertex star, while a pendant at a vertex of K_3 gives the paw, which is LC-equivalent to the path P_4 and not to the star. The development therefore carries concrete graphs through every induction and applies local complementation only where it is needed. An earlier production model contained only the leaf-merge and therefore generated only trees. It reaches the minimum only on the local-complementation classes of trees, which make up 93 of the 175 distance-hereditary orbits with $3 \leq n \leq 9$, one for each tree on 3 to 9 vertices, since locally equivalent trees are isomorphic [15]. Adding the center-merge removed this restriction.

V. MINIMUM FUSION COUNTS FOR SMALL GRAPHS

We assigned every connected graph with $3 \leq n \leq 9$ to its local-complementation orbit. There are 1, 2, 4, 11, 26, 101 and 440 orbits for $n = 3, \ldots, 9$, or 585 in total, in agreement with Danielsen and Parker [30]. By Proposition 4 the search proceeds in tiers $\mathrm{F} = n-3$, $\mathrm{F} = n$, and so on. Tier 0 is a breadth-first search over graphs in which local complementation is free and a merge at any vertex, with a fresh resource fused at a leaf or at the center, costs one fusion; true twins arise through Eq. (2). Tier 1 grows graphs by merges to $n+2$ vertices and then performs one fusion of two qubits of the same component. Both tiers are exhaustive by the normal form of Appendix A, which shows that any schedule can be reordered so that the merges come first and grow a single component, and that single-qubit Cliffords on the qubits of a merge can be absorbed by local complementations. Every fusion in the search is computed in the fixed basis of Sec. II. For the single fusion inside the component in Tier 1 we repeated the search with each of the six classes of single-qubit Clifford on one of the two fused qubits, which together with the symmetry of the measured pair covers all choices on both qubits, and for $n \leq 5$ we tried all 36 pairs. No orbit changed.

Each recorded construction is replayed by two stabilizer simulators with independent implementations of fusion and of graph extraction, a tableau simulator built on STIM [39] and an implementation over GF(2). The two share the code that replays a construction, the graph-level local complementation and the canonicalization of orbits, which uses NAUTY [40]. The closed-form merge rule used in the inner loop of the search agrees with both simulators on randomized inputs. The resulting table has one row for each of the 585 orbits, with an orbit representative and either an exact value with a witness schedule or a lower bound, and it is stored as a single content-addressed file. Nine exact values above the minimum were added later from constructions proposed by the language model.

Table I summarizes the results. An independent pendant-and-twin elimination [12] on all 585 representatives confirms that the orbits with $\mathrm{F} = n-3$ are exactly the distance-hereditary ones. Nineteen orbits have exact values above the minimum. For the sixteen orbits with $\mathrm{F} = n$, the upper bounds come from constructions and the lower bounds from Theorem 2. The three orbits with $\mathrm{F} = n+3$ are a six-vertex orbit with $\mathrm{F} = 9$, realized with eight resources, nine fusions and three local complementations, and two seven-vertex orbits with $\mathrm{F} = 10$. Their lower

bounds come from the exhaustive Tier 1 search.

To test the rank-width bound, we computed the rank-width of every orbit above the minimum exactly, by enumerating all rank decompositions. Every orbit with $n \leq 7$ that is not distance-hereditary has rank-width two, and so do all sixteen orbits with $\mathrm{F} = n$, which therefore attain the bound $\mathrm{F} \geq n$ of Theorem 1. The three orbits with $\mathrm{F} = n+3$ also have rank-width two, and the bound falls short of their cost by three. Above rank-width one, therefore, the fusion cost is not a function of rank-width. The bound improves the table for 25 open orbits, one with $n = 8$ and 24 with $n = 9$, which have rank-width three and hence $\mathrm{F} \geq n+3$, whereas the search had established only $\mathrm{F} \geq n$.

VI. COMPUTATIONAL METHODS

The search and the formal proofs were produced with Empiricist, an open-source system in which a language model proposes conjectures, constructions and complete Lean modules as structured output and never executes code. Each proposal is recorded with a status that can rise only when a verifier accepts it, a claim supported only by the model's assertion stays at the lowest status, and a refuted claim remains refuted. Each verifier must first pass a fixed suite of test cases, and claims and verifiers are identified by content hashes. Fusion outcomes are computed by the two simulators described in Sec. V, and a construction is accepted only when both agree on the resulting state up to local Clifford equivalence. Lean modules are elaborated in a sandbox without network or process creation, against a frozen copy of MATHLIB. The kernel result is checked again, the axioms must lie within {`propext`, `Classical.choice`, `Quot.sound`}, every import must belong to a fixed trusted set, and the build directory is cleared after elaboration. This checker was tested against adversarial submissions, including tampered compiled files, substitution of files between checking and use, and elaborators that hide axioms, before it was used.

For Theorem 2, the model was given the 44 orbits with $3 \leq n \leq 7$ as edge lists, each marked according to whether it attains $\mathrm{F} = n-3$, with no invariant or class name and with only the information that the property is invariant under local complementation. It proposed that the orbits attaining the minimum are the distance-hereditary graphs, recalled the standard equivalent characterizations, and identified the orbit of C_5 as the unique orbit on five vertices that does not attain it. The proposal was recorded as a conjecture, and a deterministic test for distance-heredity on all 585 orbits, including the 541 orbits on eight and nine vertices that the model had not seen, agreed with it in every case. The model then wrote the Lean proofs in a loop in which the checker returns the remaining proof obligations and the model revises the module, without running Lean itself. These checks caught several errors during the work, among them an arithmetic slip in an early hand-written count of the extremal orbits (185/400 instead of 175/410), a family theorem whose first statement had its construction built into the claim, and, while this paper was being prepared, a note that reported the linear rank-width of the six-vertex orbit with $\mathrm{F} = 9$ as its rank-width. Related uses of machine learning in mathematics include conjectures guided by data [41], new constructions in combinatorics and analysis found by program search with language models [42–44], and machine-generated proofs checked by a symbolic deduction engine [45] or by the Lean kernel [46].

VII. DISCUSSION

The combinatorial part of the constructive direction of Theorem 2 is verified in Lean, while the steps that involve quantum states, Lemma 3 and the proof of Theorem 1, are written proofs supported by the two simulators and by the exhaustive search. A complete formalization would require definitions of graph states, Pauli measurements and schedules in Lean, and rank-width is not yet available in MATHLIB.

Several questions remain open. The data of Sec. V show that F is not a function of rank-width beyond rank-width one, and it would be interesting to find the invariant that separates $\mathrm{F} = n$ from $\mathrm{F} = n+3$ among graphs of rank-width two. Theorem 2 makes the decision problem $\mathrm{F}(G) = n-3$ polynomial, since distance-hereditary graphs are recognized by pendant-and-twin elimination [12], but the complexity of computing F in general is open. It is also natural to ask whether analogous characterizations hold for larger GHZ states or for linear cluster states as resources.

DATA AND CODE AVAILABILITY

The repository `https://github.com/sghowell/empiricist` (MIT license) contains the system, the Lean development, the table of minimum fusion counts and the record of claims. The ancillary files of this paper contain the Lean modules behind every declaration in Table II, as a self-contained Lake project with a script that builds them and prints their axioms, as well as the table, the nine later constructions, and scripts that recompute every number in Sec. V, including the exact rank-widths, replay the constructions with both simulators, and repeat Tier 1 with

single-qubit Cliffords on the fused qubits. A README maps each statement of the paper to a file, and a SHA-256 manifest lists every file.

ACKNOWLEDGMENTS

This work was carried out with AI systems working under my direction. Within Empiricist, the language model Fable 5 (Anthropic) classified the orbits, proposed the distance-hereditary characterization and wrote the Lean proofs, emitting only machine-checkable output and never executing code. Claude Code (Anthropic, model Claude Opus 5.5) surveyed the literature, proved Theorem 1, wrote the remaining proofs, recomputed every number from the committed data and drafted the manuscript. Codex (OpenAI, model gpt-6-astra) independently checked the proofs, the claims and the relation to previous work, and confirmed that a later rewording of the text did not change its content; the errors it found have been corrected. I chose the problem and take full responsibility for the content of this paper.

Appendix A: The normal form behind the search

The exhaustiveness of Tiers 0 and 1 rests on two lemmas.

Lemma 7 (Absorbing single-qubit Cliffords)**.** *Let v be a vertex of a graph G with at least one neighbor, and let C be a single-qubit Clifford unitary. Then there are a graph G', obtained from G by local complementations, and a product D of single-qubit Cliffords acting trivially on v, such that $C_v|G\rangle = D\,|G'\rangle$ up to a Pauli operator and a global phase.*

Proof. Single-qubit Clifford unitaries modulo Pauli operators and phases form a group isomorphic to the symmetric group on $\{X, Y, Z\}$, acting by conjugation, and $e^{-i\pi X/4}$ and $e^{i\pi Z/4}$ act as the transpositions $(Y\,Z)$ and $(X\,Y)$, which generate it. By Eq. (1), local complementation at v multiplies the local unitary on v by $e^{-i\pi X_v/4}$, and local complementation at a neighbor u of v multiplies it by $e^{i\pi Z_v/4}$. Neither operation removes the edge $\{u, v\}$, since τ_v changes only edges inside $N(v)$ and τ_u only edges inside $N(u)$. A suitable word in τ_v and τ_u therefore gives a graph G' and a product $U = \bigotimes_w U_w$ of single-qubit Cliffords with $U|G\rangle = |G'\rangle$ up to a Pauli operator and $U_v = C$ modulo Paulis. Then $C_v|G\rangle = \big(\bigotimes_{w\neq v} U_w^{-1}\big)U|G\rangle$, which equals $D|G'\rangle$ with $D = \bigotimes_{w\neq v} U_w^{-1}$ up to a Pauli operator. □

Lemma 8 (Single-component normal form)**.** *Suppose a schedule with f fusions produces a connected graph G on n vertices. Then G is also produced by a schedule with $f' \le f$ fusions and g' resources, $3g' - 2f' = n$, of the following form. One resource serves as the seed, and each of the other $g'-1$ resources is attached by a merge, a fusion between a qubit of the current component, which is a connected graph state, and a qubit of the fresh resource, with no single-qubit Clifford on either fused qubit. Local complementations of the component may occur between merges. The remaining $f'-g'+1$ fusions follow all merges and act on two qubits of the component, and single-qubit Cliffords on the surviving qubits come last.*

Proof. A single-qubit Clifford on a qubit q commutes with every operation that does not act on q, and the only other operation that acts on q is the fusion that consumes it, if there is one. We first move each such gate to just after the preparation of its resource, to just before the fusion that consumes q, or to the end of the schedule if q survives.

Next we delete the components of the multigraph H of Proposition 4 that contain no surviving qubit, since they act on separate tensor factors. The resulting H is connected, with g' resources and $f' \le f$ fusions, and $3g' - 2f' = n$.

We then reorder the fusions. Choose a spanning tree of H, a root resource, and a breadth-first order of the resources from the root along the tree. For each resource c other than the root, with parent p, pick one fusion joining p and c, and call these fusions the merges. We place the merges first, in the order of their child resources, followed by all other fusions in their original relative order. Fusions act on disjoint pairs of qubits and commute, so the final state on the surviving qubits, conditioned on the outcomes, does not change, and only the Pauli corrections may differ. When the merge of c is performed, its qubit in p has not been consumed and c has not yet been touched, so the merge fuses a qubit of the component grown so far with a qubit of a fresh resource. Every later fusion acts on two qubits of that component.

Finally we remove the Cliffords on the qubits of the merges, processing the merges in order. Before the merge of c, the component is the graph state of a connected graph B on at least three vertices, up to single-qubit Cliffords, because the seed has three vertices and each merge adds one vertex and keeps the graph connected by Lemma 3, both joined neighborhoods being nonempty. The fused qubit a of the component has a neighbor, so Lemma 7 replaces the Clifford on a by local complementations of B and Cliffords on other qubits, which are carried forward. On the side of the fresh resource, Lemma 7 applied to its three-vertex graph removes the Clifford on the fused qubit and leaves P_3 with some center, or K_3. The merge is then a fusion without single-qubit Cliffords on either fused qubit. Cliffords

carried onto qubits that later merges consume are removed in the same way when those merges are reached, Cliffords on qubits consumed by the final fusions inside the component remain, as the lemma allows, and the rest move to the end. □

At the minimum the normal form has no fusion inside the component, so Tier 0 is exhaustive for $\mathrm{F} = n - 3$. Tier 1, which applies one such fusion after all merges, is exhaustive for $\mathrm{F} = n$, given the repetition of the search with single-qubit Cliffords on its two fused qubits described in Sec. V.

Appendix B: Principal Lean declarations

declaration	statement	file
`fusion_cost_lower_bound`	$f \geq n - 3$ in a merge model of schedules	`Foundation.lean`
`tree_min_fusions`	construction at the minimum for every tree	`TreeThm.lean`
`pathGraph_min_fusions`	paths	`Paper/PathGraph.lean`
`star_min_fusions`	stars	`Paper/Star.lean`
`complete_min_fusions`	complete graphs K_n	`Paper/Complete.lean`
`completeBipartite_min_fusions`	complete bipartite graphs $K_{m,n}$	`Paper/CompleteBipartite.lean`
`ghz3CenterMerge_iso_addFalseTwin`	the center-merge is false-twin addition	`CenterMerge.lean`
`addPendant_localComplement_center`	the identity (2)	`TrueTwin.lean`
`dh_forward`, `dh_min_fusions`	$\mathsf{DH} \Rightarrow \mathsf{Prod}^{+}_{n-3}$	`DHCharacterization.lean`
`dh_characterization`	$\mathsf{Prod}^{+}_{n-3}(G) \Leftrightarrow G \in \mathsf{DH}$	`DHCharacterization.lean`
`floor_schedule_iff_dh`	the over-approximating schedule model	`Paper/FloorBridge.lean`

TABLE II. Principal Lean declarations. Files without a directory are library modules of the repository, and files in `Paper/` are modules recorded as checked artifacts in its record of claims.

[1] S. Bartolucci, P. Birchall, H. Bombín, H. Cable, C. Dawson, M. Gimeno-Segovia, E. Johnston, K. Kieling, N. Nickerson, M. Pant, F. Pastawski, T. Rudolph, and C. Sparrow, Fusion-based quantum computation, Nature Communications **14**, 912 (2023), arXiv:2101.09310 [quant-ph].

[2] M. Gimeno-Segovia, P. Shadbolt, D. E. Browne, and T. Rudolph, From three-photon Greenberger-Horne-Zeilinger states to ballistic universal quantum computation, Physical Review Letters **115**, 020502 (2015), arXiv:1410.3720 [quant-ph].

[3] H. A. Zaidi, C. Dawson, P. van Loock, and T. Rudolph, Near-deterministic creation of universal cluster states with probabilistic Bell measurements and three-qubit resource states, Physical Review A **91**, 042301 (2015), arXiv:1410.3753 [quant-ph].

[4] M. Hein, J. Eisert, and H. J. Briegel, Multiparty entanglement in graph states, Physical Review A **69**, 062311 (2004), arXiv:quant-ph/0307130.

[5] M. Hein, W. Dür, J. Eisert, R. Raussendorf, M. Van den Nest, and H.-J. Briegel, Entanglement in graph states and its applications, in *Quantum Computers, Algorithms and Chaos*, Proceedings of the International School of Physics "Enrico Fermi", Vol. 162 (IOS Press, 2006) pp. 115–218, arXiv:quant-ph/0602096.

[6] S.-H. Lee and H. Jeong, Graph-theoretical optimization of fusion-based graph state generation, Quantum **7**, 1212 (2023), arXiv:2304.11988 [quant-ph].

[7] M. C. Löbl, L. A. Pettersson, A. Jena, L. Dellantonio, S. Paesani, and A. S. Sørensen, Generating graph states with a single quantum emitter and the minimum number of fusions, Physical Review A **111**, 052604 (2025), arXiv:2412.04587 [quant-ph].

[8] K. Staudacher, B. Jeevanesan, and T. Guggemos, Adaptive framework for failure-aware protocols in fusion-based graph-state generation, Physical Review A **114**, 032614 (2026), arXiv:2601.02087 [quant-ph].

[9] W. Cashman, G. de Felice, and A. Kissinger, Finding trail covers: near-optimal decompositions of graph states as linear fusion networks (2025), arXiv:2508.18375 [quant-ph].

[10] T. Ji, H. Weerasena, D. Farfurnik, and J. Liu, Towards efficient synthesis of quantum graph states by fusing graph motifs (2026), arXiv:2606.02880 [quant-ph].

[11] E. Howorka, A characterization of distance-hereditary graphs, The Quarterly Journal of Mathematics **28**, 417 (1977).

[12] H.-J. Bandelt and H. M. Mulder, Distance-hereditary graphs, Journal of Combinatorial Theory, Series B **41**, 182 (1986).

[13] S.-i. Oum, Rank-width and vertex-minors, Journal of Combinatorial Theory, Series B **95**, 79 (2005).

[14] A. Bouchet, Isotropic systems, European Journal of Combinatorics **8**, 231 (1987).

[15] A. Bouchet, Transforming trees by successive local complementations, Journal of Graph Theory **12**, 195 (1988).

[16] S.-i. Oum, Rank-width: Algorithmic and structural results, Discrete Applied Mathematics **231**, 15 (2017), arXiv:1601.03800 [math.CO].

[17] M. Van den Nest, A. Miyake, W. Dür, and H. J. Briegel, Universal resources for measurement-based quantum computation, Physical Review Letters **97**, 150504 (2006), arXiv:quant-ph/0604010.

[18] M. Van den Nest, W. Dür, G. Vidal, and H. J. Briegel, Classical simulation versus universality in measurement-based quantum computation, Physical Review A **75**, 012337 (2007), arXiv:quant-ph/0608060.

[19] S. Kumabe, R. Mori, and Y. Yoshimura, Complexity of graph-state preparation by Clifford circuits, Quantum **10**, 2165 (2026), arXiv:2402.05874 [quant-ph].

[20] N. Connolly, S. Nishio, D. E. Browne, W. J. Munro, and K. Nemoto, Efficient preparation of graph states using the quotient-augmented strong split tree (2026), arXiv:2603.23892 [quant-ph].

[21] J. Davies and A. Jena, Preparing graph states forbidding a vertex-minor (2025), arXiv:2504.00291 [quant-ph].

[22] A. Cabello, L. E. Danielsen, A. J. López-Tarrida, and J. R. Portillo, Optimal preparation of graph states, Physical Review A **83**, 042314 (2011), arXiv:1011.5464 [quant-ph].

[23] H. Sharma, K. Goodenough, J. Borregaard, F. Rozpędek, and J. Helsen, Minimising the number of edges in LC-equivalent graph states, Quantum **10**, 2001 (2026), arXiv:2506.00292 [quant-ph].

[24] J. C. Adcock, S. Morley-Short, J. W. Silverstone, and M. G. Thompson, Hard limits on the postselectability of optical graph states, Quantum Science and Technology **4**, 015010 (2019), arXiv:1806.03263.

[25] A. Dahlberg and S. Wehner, Transforming graph states using single-qubit operations, Philosophical Transactions of the Royal Society A **376**, 20170325 (2018), arXiv:1805.05305 [quant-ph].

[26] A. Dahlberg, J. Helsen, and S. Wehner, How to transform graph states using single-qubit operations: computational complexity and algorithms, Quantum Science and Technology **5**, 045016 (2020), arXiv:1805.05306 [quant-ph].

[27] A. Dahlberg, J. Helsen, and S. Wehner, Transforming graph states to Bell-pairs is NP-complete, Quantum **4**, 348 (2020), arXiv:1907.08019 [quant-ph].

[28] A. Dahlberg, J. Helsen, and S. Wehner, Counting single-qubit Clifford equivalent graph states is #p-complete, Journal of Mathematical Physics **61**, 022202 (2020), arXiv:1907.08024 [quant-ph].

[29] N. Connolly, S. Nishio, and K. Nemoto, Local equivalence classes of distance-hereditary graphs using split decompositions, Journal of Physics A: Mathematical and Theoretical **59**, 395310 (2026), arXiv:2602.23825 [math.CO].

[30] L. E. Danielsen and M. G. Parker, On the classification of all self-dual additive codes over GF(4) of length up to 12, Journal of Combinatorial Theory, Series A **113**, 1351 (2006), arXiv:math/0504522.

[31] J. C. Adcock, S. Morley-Short, A. Dahlberg, and J. W. Silverstone, Mapping graph state orbits under local complementation, Quantum **4**, 305 (2020), arXiv:1910.03969 [quant-ph].

[32] L. de Moura and S. Ullrich, The Lean 4 theorem prover and programming language, in *Automated Deduction – CADE 28*, Lecture Notes in Computer Science, Vol. 12699 (Springer, 2021) pp. 625–635.

[33] The mathlib Community, The Lean mathematical library, in *Proceedings of the 9th ACM SIGPLAN International Conference on Certified Programs and Proofs (CPP 2020)* (2020) pp. 367–381, arXiv:1910.09336.

[34] M. Van den Nest, J. Dehaene, and B. De Moor, Graphical description of the action of local Clifford transformations on graph states, Physical Review A **69**, 022316 (2004), arXiv:quant-ph/0308151.

[35] M. C. Löbl, L. A. Pettersson, S. Paesani, and A. S. Sørensen, Transforming graph states via Bell state measurements, Quantum **9**, 1795 (2025), arXiv:2405.02414 [quant-ph].

[36] D. E. Browne and T. Rudolph, Resource-efficient linear optical quantum computation, Physical Review Letters **95**, 010501 (2005), arXiv:quant-ph/0405157.

[37] P. L. Hammer and F. Maffray, Completely separable graphs, Discrete Applied Mathematics **27**, 85 (1990).

[38] E. Gioan and C. Paul, Split decomposition and graph-labelled trees: Characterizations and fully dynamic algorithms for totally decomposable graphs, Discrete Applied Mathematics **160**, 708 (2012).

[39] C. Gidney, Stim: a fast stabilizer circuit simulator, Quantum **5**, 497 (2021), arXiv:2103.02202 [quant-ph].

[40] B. D. McKay and A. Piperno, Practical graph isomorphism, II, Journal of Symbolic Computation **60**, 94 (2014), arXiv:1301.1493 [cs.DM].

[41] A. Davies, P. Veličković, L. Buesing, S. Blackwell, D. Zheng, N. Tomašev, R. Tanburn, P. Battaglia, C. Blundell, A. Juhász, M. Lackenby, G. Williamson, D. Hassabis, and P. Kohli, Advancing mathematics by guiding human intuition with AI, Nature **600**, 70 (2021).

[42] B. Romera-Paredes, M. Barekatain, A. Novikov, M. Balog, M. P. Kumar, E. Dupont, F. J. R. Ruiz, J. S. Ellenberg, P. Wang, O. Fawzi, P. Kohli, and A. Fawzi, Mathematical discoveries from program search with large language models, Nature **625**, 468 (2024).

[43] A. Novikov, N. Vũ, M. Eisenberger, E. Dupont, P.-S. Huang, A. Z. Wagner, S. Shirobokov, B. Kozlovskii, F. J. R. Ruiz, A. Mehrabian, M. P. Kumar, A. See, S. Chaudhuri, G. Holland, A. Davies, S. Nowozin, P. Kohli, and M. Balog, AlphaEvolve: A coding agent for scientific and algorithmic discovery (2025), arXiv:2506.13131.

[44] B. Georgiev, J. Gómez-Serrano, T. Tao, and A. Z. Wagner, Mathematical exploration and discovery at scale (2025), arXiv:2511.02864.

[45] T. H. Trinh, Y. Wu, Q. V. Le, H. He, and T. Luong, Solving olympiad geometry without human demonstrations, Nature **625**, 476 (2024).

[46] T. Hubert, R. Mehta, L. Sartran, M. Z. Horváth, G. Žužić, E. Wieser, A. Huang, J. Schrittwieser, Y. Schroecker, H. Masoom, O. Bertolli, T. Zahavy, A. Mandhane, J. Yung, I. Beloshapka, B. Ibarz, V. Veeriah, L. Yu, O. Nash, P. Lezeau, S. Mercuri, C. Sönne, B. Mehta, A. Davies, D. Zheng, F. Pedregosa, Y. Li, I. von Glehn, M. Rowland, S. Albanie, A. Velingker, S. Schmitt, E. Lockhart, E. Hughes, H. Michalewski, N. Sonnerat, D. Hassabis, P. Kohli, and D. Silver,

Olympiad-level formal mathematical reasoning with reinforcement learning, Nature **651**, 607 (2026).