Distance-hereditary graphs characterize minimum-fusion synthesis of graph states

Sean Howell*

In fusion-based quantum computation a graph state $|G\rangle$ on n qubits is assembled from small entangled resource states by destructive two-qubit fusion measurements. We study the minimum number $\mathrm{F}(G)$ of fusions when the resource is the three-qubit Greenberger-Horne-Zeilinger state, a fusion is a Bell-type measurement on any two qubits, and single-qubit Clifford operations are free. We prove $\mathrm{F}(G) \geq n + 3\,\mathrm{rw}(G) - 6$ for every connected graph G on $n \geq 3$ vertices, where rw is the rank-width: the cycle rank of the network of resources and fusions bounds the Schmidt rank of the output across every cut of a tree decomposition. At rank-width one the bound is attained, so for $n \geq 3$, $\mathrm{F}(G) = n - 3$ if and only if G is distance-hereditary; the constructive direction adds each pendant or twin of a distance-hereditary build with one fusion, and its graph-theoretic core is a Lean 4 theorem. Both directions can be assembled from published results on Schmidt-rank width and split decompositions, but we have not found the characterization stated. An exhaustive search over all 585 connected local-complementation orbits on three to nine vertices, with every construction accepted by two independently implemented stabilizer engines, gives nineteen exact values above the minimum: the rank-width bound is attained by all sixteen orbits with $\mathrm{F} = n$ and missed by the three, all of rank-width two, that need $n + 3$ fusions. The bound also raises the lower bound of 25 open orbits of rank-width three. The characterization was first proposed by a language model, working inside a harness that admits only machine-checked artifacts, from labeled data on three to seven vertices.

I. INTRODUCTION

Fusion-based quantum computation (FBQC) builds fault-tolerant computation from a supply of small, identical entangled *resource states* that are joined by *fusions*: destructive joint measurements of two qubits [1]. The three-qubit Greenberger-Horne-Zeilinger (GHZ) state is a basic resource in several photonic proposals [2, 3], and the number of fusions is a main physical cost, so for any target entangled state it is natural to ask how few fusions suffice to make it. For graph states, the stabilizer states in one-to-one correspondence with simple graphs [4, 5], this is a combinatorial optimization over graphs that has been studied with heuristics and with dynamic programming in several resource models [6–10].

We work in the model whose resource is the three-qubit GHZ state, whose graph is the path P_3; each fusion destructively measures a commuting pair of two-qubit Pauli operators that distinguishes the four Bell states, and single-qubit Clifford operations are free. Let $\mathrm{F}(G)$ be the least number of fusions that produce a state equal, up to single-qubit Cliffords and relabeling, to the graph state $|G\rangle$. Counting qubits and connected components gives $\mathrm{F}(G) \geq n - 3$ for a connected graph on $n \geq 3$ vertices (Proposition 4). Our results are a lower bound in terms of rank-width and the characterization of the graphs that attain the minimum.

Theorem 1 (Rank-width bound)**.** *For every connected graph G on $n \geq 3$ vertices,* $\mathrm{F}(G) \geq n + 3\,\mathrm{rw}(G) - 6$.

Theorem 2 (Characterization)**.** *For a connected graph G on $n \geq 3$ vertices,* $\mathrm{F}(G) = n - 3$ *if and only if G is distance-hereditary.*

Distance-hereditary graphs [11, 12] are the graphs in which every connected induced subgraph preserves distances. They are exactly the graphs of rank-width at most one [13], the graphs with no vertex-minor isomorphic to the five-cycle [14–16], and the graphs obtained from a single vertex by repeatedly adding pendant vertices and twins [12]. Rank-width is invariant under local complementation [13] and equals the Schmidt-rank width of the graph state [17, 18], so both results tie the fusion cost to a local-Clifford-invariant measure of the entanglement structure of $|G\rangle$.

a. Relation to previous work. Both theorems have close relatives. In the circuit model, Kumabe, Mori and Yoshimura [19] prove that preparing a connected graph state needs at least $n + \mathrm{rw}(G) - 2$ two-qubit Clifford gates, with exactly $n - 1$ at rank-width one; Theorem 1 is the analogue for fusions of three-qubit resources. Width-dependent fusion bounds were known before in a model with emitter-generated caterpillar resources: Löbl *et al.* [7] tabulate exact minimum fusion counts for all graph states on up to eight qubits and show that the count is at least the linear rank-width minus one. The implication from $\mathrm{F}(G) = n - 3$ to distance-hereditary in Theorem 2 also follows from the

* sean.g.howell@gmail.com

equality of Schmidt-rank width and rank-width [18] once the fusion network at the minimum is seen to be a tree, and the converse from the pendant-and-twin build of Bandelt and Mulder [12] with the graph rule for fusion [3, 6], or from the split-decomposition construction of distance-hereditary graph states by Connolly *et al.* [20] together with the construction of star graph states from GHZ states by Lee and Jeong [6]. We make the characterization explicit in this resource model and prove the more general bound; we have not found either statement, or a classification of minimum fusion counts in this model, in the literature (Section VII).

b. What is proved, and how. The paper contains three kinds of argument.

- *Written proofs.* Theorem 1 and both directions of Theorem 2 are proved in Sections II and III from the graph rule for a fusion of two disjoint graph states (Lemma 3) and standard facts about rank-width.
- *Lean theorems.* The graph-theoretic core of the constructive direction is checked by the Lean 4 kernel [21] against MATHLIB [22] with only the axioms `propext`, `Classical.choice` and `Quot.sound`: a graph is reachable from P_3 by k pendant and false-twin steps together with free local complementations if and only if it belongs to the class generated from the connected three-vertex graphs by pendant and twin additions and local complementation, on $k+3$ vertices; this class is the distance-hereditary graphs. The development also contains a counting form of the lower bound and explicit constructions for paths, stars, trees, complete graphs and complete bipartite graphs (Section IV).
- *Computation.* Two independently implemented stabilizer engines agree with the fusion rule on random inputs, and an exhaustive search over all 585 connected local-complementation orbits with $3 \le n \le 9$ agrees with Theorem 2 on every orbit and gives exact values above the minimum (Section V).

c. How the result was found. The characterization was first proposed by a language model, Fable 5, working inside a research harness that records nothing above the status of a heuristic without a machine artifact and never lets the model execute code. The model classified the orbits, proposed the distance-hereditary characterization from the 44 labeled orbits with $3 \le n \le 7$, and wrote the Lean proofs; the 541 held-out orbits with $n \in \{8, 9\}$ then agreed with the proposal without exception (Section VI). Given the ingredients above, the characterization is within easy reach of a specialist; we report its discovery as an instance of a harness producing a correct, checkable conjecture from data, not as evidence that the result is hard.

II. THE MODEL

a. Graph states and local complementation. For a simple graph $G = (V, E)$ the graph state

$$|G\rangle = \prod_{\{u,v\}\in E} \mathrm{CZ}_{uv}\,|+\rangle^{\otimes V}$$

is the unique common $+1$ eigenvector of the operators $K_v = X_v \prod_{u\in N(v)} Z_u$, $v \in V$, where $N(v)$ is the neighborhood of v. Local complementation at v replaces the subgraph induced on $N(v)$ by its complement; we write $\tau_v(G)$. It is implemented on graph states, up to a global phase, by a product of single-qubit Clifford unitaries [23],

$$|\tau_v(G)\rangle = e^{-i\pi X_v/4} \prod_{u\in N(v)} e^{i\pi Z_u/4}\,|G\rangle, \tag{1}$$

and two graph states on the same qubits are related by a product of single-qubit Clifford unitaries if and only if their graphs are related by a sequence of local complementations [23]. The qubits that survive a schedule carry no fixed labels, so we also identify isomorphic graphs, and write $G \sim_{\mathrm{LC}} H$ for the equivalence generated by local complementation and isomorphism. For $A \subseteq V$ the *cut-rank* $\rho_G(A)$ is the rank over GF(2) of the $A \times (V \setminus A)$ submatrix of the adjacency matrix, and the Schmidt rank of $|G\rangle$ across $(A, V \setminus A)$ is $2^{\rho_G(A)}$ [4].

b. Resources, fusions and schedules. A schedule starts from g copies of the three-qubit GHZ state; its graph is P_3, and it is LC-equivalent to the triangle K_3. A *fusion* on two distinct qubits a, b is the destructive measurement of the commuting observables X_aZ_b and Z_aX_b, after which a and b are discarded. This is a Bell measurement after a Hadamard on b, the convention of Refs. [6, 24]; any other Bell-type convention differs from it by single-qubit Cliffords on a and b, which are free in the model. A schedule interleaves fusions, on any pairs of qubits, with arbitrary single-qubit Clifford gates. It *produces* G if, for every outcome, the state of the surviving qubits is LC-equivalent to $|G\rangle$; different outcomes of a fusion on a stabilizer state differ by Pauli operators [6, 24], so this does not depend on the outcomes, and we treat fusions as deterministic, leaving the probabilistic success of linear-optical fusion [25] to a layer above this problem. The cost of a schedule is its number of fusions, and $\mathrm{F}(G)$ is the least cost of a schedule that produces G.

Lemma 3 (Fusion of disjoint graph states)**.** *Let G_1 and G_2 be graphs on disjoint vertex sets, a a vertex of G_1 and b a vertex of G_2. A fusion on (a, b) applied to $|G_1\rangle \otimes |G_2\rangle$ leaves, up to a Pauli operator that depends on the outcomes, the graph state of the graph on $(V_1 \cup V_2) \setminus \{a, b\}$ whose edges are the edges of G_1 and G_2 not incident to a or b, together with every pair $\{u, w\}$ with $u \in N_{G_1}(a)$ and $w \in N_{G_2}(b)$.*

This is the standard graph rule for type-II fusion [25], stated in this form in Refs. [3, 6] and in full generality in Ref. [24]. For completeness: the observable X_aZ_b anticommutes exactly with K_b and with K_u for $u \in N(a)$, and Z_aX_b exactly with K_a and with K_w for $w \in N(b)$. The standard update for measuring X_aZ_b and then Z_aX_b replaces K_u by K_uK_b and K_w by K_wK_a; multiplying these by Z_aX_b and X_aZ_b respectively removes their support on a and b and leaves $X_uZ_{N(u)\setminus\{a\}}Z_{N(b)}$ and $X_wZ_{N(w)\setminus\{b\}}Z_{N(a)}$ up to sign, the stabilizers of the stated graph. Both of our stabilizer engines also reproduce the rule on random inputs (Section VI).

Fusing a vertex a of a graph with a qubit of a fresh resource therefore adds one vertex, in one of three ways depending on the graph chosen to represent the resource (each is available, because single-qubit Cliffords on a fresh resource are free). Fusing with a *leaf* of P_3 replaces a by the center of P_3 and attaches the other leaf to it, which up to relabeling adds a *pendant* at a. Fusing with the *center* of P_3 replaces a by the two leaves, each with the neighborhood of a and not adjacent to each other, a *false twin*. Fusing with a vertex of K_3 replaces a by the other two, adjacent, vertices, a *true twin*. We call these fusions *merges*.

Proposition 4 (Counting bound)**.** *Let a schedule with g resources and f fusions produce a connected graph on $n \geq 3$ vertices, and let H be the multigraph whose vertices are the resources, with one edge for each fusion joining the resources that hold its two qubits. Then exactly one connected component H_0 of H contains surviving qubits; if it has g_0 resources, f_0 fusions and cycle rank $t = f_0 - g_0 + 1$, then $f \geq f_0 = n - 3 + 3t$. In particular $\mathrm{F}(G) \geq n - 3$, and every schedule has $f \equiv n \pmod 3$.*

Proof. Fusions in different components of H act on different tensor factors. If two components held surviving qubits the output would be a product across them, which is impossible, since every cut-rank of a connected graph is positive and so $|G\rangle$ is entangled across every bipartition. Counting the qubits of H_0 gives $3g_0 - 2f_0 = n$, and with $g_0 = f_0 - t + 1$ this is $f_0 = n - 3 + 3t$; the cycle rank of a connected multigraph is non-negative. The same count over all of H, whose other components have all their qubits fused, gives $3g - 2f = n$, so $f \equiv n \pmod 3$. □

A counting form of the bound, in a merge model of schedules that also tracks fusions which split or consume a component, is the Lean theorem `fusion_cost_lower_bound`.

III. THE RANK-WIDTH BOUND AND THE CHARACTERIZATION

a. Rank-width. A *rank decomposition* of a graph G on at least two vertices is a tree T whose internal nodes have degree three and whose leaves are the vertices of G. Each edge e of T splits the leaves into two sides $(A_e, V \setminus A_e)$, and the width of T is $\max_e \rho_G(A_e)$. The rank-width $\mathrm{rw}(G)$ is the least width of a rank decomposition [13, 16]. A connected graph on at least two vertices has $\mathrm{rw}(G) \geq 1$, and $\mathrm{rw}(G) \leq 1$ if and only if G is distance-hereditary [13].

Proof of Theorem 1. Take a schedule with $f = \mathrm{F}(G)$ fusions that produces G, and let H_0, g_0, f_0 and t be as in Proposition 4. A single-qubit gate commutes with every operation not acting on its qubit, so we may apply each gate on a fused qubit to its resource before any fusion, and each gate on a surviving qubit at the end, where it does not change Schmidt ranks. Fusions act on disjoint pairs of qubits and commute. Conditioned on the outcomes, the state of the surviving qubits is then, up to normalization and single-qubit unitaries,

$$\psi = \Big(\bigotimes_e \langle\beta_e|\Big)\Big(\bigotimes_r |R_r\rangle\Big),$$

where r runs over the resources of H_0, $|R_r\rangle$ is resource r with its gates, e runs over the fusions of H_0, and $\langle\beta_e|$ is the two-qubit bra of the outcome of e; the components of H without survivors contribute only a scalar. Choose a spanning tree S of H_0; then t fusions of H_0 lie outside S. Form a tree T from S by attaching each surviving qubit as a leaf to its resource. A resource has three qubits, each surviving, fused along an edge of S, or fused along an edge outside S, so its degree in T is at most three. Repeatedly deleting resource nodes of degree one and suppressing nodes of degree two turns T into a rank decomposition T' of G, after identifying the surviving qubits with the vertices of G.

Each edge of T' comes from a path in T, and all edges of that path induce the same cut of the surviving qubits. If the path is a single leaf edge, the cut separates one vertex and has cut-rank at most one. Otherwise it contains an edge e of S; removing e splits the resources of H_0 into two sets X and Y and the surviving qubits into A and B. The fusions joining X and Y are e and some of the t fusions outside S. Contract all fusions inside X and inside Y;

each remaining bra $\langle\beta|$ is a two-qubit state and so a sum of two product bras, and expanding them writes ψ as a sum of at most 2^{1+t} products of a state on A and a state on B. Hence the Schmidt rank of ψ across (A, B) is at most 2^{1+t}, and since ψ is LC-equivalent to $|G\rangle$, $\rho_G(A) \le 1 + t$. Every edge of T' therefore has cut-rank at most $1 + t$, so $\mathrm{rw}(G) \le 1 + t$, and Proposition 4 gives $\mathrm{F}(G) = f \ge n - 3 + 3t \ge n - 3 + 3(\mathrm{rw}(G) - 1)$. □

The argument is the fusion analogue of bounding the Schmidt-rank width of a tensor network by its bond structure [17, 18], and is close in spirit to the bound $\mathrm{F} \ge \mathrm{lrw}(G) - 1$ in the linear rank-width of Ref. [7] and the gate bound of Ref. [19]. Only the cycle rank of the fusion network enters, so the bound holds for any destructive two-qubit measurement with pure outcomes, not only for Bell-type fusions.

Proof of Theorem 2. (⇒) If $\mathrm{F}(G) = n - 3$, then $\mathrm{rw}(G) \le 1$ by Theorem 1, so G is distance-hereditary [13].

(⇐) A connected distance-hereditary graph on $n \ge 3$ vertices is obtained from a connected graph on three vertices, P_3 or K_3, by $n - 3$ additions of pendant vertices, false twins and true twins, every intermediate graph being connected [12]. Start from one resource represented as P_3 or K_3, and realize each addition at a vertex a by a merge with a fresh resource, at a leaf of P_3, at the center of P_3 or at a vertex of K_3. By Lemma 3 this schedule produces G with $n - 3$ fusions, and Proposition 4 gives $\mathrm{F}(G) = n - 3$. □

At the minimum the proof of Theorem 1 shows more: $t = 0$, so the fusion network is a tree on $n-2$ resources whose $n-3$ fusions each join two components. The constructive direction can also be read off from the split decomposition. Every node of the split decomposition of a distance-hereditary graph is a star or a complete graph [15, 26, 27]; Connolly *et al.* [20] assemble the graph state from the node graph states by type-II fusions along the split tree, and Lee and Jeong [6] build an m-vertex star from $m - 2$ GHZ states with $m - 3$ fusions. The totals are again $n - 2$ resources and $n - 3$ fusions.

IV. THE LEAN DEVELOPMENT

The Lean development is in the directory `lean/EmpiricistLean` of the accompanying repository, against MATHLIB at release `v4.31.0`. The ancillary files contain the modules behind every declaration we cite as a self-contained Lake project, with a script that builds it and prints the axioms of each declaration (Table II in Appendix B); all use only `propext`, `Classical.choice` and `Quot.sound`. The development formalizes the combinatorics of the constructive direction. The qubit-level steps, Lemma 3 and the argument of Theorem 1, are not formalized.

a. Production predicates. Graphs are MATHLIB `SimpleGraph`s on an arbitrary vertex type, and the production predicates carry exact graphs rather than equivalence classes. Let $\mathsf{Prod}_k^+(G)$ say that G is obtained from P_3 by k steps, each adding a pendant (the *leaf-merge*, `ghz3LeafMerge`) or a false twin (the *center-merge*), interleaved with any number of local complementations and isomorphisms (the inductive `ProducibleByExt`). The lemma `ghz3CenterMerge_iso_addFalseTwin` identifies the center-merge, written as the graph rewrite of Lemma 3, with false-twin addition up to isomorphism. Let DH be the class generated from P_3 and K_3 by pendant, false-twin and true-twin additions, local complementation and isomorphism (the inductive `PendantTwinBuildable`). Without the local-complementation constructor these are the connected distance-hereditary graphs on at least three vertices [12], and the constructor adds nothing, since that class is closed under local complementation [13]; this identification is not formalized.

Theorem 5 (Model characterization, Lean)**.** *For a finite graph G, $\mathsf{Prod}^+_{|V(G)|-3}(G)$ holds if and only if $G \in \mathsf{DH}$ (`dh_characterization`).*

The forward implication is a structural induction on Prod^+: each constructor of Prod^+ is one of DH. The converse (`dh_forward`) is a structural induction on DH: a pendant addition is a leaf-merge, a false-twin addition a center-merge, and a true-twin addition is realized by local complementation, a leaf-merge and local complementation, through the identity

$$\tau_u\big(\mathrm{addPendant}(G, u)\big) \;=\; \mathrm{addTrueTwin}\big(\tau_u(G),\, u\big) \tag{2}$$

(`addPendant_localComplement_center`) and the involutivity of τ_u. With `fusion_cost_lower_bound`, `dh_min_fusions` states the constructive direction of Theorem 2 at the level of the model. A further declaration, `floor_schedule_iff_dh`, extends Theorem 5 to a schedule model with one more constructor, which may replace the current graph by *any* graph with two fewer vertices at the cost of one fusion, an over-approximation of a fusion of two qubits of one component; at the minimum a vertex count excludes that constructor.

n	3	4	5	6	7	8	9	total
connected orbits	1	2	4	11	26	101	440	585
$\mathrm{F} = n-3$ (distance-hereditary)	1	2	3	8	15	42	104	175
$\mathrm{F} = n$	0	0	1	2	7	6	0	16
$\mathrm{F} = n+3$	0	0	0	1	2	0	0	3
open, $\mathrm{F} \geq n$	0	0	0	0	0	52	312	364
open, $\mathrm{F} \geq n+3$	0	0	0	0	2	1	24	27

TABLE I. Connected local-complementation orbits by number of vertices. The orbits with $\mathrm{F} = n-3$ are exactly the distance-hereditary ones. Every other orbit has rank-width two, except the 25 open orbits with $n \in \{8, 9\}$ of rank-width three, whose bound $\mathrm{F} \geq n+3$ comes from Theorem 1; the two open orbits with $n = 7$ have $\mathrm{F} \geq n+3$ from the exhaustion of Tier 1.

b. Families. Before the general theorem, the development proves constructions at the minimum for natural families, each stated together with the general lower bound so that no family theorem can be true for a vacuous reason: paths, stars and all trees by leaf-removal induction, K_n by one local complementation from a star, and $K_{m,n}$ by three local complementations from a double star. All of these graphs are distance-hereditary.

Remark 6 (Induction must track concrete graphs). Although every statement about F is invariant under local complementation, the inductions cannot be run on $\sim_{\mathrm{LC}}$ classes, because pendant addition does not descend to them: $P_3 \sim_{\mathrm{LC}} K_3$, yet a pendant at the center of P_3 gives the four-vertex star, while a pendant at a vertex of K_3 gives the paw, which is LC-equivalent to the path P_4 and not to the star. The development therefore carries exact graphs through every induction and applies local complementation only explicitly. The first production model had only the leaf-merge and so generated only trees; it witnesses the minimum only on the local-complementation classes of trees, which are 93 of the 175 distance-hereditary orbits with $3 \leq n \leq 9$, one for each tree on 3 to 9 vertices, since locally equivalent trees are isomorphic [15]. Adding the center-merge removed the obstruction.

V. THE CERTIFIED TABLEBASE

a. Search. Every connected graph with $3 \leq n \leq 9$ was assigned to its local-complementation orbit; there are $1, 2, 4, 11, 26, 101, 440$ orbits for $n = 3, \ldots, 9$, 585 in all, in agreement with Danielsen and Parker [28]. By Proposition 4 the search proceeds in tiers $\mathrm{F} = n-3$, $\mathrm{F} = n$, and so on. Tier 0 is a breadth-first search over graphs in which local complementation is free and a merge at any vertex, with a fresh resource fused at a leaf or at the center, costs one fusion; true twins arise through (2). Tier 1 grows graphs by merges to $n+2$ vertices and then performs one fusion of two qubits of the component. Both are exhaustive by the normal form of Appendix A: any schedule can be reordered so that merges come first and grow a single component, and single-qubit Cliffords on the qubits of a merge are absorbed by local complementations. Every fusion in the search is computed in the fixed basis of Section II. For the one fusion inside the component in Tier 1 we re-ran the search with each of the six classes of single-qubit Clifford on one fused qubit, which together with the symmetry of the measured pair covers all choices on both qubits (for $n \leq 5$ all 36 pairs were tried), and no orbit changed. Each recorded construction is replayed by two stabilizer engines with independent implementations of fusion and of graph extraction, a tableau simulator built on STIM [29] and an implementation over GF(2); they share the replay of a construction, the graph-level local complementation and the orbit canonicalization, which uses NAUTY [30]. The table, with 585 rows each holding an orbit representative and either an exact value with a witness schedule or a lower bound, is a single content-addressed artifact; nine exact values above the minimum were added later from model-proposed constructions.

b. Results. Table I summarizes the table. A pendant-and-twin elimination check [12], run independently on all 585 representatives, confirms that the orbits with $\mathrm{F} = n-3$ are exactly the distance-hereditary ones. Nineteen orbits have exact values above the minimum. The sixteen at $\mathrm{F} = n$ have upper bounds from constructions and lower bounds from Theorem 2. The three at $\mathrm{F} = n+3$ are a six-vertex orbit at $\mathrm{F} = 9$, realized with eight resources, nine fusions and three local complementations, and two seven-vertex orbits at $\mathrm{F} = 10$; their lower bounds come from the exhaustion of Tier 1.

c. How tight is the rank-width bound? We computed the rank-width of every orbit above the minimum exactly, by enumerating all rank decompositions. Every orbit with $n \leq 7$ that is not distance-hereditary has rank-width two, and so do all sixteen orbits with $\mathrm{F} = n$, which therefore attain the bound $\mathrm{F} \geq n$ of Theorem 1. The three orbits with $\mathrm{F} = n+3$ also have rank-width two, so the bound misses them by three: above rank-width one the fusion cost is not a function of rank-width. In the other direction the bound improves the table. Twenty-five open orbits, one with $n = 8$ and 24 with $n = 9$, have rank-width three, so $\mathrm{F} \geq n+3$, where the search had established only $\mathrm{F} \geq n$.

VI. METHOD: THE HARNESS AND THE DISCOVERY

The results were obtained with Empiricist, an open-source harness that drives a language model through research tasks under an explicit discipline. Its source, the Lean development, the tablebase and the ledger of claims are in the accompanying repository.

a. A ledger of claims with evidence. Every artifact (a computed value, a construction, a conjecture, a Lean module) is recorded at a status in the ordered set REFUTED < HEURISTIC < CONJECTURED < VERIFIED$_n$ < CERTIFIED < FORMALIZED and rises only with an evidence record from a certified verifier; REFUTED is terminal, and nothing the model merely asserts is recorded above HEURISTIC. Artifacts are addressed by content hash, and verifiers by the hash of their code and of a golden test suite that they must pass before use.

b. The model never executes. The model emits structured output, such as a schedule, a conjecture or a complete Lean module, and the harness runs every check in a sandbox.

c. Two stabilizer engines. Fusion outcomes are computed by two engines with independent implementations of fusion and of graph extraction, and a construction is accepted only when both agree on the resulting state up to local Clifford equivalence; the replay of a construction and the orbit canonicalization are shared code. The closed-form merge rule used in the hot loop of the search matches both engines on randomized inputs.

d. A hardened Lean gate. A submitted Lean module is elaborated in a sandbox without network or process creation, against a frozen read-only MATHLIB; the kernel result is re-checked, the axioms must lie within {`propext`, `Classical.choice`, `Quot.sound`}, every import must belong to an explicit trusted set, and the build directory is swept after elaboration. The gate was developed against adversarial submissions (poisoned object files, swaps between check and use, axiom-hiding elaborators) before it was used.

e. The discovery. The harness gave the model the labeled catalogue of the 44 orbits with $3 \le n \le 7$, each as an edge list tagged extremal or not, with no invariant, class name or hint beyond the true statement that the property is invariant under local complementation. The model proposed that the extremal orbits are the distance-hereditary graphs, gave the standard equivalent characterizations, and identified the smallest obstruction: the unique non-extremal orbit on five vertices is the orbit of C_5. The proposal entered the ledger as a conjecture, and a deterministic distance-hereditary check on all 585 orbits, including the 541 on eight and nine vertices that the model had not seen, agreed with it without exception. The model then wrote the Lean proofs through a loop in which the gate returns the remaining proof obligations and the model revises; it never ran Lean itself. The discipline also caught errors along the way: an arithmetic slip in an early hand-written note of the extremal split (185/400 instead of 175/410), a family theorem whose first statement had the construction built into the claim, and, in preparing this paper, a note that reported the linear rank-width of the six-vertex orbit with F = 9 as its rank-width.

VII. RELATED WORK

a. Fusion cost. Lee and Jeong [6] optimize fusion-based generation of graph states from GHZ states with graph-theoretical heuristics, construct stars with the minimum number of fusions, and state the graph rule for fusion used here. Löbl *et al.* [7] compute, by dynamic programming over local-complementation orbits, exact minimum fusion counts for all graph states on up to eight qubits when the inputs are caterpillar states from a single quantum emitter; their zero-fusion class is the local-complementation classes of caterpillars, which are the connected graphs of linear rank-width one [31], and they show that the count is at least the linear rank-width minus one. Their model differs from ours in the resource, so the values and the extremal class differ; the term tablebase is theirs. Staudacher *et al.* [8] and Cashman *et al.* [9] optimize fusion networks with linear-cluster resources, and Ji *et al.* [10] decompose targets into ring, star and linear motifs joined by type-I fusion.

b. Preparation cost in other models. Kumabe, Mori and Yoshimura [19] determine the number of two-qubit Clifford gates needed to prepare a graph state up to rank-width terms; their lower bound $n + \mathrm{rw}(G) - 2$ and their exact value $n - 1$ at rank-width one are the circuit analogues of Theorems 1 and 2. Davies and Jena [32] bound the two-qubit gate cost of preparing graph states from classes closed under vertex-minors, unconditionally for circle graphs and for bounded rank-width and, assuming a structural conjecture of Geelen, by $O(n \log n)$ for every proper vertex-minor-closed class. Minimum-gate and minimum-edge representatives of local-complementation orbits were studied by Cabello *et al.* [33] and by Sharma *et al.* [34], who apply edge minimization to reduce the GHZ resources and fusions needed for repeater graph states. Adcock *et al.* [35] bound which graph states can be produced from optical resources with postselected fusions.

c. Distance-hereditary graph states. Connolly *et al.* [20] construct every distance-hereditary graph state by fusions along its split decomposition, and Connolly, Nishio and Nemoto [36] derive the sizes of the local-equivalence classes of several families of distance-hereditary graphs. The orbits of graph states were classified by Hein *et al.* [4] for $n \le 7$ and by Danielsen and Parker [28] for $n \le 12$, and mapped by Adcock *et al.* [37]. Whether one graph state

can be transformed into another by single-qubit Clifford operations, single-qubit Pauli measurements and classical communication is decidable in time cubic in the size of the source when its rank-width and the size of the target are bounded [38]; in general the problem is NP-complete, even when the target is a tensor product of Bell pairs on specified pairs of qubits, with more efficient algorithms for particular targets [39, 40]. Separately, counting the labelled graph states in an orbit under local complementation alone, without identifying isomorphic graphs, is #P-complete [41].

d. Machine-assisted mathematics. Machine learning has guided mathematicians to conjectures from data [42], language models have produced new constructions in combinatorics and analysis through program search [43–45], and machine-generated proofs have been checked by a symbolic deduction engine [46] and by the Lean kernel [47]. Here a model proposes a characterization from data and writes the Lean proofs, and a harness admits only what a verifier accepts.

VIII. DISCUSSION AND OPEN QUESTIONS

The combinatorics of the constructive direction is checked in Lean; the qubit-level steps are written proofs, corroborated by two stabilizer engines and by the exhaustive search. A first-principles formalization would define graph states, Pauli measurements and schedules in Lean and derive Lemma 3 and the argument of Theorem 1; rank-width is not yet in MATHLIB. Three questions remain.

1. *A finer invariant.* Above rank-width one, F is not a function of rank-width (Section V). Which invariant decides between $\mathrm{F} = n$ and $\mathrm{F} = n + 3$ at rank-width two?

2. *Complexity.* Theorem 2 makes the decision problem $\mathrm{F}(G) = n - 3$ polynomial, since distance-hereditary graphs are recognized by pendant-and-twin elimination [12]. The complexity of computing F in general is open.

3. *Other resources.* Do analogous characterizations hold for larger GHZ states or for linear-cluster resources?

DATA AND CODE AVAILABILITY

The repository `https://github.com/sghowell/empiricist` (MIT license) contains the harness, the Lean development, the tablebase and the claims ledger. The ancillary files of this paper contain the Lean modules behind every declaration in Table II as a self-contained Lake project with a script that builds them and prints their axioms; the tablebase and the nine later constructions; scripts that re-derive every number in Section V, including the exact rank-widths, and replay the constructions with both engines; and the re-run of Tier 1 with single-qubit Cliffords on the fused qubits. A README maps each statement of the paper to a file, and a SHA-256 manifest lists every file.

ACKNOWLEDGMENTS

This work was carried out with AI systems working under my direction. Inside the Empiricist harness, the language model Fable 5 (Anthropic) classified the tablebase orbits, proposed the distance-hereditary characterization and wrote the Lean proofs; it emitted only machine-checkable artifacts and never executed code. Claude Code (Anthropic, model Claude Opus 5.5) surveyed the literature, proved Theorem 1, wrote the remaining written proofs, re-derived every number from the committed artifacts and drafted this manuscript. Codex (OpenAI, model gpt-6-astra) independently checked the proofs, the claims and the relation to previous work; the errors it found have been corrected. I chose the problem and take full responsibility for the content of this paper.

Appendix A: The normal form behind the search

The exhaustiveness of Tiers 0 and 1 rests on two lemmas.

Lemma 7 (Absorbing single-qubit Cliffords)**.** *Let v be a vertex of a graph G with at least one neighbor, and let C be a single-qubit Clifford unitary. Then there are a graph G', obtained from G by local complementations, and a product D of single-qubit Cliffords acting trivially on v, such that $C_v|G\rangle = D\,|G'\rangle$ up to a Pauli operator and a global phase.*

Proof. Single-qubit Clifford unitaries modulo Pauli operators and phases form a group isomorphic to the symmetric group on $\{X, Y, Z\}$, acting by conjugation, and $e^{-i\pi X/4}$ and $e^{i\pi Z/4}$ act as the transpositions $(Y\,Z)$ and $(X\,Y)$,

which generate it. By (1), local complementation at v multiplies the local unitary on v by $e^{-i\pi X_v/4}$, and local complementation at a neighbor u of v multiplies it by $e^{i\pi Z_v/4}$. Neither removes the edge $\{u, v\}$, since τ_v changes only edges inside $N(v)$ and τ_u only edges inside $N(u)$. So a suitable word in τ_v and τ_u gives a graph G' and a product $U = \bigotimes_w U_w$ of single-qubit Cliffords with $U|G\rangle = |G'\rangle$ up to a Pauli operator and $U_v = C$ modulo Paulis. Then $C_v|G\rangle = \big(\bigotimes_{w\neq v} U_w^{-1}\big)U|G\rangle$, which is $D|G'\rangle$ with $D = \bigotimes_{w\neq v} U_w^{-1}$, up to a Pauli operator. □

Lemma 8 (Single-component normal form)**.** *Suppose a schedule with f fusions produces a connected graph G on n vertices. Then some schedule with $f' \leq f$ fusions and g' resources, $3g' - 2f' = n$, produces G and has the following form. One resource is the seed. Each of the other $g' - 1$ resources is attached by a merge, a fusion between a qubit of the current component, which is a connected graph state, and a qubit of the fresh resource, with no single-qubit Clifford on either fused qubit; local complementations of the component may occur between merges. After all merges come the remaining $f' - g' + 1$ fusions, each between two qubits of the component, and single-qubit Cliffords on the surviving qubits come last.*

Proof. Single-qubit Cliffords. A single-qubit Clifford on a qubit q commutes with every operation that does not act on q, and the only other operation acting on q is the fusion that consumes it, if any. Move each such gate to just after the preparation of its resource, to just before the fusion that consumes q, or to the end of the schedule if q survives.

Discard what does not reach the output. Delete the components of the multigraph H of Proposition 4 that contain no surviving qubit; they act on separate tensor factors. Then H is connected, with g' resources and $f' \leq f$ fusions, and $3g' - 2f' = n$.

Reorder. Choose a spanning tree of H, a root resource, and a breadth-first order of the resources from the root along the tree. For each non-root resource c with parent p, pick one fusion joining p and c; these are the merges. Put the merges first, in the order of their child resources, followed by all other fusions in their original relative order. Fusions act on disjoint pairs of qubits and commute, so the final state on the surviving qubits, conditioned on the outcomes, does not change; only the Pauli corrections may. When the merge of c is performed, its qubit in p has not been consumed and c has not yet been touched, so it fuses a qubit of the component grown so far with a qubit of a fresh resource; every later fusion acts on two qubits of that component.

Remove the Cliffords on merge qubits. Process the merges in order. Before the merge of c the component is the graph state of a connected graph B on at least three vertices, up to single-qubit Cliffords: the seed has three vertices, and each merge keeps the graph connected by Lemma 3, since both joined neighborhoods are non-empty, and adds one vertex. Its fused qubit a has a neighbor, so Lemma 7 replaces the Clifford on a by local complementations of B and Cliffords on other qubits, which are carried forward. On the fresh side, Lemma 7 applied to the three-vertex graph of the resource removes the Clifford on its fused qubit, leaving P_3 with some center or K_3. The merge is then a fusion without single-qubit Cliffords on either fused qubit. Cliffords carried onto qubits consumed by later merges are removed in the same way when those merges are reached; Cliffords on qubits consumed by the final fusions inside the component stay, as the statement allows; the rest move to the end. □

At the minimum the normal form has no fusion inside the component, so Tier 0 is exhaustive for $\mathrm{F} = n - 3$. Tier 1, which applies one such fusion after all merges, is exhaustive for $\mathrm{F} = n$, given the re-run over the single-qubit Cliffords on its two fused qubits described in Section V.

Appendix B: Principal Lean declarations

[1] S. Bartolucci, P. Birchall, H. Bombín, H. Cable, C. Dawson, M. Gimeno-Segovia, E. Johnston, K. Kieling, N. Nickerson, M. Pant, F. Pastawski, T. Rudolph, and C. Sparrow, Fusion-based quantum computation, Nature Communications **14**, 912 (2023), arXiv:2101.09310 [quant-ph].

[2] M. Gimeno-Segovia, P. Shadbolt, D. E. Browne, and T. Rudolph, From three-photon Greenberger-Horne-Zeilinger states to ballistic universal quantum computation, Physical Review Letters **115**, 020502 (2015), arXiv:1410.3720 [quant-ph].

[3] H. A. Zaidi, C. Dawson, P. van Loock, and T. Rudolph, Near-deterministic creation of universal cluster states with probabilistic Bell measurements and three-qubit resource states, Physical Review A **91**, 042301 (2015), arXiv:1410.3753 [quant-ph].

[4] M. Hein, J. Eisert, and H. J. Briegel, Multiparty entanglement in graph states, Physical Review A **69**, 062311 (2004), arXiv:quant-ph/0307130.

declaration	statement	file
`fusion_cost_lower_bound`	$f \geq n-3$ in a merge model of schedules	`Foundation.lean`
`tree_min_fusions`	construction at the minimum for every tree	`TreeThm.lean`
`pathGraph_min_fusions`	paths	`Paper/PathGraph.lean`
`star_min_fusions`	stars	`Paper/Star.lean`
`complete_min_fusions`	complete graphs K_n	`Paper/Complete.lean`
`completeBipartite_min_fusions`	complete bipartite graphs $K_{m,n}$	`Paper/CompleteBipartite.lean`
`ghz3CenterMerge_iso_addFalseTwin`	the center-merge is false-twin addition	`CenterMerge.lean`
`addPendant_localComplement_center`	the identity (2)	`TrueTwin.lean`
`dh_forward`, `dh_min_fusions`	$\mathsf{DH} \Rightarrow \mathsf{Prod}^{+}_{n-3}$	`DHCharacterization.lean`
`dh_characterization`	$\mathsf{Prod}^{+}_{n-3}(G) \Leftrightarrow G \in \mathsf{DH}$	`DHCharacterization.lean`
`floor_schedule_iff_dh`	the over-approximating schedule model	`Paper/FloorBridge.lean`

TABLE II. Principal Lean declarations. Files without a directory are library modules of the repository; files in `Paper/` are modules recorded as gate-certified artifacts in its claims ledger.

[5] M. Hein, W. Dür, J. Eisert, R. Raussendorf, M. Van den Nest, and H.-J. Briegel, Entanglement in graph states and its applications, in *Quantum Computers, Algorithms and Chaos*, Proceedings of the International School of Physics "Enrico Fermi", Vol. 162 (IOS Press, 2006) pp. 115–218, arXiv:quant-ph/0602096.

[6] S.-H. Lee and H. Jeong, Graph-theoretical optimization of fusion-based graph state generation, Quantum **7**, 1212 (2023), arXiv:2304.11988 [quant-ph].

[7] M. C. Löbl, L. A. Pettersson, A. Jena, L. Dellantonio, S. Paesani, and A. S. Sørensen, Generating graph states with a single quantum emitter and the minimum number of fusions, Physical Review A **111**, 052604 (2025), arXiv:2412.04587 [quant-ph].

[8] K. Staudacher, B. Jeevanesan, and T. Guggemos, Adaptive framework for failure-aware protocols in fusion-based graph-state generation, Physical Review A **114**, 032614 (2026), arXiv:2601.02087 [quant-ph].

[9] W. Cashman, G. de Felice, and A. Kissinger, Finding trail covers: near-optimal decompositions of graph states as linear fusion networks (2025), arXiv:2508.18375 [quant-ph].

[10] T. Ji, H. Weerasena, D. Farfurnik, and J. Liu, Towards efficient synthesis of quantum graph states by fusing graph motifs (2026), arXiv:2606.02880 [quant-ph].

[11] E. Howorka, A characterization of distance-hereditary graphs, The Quarterly Journal of Mathematics **28**, 417 (1977).

[12] H.-J. Bandelt and H. M. Mulder, Distance-hereditary graphs, Journal of Combinatorial Theory, Series B **41**, 182 (1986).

[13] S.-i. Oum, Rank-width and vertex-minors, Journal of Combinatorial Theory, Series B **95**, 79 (2005).

[14] A. Bouchet, Isotropic systems, European Journal of Combinatorics **8**, 231 (1987).

[15] A. Bouchet, Transforming trees by successive local complementations, Journal of Graph Theory **12**, 195 (1988).

[16] S.-i. Oum, Rank-width: Algorithmic and structural results, Discrete Applied Mathematics **231**, 15 (2017), arXiv:1601.03800 [math.CO].

[17] M. Van den Nest, A. Miyake, W. Dür, and H. J. Briegel, Universal resources for measurement-based quantum computation, Physical Review Letters **97**, 150504 (2006), arXiv:quant-ph/0604010.

[18] M. Van den Nest, W. Dür, G. Vidal, and H. J. Briegel, Classical simulation versus universality in measurement-based quantum computation, Physical Review A **75**, 012337 (2007), arXiv:quant-ph/0608060.

[19] S. Kumabe, R. Mori, and Y. Yoshimura, Complexity of graph-state preparation by Clifford circuits, Quantum **10**, 2165 (2026), arXiv:2402.05874 [quant-ph].

[20] N. Connolly, S. Nishio, D. E. Browne, W. J. Munro, and K. Nemoto, Efficient preparation of graph states using the quotient-augmented strong split tree (2026), arXiv:2603.23892 [quant-ph].

[21] L. de Moura and S. Ullrich, The Lean 4 theorem prover and programming language, in *Automated Deduction – CADE 28*, Lecture Notes in Computer Science, Vol. 12699 (Springer, 2021) pp. 625–635.

[22] The mathlib Community, The Lean mathematical library, in *Proceedings of the 9th ACM SIGPLAN International Conference on Certified Programs and Proofs (CPP 2020)* (2020) pp. 367–381, arXiv:1910.09336.

[23] M. Van den Nest, J. Dehaene, and B. De Moor, Graphical description of the action of local Clifford transformations on graph states, Physical Review A **69**, 022316 (2004), arXiv:quant-ph/0308151.

[24] M. C. Löbl, L. A. Pettersson, S. Paesani, and A. S. Sørensen, Transforming graph states via Bell state measurements, Quantum **9**, 1795 (2025), arXiv:2405.02414 [quant-ph].

[25] D. E. Browne and T. Rudolph, Resource-efficient linear optical quantum computation, Physical Review Letters **95**, 010501 (2005), arXiv:quant-ph/0405157.

[26] P. L. Hammer and F. Maffray, Completely separable graphs, Discrete Applied Mathematics **27**, 85 (1990).

[27] E. Gioan and C. Paul, Split decomposition and graph-labelled trees: Characterizations and fully dynamic algorithms for totally decomposable graphs, Discrete Applied Mathematics **160**, 708 (2012).

[28] L. E. Danielsen and M. G. Parker, On the classification of all self-dual additive codes over GF(4) of length up to 12, Journal of Combinatorial Theory, Series A **113**, 1351 (2006), arXiv:math/0504522.

[29] C. Gidney, Stim: a fast stabilizer circuit simulator, Quantum **5**, 497 (2021), arXiv:2103.02202 [quant-ph].

[30] B. D. McKay and A. Piperno, Practical graph isomorphism, II, Journal of Symbolic Computation **60**, 94 (2014), arXiv:1301.1493 [cs.DM].

[31] B.-M. Bui-Xuan, M. M. Kanté, and V. Limouzy, A note on graphs of linear rank-width 1 (2013), arXiv:1306.1345 [cs.DM].

[32] J. Davies and A. Jena, Preparing graph states forbidding a vertex-minor (2025), arXiv:2504.00291 [quant-ph].

[33] A. Cabello, L. E. Danielsen, A. J. López-Tarrida, and J. R. Portillo, Optimal preparation of graph states, Physical Review A **83**, 042314 (2011), arXiv:1011.5464 [quant-ph].

[34] H. Sharma, K. Goodenough, J. Borregaard, F. Rozpędek, and J. Helsen, Minimising the number of edges in LC-equivalent graph states, Quantum **10**, 2001 (2026), arXiv:2506.00292 [quant-ph].

[35] J. C. Adcock, S. Morley-Short, J. W. Silverstone, and M. G. Thompson, Hard limits on the postselectability of optical graph states, Quantum Science and Technology **4**, 015010 (2019), arXiv:1806.03263.

[36] N. Connolly, S. Nishio, and K. Nemoto, Local equivalence classes of distance-hereditary graphs using split decompositions, Journal of Physics A: Mathematical and Theoretical **59**, 395310 (2026), arXiv:2602.23825 [math.CO].

[37] J. C. Adcock, S. Morley-Short, A. Dahlberg, and J. W. Silverstone, Mapping graph state orbits under local complementation, Quantum **4**, 305 (2020), arXiv:1910.03969 [quant-ph].

[38] A. Dahlberg and S. Wehner, Transforming graph states using single-qubit operations, Philosophical Transactions of the Royal Society A **376**, 20170325 (2018), arXiv:1805.05305 [quant-ph].

[39] A. Dahlberg, J. Helsen, and S. Wehner, How to transform graph states using single-qubit operations: computational complexity and algorithms, Quantum Science and Technology **5**, 045016 (2020), arXiv:1805.05306 [quant-ph].

[40] A. Dahlberg, J. Helsen, and S. Wehner, Transforming graph states to Bell-pairs is NP-complete, Quantum **4**, 348 (2020), arXiv:1907.08019 [quant-ph].

[41] A. Dahlberg, J. Helsen, and S. Wehner, Counting single-qubit Clifford equivalent graph states is #p-complete, Journal of Mathematical Physics **61**, 022202 (2020), arXiv:1907.08024 [quant-ph].

[42] A. Davies, P. Veličković, L. Buesing, S. Blackwell, D. Zheng, N. Tomašev, R. Tanburn, P. Battaglia, C. Blundell, A. Juhász, M. Lackenby, G. Williamson, D. Hassabis, and P. Kohli, Advancing mathematics by guiding human intuition with AI, Nature **600**, 70 (2021).

[43] B. Romera-Paredes, M. Barekatain, A. Novikov, M. Balog, M. P. Kumar, E. Dupont, F. J. R. Ruiz, J. S. Ellenberg, P. Wang, O. Fawzi, P. Kohli, and A. Fawzi, Mathematical discoveries from program search with large language models, Nature **625**, 468 (2024).

[44] A. Novikov, N. Vũ, M. Eisenberger, E. Dupont, P.-S. Huang, A. Z. Wagner, S. Shirobokov, B. Kozlovskii, F. J. R. Ruiz, A. Mehrabian, M. P. Kumar, A. See, S. Chaudhuri, G. Holland, A. Davies, S. Nowozin, P. Kohli, and M. Balog, AlphaEvolve: A coding agent for scientific and algorithmic discovery (2025), arXiv:2506.13131.

[45] B. Georgiev, J. Gómez-Serrano, T. Tao, and A. Z. Wagner, Mathematical exploration and discovery at scale (2025), arXiv:2511.02864.

[46] T. H. Trinh, Y. Wu, Q. V. Le, H. He, and T. Luong, Solving olympiad geometry without human demonstrations, Nature **625**, 476 (2024).

[47] T. Hubert, R. Mehta, L. Sartran, M. Z. Horváth, G. Žužić, E. Wieser, A. Huang, J. Schrittwieser, Y. Schroecker, H. Masoom, O. Bertolli, T. Zahavy, A. Mandhane, J. Yung, I. Beloshapka, B. Ibarz, V. Veeriah, L. Yu, O. Nash, P. Lezeau, S. Mercuri, C. Sönne, B. Mehta, A. Davies, D. Zheng, F. Pedregosa, Y. Li, I. von Glehn, M. Rowland, S. Albanie, A. Velingker, S. Schmitt, E. Lockhart, E. Hughes, H. Michalewski, N. Sonnerat, D. Hassabis, P. Kohli, and D. Silver, Olympiad-level formal mathematical reasoning with reinforcement learning, Nature **651**, 607 (2026).