Data sources

October 19, 2026

1 Project work, part 2 - Data sources

GitHub Repository: https://github.com/sgkop/IND320-Innlevering-sgkop

Streamlit App: https://ind320-innlevering1-sgkop.streamlit.app/

1.1 Spark-Cassandra Connection Test

[5]:
```
from pyspark.sql import SparkSession

spark = (
    SparkSession.builder
    .master("local[*]")
    .appName("SparkCassandra")
    .config(
        "spark.jars.packages",
        "com.datastax.spark:spark-cassandra-connector_2.12:3.5.1"
    )
    .config("spark.cassandra.connection.host", "localhost")
    .config("spark.cassandra.connection.port", "9042")
    .getOrCreate()
)

print("Spark-Cassandra session created")
```

```
Spark-Cassandra session created
```

Apache Spark 3.5.1 was configured with the DataStax Spark Cassandra Connector and connected to a local Cassandra instance.

1.2 NVE Magasinstatistikk API

[1]:
```
import requests
import pandas as pd

url = "https://biapi.nve.no/magasinstatistikk/api/Magasinstatistikk/
 ↪HentOffentligData"

response = requests.get(url)
```

```
response.raise_for_status()

magasin_data = response.json()

magasin_df = pd.DataFrame(magasin_data)

print(
    f"Dataset contains "
    f"{magasin_df.shape[0]} rows and "
    f"{magasin_df.shape[1]} columns."
)

magasin_df.head()
```

```
Dataset contains 14922 rows and 11 columns.
```

[1]:

	dato_Id	omrType	omrnr	iso_aar	iso_uke	fyllingsgrad	kapasitet_TWh	\
0	1995-09-03	EL	4	1995	35	0.944721	21.079208	
1	2020-11-15	EL	1	2020	46	0.974361	6.003264	
2	2011-08-28	EL	4	2011	34	0.786499	21.079208	
3	1998-07-05	EL	3	1998	27	0.793969	8.920932	
4	2011-03-27	EL	4	2011	12	0.300820	21.079208	

	fylling_TWh	neste_Publiseringsdato	fyllingsgrad_forrige_uke	\
0	19.913979	0001-01-01T00:00:00	0.936888	
1	5.849344	2020-11-25T13:00:00	0.997406	
2	16.578772	0001-01-01T00:00:00	0.787193	
3	7.082947	0001-01-01T00:00:00	0.733812	
4	6.341054	0001-01-01T00:00:00	0.311122	

	endring_fyllingsgrad
0	0.007833
1	-0.023046
2	-0.000694
3	0.060157
4	-0.010301

[11]:
```
magasin_df.info()
```

```
<class 'pandas.DataFrame'>
RangeIndex: 14913 entries, 0 to 14912
Data columns (total 11 columns):
 #   Column                   Non-Null Count  Dtype
---  ------                   --------------  -----
 0   dato_Id                  14913 non-null  str
 1   omrType                  14913 non-null  str
 2   omrnr                    14913 non-null  int64
 3   iso_aar                  14913 non-null  int64
```

```
 4   iso_uke                   14913 non-null  int64
 5   fyllingsgrad              14913 non-null  float64
 6   kapasitet_TWh             14913 non-null  float64
 7   fylling_TWh               14913 non-null  float64
 8   neste_Publiseringsdato    14913 non-null  str
 9   fyllingsgrad_forrige_uke  14913 non-null  float64
 10  endring_fyllingsgrad      14913 non-null  float64
dtypes: float64(5), int64(3), str(3)
memory usage: 1.7 MB
```

[12]:
```
magasin_df["omrType"].unique()
```

[12]:
```
<ArrowStringArray>
['EL', 'NO', 'VASS']
Length: 3, dtype: str
```

[ ]:
```
magasin_df["dato_Id"] = pd.to_datetime(
    magasin_df["dato_Id"]
)
```

[ ]:
```
0   1995-09-03
1   2020-11-15
2   2011-08-28
3   1998-07-05
4   2011-03-27
Name: dato_Id, dtype: datetime64[us]
```

[25]:
```
import matplotlib.pyplot as plt

# Filtrer og sorter på nytt
el1 = (
    magasin_df[
        (magasin_df["omrType"] == "EL") &
        (magasin_df["omrnr"] == 1)
    ]
    .copy()
)

el1["dato_Id"] = pd.to_datetime(el1["dato_Id"])


el1 = el1.sort_values("dato_Id")

plt.figure(figsize=(12,6))

plt.plot(
    el1["dato_Id"],
    el1["fyllingsgrad"]
)
```

```
plt.title("Filling Level - EL1")
plt.xlabel("Date")
plt.ylabel("Filling Level")
plt.grid(True)

plt.tight_layout()
plt.show()
```



[26]:
```
import matplotlib.pyplot as plt

plt.figure(figsize=(12, 6))

for area in [1, 2, 3, 4, 5]:

    subset = (
        magasin_df[
            (magasin_df["omrType"] == "EL") &
            (magasin_df["omrnr"] == area)
        ]
        .copy()
    )


    subset["dato_Id"] = pd.to_datetime(subset["dato_Id"])
    subset = subset.sort_values("dato_Id")

    plt.plot(
        subset["dato_Id"],
```

```
        subset["fyllingsgrad"],
        label=f"EL{area}"
    )

plt.title("Reservoir Filling Level for Norwegian Price Areas")
plt.xlabel("Date")
plt.ylabel("Filling Level")
plt.legend()
plt.grid(True)

plt.tight_layout()
plt.show()
```



1.3 MongoDB Connection test

[ ]:
```
from pymongo import MongoClient

uri = "<MONGO_URI>"
client = MongoClient(uri)
try:
    client.admin.command("ping")
    print("Connected successfully")

except Exception as e:
    raise Exception(
        "The following error occurred: ", e)
```

```
Connected successfully
```

1.4 ENTSO-E API

[3]:
```
from entsoe import EntsoePandasClient

API_KEY = "<ENTSOE_API_KEY>"

client = EntsoePandasClient(api_key=API_KEY)
```

[ ]:
```
import pandas as pd

start = pd.Timestamp("2025-01-01", tz="Europe/Brussels")
end = pd.Timestamp("2026-01-01", tz="Europe/Brussels")
```

[28]:
```
flows = client.query_crossborder_flows(
    country_code_from="NO_2",
    country_code_to="DK_1",
    start=start,
    end=end
)

flows.head()
```

[28]:
```
2025-01-01 00:00:00+01:00    0.0
2025-01-01 01:00:00+01:00    0.0
2025-01-01 02:00:00+01:00    0.0
2025-01-01 03:00:00+01:00    0.0
2025-01-01 04:00:00+01:00    0.0
dtype: float64
```

[29]:
```
len(flows)
```

[29]:
```
28053
```

The query returned 28,053 hourly observations of cross-border electricity flows between NO2 and DK1 for 2025.

1.5 Cross-Border Flow Data Processing

[19]:
```
flows_df = flows.reset_index()

flows_df.columns = ["timestamp", "flow_mw"]

flows_df.head()
```

[19]:
```
                  timestamp  flow_mw
0 2025-01-01 00:00:00+01:00      0.0
1 2025-01-01 01:00:00+01:00      0.0
2 2025-01-01 02:00:00+01:00      0.0
```

```
3 2025-01-01 03:00:00+01:00      0.0
4 2025-01-01 04:00:00+01:00      0.0
```

[21]:
```
flows_df.info()
```

```
<class 'pandas.DataFrame'>
RangeIndex: 28053 entries, 0 to 28052
Data columns (total 2 columns):
 #   Column     Non-Null Count  Dtype
---  ------     --------------  -----
 0   timestamp  28053 non-null  datetime64[us, Europe/Oslo]
 1   flow_mw    28053 non-null  float64
dtypes: datetime64[us, Europe/Oslo](1), float64(1)
memory usage: 438.5 KB
```

[ ]:
```
flows_df["connection"] = "NO2-DK1"
flows_df["direction"] = "NO_to_DK"
```

The cross-border flow data were successfully retrieved from the ENTSO-E API and prepared in a Pandas DataFrame. The dataset contains timestamps, flow values, connection identifiers and flow direction. These data will be transferred to Spark and Cassandra in the next stage of the project

1.6 Spark setup

[37]:
```
import os
import sys

os.environ["SPARK_HOME"] = r"C:\spark_temp\pyspark"
os.environ["HADOOP_HOME"] = r"C:\spark_temp\Hadoop\hadoop-3.3.1"
os.environ["JAVA_HOME"] = r"C:\Program Files\Microsoft\jdk-17.0.20.101-hotspot"

os.environ["PYSPARK_PYTHON"] = sys.executable
os.environ["PYSPARK_DRIVER_PYTHON"] = sys.executable
```

[38]:
```
from pyspark.sql import SparkSession

spark = (
    SparkSession.builder
    .master("local[*]")
    .appName("IND320")
    .config(
        "spark.jars.packages",
        "com.datastax.spark:spark-cassandra-connector_2.12:3.5.1"
    )
    .config("spark.cassandra.connection.host", "localhost")
    .config("spark.cassandra.connection.port", "9042")
    .getOrCreate()
)
```

[21]:
```
flows_simple = flows_df.copy()

flows_simple["timestamp"] = (
    flows_simple["timestamp"]
    .dt.tz_localize(None)
)
```

1.7 Cassandra storage

[24]:
```
spark_flows_df = spark.createDataFrame(flows_simple)

spark_flows_df.show(5)
```

```
+-------------------+-------+----------+---------+
|          timestamp|flow_mw|connection|direction|
+-------------------+-------+----------+---------+
|2025-01-01 00:00:00|    0.0|   NO2-DK1| NO_to_DK|
|2025-01-01 01:00:00|    0.0|   NO2-DK1| NO_to_DK|
|2025-01-01 02:00:00|    0.0|   NO2-DK1| NO_to_DK|
|2025-01-01 03:00:00|    0.0|   NO2-DK1| NO_to_DK|
|2025-01-01 04:00:00|    0.0|   NO2-DK1| NO_to_DK|
+-------------------+-------+----------+---------+
only showing top 5 rows
```

[25]:
```
spark_flows_df.write \
    .format("org.apache.spark.sql.cassandra") \
    .mode("append") \
    .options(
        table="crossborder_flows",
        keyspace="ind320"
    ) \
    .save()
```

[26]:
```
df_from_cassandra = (
    spark.read
    .format("org.apache.spark.sql.cassandra")
    .options(
        table="crossborder_flows",
        keyspace="ind320"
    )
    .load()
)

df_from_cassandra.show(5)
```

```
+----------+-------------------+---------+-------+
|connection|          timestamp|direction|flow_mw|
```

```
+----------+-------------------+---------+-------+
|   NO2-DK1|2025-01-01 00:00:00| NO_to_DK|    0.0|
|   NO2-DK1|2025-01-01 01:00:00| NO_to_DK|    0.0|
|   NO2-DK1|2025-01-01 02:00:00| NO_to_DK|    0.0|
|   NO2-DK1|2025-01-01 03:00:00| NO_to_DK|    0.0|
|   NO2-DK1|2025-01-01 04:00:00| NO_to_DK|    0.0|
+----------+-------------------+---------+-------+
only showing top 5 rows
```

[27]:
```
selected_df = df_from_cassandra.select(
    "timestamp",
    "flow_mw",
    "connection",
    "direction"
)
```

[30]:
```
selected_df.printSchema()
```

```
root
 |-- timestamp: timestamp (nullable = true)
 |-- flow_mw: double (nullable = true)
 |-- connection: string (nullable = false)
 |-- direction: string (nullable = true)
```

1.8 Bidirectional Flow Processing

[30]:
```
flows_back = client.query_crossborder_flows(
    country_code_from="DK_1",
    country_code_to="NO_2",
    start=start,
    end=end
)
```

[31]:
```
flows_back_df = flows_back.reset_index()

flows_back_df.columns = ["timestamp", "flow_mw"]

flows_back_df["connection"] = "NO2-DK1"
flows_back_df["direction"] = "DK_to_NO"
```

[32]:
```
flows_df["timestamp"] = flows_df["timestamp"].dt.tz_localize(None)

flows_back_df["timestamp"] = flows_back_df["timestamp"].dt.tz_localize(None)
```

1.9 Combining Both Flow Directions

[33]:
```
combined_df = pd.concat(
    [flows_simple, flows_back_df],
    ignore_index=True
)
```

[34]:
```
combined_df.info()
```

```
<class 'pandas.DataFrame'>
RangeIndex: 56106 entries, 0 to 56105
Data columns (total 4 columns):
 #   Column      Non-Null Count  Dtype
---  ------      --------------  -----
 0   timestamp   56106 non-null  datetime64[us]
 1   flow_mw     56106 non-null  float64
 2   connection  56106 non-null  str
 3   direction   56106 non-null  str
dtypes: datetime64[us](1), float64(1), str(2)
memory usage: 1.7 MB
```

[35]:
```
combined_df.head()
```

[35]:

	timestamp	flow_mw	connection	direction
0	2025-01-01 00:00:00	0.0	NO2-DK1	NO_to_DK
1	2025-01-01 01:00:00	0.0	NO2-DK1	NO_to_DK
2	2025-01-01 02:00:00	0.0	NO2-DK1	NO_to_DK
3	2025-01-01 03:00:00	0.0	NO2-DK1	NO_to_DK
4	2025-01-01 04:00:00	0.0	NO2-DK1	NO_to_DK

[39]:
```
combined_spark_df = spark.createDataFrame(combined_df)

combined_spark_df.show(5)
```

```
+-------------------+-------+----------+---------+
|          timestamp|flow_mw|connection|direction|
+-------------------+-------+----------+---------+
|2025-01-01 00:00:00|    0.0|   NO2-DK1| NO_to_DK|
|2025-01-01 01:00:00|    0.0|   NO2-DK1| NO_to_DK|
|2025-01-01 02:00:00|    0.0|   NO2-DK1| NO_to_DK|
|2025-01-01 03:00:00|    0.0|   NO2-DK1| NO_to_DK|
|2025-01-01 04:00:00|    0.0|   NO2-DK1| NO_to_DK|
+-------------------+-------+----------+---------+
only showing top 5 rows
```

[40]:
```
combined_spark_df.write \
    .format("org.apache.spark.sql.cassandra") \
    .mode("append") \
```

```
    .options(
        table="crossborder_flows",
        keyspace="ind320"
    ) \
    .save()
```

[41]:
```
all_df = (
    spark.read
    .format("org.apache.spark.sql.cassandra")
    .options(
        table="crossborder_flows",
        keyspace="ind320"
    )
    .load()
)
```

[42]:
```
all_df.count()
```

[42]:
```
28049
```

[39]:
```
all_df.groupBy("direction").count().show()
```

```
+---------+-----+
|direction|count|
+---------+-----+
| NO_to_DK|  471|
| DK_to_NO|  273|
+---------+-----+
```

[42]:
```
pie_df = (
    all_df.groupBy("direction")
    .sum("flow_mw")
    .toPandas()
)

pie_df
```

[42]:

	direction	sum(flow_mw)
0	NO_to_DK	515475.77
1	DK_to_NO	43139.26


[43]:
```
import matplotlib.pyplot as plt

plt.figure(figsize=(6,6))

plt.pie(
    pie_df["sum(flow_mw)"],
```

```
    labels=pie_df["direction"],
    autopct="%1.1f%%"
)

plt.title("Power flow between Norway and Denmark")
plt.show()
```



[44]:
```
line_df = all_df.toPandas()

line_df = line_df.sort_values("timestamp")
```

[45]:
```
import matplotlib.pyplot as plt


plt.figure(figsize=(12,6))

for direction in line_df["direction"].unique():
    subset = line_df[
```

```
        line_df["direction"] == direction
    ]

    plt.plot(
        subset["timestamp"],
        subset["flow_mw"],
        label=direction
    )

plt.legend()
plt.xlabel("Time")
plt.ylabel("Flow (MW)")
plt.title("Power flow NO2-DK1")
plt.show()
```



1.10 MongoDB Storage

[43]:
```
from pymongo import MongoClient

client = MongoClient(uri)

db = client["ind320"]
collection = db["crossborder_flows"]
```

[44]:
```
collection.delete_many({})
```

[46]:
```
mongo_df = all_df.toPandas()

mongo_df["timestamp"] = mongo_df["timestamp"].astype(str)

records = mongo_df.to_dict("records")
```

[ ]:
```
collection.insert_many(records)
```

[48]:
```
collection.count_documents({})
```

[48]: 28049

[49]:
```
mongo_df["timestamp"] = pd.to_datetime(mongo_df["timestamp"])

sorted(mongo_df["timestamp"].dt.month.unique())
```

[49]:
```
[np.int32(1),
 np.int32(2),
 np.int32(3),
 np.int32(4),
 np.int32(5),
 np.int32(6),
 np.int32(7),
 np.int32(8),
 np.int32(9),
 np.int32(10),
 np.int32(11),
 np.int32(12)]
```

1.11 Log

A significant part of the project work was spent configuring Apache Spark and establishing a working Spark-Cassandra environment. After encountering compatibility and startup issues, the project was migrated from the original Python environment to a clean Python 3.11 virtual environment. Spark also experienced problems related to the project's OneDrive location, which contained spaces and Norwegian characters in the file path. The issue was resolved by moving the Spark and Hadoop directories to a dedicated folder without special characters and updating the required environment variables. Following these changes, Spark started successfully, and a Spark session with the Cassandra connector was created.

The next step was integrating ENTSO-E cross-border electricity flow data into the data pipeline. Using the ENTSO-E API, hourly transmission data between the Norwegian bidding zone NO2 and the Danish bidding zone DK1 were retrieved. The solution was initially tested on one month of data before being expanded to cover the entire year 2025. Data from both directions (NO2→DK1 and DK1→NO2) were transformed into Pandas DataFrames, enriched with metadata describing connection and flow direction, and converted to Spark DataFrames.

The processed data were written to Cassandra and read back into Spark to verify that the storage process worked correctly. The data were then transferred to MongoDB Atlas, which served as the

data source for the Streamlit application. During this phase, connection issues were encountered due to MongoDB Atlas network restrictions. After updating the allow list and verifying the connection, the data could be successfully inserted into MongoDB.

For the Streamlit application, the original reservoir pages were updated to retrieve data directly from the NVE API instead of local CSV files. A new cross-border flow dashboard was also developed using MongoDB as its data source. The dashboard includes a pie chart showing the annual distribution of power flows by direction and a line chart showing flow development over time. Streamlit components such as st.columns(), st.radio(), st.pills(), and st.expander() were used to create an interactive interface.

Following feedback from the previous assignment, the reservoir pages were redesigned to improve readability. Users can now select both area type (EL, NO or VASS) and area number, allowing plots and tables to focus on individual areas rather than displaying all areas simultaneously. The data table was also simplified by focusing on numeric variables and using LineChartColumn to provide compact trend visualizations. Overall, the project provided practical experience with APIs, Apache Spark, Cassandra, MongoDB Atlas and Streamlit, while demonstrating a complete data engineering workflow from data acquisition to interactive visualization.

1.12 AI Usage

I acknowledge the use of Microsoft 365 Copilot (https://www.microsoft.com/copilot), based on the GPT-5 chat model, and Google Gemini during this project.

Microsoft 365 Copilot was used to discuss project structure, assist with debugging, explain data visualization choices, support the development of the Streamlit application, and review written documentation. Google Gemini was primarily used when troubleshooting Apache Spark configuration issues and helping identify the causes of startup and environment-related errors.

All code, visualizations, and written content were reviewed, tested, and adapted to reflect my own understanding and decisions. The final implementation, analysis, and design choices remain my own responsibility.