

Strength of DES – Key Size

- 56-bit keys have $2^{56} = 7.2 \times 10^{16}$ values
- brute force search looks hard
- recent advances have shown is possible
 - in 1997 on Internet in a few months
 - in 1998 on dedicated h/w (EFF) in a few days
 - in 1999 above combined in 22hrs!
- still must be able to recognize plaintext
- must now consider alternatives to DES

Strength of DES – Analytic Attacks

- now have several analytic attacks on DES
- these utilise some deep structure of the cipher
 - by gathering information about encryptions
 - can eventually recover some/all of the sub-key bits
 - if necessary then exhaustively search for the rest
- generally these are statistical attacks
- include
 - differential cryptanalysis
 - linear cryptanalysis
 - related key attacks

Strength of DES – Timing Attacks

- attacks actual implementation of cipher
- use knowledge of consequences of implementation to derive information about some/all subkey bits
- specifically use fact that calculations can take varying times depending on the value of the inputs to it
- particularly problematic on smartcards

Differential Cryptanalysis

- one of the most significant recent (public) advances in cryptanalysis
- known by NSA in 70's cf DES design
- Murphy, Biham & Shamir published in 90's
- powerful method to analyse block ciphers
- used to analyse most current block ciphers with varying degrees of success
- DES reasonably resistant to it, cf Lucifer

Differential Cryptanalysis

- a statistical attack against Feistel ciphers
- uses cipher structure not previously used
- design of S-P networks has output of function f influenced by both input & key
- hence cannot trace values back through cipher without knowing value of the key
- differential cryptanalysis compares two related pairs of encryptions

Differential Cryptanalysis Compares Pairs of Encryptions


- with a known difference in the input
- searching for a known difference in output
- when same subkeys are used

$$\begin{aligned}\Delta m_{i+1} &= m_{i+1} \oplus m'_{i+1} \\ &= [m_{i-1} \oplus f(m_i, K_i)] \oplus [m'_{i-1} \oplus f(m'_i, K_i)] \\ &= \Delta m_{i-1} \oplus [f(m_i, K_i) \oplus f(m'_i, K_i)]\end{aligned}$$

Differential Cryptanalysis

- have some input difference giving some output difference with probability p
- if find instances of some higher probability input / output difference pairs occurring
- can infer subkey that was used in round
- then must iterate process over many rounds (with decreasing probabilities)

Differential Cryptanalysis



Differential Cryptanalysis

- perform attack by repeatedly encrypting plaintext pairs with known input XOR until obtain desired output XOR
- when found
 - if intermediate rounds match required XOR have a **right pair**
 - if not then have a **wrong pair**, relative ratio is S/N for attack
- can then deduce keys values for the rounds
 - right pairs suggest same key bits
 - wrong pairs give random values
- for large numbers of rounds, probability is so low that more pairs are required than exist with 64-bit inputs
- Biham and Shamir have shown how a 13-round iterated characteristic can break the full 16-round DES

Linear Cryptanalysis

- another recent development
- also a statistical method
- must be iterated over rounds, with decreasing probabilities
- developed by Matsui et al in early 90's
- based on finding linear approximations
- can attack DES with 2^{43} known plaintexts, easier but still in practise infeasible

Linear Cryptanalysis

- find linear approximations with prob $p \neq \frac{1}{2}$

$$P[i_1, i_2, \dots, i_a] \oplus C[j_1, j_2, \dots, j_b] = K[k_1, k_2, \dots, k_c]$$

where i_a, j_b, k_c are bit locations in P, C, K

- gives linear equation for key bits
- get one key bit using max likelihood alg
- using a large number of trial encryptions
- effectiveness given by: $|p - \frac{1}{2}|$

DES Design Criteria

- as reported by Coppersmith in [COPP94]
- 7 criteria for S-boxes provide for
 - non-linearity
 - resistance to differential cryptanalysis
 - good confusion
- 3 criteria for permutation P provide for
 - increased diffusion

Block Cipher Design

- basic principles still like Feistel's in 1970's
- number of rounds
 - more is better, exhaustive search best attack
- function f :
 - provides “confusion”, is nonlinear, avalanche
 - have issues of how S-boxes are selected
- key schedule
 - complex subkey creation, key avalanche


Multiple Encryption & DES

- clear a replacement for DES was needed
 - theoretical attacks that can break it
 - demonstrated exhaustive key search attacks
- AES is a new cipher alternative
- prior to this alternative was to use multiple encryption with DES implementations
- Triple-DES is the chosen form

Double-DES?

- could use 2 DES encrypts on each block
 - $C = E_{K2}(E_{K1}(P))$
- issue of reduction to single stage
- and have “meet-in-the-middle” attack
 - works whenever use a cipher twice
 - since $X = E_{K1}(P) = D_{K2}(C)$
 - attack by encrypting P with all keys and store
 - then decrypt C with keys and match X value
 - can show takes $O(2^{56})$ steps

Meet in the middle attack



Triple-DES with Two-Keys

- hence must use 3 encryptions
 - would seem to need 3 distinct keys
- but can use 2 keys with E-D-E sequence
 - $C = E_{K1} (D_{K2} (E_{K1} (P)))$
 - nb encrypt & decrypt equivalent in security
 - if $K1=K2$ then can work with single DES
- standardized in ANSI X9.17 & ISO8732
- no current known practical attacks

Triple-DES with Three-Keys

- although there are no practical attacks on two-key Triple-DES, there are some indications
- can use Triple-DES with Three-Keys to avoid even these
 - $C = E_{K3} (D_{K2} (E_{K1} (P)))$
- has been adopted by some Internet applications, eg PGP, S/MIME

Algorithm	Key length	round	Mathematical operations	Applications
DES	56 Bit	16	XOR, fixed S-boxes	SET,Kerberos
Triple DES	112 or 168 bit	48	XOR, fixed S-boxes	Financial key management, PGP, S/MIME
IDEA	128 Bit	8	XOR, addition, multiplication	PGP
Blowfish	variable, 448 bit	16	XOR, variable S-Boxes, addition	
RC5	variable 2048 Bit	variable 255	addition, subtraction, XOR, round	
CAST-128	40-128 bit	16	addition, subtraction, XOR, round, fixed S-boxes	PGP

Properties of advanced block ciphers

- Variable key length
- Complex mathematical operations
- Data depended rounds
- Key depended S-box
- Multiple length key arrangement algorithms
- Variable plain/cipher text length
- Variable round number
- Operation for each half data at each round
- Variable F Function
- Key depended rounds

Modes of Operation

- block ciphers encrypt fixed size blocks
 - eg. DES encrypts 64-bit blocks with 56-bit key
- need some way to en/decrypt arbitrary amounts of data in practise
- **ANSI X3.106-1983 Modes of Use** (now FIPS 81) defines 4 possible modes
- subsequently 5 defined for AES & DES
- have **block** and **stream** modes


Electronic Codebook Book (ECB)

- message is broken into independent blocks which are encrypted
- each block is a value which is substituted, like a codebook, hence name
- each block is encoded independently of the other blocks

$$C_i = \text{DES}_{K1}(P_i)$$

- uses: secure transmission of single values

Electronic Codebook Book (ECB)



Advantages and Limitations of ECB

- message repetitions may show in ciphertext
 - if aligned with message block
 - particularly with data such graphics
 - or with messages that change very little, which become a code-book analysis problem
- weakness is due to the encrypted message blocks being independent
- main use is sending a few blocks of data

Cipher Block Chaining (CBC)


- message is broken into blocks
- linked together in encryption operation
- each previous cipher blocks is chained with current plaintext block, hence name
- use Initial Vector (IV) to start process

$$C_i = \text{DES}_{K1} (P_i \text{ XOR } C_{i-1})$$

$$C_{-1} = \text{IV}$$

- uses: bulk data encryption, authentication

Cipher Block Chaining (CBC)



Message Padding

- at end of message must handle a possible last short block
 - which is not as large as blocksize of cipher
 - pad either with known non-data value (eg nulls)
 - or pad last block along with count of pad size
 - eg. [b1 b2 b3 0 0 0 0 5]
 - means have 3 data bytes, then 5 bytes pad+count
 - this may require an extra entire block over those in message
- there are other, more esoteric modes, which avoid the need for an extra block


Advantages and Limitations of CBC

- a ciphertext block depends on **all** blocks before it
- any change to a block affects all following ciphertext blocks
- need **Initialization Vector (IV)**
 - which must be known to sender & receiver
 - if sent in clear, attacker can change bits of first block, and change IV to compensate
 - hence IV must either be a fixed value (as in EFTPOS)
 - or must be sent encrypted in ECB mode before rest of message

Cipher FeedBack (CFB)

- message is treated as a stream of bits
- added to the output of the block cipher
- result is feed back for next stage (hence name)
- standard allows any number of bit (1,8, 64 or 128 etc) to be feed back
 - denoted CFB-1, CFB-8, CFB-64, CFB-128 etc
- most efficient to use all bits in block (64 or 128)
$$C_i = P_i \text{ XOR } \text{DES}_{K1}(C_{i-1})$$
$$C_{-1} = \text{IV}$$
- uses: stream data encryption, authentication

Cipher FeedBack (CFB)



Advantages and Limitations of CFB

- appropriate when data arrives in bits/bytes
- most common stream mode
- limitation is need to stall while do block encryption after every n-bits
- note that the block cipher is used in **encryption** mode at **both** ends
- errors propagate for several blocks after the error

Output FeedBack (OFB)

- message is treated as a stream of bits
- output of cipher is added to message
- output is then feed back (hence name)
- feedback is independent of message
- can be computed in advance



$$C_i = P_i \text{ XOR } O_i$$

$$O_i = \text{DES}_{K1}(O_{i-1})$$

$$O_{-1} = \text{IV}$$

- uses: stream encryption on noisy channels

Output FeedBack (OFB)



Advantages and Limitations of OFB

- bit errors do not propagate
- more vulnerable to message stream modification
- a variation of a Vernam cipher
 - hence must **never** reuse the same sequence (key+IV)
- sender & receiver must remain in sync
- originally specified with m-bit feedback
- subsequent research has shown that only **full block feedback** (ie CFB-64 or CFB-128) should ever be used

Counter (CTR)


- a “new” mode, though proposed early on
- similar to OFB but encrypts counter value rather than any feedback value
- must have a different key & counter value for every plaintext block (never reused)

$$C_i = P_i \text{ XOR } O_i$$


$$O_i = \text{DES}_{K1}(i)$$

- uses: high-speed network encryptions

Counter (CTR)



(a) Encryption



(b) Decryption

Advantages and Limitations of CTR

- efficiency
 - can do parallel encryptions in h/w or s/w
 - can preprocess in advance of need
 - good for bursty high speed links
- random access to encrypted data blocks
- provable security (good as other modes)
- but must ensure never reuse key/counter values, otherwise could break (cf OFB)