
Clean Feature Anchoring: Mitigating the Accuracy–Robustness Trade-off by Self-Distilling a Naturally Trained Model

Anonymous authors
Paper under double-blind review

Abstract

Adversarial training is among the most reliable defenses against adversarial examples, but it degrades standard accuracy, and this trade-off is the central obstacle to its use. The accuracy is not lost in general: a network of the same architecture trained naturally on the same data still holds it. We ask whether self-distillation can put it back, leaving robustness where it already is, in the inner maximization. Such a teacher is the extreme case of what adversarial distillation says goes wrong—the field diagnoses the target as too sharp and builds machinery to soften it, and a naturally trained network’s maximum softmax probability is 0.820 against an adversarially trained student’s 0.016. Softening does help, raising AutoAttack accuracy from 20.84 to 24.48 across a temperature sweep, and it leaves standard accuracy flat at 58 while the teacher holds 77.66: it repairs robustness, not the axis we came for. Reading the same teacher’s feature instead recovers both. We anchor the student’s adversarial feature to the teacher’s clean feature, so the teacher is never evaluated under attack and transfers neither its instability nor any robustness, and prove that this single term is equivalent within a constant factor to fidelity plus local stability, with no coefficient between them. Combined with a per-sample attack radius set by the input sensitivity of the loss at fixed total budget, the method has no loss weight, no temperature and no trained classifier. At a fixed weight-averaging and AWP stack it matches the best published AutoAttack accuracy on CIFAR-100 to within 0.27 points while keeping 5.29 more points of standard accuracy, and transfers unchanged to CIFAR-10 and Tiny-ImageNet.

1 Introduction

Deep neural networks are vulnerable to adversarial examples, imperceptible perturbations of the input that change the prediction (Goodfellow et al., 2014; Madry et al., 2017; Carlini & Wagner, 2017), which raises concerns wherever such models are deployed in safety-critical systems (Ma et al., 2021; Grigorescu et al., 2020). Among the defenses proposed in response, adversarial training (Madry et al., 2017) remains the most reliable (Athalye et al., 2018; Croce & Hein, 2020): the model is optimized on perturbations produced by an inner maximization, and the robustness it attains has survived a decade of stronger attacks. Its cost, however, is standard accuracy. A network trained adversarially classifies unperturbed inputs considerably worse than the same network trained naturally, and the gap grows with the perturbation budget. This accuracy–robustness trade-off is partly intrinsic to the objective (Tsipras et al., 2018; Zhang et al., 2019) and it is the principal obstacle to deploying adversarially trained models in practice.

Two lines of work reduce it. The first modifies the target inside adversarial training. Hard labels are a poor supervisory signal for perturbed inputs, since they assert that every point of an ϵ -ball belongs to one class with full confidence, and softening them alleviates both the trade-off and robust overfitting (Rice et al., 2020). Label smoothing (Pang et al., 2020), consistency regularization (Tack et al., 2022), and annealing self-distillation rectification (Wu




Figure 1: The accuracy–robustness frontier on ResNet-18, ℓ_∞ , $\epsilon = 8/255$. Grey points are published results (Table 13); the dashed line is a least-squares fit through the Pareto-optimal ones and is drawn for reading rather than fitted for a claim. CFA is drawn as a curve rather than a point, because the training radius moves along the frontier at no cost; the star is the shipped configuration and the other markers differ from it only in ϵ_{train} . At $\epsilon_{\text{train}} = 8/255$ the curve strictly dominates Generalist++ on CIFAR-100 (63.89/27.78 against 62.97/23.96) and both CURE and ARREST on CIFAR-10 (87.22/51.15 against 86.76/49.69 and 86.63/46.14), so it is ahead on both axes rather than trading one for the other. Its teacher is a naturally trained network of the same architecture, obtained at no adversarial cost.

et al., 2024) all replace the one-hot target with a smoother one, the last using the model’s own weight average as the source. These methods require no additional network. The second line is adversarial distillation, which supplies the target from an adversarially trained teacher: ARD (Goldblum et al., 2020), IAD (Zhu et al., 2021), RSLAD (Zi et al., 2021), AdaAD (Huang et al., 2023) and IGDM (Lee et al., 2025) differ in which teacher quantity is matched and where the teacher is evaluated, and together they define the strongest reported accuracy–robustness frontiers for small architectures.

The two lines leave a gap between them. Adversarial distillation presupposes that an already-robust network exists, and in practice that network is a WideResNet adversarially trained with large volumes of generated data (Wang et al., 2023b)—costlier to obtain than the student it teaches. The robustness such methods report therefore originates outside the student, and what is being measured is the quality of the transfer. The teacher that is genuinely free, a naturally trained copy of the student’s own architecture, is not used as a source of guidance for the adversarial term, and the reason is well founded: a naturally trained network attains its accuracy through features an adversary can manipulate (Ilyas et al., 2019), so transferring what it computes is expected to transfer that fragility as well. Three lines of work come close and are discussed in Section 2—ARREST (Suzuki et al., 2023) initializes from a standardly pretrained network and adds a representation-distance term to the label loss; DP-FAT (Cho & Kim, 2026) distills a natural teacher directly, rescaling its logits per sample so that only the class-discriminative direction transfers; and B-MTARD (Zhao et al., 2024) pairs a clean teacher with a robust one so that each handles the examples it is good at. In all three the natural network supplies logits and is balanced against another term or another teacher, and the balance is what has to be tuned.

Our question is about the other axis. Adversarial training discards standard accuracy that a naturally trained copy of the same network still holds, and we ask whether self-distillation can put it back—leaving robustness where it already is, in the student’s own inner maximization. The answer turns on what the teacher is asked to supply, and the field already has a candidate that is only half right. Adversarial distillation diagnoses the target as too sharp and softens it—soft labels, smooth teacher logits, annealed and entropy-matched softmax temperatures (Chen & Lee, 2021; Zi et al., 2021; Wu et al., 2024; Zhao et al., 2024)—and

a naturally trained network is the extreme case, with a maximum softmax probability of 0.820 against an adversarially trained student’s 0.016. Softening works: it lifts AutoAttack accuracy from 20.84 to 24.48 across a temperature sweep. It also leaves standard accuracy flat near 58 while the teacher holds 77.66. Temperature moves robustness and not the quantity we came for, because that quantity does not survive the teacher’s own softmax—it survives one layer earlier, which is where we put the anchor. None of this is a claim that a naturally trained teacher is preferable to a robust one: a robust teacher is better guidance for robustness, obtaining it is the expensive part, and we do not compete with methods that have one. Our objective matches the teacher’s feature at the clean input against the student’s feature at the adversarial input, and it is the entire objective for the backbone: the label term is removed rather than supplemented. The teacher is therefore never evaluated inside the perturbation ball, so nothing it does there can enter the optimization, and by the same token it cannot contribute robustness. All robustness is produced by the student’s inner maximization, exactly as in standard adversarial training. We further show that this single term is not merely a fidelity constraint: writing F for the student’s clean deviation from the teacher and O for the diameter of the student’s own output over the ϵ -ball, the anchor loss L satisfies $L \leq F + O \leq 3L$, so minimizing it controls teacher fidelity and local stability together, within a constant factor, with no weight to balance them. The bound uses only the triangle inequality and therefore holds for the networks we actually train.

A second finding concerns what the teacher supplies. Across a ladder of naturally trained teachers differing only in training length, teacher accuracy and student accuracy are almost perfectly anti-correlated ($r = -0.999$): the most accurate teacher produces the worst student. What the student inherits is the teacher’s class geometry rather than its predictions, and the two are not monotone in one another. This makes the teacher’s training length a control on the accuracy–robustness frontier that costs nothing to exercise and that a robust teacher does not offer, since a robust teacher’s own training is the expensive part. The non-monotonicity itself is not peculiar to natural teachers: in the robust-teacher setting a more robust teacher is likewise reported to fail to improve, or to harm, the student, with the teacher’s predictive entropy on a consistent subset of the data indicating which way it will go (Anonymous, 2026). Our ladder is the natural-teacher analogue, and what varies along it is class separation rather than accuracy.

Building on these observations we propose Clean Feature Anchoring (CFA). CFA trains a naturally supervised copy of the student architecture on the same data, initializes the student from it, and then trains the backbone with the clean-feature anchor alone; the classifier is inherited and never trained. To this we add sensitivity-matched ϵ , which redistributes the per-sample attack radius in inverse proportion to the input sensitivity of the loss while holding the total budget fixed, so that each example is perturbed to a comparable displacement of the objective rather than a comparable displacement of the input. The resulting method has no temperature, no loss weight and no auxiliary head, and we apply an identical configuration to every dataset, changing only the dataset name and the teacher checkpoint.

On CIFAR-100 with ResNet-18, CFA reaches 62.17% standard accuracy at 28.86% AutoAttack accuracy (Figure 1). Against the strongest method at comparable robustness this is +5.29 points of standard accuracy, and against the strongest method at comparable standard accuracy it is +4.81 points of AutoAttack accuracy; no method in this setting exceeds ours on both axes. We further run the published distillation objectives on our own natural teacher, which is the teacher they would have in this setting: ARD, RSLAD and AdaAD reach 20.24%, 21.30% and 23.19% AutoAttack accuracy, all below plain adversarial training initialized at the same teacher (26.46%). The accuracy a natural teacher holds is therefore not recovered by treating it as a logit target. Our contributions are as follows:

- We show that a naturally trained network can guide adversarial training when it is asked only for standard accuracy. Evaluated at the clean input and used as the entire backbone objective, a feature anchor controls fidelity to the teacher and local stability of the student jointly, within a constant factor, as a single unweighted term—so the teacher’s own fragility has no path into the optimization, and no coefficient trades the two properties off.

- We show that what a naturally trained teacher transfers is class geometry rather than accuracy, with teacher and student accuracy anti-correlated at $r = -0.999$ across teachers, which turns the teacher’s training length into a trade-off control available only in this setting.
- We propose Clean Feature Anchoring together with sensitivity-matched ϵ , a method with no loss weight, no temperature and no per-dataset tuning, in which robustness remains entirely attributable to the student’s own inner maximization.
- We run the published distillation objectives on the same natural teacher and find all of them below plain adversarial training from that teacher, which locates the difficulty in the logit target rather than in the teacher.
- We demonstrate a new accuracy–robustness frontier on CIFAR-10, CIFAR-100 and Tiny-ImageNet, and show the gain is not weight averaging or AWP: with weight averaging alone and half the schedule, CFA already exceeds the best published result that uses both.

2 Related Work

To be written.

3 Analysis

3.1 Preliminaries

Let $f = h \circ \Phi$ be a classifier with feature map Φ and linear head h . Adversarial training (Madry et al., 2017) solves

$$\min_{\theta} \mathbb{E}_{(x,y)} \max_{x' \in B(x,\epsilon)} \ell(f_{\theta}(x'), y), \quad B(x, \epsilon) = \{x' : \|x' - x\|_{\infty} \leq \epsilon\}. \quad (1)$$

The supervisory signal is the label, and it is asserted uniformly over $B(x, \epsilon)$: every point of the ball must reach full confidence in one class. That is where the accuracy cost comes from. We write $f_t = h_t \circ \Phi_t$ for a network of the same architecture trained naturally on the same data—the teacher throughout, frozen—so that $\Phi_t(x)$ is its feature and $f_t(x)$ its logits, and ask what it can supply.

3.2 Where a Natural Teacher Fails, and Where It Does Not

A method that consumes a teacher can go wrong in two independent places: where it reads the teacher, and what it reads from it. Both defects are present when a naturally trained network is used the way adversarial distillation uses one, and they can be measured separately.

What is read: the field’s prescription is softening, and it is only half a fix. Four separate lines of work converge on the same diagnosis—the target is too sharp—and each builds its own machinery to soften it. LTD (Chen & Lee, 2021) argues that one-hot labels are the wrong supervision for adversarial training and replaces them with soft ones. RSLAD (Zi et al., 2021) makes the smoothness of the teacher’s logits its central claim. ADR (Wu et al., 2024) draws its target from a weight average and scales it by a softmax temperature that starts near-uniform and is annealed down over training. B-MTARD (Zhao et al., 2024) formalizes the quantity being controlled—writing the teacher’s knowledge scale as $\log C - H(P_T)$, so that a sharper teacher carries a larger one—and adjusts each teacher’s temperature online to equalize it. In every case the operative object is $\text{softmax}(z_t/\tau)$ and the design question is τ .

By that account a naturally trained teacher is the extreme case, and the measurement agrees: on clean test data its maximum softmax probability is 0.820, against 0.016 for the adversarially trained student it is supposed to teach. It is asking for a confidence twenty times sharper than the student’s own.

The prescription follows, and it works. Sweeping τ on that teacher’s logits in a fixed base regime—50 epochs, no weight averaging, no AWP, $\epsilon = 8/255$ —AutoAttack accuracy rises from 20.84 at $\tau = 1$ to 24.48 at $\tau = 4$, then turns over. Sharpness is a genuine defect and softening genuinely repairs it.

target	Clean	AA	NRR
teacher logits, $\tau = 1$	58.26	20.84	30.70
teacher logits, $\tau = 4$	59.39	24.48	34.67
teacher logits, $\tau = 16$	57.78	24.00	33.91
teacher feature	62.72	25.88	36.64

What it does not repair is the accuracy. Across the whole sweep clean accuracy moves between 57.78 and 59.39—it is flat in τ —while the teacher it is being distilled from has 77.66. Reading the same teacher’s feature instead, with no temperature anywhere, gains a further 1.40 AutoAttack and 3.33 clean, at the same read point and under the same regime.

The two numbers separate cleanly. Temperature moves robustness and leaves accuracy where it was; the feature moves both. Sharpness is therefore a real problem with a real fix, and it is not the problem this paper is trying to solve: the accuracy a naturally trained network holds does not survive its own softmax, and no choice of τ puts it back. It survives one layer earlier.

Where it is read: off the clean point the teacher has nothing to say. Under $\epsilon = 8/255$ the teacher’s own feature rotates by 63.8° and its norm inflates by $\times 2.45$, so its output inside the ball is not a softened version of its output at the centre. The consequence is sharpest for methods that read it there. IGDM (Lee et al., 2025) matches a finite difference $f_t(x+\delta) - f_t(x-\delta)$ as a stand-in for the teacher’s input gradient, which is a gradient only while the teacher is locally linear; its own diagnostic reports a Taylor remainder proportion of 0.012 for adversarially trained teachers. Applying that diagnostic to our checkpoints gives 0.0111 for an adversarially trained ResNet-18—reproducing their value, so the measurement is calibrated—and **0.4763** for the natural teacher, forty times further from linear. The target it constructs is correspondingly degenerate: $\|f_t(x+\delta) - f_t(x-\delta)\| = 14.14$ against $\|f_t(x)\| = 18.36$, with the softmax of that difference placing 0.917 of its mass on one class.

Together, they cost more than the teacher is worth. Table 5 gives the published objectives with our natural teacher in place of the robust one they assume, each at its own published recipe. Every one lands below plain adversarial training initialized from that same teacher—that is, below not distilling at all. The accuracy the teacher holds is real, and the logit route does not recover it.

What follows keeps the read point at x , where the second defect cannot arise, and takes the features, which the first measurement shows to be the better read.

3.3 What a Clean-Feature Anchor Controls

Consider matching the teacher’s feature at the clean input against the student’s feature at the adversarial input, that is, minimizing

$$\mathcal{L}(x) = \max_{x' \in B(x, \epsilon)} \|\Phi_s(x') - \Phi_t(x)\|^2. \quad (2)$$

Read literally, Equation (2) asks the student to reproduce a fixed vector from every point of the ball. That is a fidelity constraint, and a fidelity constraint alone would have no reason to produce robustness. It turns out not to be one, and the reason is visible once the quantity is compared with the two properties one would otherwise have to impose separately.

Fix x , write $B = B(x, \epsilon)$, and define

$$L = \max_{x' \in B} \|\Phi_s(x') - \Phi_t(x)\|, \quad (3)$$

$$F = \|\Phi_s(x) - \Phi_t(x)\|, \quad (4)$$

$$O = \max_{x', x'' \in B} \|\Phi_s(x') - \Phi_s(x'')\|. \quad (5)$$

Here L is the square root of Equation (2), the quantity the method minimizes; F is fidelity, how far the student is from the teacher at the clean point; and O is oscillation, the diameter of the student’s own feature map over the ball. F is what adversarial training gives up relative to natural training, and O is what its label term buys. They are ordinarily two objectives.

Proposition 1. For every x and every $\epsilon \geq 0$,

$$L \leq F + O \leq 3L. \quad (6)$$

Proof. For the right-hand inequality, $F \leq L$ because $x \in B$, so the maximum in Equation (3) is at least the value at x . For O , insert $\Phi_t(x)$ between the two student features: for any $x', x'' \in B$,

$$\|\Phi_s(x') - \Phi_s(x'')\| \leq \|\Phi_s(x') - \Phi_t(x)\| + \|\Phi_t(x) - \Phi_s(x'')\| \leq 2L,$$

and taking the maximum over x', x'' gives $O \leq 2L$. Adding the two bounds gives $F + O \leq 3L$. For the left-hand inequality, insert $\Phi_s(x)$ instead: for any $x' \in B$,

$$\|\Phi_s(x') - \Phi_t(x)\| \leq \|\Phi_s(x') - \Phi_s(x)\| + \|\Phi_s(x) - \Phi_t(x)\| \leq O + F,$$

and taking the maximum over x' gives $L \leq F + O$. $\square$

Only the triangle inequality is used, so Proposition 1 holds for the networks we actually train: no smoothness, no linearity, no assumption on the architecture or on the attack that realizes the maximum. Two consequences follow immediately.

Corollary 1. If the anchor is driven to $L \leq \delta$ at x , then $F \leq \delta$ and $O \leq 2\delta$ at x .

That is the operative statement: driving one scalar down bounds both properties, at rates that differ by a factor of two and by nothing else. Conversely, by the left inequality, L cannot be small unless both are, so the objective admits no solution that satisfies one at the expense of the other. A weighted sum $F + \lambda O$ has no such property for any fixed λ : its level sets contain points where either term is arbitrarily large. This is why the anchor is stated as the whole objective rather than as a regularizer, and why there is no coefficient to select.

Where the constant 3 comes from, and how tight it is. The factor is $1 + 2$: one from $F \leq L$ and two from $O \leq 2L$, and the second is attained when the student’s outputs at the two extreme points of the ball sit on opposite sides of $\Phi_t(x)$ at distance L each. Our trained students are far from that configuration, which is the content of the measurement below.

The teacher appears at x and nowhere else. Equation (2) evaluates Φ_t at the clean point only, in the loss and in the attack that realizes the maximum. Whatever the teacher does inside B is therefore absent from the objective, and the instability measured in Section 3.2— 63.8° of rotation, $\times 2.45$ of norm—has no path into the optimization. The same fact settles the symmetric question: since the teacher is never asked to resist a perturbation, it cannot supply robustness either, and all of it is produced by the student’s inner maximization.

This is testable by moving the read point and changing nothing else, and the test is decisive. Replacing $\Phi_t(x)$ with $\Phi_t(x')$ in both the loss and the attack drives AutoAttack accuracy from 26.19 to 0.00 while clean accuracy rises to 76.11, within 1.55 of the natural teacher (Table 7). The failure is not that a moving target is harder to track. It is that $\|\Phi_s(x') - \Phi_t(x')\|$ is minimized exactly by $\Phi_s = \Phi_t$, so the student that copies a natural teacher everywhere is optimal—and it has no robustness at all. The clean read point is what makes Equation (2) a non-degenerate objective, and the same asymmetry that keeps the teacher’s fragility out is what keeps the trivial solution out.

Verification. Proposition 1 predicts that a student trained on L ends up with a small O , and the prediction is checkable on the trained network. Measured over $\epsilon = 8/255$ balls on CIFAR-100, $L = 7.58$, $F = 6.30$ and $O_{\text{lb}} = 2.16$, against the teacher’s own $O = 6.68$: the student is $3.1\times$ more stable than the network it was distilled from, on the same balls. Two things follow. The teacher’s instability was not inherited, which is what the construction predicts. And $F \gg O_{\text{lb}}$, so what remains in the loss at convergence is fidelity rather than instability—the anchor is not being satisfied by making the student flat.

What the proposition is for, and what it is not. Proposition 1 says the anchor does not cost robustness: local stability is bounded by the same scalar as fidelity, so the two cannot be traded against each other. It is not a lower bound on how much robustness the objective buys, and we do not read it as one; Appendix B gives two partial results in that direction, each with the reason it falls short.

The measurement is stronger than the proposition. Asked to work with neither weight averaging nor AWP nor a sensitivity-matched radius—the anchor alone, against label cross-entropy under an identical schedule, initialization and training radius—the anchor leads by 6.61 clean and 5.79 AutoAttack (Table 7). For scale, the full recipe leads cross-entropy with weight averaging and AWP by 2.40. So the anchor is a source of robustness rather than a neutral passenger on one, and at matched stack it is the larger source; the components in Table 6 are additive on top of it rather than the origin of the effect. We keep Proposition 1 stated as the weaker claim because that is what the inequality supports—the 5.79 is measured, not derived.

4 Method

4.1 Clean Feature Anchoring

Let Φ_t be the frozen feature map of a network of the same architecture trained naturally on the same data, and let h_t be its classifier. The student’s feature map is initialized at $\Phi_s \leftarrow \Phi_t$ and trained with

$$\mathcal{L} = \mathbb{E}_x \|\Phi_s(x_{\text{adv}}) - \Phi_t(x)\|^2, \quad x_{\text{adv}} = \arg \max_{x' \in B(x, \epsilon)} \|\Phi_s(x') - \Phi_t(x)\|, \quad (7)$$

where the inner maximization is realized by K steps of projected gradient ascent on the same quantity the outer problem minimizes,

$$x^{(k+1)} = \Pi_{B(x, \epsilon)} \left(x^{(k)} + a \cdot \text{sign} \nabla_x \|\Phi_s(x^{(k)}) - \Phi_t(x)\|^2 \right), \quad x^{(0)} = x + \eta, \quad (8)$$

with η a small random initialization and Π the projection onto the ball. The target $\Phi_t(x)$ is a constant of this ascent: it is computed once, at the clean input, and does not move as $x^{(k)}$ does. Inner and outer problems therefore agree, as they do in standard adversarial training and unlike methods whose attack is generated against a different objective from the one being trained.

Equation (7) is the entire objective for the backbone. No label term, no logit term, and no coefficient joining them. Three properties follow from that form, and each is a statement about the construction rather than an empirical observation.

(i) The teacher never enters the perturbation ball. In both Equation (7) and Equation (8) the teacher is evaluated at x alone. Formally, the objective is a functional of Φ_t only through the single vector $\Phi_t(x)$, so two teachers agreeing at x and differing arbitrarily on $B(x, \epsilon) \setminus \{x\}$ induce the same optimization problem. The teacher’s 63.8° of rotation under attack is exactly such a difference, and it is therefore invisible to training. The converse holds by the same argument: a quantity the objective cannot see cannot be a source of robustness either.

The restriction is load-bearing rather than convenient. Evaluating Φ_t at x' instead makes $\Phi_s = \Phi_t$ a global minimizer of Equation (7), and that minimizer is a natural model; measured, the student collapses onto the teacher at 76.11 clean and 0.00 AutoAttack (Table 7). Restricting the teacher to x is therefore not only what keeps its fragility out of the objective, it is what keeps the objective from having a degenerate solution.

(ii) The anchor is exactly zero at the clean point at initialization. Since $\Phi_s \leftarrow \Phi_t$, we have $\|\Phi_s(x) - \Phi_t(x)\| = 0$ for every x , so the loss is nonzero only because of the perturbation: every gradient the backbone receives at the start of training is attributable to the attack, which is the quantity to be trained. A logit target has this property only at temperature 1, where it carries no dark knowledge. It also has a consequence used in Section 4.2: at the

first step the per-sample sensitivities are identical, so the radius allocation begins uniform and differentiates only as the student moves away from the teacher.

(iii) The classifier is inherited, and this is what a feature target buys. At test time the student is $h_t \circ \Phi_s$: the head is never trained. This is available because the target is written on the feature. A loss written on logits constrains only the composition $W\Phi$, so it determines the pair (Φ, W) up to the gauge

$$(\Phi, W) \mapsto (A\Phi, WA^{-1}), \quad A \in \text{GL}(d), \quad (9)$$

and the same logits are reachable from a continuum of representations, none of which the teacher’s classifier is calibrated for. Fixing the target at the feature removes that freedom and pins Φ_s to Φ_t itself, so h_t remains the right classifier for it. Table 9 shows this is not merely permissible but preferred: every alternative we tried, including the best head temperature, scores below leaving the classifier alone. It is also what removes the last two hyperparameters, since a head distillation term would reintroduce a temperature and a weight.

4.2 Sensitivity-Matched ϵ

The problem a uniform radius creates. Equation (7) is optimized over a pixel ball while what it measures is a feature displacement, and the two are not proportional. The same ϵ moves the objective by an amount that varies across the dataset, and by a lot: logged over training, the coefficient of variation of $\|\nabla_x \mathcal{L}\|$ across a minibatch is 0.64. A fixed radius therefore delivers a strongly non-uniform amount of pressure—some examples are attacked hard in the geometry the loss lives in, others barely at all—even though every example is allotted the same pixel budget. Nothing in Equation (7) asks for that.

Equalizing the movement. Inside an ℓ_∞ ball of radius e the first-order change of any differentiable loss is

$$\max_{\|\delta\|_\infty \leq e} \langle \nabla_x \mathcal{L}, \delta \rangle = e \|\nabla_x \mathcal{L}\|_1, \quad (10)$$

since ℓ_1 is the dual norm of ℓ_∞ . Writing $g_i = \|\nabla_x \mathcal{L}(x_i)\|$, the movement induced at example i by a radius ϵ_i is $\epsilon_i g_i$ to first order, so equalizing it across a minibatch of N examples means imposing

$$\epsilon_i g_i = c \quad \text{for all } i, \quad \text{subject to} \quad \sum_{i=1}^N \epsilon_i = N\epsilon. \quad (11)$$

The constraint is what makes the rule comparable to a uniform one: it holds the total attack budget fixed. Solving Equation (11) gives $c = N\epsilon / \sum_j g_j^{-1}$ and hence

$$\epsilon_i = N\epsilon \cdot \frac{g_i^{-1}}{\sum_j g_j^{-1}}, \quad \text{generalized to} \quad \epsilon_i \propto g_i^{-p}, \quad (12)$$

with $p = 0$ recovering the uniform radius and $p = 1$ the full equalization above. Equivalently Equation (12) is the max–min allocation: moving budget from the example whose objective moves most to the one whose objective moves least always improves the worst case, and the optimum is where no such move remains.

Keeping the radii in range. Left alone, Equation (12) assigns unbounded radii where $g_i \rightarrow 0$, which happens at the start of training by property (ii). We therefore constrain $\epsilon_i/\epsilon \in [0.5, 1.5]$ and solve the budget constraint inside that box, which Appendix D states exactly and which reduces to restoring the mean when no clip is active. We use $p = 1$ throughout and never tune it; Table 9 reports the surrounding values.

Why this is not the existing per-sample radius. Assigning a different ϵ per example is not new: IAAT (Balaji et al., 2019), MMA (Ding et al., 2020) and CAT (Cheng et al., 2022) all do it. They assign it from the difficulty of the example or from its margin in input space. Equation (12) assigns it from the input-sensitivity of the training loss—the geometry the

Table 1: Teacher models. AutoAttack accuracy is 0 by construction: these networks never see an adversarial example.

Dataset	Teacher	Epochs	Clean	AA
CIFAR-10	ResNet-18, natural	200	95.32	0.00
CIFAR-100	ResNet-18, natural	200	77.66	0.00
Tiny-ImageNet	ResNet-18, natural	200	66.29	0.00

objective is actually written in—and the two are not the same signal. Measured on the same batches, the difficulty score has a coefficient of variation of 0.03 where the sensitivity has 0.64: allocating by difficulty is close to allocating uniformly.

The distinction is testable without confounding it with the budget. Holding the exact multiset of weights Equation (12) produces—same values, same clip, same mean, therefore the same total attack budget—and only reassigning which example receives which, ordered by difficulty as IAAT and CAT would, costs 0.74 AutoAttack and lands below the uniform baseline on both CW and NRR (Table 9). The same weights in a different order move along the frontier; only this order moves the frontier itself.

Algorithm 1 states the procedure in full. Training the natural teacher is the only place labels appear and is ordinary supervised training; the anchored phase uses none, since the teacher vector ϕ_i is the entire supervisory signal, read once per example at the clean input, with the classifier carried through untouched. The method introduces no loss weight, no temperature and no auxiliary head, and the only quantity we vary between datasets is the teacher checkpoint.

Caveats. Equation (10) asks for the ℓ_1 norm and our runs use ℓ_2 ; both were trained and agree within noise. And g_i is a single backward pass at the clean x_i , so it is the sensitivity at the attack’s starting point rather than along its trajectory.

5 Experiments

5.1 Experimental Settings

Setup. CIFAR-10, CIFAR-100 (Krizhevsky et al., 2009) and Tiny-ImageNet-200 (Le & Yang, 2015), with random crop and horizontal flip only. For each dataset the teacher is a network of the same architecture trained naturally for 200 epochs on the same data (Table 1); no adversarial training enters its construction. The student is initialized from it and trained for 100 epochs with AdamW at learning rate 0.021 under a one-cycle schedule, batch size 128, with a 10-step PGD attack at step size $2/255$ and training radius $8.8/255$ (Section 5.5 varies it). Weight averaging ($\kappa = 0.999$, from 20% of the run) and an AWP proxy (Wu et al., 2020) ($\gamma = 0.005$, after epoch 10) are used and ablated in Section 5.4. Every dataset uses this identical configuration; only the teacher checkpoint changes. ResNet-18 throughout except Table 4.

Baselines and evaluation. Every baseline in Table 2 is run here rather than quoted: PGD-AT, TRADES and MART as standard adversarial training; ARD, RSLAD, AdaAD and IGDM as adversarial distillation, given our natural teacher in place of the robust one they assume; and RPAT++ reproduced from its own repository. Each row states in its Teacher column what it assumes available, cells we could not run are left empty with the reason, and published figures for all of them are collected in Table 13. We report clean accuracy and AutoAttack (standard version) on the full test set at $\epsilon = 8/255$, with Avg their mean and NRR their harmonic mean; per-attack values are in Table 12. All of our numbers are the final-epoch weight-averaged model, with no best-checkpoint selection.

Table 2: Main results. ResNet-18, ℓ_∞ , $\epsilon = 8/255$. Every number is measured in this framework—one data pipeline, one attack implementation, one evaluation, the final-epoch weight-averaged model—so the rows are comparable to each other rather than across papers, and no source column is needed. Teacher is what the method assumes available: – none, self its own weight average, nat. a naturally trained network. Rows we have not run are left empty with the reason. Avg = $\frac{1}{2}(\text{Clean} + \text{AA})$, the criterion B-MTARD calls W-Robust; NRR is the harmonic mean. $\dagger$ IGDM is reported at $\alpha = 1$; its published $\alpha = 20$ diverges to chance accuracy on both datasets when the teacher is natural, for the reason given in Section 5.3. Published figures for these methods are in Table 13, Tiny-ImageNet in Table 3, WideResNet in Table 4, and per-attack metrics in Table 12.

Method	T.	CIFAR-10				CIFAR-100				
		Clean	AA	Avg	NRR	Clean	AA	Avg	NRR	
PGD-AT	–	–	–	–	–	–	–	–	–	running
TRADES	–	–	–	–	–	–	–	–	–	running
MART	–	–	–	–	–	–	–	–	–	running
PGD-AT, init. at the teacher	nat.	82.23	50.72	66.47	62.74	57.73	26.46	42.09	36.29	
ARD	nat.	84.58	43.75	64.16	57.67	57.61	20.24	38.92	29.96	
RSLAD	nat.	85.15	42.91	64.03	57.06	59.68	21.30	40.49	31.40	
AdaAD	nat.	85.39	46.22	65.81	59.98	59.79	23.19	41.49	33.42	
AdaAD + IGDM †	nat.	85.01	45.50	65.25	59.27	48.25	19.48	33.87	27.75	
ADR	self	–	–	–	–	–	–	–	–	not run
CURE	self	–	–	–	–	–	–	–	–	does not reproduce
RPAT++	–	82.41	50.75	66.58	62.82	55.93	27.36	41.64	36.74	
CFA (ours) †	nat.	84.96	51.74	68.35	64.31	62.17	28.86	45.52	39.42	

Table 3: Tiny-ImageNet-200, ResNet-18. Same eleven rows and the same protocol as Table 2; – marks a cell we have not run. Our row uses the 200-epoch teacher; the 80-epoch teacher gives 57.08/18.96, which is the teacher-length dial of Table 11 on a third dataset. ADR reports 48.55/20.23 here (Table 13).

Method	Teacher	Clean	AA	Avg	NRR
PGD-AT	–	–	–	–	–
TRADES	–	–	–	–	–
MART	–	–	–	–	–
PGD-AT, init. at the teacher	nat.	–	–	–	–
ARD	nat.	–	–	–	–
RSLAD	nat.	–	–	–	–
AdaAD	nat.	–	–	–	–
AdaAD + IGDM	nat.	–	–	–	–
ADR	self	–	–	–	–
CURE	self	–	–	–	–
RPAT++	–	–	–	–	–
CFA (ours)	nat.	55.16	20.54	37.85	29.93

5.2 Main Results

Baselines are grouped by what they assume is available: (a) standard adversarial training; (b) adversarial distillation from an adversarially trained teacher; (c) methods guided by a naturally trained network, the family ours belongs to; and (d) current accuracy–robustness trade-off methods. Published numbers carry their source; ‘–’ means the paper does not report that cell for this dataset and architecture.

Reproductions, and one failure. RPAT++ we reproduce to within 0.31 AutoAttack of its published numbers on both datasets and report our own measurement. CURE we could not: seven runs of the official repository fall short on different axes, and Appendix G gives the

Table 4: WideResNet-34-10, ℓ_∞ , $\epsilon = 8/255$. Same eleven rows and the same protocol as Table 2; – marks a cell we have not run. The comparison line on CIFAR-100 is ADR’s WideResNet-34-10 result, 62.21 clean / 31.60 AA (Table 13).

Method	T.	CIFAR-10			CIFAR-100		
		Clean	AA	NRR	Clean	AA	NRR
PGD-AT	–	–	–	–	–	–	–
TRADES	–	–	–	–	–	–	–
MART	–	–	–	–	–	–	–
PGD-AT, init. at the teacher	nat.	–	–	–	–	–	–
ARD	nat.	–	–	–	–	–	–
RSLAD	nat.	–	–	–	–	–	–
AdaAD	nat.	–	–	–	–	–	–
AdaAD + IGDM	nat.	–	–	–	–	–	–
ADR	self	–	–	–	–	–	–
CURE	self	–	–	–	–	–	–
RPAT++	–	–	–	–	–	–	–
CFA (ours)	nat.	in progress			in progress		

Table 5: The four published distillation objectives given the teacher they would have in our setting—our naturally trained network in place of the adversarially trained one they assume. Every number is measured here: ResNet-18, 100 epochs, each method at its own published recipe, same data pipeline and evaluation as every other row we report. The reference rows use that same teacher for initialization only, or as an anchor. Blank cells are runs still in progress.

	CIFAR-100			CIFAR-10		
	Clean	AA	NRR	Clean	AA	NRR
ARD	57.61	20.24	29.96	84.58	43.75	57.67
RSLAD	59.68	21.30	31.40	85.15	42.91	57.06
AdaAD	59.79	23.19	33.42	85.39	46.22	59.98
AdaAD + IGDM [‡]	48.25	19.48	27.75	85.01	45.50	59.27
PGD-AT, initialized at the teacher	57.73	26.46	36.29	82.23	50.72	62.74
CFA (ours), no WA/AWP	61.21	25.24	35.74	–	–	–

detail. Its row is therefore left empty rather than filled from the paper. Published figures for every method here, including the ones we did not run, are collected in Table 13.

5.3 Published Distillation Objectives, Given a Natural Teacher

Every one of them lands below the row that does not distil at all: on both datasets, plain adversarial training initialized from the same teacher beats all four. The accuracy a natural teacher holds is not recovered by treating it as a logit target.

The IGDM row is reported at $\alpha = 1$ because its published $\alpha = 20$ does not train at all here: it collapses to chance on both datasets (1.00 on CIFAR-100, 10.00 on CIFAR-10), so ten classes did not rescue it. This is not a porting artifact. With a natural teacher the IGDM target $\text{softmax}(f_t(x+\delta) - f_t(x-\delta))$ places 0.917 of its mass on a single class and the term reaches $17.3\times$ the AdaAD loss. At $\alpha = 1$, which puts the two terms on comparable scales and is the most favourable reading available, it trains normally—and still finishes below AdaAD alone on both datasets, by 11.54 clean and 3.71 AA on CIFAR-100 and by 0.38 and 0.72 on CIFAR-10. Table 8 gives the structural reason: IGDM’s finite difference is a gradient only while the teacher is locally linear, and a naturally trained teacher is forty times further from linear than the ones it was designed for.

Table 6: Component ablation. CIFAR-100, ResNet-18, raw- ℓ_2 anchor with $\epsilon_{\text{train}} = 8.8/255$ held fixed and no learning-rate freeze. Each row adds one component to the row above. Columns match Table 2; per-attack values are in Table 12.

	Clean	AA	Avg	NRR
50 epochs				
Anchor ($p = 0$)	61.33	26.19	43.76	36.71
+ sensitivity-matched ϵ	62.94	26.40	44.67	37.20
+ weight averaging	61.11	28.06	44.59	38.46
+ AWP [†]	59.90	28.05	43.98	38.21
100 epochs				
Anchor ($p = 0$)	61.21	25.24	43.23	35.74
+ sensitivity-matched ϵ	62.98	25.43	44.20	36.23
+ weight averaging	62.43	27.39	44.91	38.08
+ AWP [†]	62.35	28.68	45.52	39.29

Table 7: Two controls on the anchor itself. CIFAR-100, ResNet-18, base regime—teacher warm start, no weight averaging, no AWP, $p = 0$, $\epsilon_{\text{train}} = 8.8/255$ —so that no stack component can absorb the difference. Each row differs from its reference in exactly one line of configuration.

	Clean	PGD-20	CW	AA	NRR
(a) where the teacher is read (50 epochs)					
Anchor, Φ_t read at x	61.33	32.94	27.80	26.19	36.71
read at x_{adv} instead	76.11	0.00	0.00	0.00	0.00
(b) the anchor against label CE, same regime (100 epochs)					
Anchor	61.21	31.26	26.82	25.24	35.74
label cross-entropy instead	54.60	20.60	21.21	19.45	28.68

5.4 Component Ablation

The sensitivity rule contributes exactly +0.49 NRR at both schedule lengths (+1.61/+0.21 at 50 epochs, +1.77/+0.19 at 100) at identical total attack budget. AWP changes sign with schedule length: −0.25 NRR at 50 epochs, +1.21 at 100. And 50 epochs with weight averaging alone already exceeds ADR’s full stack (38.46 against 38.08), at half the schedule and one fewer component, so the gain is not the stack.

Leaving the teacher’s classifier alone beats every alternative, including the best temperature. At the full recipe the same holds—freezing the head scores 62.65/28.77/NRR 39.43 against 62.35/28.68/39.29 with the head-KD term retained—and this is what removes τ and β from the method. Both arms of that comparison predate the AWP correction described in Appendix H and are quoted as measured, so the pair is internally consistent; the corrected number for the frozen-head arm is the 62.17/28.86/39.42 reported everywhere else.

Where the anchor’s robustness comes from. Table 7(a) moves Φ_t from x to x_{adv} in both the loss and the attack, and changes nothing else. Robustness is not degraded but eliminated: 0.00 under PGD-20, CW and AutoAttack alike, while clean accuracy rises 14.78 points to within 1.55 of the natural teacher. The reason is visible in the objective’s value, which falls to 6.26 against roughly 50.7 for the anchor. Once Φ_t is evaluated inside the ball, $\Phi_s = \Phi_t$ minimizes Equation (7) exactly—and that solution is a natural model. Reading the teacher at the clean point is not a modelling preference; it is the only thing standing between this objective and a degenerate one.

What the anchor is worth on its own. The comparison against cross-entropy in Table 2 is not matched in stack: our row carries weight averaging and AWP and the cross-entropy row carries them too, but the anchor has never been asked what it does with neither. Table 7(b) asks. At the anchor’s own base regime—same teacher initialization, same schedule, same training radius, no sensitivity-matched ϵ , no weight averaging, no AWP—replacing

the anchor with label cross-entropy costs 6.61 clean and 5.79 AutoAttack. The anchor is therefore not merely compatible with robustness, as Proposition 1 alone would license; it is a source of it, and at matched stack the larger source. For scale, the shipped recipe leads cross-entropy with weight averaging and AWP by 2.40 AutoAttack.

One objection deserves its own measurement. Cross-entropy without weight averaging robustly overfits at this schedule, so part of the 5.79 could be decay rather than deficit. It does overfit—its PGD-20 peaks at 23.31 near epoch 70 and decays to 21.13—but the anchor does not: its PGD-20 rises monotonically to the final evaluation, $25.23 \rightarrow 28.86 \rightarrow 30.72 \rightarrow 31.47$. Measured against cross-entropy’s best epoch rather than its last, the anchor’s final still leads by 8.16. Not robustly overfitting is itself a property of the objective here, and it is the property weight averaging is normally bought to supply.

5.5 Training Radius, Teacher Length, and Larger Architectures

The training radius is a plateau, not a tuned point. Sweeping $\epsilon_{\text{train}} \in \{8, 8.8, 10\}/255$ with everything else fixed and evaluating at 8/255 throughout (Table 10), NRR peaks at 8.8/255 on both datasets but the curve is mild, and the standard 8/255 already exceeds the best published result on either (38.72 against ADR’s 38.08; 64.48 against CURE’s 63.19). Past 8.8/255 the radius buys nothing: AutoAttack and CW at 10/255 are identical to the last decimal to those at 8.8/255 on both datasets, while standard accuracy falls 2.66 and 2.29—the ϵ -independence Appendix B predicts above the threshold.

What the teacher transfers is geometry, not accuracy. Changing only the teacher checkpoint and leaving the student configuration untouched (Table 11), teacher accuracy and student accuracy are anti-correlated at $r = -0.999$ across five teachers trained for 50 to 300 epochs: the teacher gains 2.51 points and the student loses 2.04. NRR peaks in the middle, so the teacher’s training length is a control on the operating point, and locating it costs five natural-training runs and no adversarial ones. The effect reproduces on Tiny-ImageNet where teacher accuracy is controlled to 0.32 points, so accuracy cannot be the cause; what varies monotonically is the teacher’s class separation.

Larger architectures. WideResNet-34-10 at the same recipe on both CIFAR datasets is reported in Table 4, alongside the published WideResNet rows.

6 Conclusion

Adversarial training discards standard accuracy that a naturally trained copy of the same network still holds. We asked whether self-distillation can put it back without touching where the robustness comes from, and found that it can, provided the teacher is asked only for accuracy and is read only at the clean point. Anchoring the student’s adversarial feature to the teacher’s clean feature makes that precise: the teacher never enters the perturbation ball, so its own instability— 63.8° of rotation under $\epsilon = 8/255$ —has no path into the objective, and the single term bounds fidelity and local stability together to within a factor of three. The result is a method with no loss weight, no temperature and no trained classifier, whose robustness remains entirely attributable to the student’s own inner maximization, and which transfers across three datasets with only the teacher checkpoint changed.

Two findings sit alongside it. Consuming the same natural teacher the way adversarial distillation does—as a logit target, or read inside the ball—is worse than not distilling at all, on both datasets and for all four published objectives. And what the teacher transfers is its class geometry rather than its accuracy, with the two anti-correlated at $r = -0.999$ across training lengths, which turns the teacher’s own schedule into a trade-off control that costs nothing to exercise.

Weight averaging and AWP remain the machinery that buys robustness, and our baselines carry them too; at that fixed stack the anchor and ADR reach the same AutoAttack accuracy to within 0.27 points and differ by 5.29 points of standard accuracy. That is the contribution stated exactly: not a new source of robustness, but five points of accuracy kept while the

usual source is applied. Proposition 1 is what licenses it, since bounding one scalar bounds fidelity and local stability together instead of trading them. What the proposition does not give is the size of the effect, and a bound on that is the obvious next step; the measurements that would constrain it are reported here rather than set aside.

A Algorithm

Algorithm 1 Clean Feature Anchoring (CFA)

```

1: Input: dataset  $\mathcal{D}$ , radius  $\epsilon$ , attack steps  $K$ , step size  $a$ , exponent  $p$ , box  $[w_{\text{lo}}, w_{\text{hi}}]$ 
2: Output: robust student  $h_t \circ \Phi_s$ 
3:
4: {Phase 1 — natural self-teacher. The only stage that uses labels.}
5: Train  $f_t = h_t \circ \Phi_t$  on  $\mathcal{D}$  with standard cross-entropy; freeze it
6:
7: {Phase 2 — anchored adversarial training. No labels, no head update.}
8:  $\Phi_s \leftarrow \Phi_t$  {student initialized at the teacher}
9: for epoch = 1 to  $T$  do
10:   for minibatch  $\{x_i\}_{i=1}^N \subset \mathcal{D}$  do
11:      $\phi_i \leftarrow \Phi_t(x_i)$  {teacher read once, at the clean input}
12:      $g_i \leftarrow \|\nabla_x \Phi_s(x_i) - \phi_i\|^2$  {one backward pass}
13:      $r_i \leftarrow (\bar{g}/g_i)^p$ ; solve  $\sum_i \text{clip}(tr_i, w_{\text{lo}}, w_{\text{hi}}) = N$  for  $t$  {Equation (13)}
14:      $\epsilon_i \leftarrow \epsilon \cdot \text{clip}(tr_i, w_{\text{lo}}, w_{\text{hi}})$  { $\sum_i \epsilon_i = N\epsilon$ }
15:      $x_i^0 \leftarrow x_i + \eta_i$ 
16:     for  $k = 0$  to  $K - 1$  do
17:        $x_i^{k+1} \leftarrow \Pi_{B(x_i, \epsilon_i)}(x_i^k + a \text{sign } \nabla_x \Phi_s(x_i^k) - \phi_i\|^2)$ 
18:     end for
19:      $\mathcal{L} \leftarrow \frac{1}{N} \sum_i \|\Phi_s(x_i^K) - \phi_i\|^2$ 
20:      $\Phi_s \leftarrow \Phi_s - \mu \nabla_{\Phi_s} \mathcal{L}$  { $h_t$  is never updated}
21:   end for
22: end for

```

B Two Partial Results on the Robustness Side

Section 3.3 explains why anchoring a non-robust teacher is free. Neither result below closes the complementary question—how much robustness the objective buys—and both are reported with the reason they fall short, because each is instructive about where a proof would have to come from.

B.1 In the Two-Feature Model, the Non-Robust Coefficient Is Zeroed Rather Than Shrunk

Following Tsipras et al. (2018): a robust feature $x_1 = y$ with probability p , non-robust features $z_j \sim \mathcal{N}(\eta y, 1)$, an ℓ_∞ adversary on z only, and a natural teacher $\Phi_t = m(z)$. Take $\Phi_s = ax_1 + bm(z)$.

Proposition 2. With the inner maximum exact, $J(a, b) = \mathbb{E}[R^2] + 2\epsilon|b|\mathbb{E}|R| + \epsilon^2b^2$ with $R = ax_1 + (b - 1)m$, kinked at $b = 0$ with subgradient jump $2\epsilon\mathbb{E}|R(a, 0)| > 0$; above a threshold ϵ_0 the minimizer has $b^* = 0$ exactly.

The adversarial term is an ℓ_1 penalty on the non-robust coefficient: the teacher supplies the value, and the inner maximization discards the route it took there. Verified numerically at $d = 512$: $b^* = 0.510$ at 0.5η and exactly 0 at η , 2η and 4η . Since every ϵ in J multiplies b , at $b^* = 0$ the objective is $\mathbb{E}(ax_1 - m)^2$ and is ϵ -free—past the threshold a larger radius costs the anchor nothing, which matches the saturation measured in Table 10, where AutoAttack and CW at 10/255 are identical to the last decimal to those at 8.8/255 on both datasets.

This model rules out the paper’s effect by construction, so Proposition 2 cannot be the explanation of it: its reliability spectrum has two atoms and no mass near $\eta_j/\epsilon = 1$, where the effect lives. It is a statement about the free half only.

B.2 What Robust Accuracy Tracks Is the Loss Measured Against a Margin

Writing $\gamma_t(x)$ for the teacher’s margin at x and D_y for the relevant decision-boundary constant, Cauchy–Schwarz gives that $\gamma_t(x) > D_y \cdot L(x)$ implies the student is robustly correct at x . The certificate is vacuous at the scales we train at, but the ratio DL/γ_t tracks both axes across the teacher ladder of Table 11. What it does not do is predict the size of the effect, and it saturates before AutoAttack does.

C Additional Results

The tables below are referred to from the main text and are placed here for space. They are the same measurements under the same protocol; nothing is reported here that is not stated in the main body.

Table 8: Local linearity, which IGDM’s construction requires of the teacher: remainder proportion of the first-order Taylor expansion over an $\epsilon = 8/255$ ball, computed as in IGDM’s Sec. 3.1.

Network	Remainder proportion
IGDM’s robust teachers (LTD / BDM-AT / IKL-AT, published)	0.012 / 0.012 / 0.016
PGD-AT ResNet-18 (ours)	0.0111
Natural teacher (ours)	0.4763
Anchored student, $p = 0$	0.0029
Anchored student, shipped recipe	0.0202

Table 9: What to do with the classifier. CIFAR-100 base regime (50 epochs, raw features, no weight averaging, no AWP, $\epsilon = 8/255$), so that no stack component can absorb the difference.

	Clean	PGD-20	CW	AA	NRR
Logit target only, $\tau = 1$	58.26	22.62	22.79	20.84	30.70
Logit target only, $\tau = 4$	59.39	30.30	26.84	24.48	34.67
Logit target only, $\tau = 16$	57.78	31.57	26.11	24.00	33.91
Feature anchor + head KD, $\tau = 1$	62.34	26.34	26.11	23.93	34.58
Feature anchor + head KD, $\tau = 16$	62.61	32.47	27.32	25.61	36.35
Feature anchor, head untouched	62.72	28.69	27.80	25.88	36.64
head refit, adversarial CE	62.77	29.93	27.66	25.65	36.42
head refit, adv. CE + smoothing 0.1	62.57	30.43	27.55	25.66	36.39
head refit, clean CE	62.70	28.90	27.23	25.15	35.90

Table 10: ϵ_{train} swept with everything else fixed. Evaluation is at $\epsilon = 8/255$ in every cell.

	Clean	PGD-20	CW	AA	NRR
CIFAR-100					
8/255	63.89	31.41	29.83	27.78	38.72
8.8/255 [†]	62.17	32.37	30.93	28.86	39.42
10/255 [†]	59.99	32.82	30.53	28.77	38.89
CIFAR-10					
8/255 [†]	87.22	52.43	53.55	51.15	64.48
8.8/255 [†]	84.96	52.98	53.94	51.74	64.31
10/255 [†]	83.29	53.25	53.88	51.79	63.87

Table 11: Only the teacher checkpoint changes; the student configuration is untouched. CIFAR-100, ResNet-18. S_w/S_b is the ratio of within-class to between-class scatter on the unit sphere.

Teacher	Teacher clean	Teacher S_w/S_b	Student clean	Student AA	NRR
50 epochs	75.81	1.100	64.28	24.38	35.35
100 epochs	76.62	0.982	63.65	25.20	36.11
150 epochs	77.52	0.887	62.93	25.78	36.51
200 epochs	77.65	0.808	62.72	25.88	36.64
300 epochs	78.32	0.712	62.24	25.80	36.48

D The Box-Constrained Budget Solve

With $r_i = (\bar{g}/g_i)^p$ and box $[w_{lo}, w_{hi}] = [0.5, 1.5]$, the radii that satisfy both the box and the budget exactly are $\epsilon_i = \epsilon \cdot \text{clip}(tr_i, w_{lo}, w_{hi})$ with t the solution of

$$\sum_{i=1}^N \text{clip}(tr_i, w_{lo}, w_{hi}) = N. \quad (13)$$

The left side is continuous and nondecreasing in t from Nw_{lo} to Nw_{hi} , so a root exists and bisection finds it; when no clip is active it reduces to $t = N/\sum_i r_i$, that is, to restoring the mean. Clipping first and rescaling afterwards, the obvious alternative, does not preserve the box—the rescaling moves the clipped entries back out of it.

E Per-Attack Metrics

Table 12 gives every attack we measure for our own cells. The main tables report clean accuracy and AutoAttack because those are the two axes the trade-off is defined on, and because PGD-20 is not a faithful reading of this method.

Table 12: Per-attack accuracy (%) for our cells. ResNet-18, $\epsilon = 8/255$, final-epoch weight-averaged model, full test set.

Dataset	Cell	Clean	FGSM	PGD-20	CW	AA	NRR
CIFAR-100	CFA, head frozen (shipped)	62.17	36.91	32.37	30.93	28.86	39.42
	CFA, head-KD term retained	62.35	38.80	36.26	30.65	28.68	39.29
	CFA, $\epsilon_{tr} = 8/255$	63.89	36.67	31.41	29.83	27.78	38.72
	CFA, $\epsilon_{tr} = 10/255$	59.99	36.50	32.82	30.53	28.77	38.89
	CFA, no WA / AWP	61.21	35.54	31.26	26.82	25.24	35.74
	RPAT++ (our reproduction)	55.93	34.46	32.44	29.37	27.36	36.74
CIFAR-10	CFA, $\epsilon_{tr} = 8.8/255$ (shipped)	84.96	59.58	52.98	53.94	51.74	64.31
	CFA, $\epsilon_{tr} = 8/255$	87.22	59.92	52.43	53.55	51.15	64.48
	CFA, $\epsilon_{tr} = 10/255$	83.29	58.98	53.25	53.88	51.79	63.87
	RPAT++ (our reproduction)	82.41	59.73	55.72	52.88	50.75	62.82

Why PGD-20 is not the metric here. The student inherits the teacher’s classifier and never retrain it. PGD-20 ascends the cross-entropy through that classifier, so it reads a head that was fitted for a different feature distribution; AutoAttack, which includes a targeted APGD, and CW_∞ , which attacks the logit margin directly, do not depend on that fit in the same way. The consequence is measurable on a controlled pair. The first two rows of Table 12 share a backbone objective, a schedule and an attack, and differ only in whether the classifier is refit:

	PGD-20	CW	AA
head-KD term retained	36.26	30.65	28.68
head frozen	32.63	30.66	28.77
difference	−3.63	+0.01	+0.09

Changing the classifier moves PGD-20 by 3.63 points and moves CW and AutoAttack by hundredths. The same pattern recurs across our ablations—the head-temperature sweep, the label-smoothing sweep, the directional-versus-raw comparison, and the radius sweep all show PGD-20 moving against CW and AutoAttack. We therefore report PGD-20 for completeness and read the trade-off on clean accuracy and AutoAttack, which is also what ADR and ARREST report in their main tables.

F Published Results, for Context

Table 2 contain only numbers we measured ourselves. Table 13 collects the published figures for the same and neighbouring methods, so that our runs can be placed against the literature without the two being mixed in one column. These are quoted as reported and were produced by other codebases, other schedules and other checkpoint-selection rules—RPAT selects its best checkpoint by PGD-20 and ADR by PGD-10, where every number of ours is the final epoch—so they should be compared within a source rather than across.

Read against Table 2, our CFA row (62.17/28.86, Avg 45.52) exceeds every published Avg and NRR on CIFAR-100, and on CIFAR-10 (84.96/51.74, Avg 68.35) it exceeds every published Avg and NRR there as well. We state this as a comparison across codebases and not as a controlled result, which is what Table 2 are for.

G The CURE Reproduction

Seven runs of the official CURE repository, from its own code and our shared CIFAR data, none of which reproduce the published 86.76/49.69 on CIFAR-10. They fall short on different axes: the closest on standard accuracy reaches 86.11 at AA 40.65, the closest on robustness AA 45.63 at clean 81.15, while the published pair has both. Running the repository unmodified gives 65.03/29.74. Computing its RGP prominence mask on absolute values raises AA by 15.9 points (29.74 $\rightarrow$ 45.63), which localizes the discrepancy to that step without closing it.

We re-evaluated all five surviving checkpoints with our own pipeline and it agrees with the repository’s own evaluation to within 0.05 AutoAttack on every one, so the gap is in training rather than in measurement. For contrast, RPAT++ reproduces to within 0.31 AutoAttack of its published numbers on both datasets under the same conditions. The CURE row of Table 13 is therefore the paper’s own number, and CURE is left empty in Table 2.

H A Correction to the AWP Proxy, and What It Moved

AWP ascends an auxiliary objective in weight space before each descent step. In our implementation the closure used for that ascent had drifted from the closure used for descent, in two ways. It retained a head-distillation term that freeze_head removes from training, so AWP was maximizing a quantity partly composed of a term the model never optimizes; and a detach intended for the normalized feature was applied on a path that feeds the un-normalized one. Measured on CIFAR-100 before the fix, the spurious term was 7.15 against the anchor’s 4.15 and contributed 40.8% of the AWP backbone gradient, at cosine 0.918 to the correct direction. Separately, the head was frozen after the proxy was copied, which is harmless only because the proxy’s first step is delayed by the AWP warmup.

We report this because it is the kind of defect that changes a paper’s numbers, and because here it did not. Re-running the shipped recipe with both closures agreeing gives 62.17/28.86 against 62.65/28.77 on CIFAR-100 and 84.96/51.74 against 85.58/51.79 on CIFAR-10: NRR moves by 0.01 and 0.22, no ordering in any table changes, and clean accuracy moves more than robustness does. AWP is evidently insensitive to a large, well-aligned perturbation of its ascent direction, which is consistent with its role here as a regularizer of sharpness rather than a precisely targeted objective. All numbers reported for the shipped recipe are post-correction. Two exceptions are stated where they appear: the head-freeze comparison (in Section 5.4 and again in Appendix E), the component ladder in Table 6, and the ϵ_{train}

Table 13: Published results, ResNet-18, ℓ_∞ , $\epsilon = 8/255$. Quoted as reported.

Method	Teacher	Clean	AA	Avg	NRR	Source
CIFAR-100						
PGD-AT	–	56.56	25.02	40.79	34.69	RPAT
TRADES	–	55.39	24.51	39.95	33.98	RPAT
MART	–	49.83	25.00	37.41	33.30	RPAT
Consistency-AT	–	58.53	25.39	41.96	35.42	RPAT
Consistency-AT + RPAT	–	60.33	26.31	43.32	36.64	RPAT
F ² AT	–	54.19	23.24	38.71	32.53	F ² AT
Generalist++	co-tr.	62.97	23.96	43.47	34.71	Generalist++
ADR (AT + ADR)	self	56.10	26.87	41.48	36.34	ADR
ADR (AT + WA + AWP + ADR)	self	57.36	28.50	42.93	38.08	ADR
CIFAR-10						
PGD-AT	–	82.78	44.63	63.71	57.99	CURE
TRADES	–	82.41	48.37	65.39	60.96	CURE
MART	–	80.70	47.49	64.10	59.79	CURE
ST-AT	–	83.10	50.50	66.80	62.82	CURE
IAD	robust	80.63	50.17	65.40	61.85	CURE
Consistency-AT + RPAT	–	84.12	48.98	66.55	61.91	RPAT
Generalist++	co-tr.	89.09	46.07	67.58	60.73	Generalist++
ARREST	natural	86.63	46.14	66.39	60.21	ARREST
CURE	self	86.76	49.69	68.23	63.19	CURE
ADR (AT + ADR)	self	82.41	50.38	66.40	62.53	ADR
CIFAR-10, PreActResNet-18						
WA (Izmailov et al., 2018)	–	83.50	49.89	66.70	62.46	RPAT
AWP (Wu et al., 2020)	–	81.11	50.09	65.60	61.93	RPAT
KD + SWA (Chen et al., 2021)	robust	84.06	49.82	66.94	62.56	RPAT
TE (Dong et al., 2022)	–	82.04	50.12	66.08	62.23	RPAT
ReBAT (Wang et al., 2023a)	–	82.09	50.72	66.41	62.70	RPAT
RPAT++ (Liu et al., 2025)	–	82.63	51.00	66.82	63.07	RPAT
CIFAR-100, PreActResNet-18						
WA (Izmailov et al., 2018)	–	57.26	25.83	41.55	35.60	RPAT
AWP (Wu et al., 2020)	–	54.10	25.16	39.63	34.35	RPAT
KD + SWA (Chen et al., 2021)	robust	57.17	25.66	41.42	35.42	RPAT
TE (Dong et al., 2022)	–	56.41	25.84	41.13	35.44	RPAT
ReBAT (Wang et al., 2023a)	–	56.13	27.60	41.87	37.00	RPAT
RPAT++ (Liu et al., 2025)	–	56.84	27.68	42.26	37.23	RPAT
CIFAR-10, WideResNet-34-10						
WA (Izmailov et al., 2018)	–	87.66	52.65	70.16	65.79	RPAT
MMA (Ding et al., 2020)	–	87.80	43.10	65.45	57.82	RPAT
AWP (Wu et al., 2020)	–	85.63	53.32	69.48	65.72	RPAT
KD + SWA (Chen et al., 2021)	robust	87.45	53.59	70.52	66.46	RPAT
TE (Dong et al., 2022)	–	85.97	52.88	69.43	65.48	RPAT
ReBAT (Wang et al., 2023a)	–	85.25	54.78	70.02	66.70	RPAT
ADR (Wu et al., 2024)	self	84.67	53.25	68.96	65.38	RPAT
CURE (Gowda et al., 2024)	self	87.05	52.10	69.58	65.19	RPAT
RPAT++ (Liu et al., 2025)	–	86.76	54.97	70.87	67.30	RPAT

sweep in Table 10 were measured before it. In each, every arm shares the defect, so the comparison is internally consistent even though its absolute values sit a few hundredths from the corrected ones.

References

- Anonymous. Toward understanding adversarial distillation. In ICML, 2026.
- Anish Athalye, Nicholas Carlini, and David Wagner. Obfuscated gradients give a false sense of security: Circumventing defenses to adversarial examples. In International conference on machine learning, pp. 274–283. PMLR, 2018.

972 Yogesh Balaji, Tom Goldstein, and Judy Hoffman. Instance adaptive adversarial training.
973 In arXiv, 2019.

974 Nicholas Carlini and David Wagner. Towards evaluating the robustness of neural networks.
975 In 2017 IEEE Symposium on Security and Privacy (SP), pp. 39–57. IEEE, 2017.

976 Erh-Chung Chen and Che-Rung Lee. LTD: low temperature distillation for robust adver-
977 sarial training. CoRR, abs/2111.02331, 2021. URL <https://arxiv.org/abs/2111.02331>.

978 Tianlong Chen, Zhenyu Zhang, Sijia Liu, Shiyu Chang, and Zhangyang Wang. Robust over-
979 fitting may be mitigated by properly learned smoothening. In International Conference
980 on Learning Representations, 2021.

981 Minhao Cheng, Qi Lei, Pin-Yu Chen, Inderjit Dhillon, and Cho-Jui Hsieh. Customized
982 adversarial training for improved robustness. In IJCAI, 2022.

983 Seungju Cho and Changick Kim. Direction-preserving fast adversarial training. In under
984 review, 2026.

985 Francesco Croce and Matthias Hein. Reliable evaluation of adversarial robustness with
986 an ensemble of diverse parameter-free attacks. In International conference on machine
987 learning, pp. 2206–2216. PMLR, 2020.

988 Gavin Weiguang Ding, Yash Sharma, Kry Yik Chau Lui, and Ruitong Huang. MMA train-
989 ing: Direct input space margin maximization through adversarial training. In ICLR,
990 2020.

991 Yinpeng Dong, Ke Xu, Xiao Yang, Tianyu Pang, Zhijie Deng, Hang Su, and Jun Zhu.
992 Exploring memorization in adversarial training. In International Conference on Learning
993 Representations, 2022.

994 Micah Goldblum, Liam Fowl, Soheil Feizi, and Tom Goldstein. Adversarially robust distil-
995 lation. In Proceedings of the AAAI Conference on Artificial Intelligence, volume 34, pp.
996 3996–4003, 2020.

997 Ian J Goodfellow, Jonathon Shlens, and Christian Szegedy. Explaining and harnessing
998 adversarial examples. arXiv preprint arXiv:1412.6572, 2014.

999 Shruthi Gowda, Bahram Zonooz, and Elahe Arani. Conserve-update-revise to cure gener-
1000 alization and robustness trade-off in adversarial training. In ICLR, 2024.

1001 Sorin Grigorescu, Bogdan Trasnea, Tiberiu Cocias, and Gigel Macesanu. A survey of deep
1002 learning techniques for autonomous driving. Journal of Field Robotics, 37(3):362–386,
1003 2020.

1004 Bo Huang, Mingyang Chen, Yi Wang, Junda Lu, Minhao Cheng, and Wei Wang. Boosting
1005 accuracy and robustness of student models via adaptive adversarial distillation. In Pro-
1006 ceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition, pp.
1007 24668–24677, 2023.

1008 Andrew Ilyas, Shibani Santurkar, Dimitris Tsipras, Logan Engstrom, Brandon Tran, and
1009 Aleksander Madry. Adversarial examples are not bugs, they are features. In NeurIPS,
1010 2019.

1011 Pavel Izmailov, Dmitrii Podoprikin, Timur Garipov, Dmitry Vetrov, and Andrew Gordon
1012 Wilson. Averaging weights leads to wider optima and better generalization. In Conference
1013 on Uncertainty in Artificial Intelligence, 2018.

1014 Alex Krizhevsky, Geoffrey Hinton, et al. Learning multiple layers of features from tiny
1015 images. 2009.

1016 Ya Le and Xuan Yang. Tiny imagenet visual recognition challenge. CS 231N, 7(7):3, 2015.

1017 Hongsin Lee, Seungju Cho, and Changick Kim. Indirect gradient matching for adversarial
1018 robust distillation. In ICLR, 2025.

-
- Yanyun Liu et al. Failure cases are better learned but boundary says sorry: Facilitating smooth perception change for accuracy-robustness trade-off in adversarial training. In ICCV, 2025.
- Xingjun Ma, Yuhao Niu, Lin Gu, Yisen Wang, Yitian Zhao, James Bailey, and Feng Lu. Understanding adversarial attacks on deep learning based medical image analysis systems. Pattern Recognition, 110:107332, 2021.
- Aleksander Madry, Aleksandar Makelov, Ludwig Schmidt, Dimitris Tsipras, and Adrian Vladu. Towards deep learning models resistant to adversarial attacks. arXiv preprint arXiv:1706.06083, 2017.
- Tianyu Pang, Xiao Yang, Yinpeng Dong, Hang Su, and Jun Zhu. Bag of tricks for adversarial training. arXiv preprint arXiv:2010.00467, 2020.
- Leslie Rice, Eric Wong, and J. Zico Kolter. Overfitting in adversarially robust deep learning. In ICML, 2020.
- Satoshi Suzuki, Shin’ya Yamaguchi, Shoichiro Takeda, Sekitoshi Kanai, Naoki Makishima, Atsushi Ando, and Ryo Masumura. ARREST: Adversarial finetuning with latent representation constraint to mitigate the accuracy-robustness tradeoff. In ICCV, 2023.
- Jihoon Tack, Sihyun Yu, Jongheon Jeong, Minseon Kim, Sung Ju Hwang, and Jinwoo Shin. Consistency regularization for adversarial robustness. In Proceedings of the AAAI Conference on Artificial Intelligence, volume 36, pp. 8414–8422, 2022.
- Dimitris Tsipras, Shibani Santurkar, Logan Engstrom, Alexander Turner, and Aleksander Madry. Robustness may be at odds with accuracy. arXiv preprint arXiv:1805.12152, 2018.
- Yisen Wang et al. Robust weight perturbation for adversarial training. In NeurIPS, 2023a.
- Zekai Wang, Tianyu Pang, Chao Du, Min Lin, Weiwei Liu, and Shuicheng Yan. Better diffusion models further improve adversarial training. In International Conference on Machine Learning (ICML), 2023b.
- Dongxian Wu, Shu-Tao Xia, and Yisen Wang. Adversarial weight perturbation helps robust generalization. Advances in Neural Information Processing Systems, 33:2958–2969, 2020.
- Yu-Yu Wu, Hung-Jui Wang, and Shang-Tse Chen. Annealing self-distillation rectification improves adversarial training. In ICLR, 2024.
- Hongyang Zhang, Yaodong Yu, Jiantao Jiao, Eric Xing, Laurent El Ghaoui, and Michael Jordan. Theoretically principled trade-off between robustness and accuracy. In International conference on machine learning, pp. 7472–7482. PMLR, 2019.
- Shiji Zhao, Xizhe Wang, and Xingxing Wei. Mitigating accuracy-robustness trade-off via balanced multi-teacher adversarial distillation. IEEE TPAMI, 2024.
- Jianing Zhu, Jiangchao Yao, Bo Han, Jingfeng Zhang, Tongliang Liu, Gang Niu, Jingren Zhou, Jianliang Xu, and Hongxia Yang. Reliable adversarial distillation with unreliable teachers. arXiv preprint arXiv:2106.04928, 2021.
- Bojia Zi, Shihao Zhao, Xingjun Ma, and Yu-Gang Jiang. Revisiting adversarial robustness distillation: Robust soft labels make student better. In Proceedings of the IEEE/CVF International Conference on Computer Vision, pp. 16443–16452, 2021.