

DS-K1T673DX

HIKVISION



Features

- Hikvision
- Autonomous biometric reader for access and presence control
- Identification by MF DESFire card, facial recognition, password and/or combinations
- 7" IPS colour touch screen
- Capacity 10.000 faces, 50.000 cards, 10.000 fingerprints (with fingerprint module) and 150.000 records
- TCP/IP, RS485 and Wiegand communication
- Integrated controller (door sensor, push button and relay)
- Dual-sensor camera for anti-spoofing technology
- Remote openings from Hik-Connect
- Compatible with software iVMS-4200
- Suitable for exterior IP65

Specifications

Brand	Hikvision
Model	DS-K1T673DX
Operating system	Linux
Capacity	Up to 10.000 faces, 10.000 fingerprints (with fingerprint module) and 50.000 cards/passwords
Records	150.000 registers
Identification modes	Facial recognition, RFID card, PIN and/or combinations Identification of up to 5 people at once through face recognition
Proximity card	MF DESFire (13.56 MHz)
Screen	7" IPS color touch screen LCD
Camera	2 Mpx with dual sensor for face recognition
Facial recognition verification time	< 0.2 sec
Facial recognition accuracy	> 99%
Facial recognition distance	0.3 m to 3 m
Communication	TCP/IP, RS485 and Wiegand
Integrated controller	Wiegand 26/34, door sensor, pushbutton and relay
Alarms	Tamper, 1 x alarm input, 1 x alarm output
Audio	Bidirectional audio Audio output 3.5 mm
Special functions	Operation as a video door entry system USB input for peripheral module connection
Software	iVMS-4200 / iVMS-4200 AC
Mobile application	Hik-Connect
Power	DC 12-24 V / 2 A max.
Degree of protection	Suitable for exterior IP65
Temp. operation	-30° C ~ +60° C
Dimensions	110.5 (W) x 209.2 (H) x 24 (D) mm
Weight	570 g