

# Competition on **Permutation-based Combinatorial Optimization Problems**

Leticia Hernando, **Josu Ceberio**, Alexander Mendiburu, Jose A. Lozano

Intelligent Systems Group  
Department of Computer Science and Artificial Intelligence  
University of the Basque Country UPV/EHU



Genetic and Evolutionary Algorithms Conference (GECCO 2014)  
Vancouver, BC, Canada, 12-16 July 2014

# The Aim

To obtain an overview of the performance of heuristic and metaheuristic algorithms on permutation problems

# Submissions

- **Submission 1.** Mirah Alves and Romario Rogerio. *Greedy Randomized Adaptive Search Procedure (GRASP)*.
- **Submission 2.** Mikel Artetxe. *A Randomized Tabu Search-based Memetic Algorithm for permutation-based combinatorial optimization problems*.

# Submissions

- **Submission 1.** Mirah Alves and Romario Rogerio. *Greedy Randomized Adaptive Search Procedure (GRASP)*.
- **Submission 2.** Mikel Artetxe. *A Randomized Tabu Search-based Memetic Algorithm for permutation-based combinatorial optimization problems*.


*Due to a lack of proposals we could not carry out the competition.*

*In the future, we will consider focusing on a particular problem, and provide more time to develop competitive proposals.*



city100.txt: -4039.860428

psychicorigami.com



TSP, QAP, PFSP, LOP, API

# Permutation-based Problems



# What are they?

- Specific subset of combinatorial optimization problems.

# What are they?

- Specific subset of combinatorial optimization problems.
- Coded naturally as permutations.

# What are they?

- Specific subset of combinatorial optimization problems.
- Coded naturally as permutations.
- Do not belong to the discrete and continuous domain problems.



# The Problems

- Travelling Salesman Problem (TSP).
- Quadratic Assignment Problem (QAP).
- Linear Ordering Problem (LOP).
- Permutation Flowshop Scheduling Problem (PFSP).

# The Problems

- Travelling Salesman Problem (TSP).
- Quadratic Assignment Problem (QAP).
- Linear Ordering Problem (LOP).
- Permutation Flowshop Scheduling Problem (PFSP).
- Artificial Permutation Instances

L. Hernando, A. Mendiburu and J. A. Lozano, *A Tunable Generator of Instances of Permutation-based Combinatorial Optimization Problems*, 2014.



# Artificial Permutation Instances

## Aim:

- To generate instances with specific complexities
- To evaluate and compare algorithms in different scenarios



# Artificial Permutation Instances

## Aim:

- To generate instances with specific complexities
- To evaluate and compare algorithms in different scenarios

## Inspiration:

- The landscape generator for continuous domains of *Gallagher et al.*
- Instead of using the *Gaussian* distribution, the *Mallows model* for permutation domains is used.



# The Mallows model

$$P(\pi|\sigma, \theta) = \frac{1}{\psi(\theta)} e^{-\theta d(\pi, \sigma)}$$



# The Mallows model

$$P(\pi|\sigma, \theta) = \frac{1}{\psi(\theta)} e^{-\theta d(\pi, \sigma)}$$

$\sigma$  → Central permutation



# The Mallows model

$$P(\pi|\sigma, \theta) = \frac{1}{\psi(\theta)} e^{-\theta d(\pi, \sigma)}$$

$\sigma$  → Central permutation

$\theta$  → Spread parameter



# The Mallows model

$$P(\pi|\sigma, \theta) = \frac{1}{\psi(\theta)} e^{-\theta d(\pi, \sigma)}$$

$\sigma$  → Central permutation       $d(\pi, \sigma)$  → Distance metric

$\theta$  → Spread parameter





# The Mallows model

$$P(\pi|\sigma, \theta) = \frac{1}{\psi(\theta)} e^{-\theta d(\pi, \sigma)}$$

$\sigma$  → Central permutation


$d(\pi, \sigma)$  → Distance metric

$\theta$  → Spread parameter

$\psi(\theta)$  → Normalization function



# The Mallows model



# Instance Generator

- Choose  $m$  central permutations  $\rightarrow \sigma_1, \sigma_2, \dots, \sigma_m$



# Instance Generator

- Choose  $m$  central permutations  $\rightarrow \sigma_1, \sigma_2, \dots, \sigma_m$
- Choose  $m$  spread parameters  $\rightarrow \theta_1, \theta_2, \dots, \theta_m$



# Instance Generator

- Choose  $m$  central permutations  $\rightarrow \sigma_1, \sigma_2, \dots, \sigma_m$
- Choose  $m$  spread parameters  $\rightarrow \theta_1, \theta_2, \dots, \theta_m$
- Choose  $m$  weights  $\rightarrow \omega_1, \omega_2, \dots, \omega_m$



# Instance Generator

- Choose  $m$  central permutations  $\rightarrow \sigma_1, \sigma_2, \dots, \sigma_m$
- Choose  $m$  spread parameters  $\rightarrow \theta_1, \theta_2, \dots, \theta_m$
- Choose  $m$  weights  $\rightarrow \omega_1, \omega_2, \dots, \omega_m$
- The fitness value of each permutation  $\pi$  is calculated as:

$$f(\pi) = \max_i \{ \omega_i P_i(\pi | \sigma_i, \theta_i) \}$$



# Particularities

By tuning the parameters, **different shapes** of landscapes can be generated.

- Fix the **number of local optima** (Mallows models)
- Define the size of the **attraction basins** of the local optima by tuning the spread parameters and the **weights**.



# Competition on **Permutation-based Combinatorial Optimization Problems**

Thank you for your attention !!

Comments, suggestions, questions...  
[competition.gecco2014@ehu.es](mailto:competition.gecco2014@ehu.es)

Or  
contact with me!

