

GADTs Meet Their Match:

Pattern-Matching Warnings That Account for GADTs, Guards, and Laziness

SEBASTIAN GRAF, Karlsruhe Institute of Technology, Germany

SIMON PEYTON JONES, Microsoft Research, UK

Authors' addresses: Sebastian Graf, Karlsruhe Institute of Technology, Karlsruhe, Germany, sebastian.graf@kit.edu; Simon Peyton Jones, Microsoft Research, Cambridge, UK, simonpj@microsoft.com.

Guard Syntax

$K \in$	Con	$n \in$	\mathbb{N}
$x, y, a, b \in$	Var	$\gamma \in$	TyCt $::= \tau_1 \sim \tau_2 \mid \dots$
$\tau, \sigma \in$	Type	$g \in$	Grd $::= \text{let } x : \tau = e$
$e \in$	Expr		$\mid K \bar{a} \bar{\gamma} \bar{y} : \bar{\tau} \leftarrow x$
			$\mid !x$
			$\mid \dots$

Constraint Formula Syntax

$\Gamma ::= \emptyset \mid \Gamma, x : \tau \mid \Gamma, a$	Context
$\delta ::= \checkmark \mid \times \mid K \bar{a} \bar{\gamma} \bar{y} : \bar{\tau} \leftarrow x \mid x \not\approx K \mid x \approx \perp \mid x \not\approx \perp \mid x \approx e$	Constraint Literals
$\Delta ::= \delta \mid \Delta \wedge \Delta \mid \Delta \vee \Delta$	Formula

Clause Tree Syntax

$t_G, u_G \in \text{Gdt} ::= \text{Rhs} \mid t_G; u_G \mid \text{Guard } g \ t_G$	
$t_A, u_A \in \text{Ant} ::= \text{AccessibleRhs} \mid \text{InaccessibleRhs} \mid t_A; u_A \mid \text{MayDiverge } t_A$	

Checking Guard Trees

$$\mathcal{U}(\Delta, \text{Gdt}) = \Delta$$

$\mathcal{U}(\Delta, \text{Rhs})$	$= \times$
$\mathcal{U}(\Delta, (t; u))$	$= \mathcal{U}(\mathcal{U}(\Delta, t), u)$
$\mathcal{U}(\Delta, \text{Guard } (!x) \ t)$	$= \mathcal{U}(\Delta \wedge (x \not\approx \perp), t)$
$\mathcal{U}(\Delta, \text{Guard } (\text{let } x = e) \ t)$	$= \mathcal{U}(\Delta \wedge (x \approx e), t)$
$\mathcal{U}(\Delta, \text{Guard } (K \bar{a} \bar{\gamma} \bar{y} : \bar{\tau} \leftarrow x) \ t)$	$= (\Delta \wedge (x \not\approx K) \wedge (x \not\approx \perp)) \vee \mathcal{U}(\Delta \wedge (K \bar{a} \bar{\gamma} \bar{y} : \bar{\tau} \leftarrow x), gs)$

$$\mathcal{A}_\Gamma(\Delta, \text{Gdt}) = \text{Ant}$$

$\mathcal{A}_\Gamma(\Delta, \text{Rhs})$	$= \begin{cases} \text{InaccessibleRhs}, & \mathcal{V}(\Gamma, \Delta) \Rightarrow \emptyset \\ \text{AccessibleRhs}, & \text{otherwise} \end{cases}$
$\mathcal{A}_\Gamma(\Delta, (t; u))$	$= \mathcal{A}_\Gamma(\Delta, t); \mathcal{A}_\Gamma(\mathcal{U}(\Delta, t), u)$
$\mathcal{A}_\Gamma(\Delta, \text{Guard } (!x) \ t)$	$= \begin{cases} \mathcal{A}_\Gamma(\Delta \wedge (x \not\approx \perp), t), & \mathcal{V}(\Gamma, \Delta \wedge (x \approx \perp)) \Rightarrow \emptyset \\ \text{MayDiverge } \mathcal{A}_\Gamma(\Delta \wedge (x \not\approx \perp), t) & \text{otherwise} \end{cases}$
$\mathcal{A}_\Gamma(\Delta, \text{Guard } (\text{let } x = e) \ t)$	$= \mathcal{A}_\Gamma(\Delta \wedge (x \approx e), t)$
$\mathcal{A}_\Gamma(\Delta, \text{Guard } (K \bar{a} \bar{\gamma} \bar{y} : \bar{\tau} \leftarrow x) \ t)$	$= \mathcal{A}_\Gamma(\Delta \wedge (K \bar{a} \bar{\gamma} \bar{y} : \bar{\tau} \leftarrow x), t)$

Putting it all together

- (0) Input: Context with match vars Γ and desugared Gdt t
- (1) Report n value vectors of $\mathcal{V}(\Gamma, \mathcal{U}(\checkmark, t)) \Rightarrow V$ as uncovered
- (2) Report the collected redundant and not-redundant-but-inaccessible clauses in $\mathcal{A}_\Gamma(\checkmark, t)$
(TODO: Write a function that collects the RHSs, maybe add numbers to Rhs to distinguish).

Generating Inhabitants

$$\boxed{\mathcal{V}(\Gamma, \Delta) \Rightarrow \mathcal{P}(V)}$$

This is provideEvidence

$$\frac{}{\mathcal{V}(\Gamma, \times) \Rightarrow \emptyset} \quad \frac{\mathcal{V}(\Gamma, \Delta_1) \Rightarrow V_1 \quad \mathcal{V}(\Gamma, \Delta_2) \Rightarrow V_2}{\mathcal{V}(\Gamma, \Delta_1 \vee \Delta_2) \Rightarrow V_1 \cup V_2} \quad \frac{}{\mathcal{V}(\Gamma, \Delta) \Rightarrow \{v \mid \mathcal{V}(\Gamma, \Delta) \Rightarrow v\}}$$

$$\boxed{\mathcal{V}(\Gamma, \Delta) \Rightarrow V}$$

$$\frac{\mathcal{T}(\Delta)}{\mathcal{V}(\emptyset, \Delta) \Rightarrow ()} \quad \frac{\mathcal{V}((x_1 : \sigma_1, \dots, x_n : \sigma_n, \Gamma), (K(x_1 : \sigma_1) \dots (x_n : \sigma_n) \leftarrow y, \Delta)) \Rightarrow (a_1, \dots, a_n, v_2, \dots, v_m))}{\mathcal{V}(y : \tau, \Gamma, \Delta) \Rightarrow (K x_1 \dots x_n, v_2, \dots, v_m)}$$

no more fuel

$$\frac{}{\mathcal{V}(x_1 : \tau_1, \dots, x_n : \tau_n, \Delta) \Rightarrow (_, \dots, _)}$$

$$\boxed{\mathcal{T}(\Delta)}$$

Test a Δ for satisfiability

This figure is completely out of date, don't waste your time

Test if Oracle state Delta is unsatisfiable

$$\frac{\boxed{\not\vdash_{\text{SAT}} \Gamma \vdash \Delta} \quad \not\vdash_{\text{SAT}} \Gamma \vdash \text{fus} \Gamma \triangleright \Delta}{\not\vdash_{\text{SAT}} \Gamma \vdash \Delta}$$

Test a list of SAT roots for inhabitants

$$\frac{\boxed{\not\vdash_{\text{SAT}} \Gamma \vdash \bar{x} \triangleright \Delta} \quad \not\vdash_{\text{SAT}} \Gamma \vdash x_i \triangleright \Delta}{\not\vdash_{\text{SAT}} \Gamma \vdash \bar{x} \triangleright \Delta}$$

Test a single SAT root for inhabitants

$$\frac{\boxed{\not\vdash_{\text{SAT}} \Gamma \vdash x \triangleright \Delta} \quad \not\vdash_{\text{SAT}} \Gamma \vdash \wedge \Delta x \approx \perp \quad \{\bar{K}\} \text{ COMPLETE set} \quad \overline{\forall \bar{y} : \bar{\tau}. \not\vdash_{\text{SAT}} \Gamma, \bar{y} : \bar{\tau} \vdash \wedge \Delta x \approx K \bar{y}}}{\not\vdash_{\text{SAT}} \Gamma \vdash x \triangleright \Delta}$$

Add a single equality to Δ

$$\boxed{\not\vdash_{\text{SAT}} \Gamma \vdash \wedge \Delta \delta}$$

Term stuff: Bottom, negative info, positive info + generativity, positive info + univalence

$$\frac{x \not\approx sth \in \Delta}{\not\vdash_{\text{SAT}} \Gamma \vdash \wedge \Delta x \approx \perp} \quad \frac{x \approx K \bar{y} \in \Delta}{\not\vdash_{\text{SAT}} \Gamma \vdash \wedge \Delta x \approx \perp}$$

$$\frac{x \not\approx K \in \Delta}{\not\vdash_{\text{SAT}} \Gamma \vdash \wedge \Delta x \approx K \bar{y}} \quad \frac{x \approx K_i \bar{y} \in \Delta \quad i \neq j \quad K_i \text{ and } K_j \text{ generative}}{\not\vdash_{\text{SAT}} \Gamma \vdash \wedge \Delta x \approx K_j \bar{z}}$$

$$\frac{x \approx K \bar{\tau} \bar{y} \in \Delta \quad \not\vdash_{\text{SAT}} \Gamma \vdash \wedge \Delta \tau_i \sim \sigma_i}{\not\vdash_{\text{SAT}} \Gamma \vdash \wedge \Delta x \approx K \bar{\sigma} \bar{z}} \quad \frac{x \approx K \bar{\tau} \bar{y} \in \Delta \quad \not\vdash_{\text{SAT}} \Gamma \vdash \wedge \Delta y_i \approx z_i}{\not\vdash_{\text{SAT}} \Gamma \vdash \wedge \Delta x \approx K \bar{\sigma} \bar{z}}$$

Type stuff: Hand over to unspecified type oracle

$$\frac{\tau_1 \text{ and } \tau_2 \text{ incompatible to Givens in } \Delta \text{ according to type oracle}}{\not\vdash_{\text{SAT}} \Gamma \vdash \wedge \Delta \tau_1 \sim \tau_2}$$

Mixed: Instantiate K and see if that leads to a contradiction TODO: Proper instantiation

$$\frac{\overline{\not\vdash_{\text{SAT}} \Gamma \vdash y \triangleright \Delta \cup y \not\approx \perp}}{\not\vdash_{\text{SAT}} \Gamma \vdash \wedge \Delta x \approx K \bar{y}}$$