

beliefprop_cpu::Retrieve
OutputDisparityUseSIMDVectors

beliefprop_cpu::RunBPIteration
UsingCheckerboardUpdatesNoPacked
Instructions

beliefprop_cpu::RunBPIteration
UsingCheckerboardUpdatesUseSIMDVectors
Process

beliefprop::MemoryAligned
AtDataStart

```
graph LR; A[beliefprop_cpu::Retrieve OutputDisparityUseSIMDVectors] --> D[beliefprop::MemoryAligned AtDataStart]; B[beliefprop_cpu::RunBPIteration UsingCheckerboardUpdatesNoPacked Instructions] --> D; C[beliefprop_cpu::RunBPIteration UsingCheckerboardUpdatesUseSIMDVectors Process] --> D;
```

The diagram illustrates a flow where three different CPU-based belief propagation functions converge on a single memory-aligned data start point. The first function, 'beliefprop_cpu::Retrieve OutputDisparityUseSIMDVectors', is located at the top left. The second, 'beliefprop_cpu::RunBPIteration UsingCheckerboardUpdatesNoPacked Instructions', is in the middle left. The third, 'beliefprop_cpu::RunBPIteration UsingCheckerboardUpdatesUseSIMDVectors Process', is at the bottom left. All three have arrows pointing to a gray-shaded box on the right labeled 'beliefprop::MemoryAligned AtDataStart'.