Console Output


```
Latitude per el usuario Find Stored Parameters Arrow
Latitude per el usuario Find Stored
[Pipeline] sh
Running on Jenkins in C:\ProgramData\Jenkins\.jenkins\workspace\BDD-with-Cucumber
[Pipeline] {
[Pipeline] stage
[Pipeline] { (Declarative: Tool Install)
[Pipeline] tool
[Pipeline] envVarsForTool
[Pipeline] }
[Pipeline] // stage
[Pipeline] withEnv
[Pipeline] {
[Pipeline] stage
[Pipeline] { (Checkout)
[Pipeline] bat
[Pipeline] // stage
[Pipeline] withEnv
[Pipeline] }
[Pipeline] // node
The recommended git tool is: NONE
using credential github-credentials
Cloning repository https://github.com/mbrdevtech/bdd-with-cucumber
 > git.exe init C:\ProgramData\Jenkins\.jenkins\workspace\BDD-with-Cucumber # timeout=10
Fetching upstream changes from https://github.com/mbrdevtech/bdd-with-cucumber
 > git.exe --version # timeout=10
 > git --version # 'git version 2.45.2.windows.1'
 > git.exe fetch --tags --force --progress -- https://github.com/mbrdevtech/bdd-with-cucumber +refs/heads/*:refs/remotes/origin/* # timeout=10
 > git.exe config remote.origin.url https://github.com/mbrdevtech/bdd-with-cucumber # timeout=10
 > git.exe config --add remote.origin.fetch +refs/heads/*:refs/remotes/origin/* # timeout=10
Avoid second fetch
 > git.exe rev-parse "origin/main^{commit}" # timeout=10
Checking out Revision 8f1e1ed1ca1ca1ca1ca1ca1ca1ca1ca1ca1ca1ca (origin/main)
 > git.exe config core.sparsecheckout # timeout=10
 > git.exe checkout -f 8f1e1ed1ca1ca1ca1ca1ca1ca1ca1ca1ca1ca1ca # timeout=10
Commit message: "Fix: Corregir nombre de archivo de reporte JSON en Jenkinsfile"
 > git.exe rev-list --no-walk 8f1e1ed1ca1ca1ca1ca1ca1ca1ca1ca1ca1ca1ca # timeout=10
[Pipeline] tool
[Pipeline] // withEnv
[Pipeline] }
[Pipeline] // stage
[Pipeline] stage
[Pipeline] { (Install)
[Pipeline] bat
[Pipeline] // stage
[Pipeline] withEnv
[Pipeline] }
[Pipeline] // node
[Pipeline] End of Pipeline
ERROR: Unable to find project for persisting: https://github.com/mbrdevtech/bdd-with-cucumber
Finished: SUCCESS
```

```
C:\ProgramData\Jenkins\.jenkins\workspace\BDD-with-Cucumber>node install
npm deprecated inflight@1.0.6: This module is not supported, and leaks memory. Do not use it. Check out lru-cache if you want a good and tested way to coalesce async requests by a key value, which is much more comprehensive and powerful.
npm deprecated glob@7.2.3: Glob versions prior to v9 are no longer supported
npm deprecated rimraf@3.0.2: Rimraf versions prior to v4 are no longer supported
npm deprecated glob@7.1.6: Glob versions prior to v9 are no longer supported
npm deprecated rimraf@2.7.1: Rimraf versions prior to v4 are no longer supported
npm deprecated glob@7.2.3: Glob versions prior to v9 are no longer supported
npm deprecated rimraf@3.0.2: Rimraf versions prior to v4 are no longer supported
npm deprecated eslint@8.57.1: This version is no longer supported. Please see https://eslint.org/version-support for other options.

> bcrypt@5.1.1 install C:\ProgramData\Jenkins\.jenkins\workspace\BDD-with-Cucumber\node_modules\bcrypt
> node-pre-gyp install --fallback-to-build

[bcrypt] Success: "C:\ProgramData\Jenkins\.jenkins\workspace\BDD-with-Cucumber\node_modules\bcrypt\lib\binding\napi-v3\bcrypt_lib.node" is installed via remote

> bcrypt@5.1.1 postinstall C:\ProgramData\Jenkins\.jenkins\workspace\BDD-with-Cucumber\node_modules\bcrypt
> node-pre-gyp rebuild

[bcrypt] Success: "C:\ProgramData\Jenkins\.jenkins\workspace\BDD-with-Cucumber\node_modules\bcrypt\lib\binding\napi-v3\bcrypt_lib.node" is installed via remote
```