

Jupyter Lab Documentation

Using Jupyter in the A100 server

- Launch a terminal and login into the server using your credentials. Replace username with your credentials

```
sshusername@10.96.50.180
```

- In the same terminal launch Jupyter Lab.

```
jupyter-lab --no-browser
```

- Here is a screenshot showing the port and token

```
raygun@dgx100:~$ jupyter-lab --no-browser
[I 2024-08-01 17:01:51.074 ServerApp] jupyter_lsp | extension was successfully linked.
[I 2024-08-01 17:01:51.077 ServerApp] jupyter_server_terminals | extension was successfully linked.
[I 2024-08-01 17:01:51.080 ServerApp] jupyterlab | extension was successfully linked.
[I 2024-08-01 17:01:51.084 ServerApp] notebook | extension was successfully linked.
[I 2024-08-01 17:01:51.290 ServerApp] notebook_shim | extension was successfully linked.
[I 2024-08-01 17:01:51.313 ServerApp] notebook_shim | extension was successfully loaded.
[I 2024-08-01 17:01:51.314 ServerApp] jupyter_lsp | extension was successfully loaded.
[I 2024-08-01 17:01:51.315 ServerApp] jupyter_server_terminals | extension was successfully loaded.
[I 2024-08-01 17:01:51.318 LabApp] JupyterLab extension loaded from /mnt/bst/ramazan/raygun/.local/lib/python3.8/site-packages/jupyterlab
[I 2024-08-01 17:01:51.318 LabApp] JupyterLab application directory is /mnt/bst/ramazan/raygun/.local/share/jupyter/lab
[I 2024-08-01 17:01:51.319 LabApp] Extension Manager is 'pypi'.
[I 2024-08-01 17:01:51.328 ServerApp] jupyterlab | extension was successfully loaded.
[I 2024-08-01 17:01:51.332 ServerApp] notebook | extension was successfully loaded.
[I 2024-08-01 17:01:51.332 ServerApp] The port 8888 is already in use, trying another port.
[I 2024-08-01 17:01:51.332 ServerApp] Serving notebooks from local directory: /mnt/bst/ramazan/raygun
[I 2024-08-01 17:01:51.332 ServerApp] Jupyter Server 2.14.2 is running at:
[I 2024-08-01 17:01:51.332 ServerApp] http://localhost:8889/lab?token=545f9b64b7de2e36fe2fb38e0dc344efc74bd96502c8575c
[I 2024-08-01 17:01:51.332 ServerApp] http://127.0.0.1:8889/lab?token=545f9b64b7de2e36fe2fb38e0dc344efc74bd96502c8575c
[I 2024-08-01 17:01:51.332 ServerApp] Use Control-C to stop this server and shut down all kernels (twice to skip confirmation).
[C 2024-08-01 17:01:51.336 ServerApp]

To access the server, open this file in a browser:
file:///mnt/bst/ramazan/raygun/.local/share/jupyter/runtime/jpserver-71191-open.html
Or copy and paste one of these URLs:
http://localhost:8889/lab?token=545f9b64b7de2e36fe2fb38e0dc344efc74bd96502c8575c
http://127.0.0.1:8889/lab?token=545f9b64b7de2e36fe2fb38e0dc344efc74bd96502c8575c
[I 2024-08-01 17:01:51.458 ServerApp] Skipped non-installed server(s): bash-language-server, dockerfile-language-server-nodejs, javascript-typescript-langs
erver, jedi-language-server, julia-language-server, pyright, python-language-server, python-lsp-server, r-languageserver, sql-language-server, texlab, type
script-language-server, unified-language-server, vscode-css-languageserver-bin, vscode-html-languageserver-bin, vscode-json-languageserver-bin, yamllangua
ge-server
```

- Open another terminal and use the 8889 port to perform ssh forwarding. The port could be different.

```
ssh -L 8889:localhost:8889 username@10.96.50.180
```

- Copy the url from the initial terminal and paste in the browser

