What a recordist-blocked split costs a bioacoustic foundation model

Mag. art. Shahab Nedaei
variable.gallery
ned.tabulov@gmail.com

4 August 2026

Abstract

Standard evaluation in bioacoustics splits recordings at random. Where a species' recordings come disproportionately from one recordist, a random split puts recordings by that person on both sides of the partition, and the reported accuracy is partly a measure of recorder identity rather than of the bird. Holding recordists out is not a new idea: Stowell and Plumbley [2] did it twelve years ago and stated the rationale in the words we would use. What has never been published is the *quantity* — what blocking costs a current foundation model — and without that number the practice stays easy to ignore. Measuring it on an archive corpus is not straightforward, because both of the field's archive-scale models were trained on the archives. Perch 2.0 trained on xeno-canto and iNaturalist; BirdNET V2.4 trained on xeno-canto; BirdSet excludes BirdNET from its own evaluation for exactly this reason. A top-1 comparison on archive audio therefore partly measures which recordings were memorised. We close that with two changes that also make the experiment cheaper. The models are **frozen** and only a linear probe is trained, so whatever either model memorised is identical on both sides of the comparison and cancels out of the difference. And the audio was **uploaded after both training snapshots** — xeno-canto's `since:` tag filters on upload date, which is a one-directional guarantee rather than an estimate. Because the discriminator is upload date rather than archive provenance, "reproduced on both models" becomes possible on a xeno-canto corpus, which the pre-registered design had ruled out. On **[TODO: N]** recordings uploaded after 2025-09-01, covering **[TODO: S]** species from **[TODO: R]** recordists, a linear probe over frozen features loses **[TODO: drop]** points of top-1 accuracy under a recordist-blocked split relative to a random one **[TODO: on both models / and the models disagree]**. **[TODO: error-ratio sentence.]** We also report the drop as a function of how many species are in the label set, because a bar written in accuracy points is far harsher near the ceiling than in the middle of the range, and a 62-class result and an 886-class result are not comparable in points. Separately, and on identical rows, the two foundation models disagree about the size of the recordist confound by more than either differs from a 32-dimensional space trained on one small corpus: Perch sits 16.5 % below that space and BirdNET 24 % above it. If recorder invariance were a product of archive-scale training, both would sit below. It is better read as a property of the archives that any model trained on them inherits. The deliverable is not a system. It is a number, a threat model and the code: block your splits by recordist, here is what it costs, here is how to reproduce it.

1 Introduction

Automatic species classification from sound is used for real monitoring and real conservation decisions. BirdNET [1] and Perch [3] are deployed by ecologists, and their benchmark numbers set expectations about what a deployment will do.

Those numbers come from evaluations that split recordings at random. That is only sound if a recording's provenance carries no information about its label. In the archives it does. A species' recordings are contributed by volunteers, and for many species they come disproportionately from a handful of people. A recordist is not only a person: they are a microphone, a preamplifier, a set of recording habits, a geographic range and a preferred time of day. When recordings by one person land on both sides of a random split, a model can reach the right species by recognising the person.

This matters beyond the leaderboard, because the failure has a deployment shape. A recordist is functionally *a recorder and a site*. Generalising across recordists is the same problem as generalising to a new device in a new place, which is the transition the field already knows disappoints [3]. Naming a measurable cause, and pricing it, is more actionable than the observation that deployment is hard.

What this paper contributes. One number, measured carefully, plus the method that makes it measurable at all. Specifically:

1. **The cost of blocking**, for a linear probe over frozen features from two independent foundation models, on audio neither model can have trained on (§6).

2. **A contamination-free design** for asking the question on archive audio, which the obvious design cannot do (§3). This is what lets both models be tested on the same corpus.

3. **The observation that the pre-registered gate was written in the wrong unit.** Accuracy points are not comparable across label-set sizes, and we show the drop's dependence on class count directly (§6.1).
4. **Evidence that the structure is in the archives rather than in one model** (§7): read on identical rows, Perch and BirdNET disagree about the size of the recordist confound by more than either differs from a 32-d space trained on one small corpus. Recorder invariance is not conferred by archive-scale training.
5. **Code and a fixed population**, so the number can be checked rather than believed (§10).

What it does not contribute. Not the practice of recordist-blocked evaluation, which is twelve years old. Not a new model, not a new architecture, and not a claim that these models are bad. A model that reads recorder identity is doing something reasonable with the data it was given; the problem is the evaluation protocol that rewards it.

2 What is already known, and what is not

The practice exists, and is older than the models. Stowell and Plumbley [2] split by recordist and gave the rationale plainly: the approach "tests whether the system can generalise to recordings from unknown recordists, rather than adapting to any specifics of the known recordists". Read against the full text rather than the abstract, two details matter here. The stratification was applied to *one* of their four datasets — `bldawn`, 20 recordings each from three UK recordists, three-fold, training on two recordists and testing on the held-out third. And the paper reports **no random-against-blocked comparison**: recordist stratification is used where it is used, and its cost is never priced. The Cornell CBI dataset is likewise partitioned so that no recordist spans two partitions.

The quantity does not exist. We checked this against sources rather than abstracts. Neither the 2026 foundation-model comparative review (arXiv:2508.01277) nor the 2025 large-scale training recipe (arXiv:2508.11845) reports a random-against-blocked accuracy comparison. Nobody has published what a recordist-blocked split costs a current foundation model.

So the claim moves. The deliverable is not *block your splits*, which is known and ignored. It is *here is what one costs*. That is a smaller claim than the project originally registered, and it is the one that is actually unoccupied. It is also the claim most likely to change behaviour, because the reason a twelve-year-old recommendation gets ignored is that nobody has priced ignoring it.

3 Why the obvious experiment is invalid

The experiment as first designed was: take a public archive-derived corpus, take Perch and BirdNET off the shelf, evaluate top-1 species accuracy twice, changing only the split. That design does not work, and the reason is worth stating because it applies to any evaluation of these models on archive audio.

Both models trained on the archives. Perch 2.0's technical report [3] lists roughly 1.5 M recordings over 14 500 classes drawn from xeno-canto, iNaturalist research-grade audio via GBIF, the Tierstimmenarchiv and FSD50K. BirdNET V2.4 [1] trained on xeno-canto. BirdSet already excludes BirdNET from evaluation on its `XCM`/`XCL` splits on precisely these grounds, since those splits are drawn from xeno-canto.

Why that is fatal rather than merely untidy. A memorised recording is scored correctly for reasons that have nothing to do with acoustics, and a model that memorised a recording will also place it near that recording's siblings. So on archive audio, top-1 accuracy measures memorisation as much as generalisation — and the *gap* between two splits partly measures which recordings were memorised, rather than what blocking costs. Under the pre-registered design this made "reproduced on both models" unreachable on any xeno-canto-derived corpus.

Two changes fix it, and both make the experiment cheaper.

1. **Freeze the model; train only a linear probe.** The foundation model is a fixed feature extractor in both arms. Whatever it memorised is therefore present identically on both sides of the comparison and cancels out of the difference. What differs between the arms is only the probe's training set, which is the thing the claim is about.
2. **Use audio uploaded after both training snapshots.** Xeno-canto's `since:` tag filters on *upload* date. A recording uploaded after a model's data snapshot cannot have been in that snapshot regardless of when it was recorded, which makes it a one-directional guarantee rather than an estimate. We set the bound to 2025-09-01: one month past Perch 2.0's publication, and more than two years past BirdNET V2.4's June 2023 release. No attempt at precision is made, because the argument needs the bound to be safe rather than tight.

This is what makes the two-model requirement satisfiable. Because the discriminator is upload date and not archive provenance, the objection that disqualifies BirdNET on a xeno-canto corpus does not apply: the audio postdates its training set by two years. The design constraint that broke the registered method is

dissolved rather than worked around, and both models can be read on identical rows.

What the design still cannot claim. A linear probe over frozen features is not a fine-tuned model, and the absolute accuracies here are not comparable to a published benchmark number. That is deliberate: the quantity of interest is a *difference* between two splits under an otherwise identical procedure, and the frozen-feature design is what makes that difference attributable to the split. Whether full fine-tuning would widen or narrow the gap is open, and §8 says so.

4 Data

The query, and a warning that belongs in it. The population is every xeno-canto recording matching `grp:birds since:2025-09-01 q:A`. The group tag is not optional. Xeno-canto hosts bats, frogs, grasshoppers and land mammals alongside birds, and the same query without `grp:birds` returned 6 000 recordings of which **none were birds** — 3 035 bats, 1 568 frogs, 926 grasshoppers and 471 land mammals. Pagination simply never reached the birds. Nothing errored, and the first downloads were 256 kHz ultrasonic bat clips that decoded perfectly well and would have entered a bird model as though they were birdsong. Any replication must carry the group tag.

Census. The complete query returns **21 928** recordings, of which 21 709 have downloadable audio; xeno-canto redacts the file for species it considers at risk from trapping or disturbance, and no query gets round it. Those recordings cover **4 305** species and **961** recordists.

The species floor is the experiment, not a convenience. Under a recordist-blocked split, a species whose recordings all come from one recordist lands entirely on one side of the partition and cannot be classified at all. That is an empty test class, not leakage, and scoring it as an error would manufacture the result the experiment is looking for. We therefore keep only species with at least 6 recordings from at least **2 distinct recordists**, which is **886** species covering 13 646 recordings, and we report the number excluded.

A cap of 12 recordings per species, which improves the experiment. The scorable population is severely skewed: 6 recordings at the floor, a median of 9, and a maximum of 338. Left uncapped, a handful of species would supply a large share of the probe's training rows and the class prior would do work that the features are supposed to do. Capping at 12 reduces the imbalance from 56:1 against the floor to 2:1, loses *no* species because the floor is 6, and reduces the download by roughly 5 300 recordings.

The cap has to be recordist-aware. Consider a species with 20 recordings where one recordist contributed 19 and a second contributed 1: an ordinary random sample of 12 drops that second recordist about 40 % of the time, the species falls to a single recordist, and it becomes unscorable under a blocked split *after* having been counted as scorable. Selection therefore round-robins across a species' recordists, which keeps every recordist for as long as the cap allows, and an assertion checks that the scorable species set is unchanged by capping.

The population actually scored is **8 321** recordings over **886** species and **649** recordists, with 6 to 12 recordings per species and at least 2 recordists each. For scale, the pilot that preceded this run scored 62 species over 2 158 recordings on one model — and of those 2 158 only **730** cleared its floor and were actually scored, a distinction worth keeping because the larger number is the one easily mistaken for the sample size. Table 2 sets the two runs side by side.

5 Method

Features. Each recording is decoded, mixed to mono, resampled, and cut into the model's native window: 5 s at 32 kHz for Perch (six windows, 30 s) and 3 s at 48 kHz for BirdNET (ten windows, the same 30 s). Window embeddings are mean-pooled to one vector per recording — 1536-d for Perch, 1024-d for BirdNET's backbone. Both models are ONNX exports run without gradients; neither is updated at any point.

Probe. A multinomial logistic regression with an L2 penalty ($C = 1$), on features standardised using the *training* side's mean and variance only. Standardising over both sides would leak the test set's statistics across the partition, which is the same class of error the paper is about.

The probe runs on the GPU, and that required a check. At 886 classes in 1536 dimensions a full-batch multinomial fit costs on the order of 10^{10} multiply–adds per iteration, which is not tractable on CPU across 20 folds, two arms and two models. The probe is therefore implemented in PyTorch with full-batch L-BFGS, minimising the same objective scikit-learn minimises. Swapping the estimator silently would make this run incomparable with the pilot, so the two are checked against each other on synthetic data and on the pilot's real features; they agree to within one accuracy point, and the check fails loudly if they do not.

Three arms. All three restrict each fold to the classes present on *both* sides before scoring, and that restriction must be applied to every arm or the comparison is rigged: a blocked split strands whole species on one side, and dropping those from the blocked arm alone would leave it a smaller and easier label set than the random arm, which inflates blocked accuracy and understates the very drop being measured.

- **A — random.** 30 % of each species' recordings held out, stratified by species. This is the standard protocol.
- **B — recordist-blocked.** 30 % of recordists held out; every recording by a held-out recordist is on the test side.
- **C — paired, and this is the number we quote.** Each blocked fold's surviving class set is reused for a random fold at the same held-out fraction, so the two differ in exactly one thing: whether a recordist may appear on both sides. Arms A and B are not scored on the same task, because blocked folds end up with fewer classes, and fewer classes is an easier problem.

Twenty folds per arm, seeded. Because the folds are paired, the per-fold difference is the statistic with the least noise in it, and we report its spread and the number of folds in which blocking was worse, not only the mean.

Reporting the effect in two units. The pre-registered gate is a drop of more than 10 points of top-1 accuracy, reproduced on both models, and it is scored as written. But points are a poor unit near the ceiling: the pilot's 9.68 points at 93 % accuracy was 2.44× the errors, whereas the same 9.68 points at 60 % accuracy would be 1.24×. We therefore report the error-rate ratio beside the gate, and §6.1 shows what the points figure does as the label set grows.

6 Results

[TODO: This section is filled from pipeline/analysis/w0_full.json when the run completes. Nothing below this marker should be read as measured until then.]

6.1 The drop depends on how many species are in the label set

[TODO: class-count sweep table: 62 / 150 / 300 / 500 / 886 classes, drop in points and error ratio at each, on the same recordings and the same folds.]

The reason to report this is that it decides how the pre-registered gate should be read. If the points-drop climbs with class count while the error ratio stays roughly flat, then the ratio is the invariant and a bar written in points was partly a bar on how many species happened to clear our sampling floor — which is a fact about corpus depth, not about recordists.

7 The structure is in the archives, not in one model

A drop measured on one model could be a property of that model. The measurements in this section are a separate experiment, on a separate population, and they are what rules that out. They use nearest-neighbour retrieval lift against a permutation null rather than a probe: for a given grouping, how much more often is a recording's nearest neighbour in its own group than chance allows.

Table 1: Nearest-neighbour lift over a permutation null, same rows, same estimator. Every space is confounded in the same direction; they differ only in degree. **The two foundation models disagree with each other by more than either differs from a 32-d space trained on one small corpus**, which is the observation this section exists for.

population	space	species	recordist
T1	critic 32-d	—	+0.0891
1 567 rec.	Perch 1536-d	—	+0.0744
135 rec'ists	BirdNET 1024-d	—	+0.1107
T3	critic 32-d	+0.0074	+0.1684
1 644 rec.	Perch 1536-d	+0.0588	+0.1155
760 rec'ists	BirdNET 1024-d	+0.0393	+0.1755

Three embedding spaces are compared on *identical rows* with an identical estimator — Perch 2.0 at 1536-d, BirdNET V2.4 at 1024-d, and a 32-d task-specific space trained on this project's own corpus (the "critic", described in the companion system paper). Two populations: one drawn to be recordist-stratified, one drawn as species pairs.

Every space carries it, and the two big models disagree about how much. On the recordist-stratified population, Perch sits **16.5 % below** the small corpus-specific space and BirdNET **24 % above** it. On the species-pair population Perch is 31.4 % below and BirdNET 4 % above. Two models trained by different groups on overlapping archives, read on the same recordings by the same estimator, differ from each other more than either differs from a 32-d space trained on one project's corpus.

What that licenses, and what it does not. It licenses the claim that **recorder invariance is not conferred by archive-scale training**. If it were, both archive-scale models would sit below the small space, and one of them sits above it. The structure is better explained as a property of the archives that any model trained on them inherits to some degree. It does *not* license a ranking of the two models: the populations here are small, and the T3 recordist column rests on a coverage of only 0.329 because most recordists in that draw have too few recordings for the estimator's floor.

And the structure survives on audio the model never saw. Repeating the recordist measurement on the post-cutoff population of §4 — rows Perch provably did not train on — gives a recordist lift of +0.441

against a species lift of +0.750 on 293 matched rows where both groupings clear the estimator's floor, both at the permutation floor for significance. Whatever the recordist structure is, it is not Perch recognising its own training data.

A caution about a number we have retracted elsewhere. An earlier and louder version of this project's headline was a recordist lift of +0.488 against a species lift of +0.196, at *syllable* level. A benchmark split is a *recording*-level operation, and at recording level on the same corpus the ordering reverses: species +0.229 against recordist +0.196. That reversal is itself a selection artefact — the estimator's eight-member floor at recording level means "species with at least eight recordings", which is 77 of 3 636, and recordings per species correlates with recordists per species at $r = +0.923$. The honest reading is that the recording-level figures are the ones relevant to a split, that they are smaller than the syllable-level ones, and that the population which makes them measurable is the population where the confound is weakest. The pre-registered 10-point gate should not have been treated as likely on the strength of +0.488.

8 Threats to validity

One archive, one quality tier. Everything here is xeno-canto at `q:A`. Quality A keeps the audio comparable but selects recordings that a human judged clean, and cleanliness may correlate with recordist skill — which is the variable under test. A replication across quality tiers would say whether the effect is larger or smaller in the messier part of the archive.

Upload date is not recording date. The guarantee is one-directional and that is all it needs to be: a recording uploaded after a snapshot was not in that snapshot. It does not follow that these recordings are acoustically representative of the archive as a whole, and a corpus of recent uploads may over-represent currently active recordists.

A probe is not a fine-tuned model. The frozen-feature design is what makes the difference attributable to the split, at the cost of not being the number a practitioner would report from fine-tuning. The direction of that difference is not predictable from this experiment.

Recordist identity is self-reported metadata. One person with two accounts reads as two recordists and weakens blocking; two people sharing an account reads as one and strengthens it. Both push in known directions but neither is quantified here.

The class-count dependence cuts both ways. It is a finding about the gate's unit, but it also means our own headline number is a statement about an 886-class problem. A reader comparing it to a benchmark with a different label-set size should compare error ratios.

Table 2: The pilot and this run. The pilot's limits were not properties of the archive: its catalogue held exactly 6 000 recordings because its search stopped at 60 pages, and it selected by *recordist* because it inherited that rule from a different experiment whose unit was the recordist.

	pilot	this run
catalogue read	6 000	21 928
selection unit	recordist	species
recordings	2 158	8 321
embedded		
recordings scored	730	[TODO: N]
species scored	62	886
recordists	137	649
models	Perch only	Perch + BirdNET
probe	CPU, sklearn	GPU, verified equivalent

9 What to do about it

For benchmark maintainers. Report both numbers. A random split and a recordist-blocked split, with the recordist coverage of the corpus stated, so that readers can see the gap rather than infer it. Blocking need not replace random splitting to be useful; the gap is the informative quantity.

For practitioners. Where a deployment will meet new recorders in new places — which is most deployments — the blocked figure is the closer estimate, and the gap measured here is the scale of the optimism in the random one.

For corpus builders. Recordist metadata is what makes any of this measurable. Archives that keep it, and evaluations that use it, cost little and are the precondition for pricing this failure at all.

10 Reproducibility

Every number is produced by a script that prints its pre-registered gate before its result and writes a JSON sidecar beside itself. The catalogue is cached, so the population is fixed rather than re-searched.

An `XC_API_KEY` is required for the fetch; xeno-canto API v3 needs a personal key. The embeddings are cached, so the analysis can be re-run without re-downloading, and `w0_recordist_split.py --self-test` checks the split machinery against two synthetic worlds with known answers — one where recordist is assigned at random, where blocking must cost nothing, and one where recordist is confounded with species, where blocking must be devastating.

Data and code availability

Table 3: What reproduces what. Filenames are relative to `pipeline/analysis/` in the project repository; the `analysis/` prefix is dropped here because it does not fit a two-column measure.

script	what it does
`w0_full_catalogue.py`	pages the complete post-cutoff catalogue and reports what it can support
`w0_full_fetch.py`	selects the scorable population, downloads it, embeds it through both models, checkpointed and resumable
`w0_probe.py`	the GPU probe, and `--verify` for its equivalence to scikit-learn
`w0_full.py`	the three arms, the gate, and the class-count sweep
`w0_recordist_split.py`	the earlier pilot, kept runnable and unchanged

[TODO: Zenodo DOI for the archived release.] No audio is redistributed: the fetch scripts retrieve it from xeno-canto under the contributors' own licences, and the cached catalogue records exactly which recordings were used.

Acknowledgements

[TODO: acknowledgements, funding statement, or an explicit statement of none.] The recordings this paper is about were contributed to xeno-canto [4] by volunteers, and the recordist metadata that makes the measurement possible is their work.

References

[1] Stefan Kahl, Connor M. Wood, Maximilian Eibl, and Holger Klinck. BirdNET: A deep learning solution for avian diversity monitoring. *Ecological Informatics*, 61:101236, 2021. doi: 10.1016/j.ecoinf.2021.101236. URL https://doi.org/10.1016/j.ecoinf.2021.101236. Model weights CC BY-NC-SA 4.0; the BirdNET-Analyzer code is MIT.

[2] Dan Stowell and Mark D. Plumbley. Automatic large-scale classification of bird sounds is strongly improved by unsupervised feature learning. *PeerJ*, 2:e488, 2014. doi: 10.7717/peerj.488. URL https://doi.org/10.7717/peerj.488. Source of the recordist-stratified split. Verified against the full text: the stratification is applied to the `bldawn` dataset only — 20 recordings each from three UK recordists, three-fold, training on two recordists and testing on the held-out third — and the paper reports *no* random-against-blocked accuracy comparison.

[3] Bart van Merriënboer, Vincent Dumoulin, Jenny Hamer, Lauren Harrell, Andrea Burns, and Tom Denton. Perch 2.0: The bittern lesson for bioacoustics, 2025. URL https://arxiv.org/abs/2508.04665. 1536-d embedding, EfficientNet-B3 trunk, 14 795 output classes of which 14 597 are species, 5 s at 32 kHz; code Apache 2.0.

[4] Xeno-canto Foundation. xeno-canto: sharing wildlife sounds from around the world. https://xeno-canto.org. Per-recording Creative Commons licences; accessed 2026-08-01.