

1246. Palindrome Removal

Hard👍 247🔒 9🤍 Add to List🔖 Share

Given an integer array `arr`, in one move you can select a **palindromic** subarray `arr[i], arr[i+1], ..., arr[j]` where `i <= j`, and remove that subarray from the given array. Note that after removing a subarray, the elements on the left and on the right of that subarray move to fill the gap left by the removal.

Return the minimum number of moves needed to remove all numbers from the array.

Example 1:

Input: `arr = [1,2]`
Output: 2

Example 2:

Input: `arr = [1,3,4,1,5]`
Output: 3
Explanation: Remove [4] then remove [1,3,1] then remove [5].

Constraints:

- `1 <= arr.length <= 100`
- `1 <= arr[i] <= 20`

Accepted 8,103Submissions 17,677

Seen this question in a real interview before?

YesNo

Companies👤 1

0 ~ 6 months6 months ~ 1 year1 year ~ 2 years

Microsoft6

Related Topics

ArrayDynamic Programming

Hide Hint 1

Use dynamic programming.

Hide Hint 2

Let `dp[i][j]` be the solution for the sub-array from index `i` to index `j`.

Hide Hint 3

Notice that if we have `S[i] == S[j]` one transition could be just `dp[i + 1, j + 1]` because in the last turn we would have a palindrome and we can extend this palindrome from both sides, the other transitions are not too difficult to deduce.

```
1class Solution {
2    public int minimumMoves(int[] arr) {
3
4    }
5}
```