

Defuzzification and fuzzy control systems

Shabana K M

PhD Research Scholar

Department of Computer Science and Engineering

IIT Palakkad

18 June 2021



INDIAN INSTITUTE
OF TECHNOLOGY
PALAKKAD

Fuzzy output


- The output of a fuzzy inference engine can be a single fuzzy set or union of two or more fuzzy sets

Fuzzy output


- The output of a fuzzy inference engine can be a single fuzzy set or union of two or more fuzzy sets
- Consider the following two rules in the fuzzy logic system:
R1: IF x is A THEN y is C_1
R2: IF x is B THEN y is C_2

Fuzzy output


- The output of a fuzzy inference engine can be a single fuzzy set or union of two or more fuzzy sets
- Consider the following two rules in the fuzzy logic system:
R1: IF x is A THEN y is C_1
R2: IF x is B THEN y is C_2
- Here the output fuzzy set $C = C_1 \cup C_2$




Fuzzy Output




Fuzzy Output



Fuzzy Output




Fuzzy Output




What is the **crisp value** that can be inferred from the above rules given an input x' ?

Defuzzification



- the process of converting a fuzzified output into a single crisp value with respect to a fuzzy set

Defuzzification




- the process of converting a fuzzified output into a single crisp value with respect to a fuzzy set
- fuzzy results cannot be used to drive a control mechanism

The diagram illustrates the Fuzzy Inference Process. It starts with an 'Input' (red arrow) entering a 'Fuzzifier' (light blue box). The output of the Fuzzifier goes into the 'Inference Engine' (light red box). The output of the Inference Engine goes into the 'Defuzzifier' (green box), which is highlighted with a red border. The output of the Defuzzifier is the 'Output' (red arrow). A 'Fuzzy Knowledge base' (blue cylinder) provides input to the Fuzzifier, Inference Engine, and Defuzzifier.

- ◀ ◻ ▶ ◀ ◻ ▶ ◀ ≡ ▶ ◀ ≡ ▶ ≡

Defuzzification



- the process of converting a fuzzified output into a single crisp value with respect to a fuzzy set
- fuzzy results cannot be used to drive a control mechanism
- the defuzzified value represents the action to be taken in controlling the process
- there are many defuzzification techniques, each with its own advantages and drawbacks

Centroid method: CoG

Center of gravity method (CoG)

- find the point x^* where a vertical line would slice the aggregate into two equal masses

Centroid method: CoG


Center of gravity method (CoG)

- find the point x^* where a vertical line would slice the aggregate into two equal masses
- x^* represents the center of gravity of the fuzzy set

Centroid method: CoG

Center of gravity method (CoG)


- find the point x^* where a vertical line would slice the aggregate into two equal masses
- x^* represents the center of gravity of the fuzzy set
- Graphically,



Centroid method: CoG

Center of gravity method (CoG)


- find the point x^* where a vertical line would slice the aggregate into two equal masses
- x^* represents the center of gravity of the fuzzy set
- Graphically,



- Mathematically the CoG can be expressed as follows:

$$x^* = \frac{\int x \cdot \mu_c(x) dx}{\int \mu_c(x)}$$

Centroid method: CoG



Maxima methods

- the crisp value is determined based on values with maximum membership

Maxima methods

- the crisp value is determined based on values with maximum membership
- there are different maxima methods with different conflict resolution strategies for multiple maxima

Maxima methods

- the crisp value is determined based on values with maximum membership
- there are different maxima methods with different conflict resolution strategies for multiple maxima
 - 1 Max membership method
 - 2 First of Maxima method (FOM)
 - 3 Last of Maxima method (LOM)
 - 4 Mean of Maxima method (MOM)

Max membership method

- also called height method

Max membership method


- also called height method
- this method is applicable when the fuzzy set is **unimodal**

Max membership method

- also called height method
- this method is applicable when the fuzzy set is **unimodal**
- the crisp value x^* is defined by: $\mu_C(x^*) > \mu_C(x)$ for all $x \in \mathcal{X}$

Max membership method

- also called height method
- this method is applicable when the fuzzy set is **unimodal**
- the crisp value x^* is defined by: $\mu_C(x^*) > \mu_C(x)$ for all $x \in \mathcal{X}$



First of Maxima Method (FOM)


- This method determines the **smallest** value of the domain with maximum membership value

First of Maxima Method (FOM)

- This method determines the **smallest** value of the domain with maximum membership value
- The crisp value $x^* = \min\{x \mid \mu_C(x) = \max_w \mu_C(w)\}$

First of Maxima Method (FOM)

- This method determines the **smallest** value of the domain with maximum membership value
- The crisp value $x^* = \min\{x \mid \mu_C(x) = \max_w \mu_C(w)\}$



Last of Maxima Method (LOM)


- This method determines the **largest** value of the domain with maximum membership value

Last of Maxima Method (LOM)

- This method determines the **largest** value of the domain with maximum membership value
- The crisp value $x^* = \max\{x \mid \mu_C(x) = \max_w \mu_C(w)\}$

Last of Maxima Method (LOM)

- This method determines the **largest** value of the domain with maximum membership value
- The crisp value $x^* = \max\{x \mid \mu_C(x) = \max_w \mu_C(w)\}$



Mean of Maxima Method (MOM)


- This method determines the **mean** of the elements of the domain with maximum membership value

Mean of Maxima Method (MOM)

- This method determines the **mean** of the elements of the domain with maximum membership value
- The crisp value $x^* = \frac{\sum_{x_i \in M} x_i}{|M|}$
where $M = \{x_i \mid \mu_C(x_i) = \max_w \mu_C(w)\}$

Mean of Maxima Method (MOM)

- This method determines the **mean** of the elements of the domain with maximum membership value
- The crisp value $x^* = \frac{\sum_{x_i \in M} x_i}{|M|}$
 where $M = \{x_i \mid \mu_C(x_i) = \max_w \mu_C(w)\}$



Weighted average method

- can be used only for symmetrical output membership functions

Weighted average method


- can be used only for symmetrical output membership functions

- The crisp value $x^* = \frac{\sum_C \mu_C(\bar{z}_C) \cdot \bar{z}_C}{\sum_C \mu_C(\bar{z}_C)}$

where \bar{z}_C is the centroid of the membership function C


Weighted average method

- can be used only for symmetrical output membership functions
- The crisp value $x^* = \frac{\sum_C \mu_C(\bar{z}_C) \cdot \bar{z}_C}{\sum_C \mu_C(\bar{z}_C)}$
where \bar{z}_C is the centroid of the membership function C
- For instance,



Weighted average method

- can be used only for symmetrical output membership functions
- The crisp value $x^* = \frac{\sum_C \mu_C(\bar{z}_C) \cdot \bar{z}_C}{\sum_C \mu_C(\bar{z}_C)}$
where \bar{z}_C is the centroid of the membership function C
- For instance,



- Here $x^* = \frac{k_2 \cdot x_1 + k_3 \cdot x_2 + k_1 \cdot x_3}{k_1 + k_2 + k_3}$

Types of fuzzy inference systems

- Two main types of fuzzy inference systems are:
 - Mamdani-type
 - Sugeno-type

Types of fuzzy inference systems

- Two main types of fuzzy inference systems are:
 - Mamdani-type
 - Sugeno-type
- Mamdani-type inference expects the output membership functions to be fuzzy sets

Types of fuzzy inference systems

- Two main types of fuzzy inference systems are:
 - Mamdani-type
 - Sugeno-type
- Mamdani-type inference expects the output membership functions to be fuzzy sets
- The output membership functions are only linear or constant for the Sugeno-type fuzzy inference

Mamdani fuzzy inference systems

- have more intuitive and easier to understand rule bases

Mamdani fuzzy inference systems

- have more intuitive and easier to understand rule bases
 - well-suited to applications where rules are created from human expert knowledge, e.g. medical diagnostics

Mamdani fuzzy inference systems

- have more intuitive and easier to understand rule bases
 - well-suited to applications where rules are created from human expert knowledge, e.g. medical diagnostics
- output of each rule is a fuzzy set derived from the output membership function


Mamdani fuzzy inference systems

- have more intuitive and easier to understand rule bases
 - well-suited to applications where rules are created from human expert knowledge, e.g. medical diagnostics
- output of each rule is a fuzzy set derived from the output membership function
- the output fuzzy sets are combined into a single fuzzy set using an aggregation method

Mamdani fuzzy inference systems

- have more intuitive and easier to understand rule bases
 - well-suited to applications where rules are created from human expert knowledge, e.g. medical diagnostics
- output of each rule is a fuzzy set derived from the output membership function
- the output fuzzy sets are combined into a single fuzzy set using an aggregation method
- the combined output fuzzy set is defuzzified to compute a final crisp output value

Mamdani fuzzy inference systems



Sugeno fuzzy inference systems

- uses singleton output membership functions that are either constant or a linear function of the input values

Sugeno fuzzy inference systems

- uses singleton output membership functions that are either constant or a linear function of the input values
- defuzzification involves computation of a weighted average or weighted sum of a few data points

Sugeno fuzzy inference systems

- uses singleton output membership functions that are either constant or a linear function of the input values
- defuzzification involves computation of a weighted average or weighted sum of a few data points
 - use a single spike as the output membership function rather than a distributed fuzzy set

Sugeno fuzzy inference systems

- uses singleton output membership functions that are either constant or a linear function of the input values
- defuzzification involves computation of a weighted average or weighted sum of a few data points
 - use a single spike as the output membership function rather than a distributed fuzzy set
 - more computationally efficient compared to Mamdani system

Sugeno fuzzy inference systems

- uses singleton output membership functions that are either constant or a linear function of the input values
- defuzzification involves computation of a weighted average or weighted sum of a few data points
 - use a single spike as the output membership function rather than a distributed fuzzy set
 - more computationally efficient compared to Mamdani system
- a typical fuzzy rule in a Sugeno fuzzy model has the form:

IF x is A and y is B THEN $z = px + qy + r$, where

Sugeno fuzzy inference systems

- uses singleton output membership functions that are either constant or a linear function of the input values
- defuzzification involves computation of a weighted average or weighted sum of a few data points
 - use a single spike as the output membership function rather than a distributed fuzzy set
 - more computationally efficient compared to Mamdani system
- a typical fuzzy rule in a Sugeno fuzzy model has the form:

IF x is A and y is B THEN $z = px + qy + r$, where

- x, y are crisp inputs; A, B are fuzzy sets
- p, q, r are constants

Sugeno fuzzy inference systems

- uses singleton output membership functions that are either constant or a linear function of the input values
- defuzzification involves computation of a weighted average or weighted sum of a few data points
 - use a single spike as the output membership function rather than a distributed fuzzy set
 - more computationally efficient compared to Mamdani system
- a typical fuzzy rule in a Sugeno fuzzy model has the form:
$$\text{IF } x \text{ is } A \text{ and } y \text{ is } B \text{ THEN } z = px + qy + r, \text{ where}$$
 - x, y are crisp inputs; A, B are fuzzy sets
 - p, q, r are constants
- for a zero-order Sugeno-system, $p = q = 0$

Sugeno fuzzy inference systems


- uses singleton output membership functions that are either constant or a linear function of the input values
- defuzzification involves computation of a weighted average or weighted sum of a few data points
 - use a single spike as the output membership function rather than a distributed fuzzy set
 - more computationally efficient compared to Mamdani system

- a typical fuzzy rule in a Sugeno fuzzy model has the form:

IF x is A and y is B THEN $z = px + qy + r$, where

- x, y are crisp inputs; A, B are fuzzy sets
- p, q, r are constants
- for a zero-order Sugeno-system, $p = q = 0$
- for a first-order Sugeno-system, p and q are non-zero

Sugeno fuzzy inference systems




Each rule generates two values:

- z_i - Rule output level, which is either a constant value or a linear function of the input values:

$$z_i = a_i x + b_i y + c_i$$

Sugeno fuzzy inference systems



Each rule generates two values:

- z_i - Rule output level, which is either a constant value or a linear function of the input values:

$$z_i = a_i x + b_i y + c_i$$

- x and y are values of input 1 and input 2 respectively
- a_i , b_i and c_i are constant coefficients

Sugeno fuzzy inference systems

- w_i - Rule firing strength derived from the rule antecedent (IF part of the rule)

$$w_i = \text{AndMethod}(F_1(x), F_2(y))$$

Sugeno fuzzy inference systems

- w_i - Rule firing strength derived from the rule antecedent (IF part of the rule)

$$w_i = \text{AndMethod}(F_1(x), F_2(y))$$

- Here, $F_1(\dots)$ and $F_2(\dots)$ are the membership functions for inputs 1 and 2, respectively.

Sugeno fuzzy inference systems

- w_i - Rule firing strength derived from the rule antecedent (IF part of the rule)

$$w_i = \text{AndMethod}(F_1(x), F_2(y))$$

- Here, $F_1(\dots)$ and $F_2(\dots)$ are the membership functions for inputs 1 and 2, respectively.
- The output of each rule is the weighted output level, which is the product of w_i and z_i

Sugeno fuzzy inference systems


- w_i - Rule firing strength derived from the rule antecedent (IF part of the rule)

$$w_i = \text{AndMethod}(F_1(x), F_2(y))$$

- Here, $F_1(\dots)$ and $F_2(\dots)$ are the membership functions for inputs 1 and 2, respectively.
- The output of each rule is the weighted output level, which is the product of w_i and z_i
- The final output of the system is the weighted average over all rule outputs:

$$\text{final output} = \frac{\sum_{i=1}^N w_i \cdot z_i}{\sum_{i=1}^N w_i}$$

Sugeno fuzzy inference systems



Mamdani vs. Sugeno inference systems

Mamdani fuzzy inference system

- well-suited to human input

Mamdani vs. Sugeno inference systems

Mamdani fuzzy inference system

- well-suited to human input
- more interpretable rule base

Mamdani vs. Sugeno inference systems

Mamdani fuzzy inference system

- well-suited to human input
- more interpretable rule base
- entails a substantial computational burden

Mamdani vs. Sugeno inference systems

Mamdani fuzzy inference system

- well-suited to human input
- more interpretable rule base
- entails a substantial computational burden

Sugeno fuzzy inference system

- computationally efficient

Mamdani vs. Sugeno inference systems

Mamdani fuzzy inference system

- well-suited to human input
- more interpretable rule base
- entails a substantial computational burden

Sugeno fuzzy inference system

- computationally efficient
- well-suited to mathematical analysis

References

- 1 <https://cse.iitkgp.ac.in/~dsamanta/courses/sca/resources/slides/FL-03%20Defuzzification.pdf>
- 2 <https://cse.iitkgp.ac.in/~dsamanta/courses/archive/sca/Archives/Chapter%205%20Defuzzification%20Methods.pdf>
- 3 https://uomustansiriyah.edu.iq/media/lectures/5/5_2018_12_17!10_42_05_AM.pdf
- 4 https://en.wikipedia.org/wiki/Fuzzy_control_system
- 5 http://grs.dlmu.edu.cn/__local/A/2D/96/CE49C21FAF3D85CC999B786FF3E_1908A5F3_73ECC.pdf
- 6 <https://in.mathworks.com/help/fuzzy/types-of-fuzzy-inference-systems.html>
- 7 <https://www.sciencedirect.com/topics/engineering/fuzzy-inference>