

Interactive Social Engineering Scenario & UI Development Specification

100 dynamic six-stage scenarios across WhatsApp, Instagram, Email and SMS/Text Messages

Purpose Offline training-cum-evaluation for military personnel	Scope Four simulated communication applications	Safety Fictional, non-operational and locally contained
--	---	---

Version 1.0 | 02 September 2026 | English

Prepared as an implementation handoff. Real credentials, real service details, live links, real payment flows and real delivery are explicitly out of scope.

Document Purpose and Use

This specification translates the project concept and product-design materials into an implementable learner experience. A learner identifies themselves, enters a dashboard that behaves like a contained mobile-communications environment, completes 10 randomized multi-step scenarios, receives an explainable score out of 100, and retains attempt history for future comparison.

Safety boundary - non-negotiable

This is a defensive education sandbox. Use reserved example domains, invalid training numbers, generated identities, inert files and local routes only. Do not transmit messages, access real accounts, collect real passwords/OTPs/payment data, invoke a real dialer, resolve DNS, or expose genuine unit information.

Contents

Document Purpose and Use	2
Contents	3
1. Product Scope and Design Principles	4
2. Screen 1 - Login / Identification	5
Required states	5
3. Screen 2 - Post-Login Dashboard	6
4. Common Simulation UI and State Model	7
Canonical six-stage state machine	7
5. Scoring, Randomization and Attempt Rules	8
6. Data, Administration and Acceptance Criteria	9
Admin / instructor minimum	9
Release acceptance checklist	9
Scenario Bank: WhatsApp	10
Scenario Bank: Instagram	36
Scenario Bank: Email	62
Scenario Bank: SMS	88
7. Results, Feedback and Progress Comparison	114
8. Authoritative Research Basis	115
Appendix A - Scenario Content Authoring Schema	116

1. Product Scope and Design Principles

The product measures judgment, not memorization. Normal and harmful communications are mixed so that reporting everything is not a winning strategy. The engine records the decision path - sender inspection, link/file/profile inspection, hesitation, verification, response and reporting - rather than only the final label.

Principle	Developer requirement	Acceptance signal
Realistic but recognizable as training	Use familiar interaction patterns and proportions, with a persistent low-salience 'TRAINING SIMULATION' rail; avoid trademark-perfect copying.	Learners can navigate naturally without mistaking the application for a live service.
Action, not quiz	Unsafe and safe controls must be interactive. Branches change local screens, score events and feedback.	Every scenario produces at least six ordered UI events.
Balanced discrimination	At least 20% of the bank is legitimate-but-plausibly-suspicious; false reporting and unnecessary abandonment can lose marks.	Bank totals 80 malicious + 20 legitimate.
Context-aware difficulty	Difficulty reflects cue quality, premise alignment, sender familiarity and number of verification steps - not only grammar mistakes.	Each platform has 8 easy, 9 medium and 8 hard cases.
Military relevance without exposure	Use fictional Unit Falcon/HQ Alpha-style entities. Never use real names, locations, schedules, capabilities, rosters or procedures.	Military-context tag is visible to content authors, never populated from live data.
Offline containment	All browser, file, QR, call, login and payment experiences are local mocks behind a deny-by-default network boundary.	Network-off test completes all 100 scenarios.

Research-to-design note
NIST SP 800-50 Rev. 1 supports lifecycle-based learning, behavior change, evaluation and continuous improvement. NIST's Phish Scale shows why message difficulty and recipient context should accompany click/report metrics. CISA, Google, Meta/WhatsApp, I4C, CERT-In, RBI, FTC, NSA and Army guidance consistently reinforce pausing, inspecting, independently verifying, protecting secrets, reporting and limiting social-media exposure.

2. Screen 1 - Login / Identification

The first screen establishes identity for local progress tracking; it is not an authentication replica and must not request a real password.

Region	UI component	Behavior / developer note
Header	Product title, training crest placeholder, Version, English label	Use generic artwork. Show 'OFFLINE TRAINING SYSTEM' and the current local-device status.
Identity	Full name / username field	Required; 2-60 characters; trim whitespace; reject control characters; permit common punctuation. Label must remain visible above the field.
Identity	Personal / Service Number field	Required; 3-24 alphanumeric characters plus hyphen. Store normalized value as the profile key; mask all but the last four characters on later screens.
Primary action	Start / Continue button	Disabled until client validation passes. On submit, retrieve the existing local profile or create a new one, then open the briefing/dashboard.
Existing profile	Profile found card	Show masked number, last attempt date, attempts completed and 'Continue as this learner'. Never reveal another learner's results before confirmation.
Errors	Inline field errors + non-blocking banner	Differentiate required, format, duplicate active session and local storage unavailable. Preserve valid field values after errors.
Support	Offline indicator, accessibility, privacy note, help	Keyboard navigable; high-contrast focus; 200% zoom; note that actions are simulated and training records stay on the local system.
Footer	Instructor help / Exit	Help shows locally stored rules and the approved unit support route. Exit returns to the device welcome screen without retaining unsubmitted fields.

Login data contract
Create/read LearnerProfile {profile_id, display_name, service_no_normalized, service_no_masked, created_at, last_seen_at}. Do not add password, Aadhaar, phone, email, rank or real unit fields to Version 1. Log consent/briefing acknowledgement as a versioned boolean and timestamp.

Required states

State	Visual response	Next transition
Blank	Empty fields, short instruction, Start disabled.	Typing -> Validating
Validating	Inline checks; no full-page spinner.	Valid -> Profile lookup; invalid -> Error
New profile	One-line confirmation and briefing acknowledgement.	Confirm -> Dashboard
Returning profile	Masked match and last-attempt summary.	Continue -> Dashboard
Storage error	Plain-language banner; Retry and instructor support controls.	Retry -> lookup; Exit -> Welcome

3. Screen 2 - Post-Login Dashboard

The dashboard is the persistent anchor and should feel like a simulated mobile communication hub on a desktop screen. Scenarios arrive as timed notifications; the learner enters the relevant app from a toast or tile and returns here after each resolution.

Zone	Component	Behavior / developer note
Top rail	Training banner + notification bar	Persistent 'TRAINING SIMULATION - OFFLINE'. Show local clock, sound state, connection-off indicator and the latest synthetic notification.
Learner	Profile chip	Display name + masked service number; menu contains attempt history, accessibility, restart (instructor-controlled) and logout.
Attempt	Progress card	Scenario n/10, segmented progress bar, elapsed time and status. Hide the running score in assessment mode; training mode may show points after feedback.
App grid	WhatsApp, Instagram, Email, SMS/Text tiles	Four equally weighted tiles with recognizable generic icons, unread badges, last-event preview and status dot. Do not lock apps into a fixed sequence.
Notifications	Stacked toast tray	Queue at most three. Clicking a toast deep-links to its scenario; dismiss logs an event but does not remove the required scenario.
Scenario queue	Orchestrator status	Display 'New activity will arrive shortly' and a Resume button after interruption. Do not reveal difficulty, malicious/legitimate label or attack family.
Support	Rules / Report simulation issue	Rules explain synthetic content and safe operation. Simulation-issue report is separate from the scenario's report-phishing control.
Completion	Results gateway	After 10 resolved scenarios, replace app grid CTA with View results. Preserve attempt atomically before displaying feedback.

Notification behavior
Deliver the next event 1-4 seconds after the dashboard becomes idle. Badge count, toast preview and app list must all reflect the same scenario state. If the learner opens the wrong app, show only benign background items and log navigation; never expose which tile is 'correct'.

4. Common Simulation UI and State Model

Shared component	Required behavior	Containment / scoring note
Simulation shell	Centered mobile viewport (target 390 x 844 logical px) within responsive desktop frame; optional full-width email view.	Persistent training rail outside the simulated app; scenario content cannot escape its root.
Safe browser	Render reserved .example or training.local pages with address bar, Back, Close and page states.	Block DNS/network. Clicking is scoreable; typed data is replaced by tokens and never treated as real.
File viewer	Preview inert PDF/image/text; risky file types show a simulated open/install branch.	Never execute, extract macros, mount archives or call host handlers.
QR inspector	Decode only a scenario-supplied local payload and show the full synthetic target before an Open choice.	Camera and host clipboard are disabled.
Call / voice screen	Synthetic caller, timer, captions and choices: Decline, Accept, End, Verify, Report.	Use generated audio or text captions; no microphone/camera permission and no real dialer.
Trusted Directory	Search synthetic official contacts and compare with sender; show provenance such as 'local approved directory'.	Numbers/links inside the suspect message cannot populate the trusted result.
Action sheet	Reply, Forward, Delete, Mark safe, Verify, Report, Block/Restrict as appropriate.	Every choice emits a stable event code and can trigger a branch; avoid disabling the wrong option.
Rationale input	Optional 250-character one-line explanation in selected scenarios.	Sanitize locally; no paste of real secrets; store only if policy permits.
Feedback card	Result, points, observed cues, preferred action, impact and one prevention habit.	Training mode immediate; assessment mode may defer detail until attempt completion.

Canonical six-stage state machine

State	Entry	Allowed transitions	Core events
1 Notify	Dashboard idle	Open toast/tile -> 2; dismiss -> remain	notification_seen, notification_dismissed, open_latency_ms
2 Open	App routed	Read -> 3; premature action -> 4	item_opened, dwell_ms, premature_reply
3 Inspect	Detail controls available	Inspect -> 4; skip -> 4	sender_inspected, link_hover_ms, profile_viewed, file_previewed
4 Branch	Risk/legitimate action exposed	Safe refusal/use -> 5; risky action -> local consequence -> 5	link_opened, reply_sent, data_submitted, payment_attempted, install_attempted
5 Verify	Action/verification tools available	Trusted check/report -> 6; in-message check -> 4 or 6	verify_started, verify_source, report_selected, block_selected
6 Resolve	Final action chosen	Feedback -> dashboard; abandon -> resumable	resolution_code, rationale, scenario_points, duration_ms

5. Scoring, Randomization and Attempt Rules

Each scenario awards up to 10 points. Positive evidence is earned; unsafe or unjustifiably over-cautious behavior subtracts points. Clamp each scenario to 0-10, then sum 10 scenarios for a 0-100 attempt score.

Event	Points	Rule
INSPECT_CONTEXT	+2	Inspect a meaningful sender/link/file/profile/thread signal before acting.
SAFE_PIVOT / CORRECT_USE	+3	Refuse the malicious pivot or correctly use the legitimate in-app path.
TRUSTED_VERIFY	+3	Verify through a known, independent source - not contact data supplied by the message.
RESOLVE_CORRECT	+2	Report/block/retain/continue as the verified disposition requires.
PREMATURE_REPLY	-1	Reply or act before reading context.
RISKY_OPEN / REPLY	-3	Open a suspect link/file, call the supplied number, or engage a stranger.
SECRET / PAYMENT / INSTALL / DATA RELEASE	-8	Submit a password/OTP/PIN, attempt payment, install an app, approve device link, or disclose protected details.
FALSE REPORT / BLOCK	-4	Report/block a legitimate item despite sufficient confirming evidence.
NEEDLESS REJECT / IGNORE	-2	Abandon a legitimate time-relevant task without using the available verification path.

Attempt constraint	Version 1 rule
Scenario count	Exactly 10 resolved scenarios.
Platform coverage	Use a rotating 3/3/2/2 allocation so every platform appears and long-run exposure is balanced.
Difficulty	Target 3 Easy, 4 Medium and 3 Hard. Permit one-step relaxation only if exclusions make selection impossible.
Disposition	Exactly 8 malicious/deceptive and 2 legitimate, with legitimate items from different platforms.
Military context	Include 2-4 fictional military-context cases per attempt; never populate from real unit data.
Variety	At least five psychological triggers; no attack family more than twice.
Repeat control	Exclude the learner's most recent 20 scenario IDs where possible; store the deterministic selection seed.
Adaptation	Do not change difficulty mid-attempt in scored baseline mode. Adaptive practice is a separate mode so comparisons remain meaningful.
Integrity	Persist event ledger and scenario result transactionally before issuing the next dashboard notification.

Interpretation safeguard
Do not label a learner psychologically vulnerable from a single mistake. Report behavior by scenario family/trigger and show confidence only after repeated exposure. Difficulty and recipient context should accompany click/report rates; NIST's Phish Scale supports this contextual interpretation.

6. Data, Administration and Acceptance Criteria

Entity	Minimum fields
LearnerProfile	profile_id, display_name, service_no_normalized, service_no_masked, briefing_version, created_at, last_seen_at
ScenarioDefinition	scenario_id, platform, level, disposition, family, trigger, military_flag, version, six states, expected actions, feedback, active
Attempt	attempt_id, profile_id, seed, mode, started_at, completed_at, status, total_score, version
ScenarioRun	run_id, attempt_id, scenario_id, ordinal, started_at, resolved_at, score_0_10, outcome_code
Event	event_id, run_id, sequence, event_code, client_ts, elapsed_ms, synthetic_target_id, points_delta, metadata_allowlist
ProgressSnapshot	profile_id, attempt_count, last_score, best_score, platform/family aggregates, generated_at

Admin / instructor minimum

Capability	Requirement
Scenario manager	Create/edit/clone/deactivate versioned scenarios; validate all six stages and synthetic asset references before publishing.
Attempt viewer	Filter by learner and date; show scores, action path and remediation without exposing sensitive typed content.
Exports	Offline CSV/PDF summary to an instructor-selected local path; clearly mark training data and version.
Controls	Reset an incomplete attempt, archive a profile under local policy, and configure training vs assessment feedback timing.
Audit	Append-only change log for scenario publication, resets, exports and configuration changes.

Release acceptance checklist

Area	Pass condition
Content	100 active scenarios: 25 per platform; each has 6 stages, scoring, end-state and feedback; totals match the documented mix.
Offline safety	With network disabled, all scenarios, assets, reports and feedback work. Network monitor shows no outbound attempts.
Scoring	Automated tests cover the safe path, every critical unsafe action, false-positive penalties and 0-10 clamping.
State recovery	Closing/reopening resumes at the last committed state without duplicating points or skipping events.
Accessibility	Keyboard-only completion, visible focus, readable contrast, labels, 200% zoom and no color-only meaning.
Privacy	No real password/OTP/payment/biometric field; logs use event allowlists; exports are explicit and local.
Consistency	Badge, toast, app list, thread and backend state remain synchronized under interruption and retry.

Scenario Bank: WhatsApp

Twenty-five six-stage scenarios for the simulated WhatsApp environment. Composition: 8 easy, 9 medium, 8 hard; 20 malicious/deceptive and 5 legitimate controls; 10 fictional military-context cases.

Implementation rule

All senders, messages, accounts, numbers, links, QR codes, files, calls and payment screens are synthetic. No scenario may resolve outside the local application. The learner can take unsafe-looking actions, but they only change local state and scoring.

ID	Scenario	Level	Case	Family	M	ID	Scenario	Level	Case	Family	M
W01	The Accidental Login Code	Easy	Malicious	Account takeover / OTP theft		W14	Movement Order APK	Medium	Malicious	Military spearphishing / malicious app	Y
W02	Parcel Redelivery Fee	Easy	Malicious	Delivery impersonation / payment phishing		W15	Senior's Urgent Voice Note	Medium	Malicious	Synthetic-media impersonation / data request	Y
W03	Known Sports Meet Group	Easy	Legitimate	Legitimate group invitation	Y	W16	Verified Vehicle-Pool Change	Medium	Legitimate	Legitimate operational administration	Y
W04	Friend on a New Number	Easy	Malicious	Known-contact impersonation / emergency payment		W17	Part-Time Rating Tasks	Medium	Malicious	Task/job scam	
W05	KYC Suspension Warning	Easy	Malicious	Bank impersonation / credential phishing		W18	Hijacked Group Admin Roster Link	Hard	Malicious	Compromised admin / group spearphishing	Y
W06	Unit Clerk ID Photo Request	Easy	Malicious	Military impersonation / information collection	Y	W19	Commander Clone Requests Location	Hard	Malicious	Military impersonation / location collection	Y
W07	Expected Family Document	Easy	Legitimate	Legitimate document exchange		W20	Supplier Bank-Detail Change	Hard	Malicious	Procurement impersonation / payment diversion	
W08	Festival Reward QR	Easy	Malicious	Prize scam / QR phishing		W21	Verified Senior Requests Secure Follow-Up	Hard	Legitimate	Legitimate minimal notification	Y
W09	Compromised Colleague Gift Cards	Medium	Malicious	Compromised-contact fraud	Y	W22	Long-Game Online Friendship	Hard	Malicious	Relationship grooming / investment fraud	
W10	Survey Device-Link QR	Medium	Malicious	Linked-device takeover / QR deception		W23	Family Welfare Pretext	Hard	Malicious	Military-family targeting / operational elicitation	Y
W11	Expected Welfare Appointment	Medium	Legitimate	Legitimate appointment confirmation		W24	Remote Support Screen Share	Hard	Malicious	Tech-support scam / remote access	
W12	Digital Arrest Escalation	Medium	Malicious	Government impersonation / digital arrest		W25	Known Contact Sends a Linking Code	Hard	Malicious	Compromised-contact device linking	
W13	Guaranteed IPO Group	Medium	Malicious	Investment-group fraud							

The Accidental Login Code

Platform WhatsApp	Difficulty Easy	Disposition Malicious	Attack / case family Account takeover / OTP theft	Primary trigger Helpfulness + urgency
----------------------	--------------------	--------------------------	--	--

Stage	Learner flow + synthetic content	UI to build	Expected safe behavior	Scoring event
1 Event	Dashboard notification: 'Unknown: I sent a 6-digit code to you by mistake. Please send it back now.' The WhatsApp badge increments and the toast routes into the scenario.	Dashboard toast, WhatsApp-style tile, unread badge, timestamp and synthetic sender preview.	Notice the source and time; open the full item before acting. Do not reply from the preview.	NOTIFY_SEEN +0; open latency and route logged.
2 Open	Open the unread chat from an unsaved number. Context presented: An unknown number apologizes for entering the learner's number by mistake.	Chat list, unread pill, thread header, bubbles, delivery ticks and prior-message history.	Read the full thread/message and prior context before choosing any action.	ITEM_OPEN +0; premature reply/action -1; dwell time logged.
3 Inspect	Open details and examine the full number, absent mutual groups and the system code warning	Contact/group info sheet with full number, mutual groups, join date, media and report controls.	Check this decision signal: A genuine login code is secret and the requester cannot need a code delivered to someone else.	INSPECT_CONTEXT +2; inspection path and time logged.
4 Branch	The interaction advances to a simulated system-code bubble followed by a reply composer	Chat-native preview plus offline safe browser/file viewer/call screen; every risky control remains selectable and scored.	Do not type or forward the six-digit code. Use Back/Close or safe preview only; no secret, payment, install or data release.	SAFE_PIVOT +3; risky open/reply -3; secret/payment/install/data release -8.
5 Verify	The learner opens Verify / More actions. Verification route: check account activity/linked devices from Settings, not through the stranger	Three-dot action sheet and independent Trusted Directory overlay; in-message numbers are never treated as trusted.	Verify independently: check account activity/linked devices from Settings, not through the stranger Then use the platform report/block path or the unit reporting route.	TRUSTED_VERIFY +3; report-only without checking +1; verification through message +0.
6 Resolve	Final expected resolution: do not reply; report and block the number; review linked devices	Outcome card, concise feedback, warning-sign chips, event summary and Return to dashboard.	Complete the resolution and return to the dashboard.	RESOLVE_CORRECT +2; contradictory unsafe final -4; scenario capped 0-10.

End-state Chat closes as Reported + Blocked; account-security checklist is offered locally.	Concise learner feedback Never share a login or verification code. An 'accidental' code request is an account-takeover attempt.
--	--

Parcel Redelivery Fee

Platform WhatsApp	Difficulty Easy	Disposition Malicious	Attack / case family Delivery impersonation / payment phishing	Primary trigger Urgency + curiosity
----------------------	--------------------	--------------------------	---	--

Stage	Learner flow + synthetic content	UI to build	Expected safe behavior	Scoring event
1 Event	Dashboard notification: 'QuickParcel Support: Delivery failed. Pay INR 25 today to avoid return.' The WhatsApp badge increments and the toast routes into the scenario.	Dashboard toast, WhatsApp-style tile, unread badge, timestamp and synthetic sender preview.	Notice the source and time; open the full item before acting. Do not reply from the preview.	NOTIFY_SEEN +0; open latency and route logged.
2 Open	Open the business chat and parcel card. Context presented: A business-style account claims a parcel cannot be delivered until a small fee is paid.	Chat list, unread pill, thread header, bubbles, delivery ticks and prior-message history.	Read the full thread/message and prior context before choosing any action.	ITEM_OPEN +0; premature reply/action -1; dwell time logged.
3 Inspect	Open details and examine business-account details, spelling, tracking number and preview domain	Contact/group info sheet with full number, mutual groups, join date, media and report controls.	Check this decision signal: The learner did not expect this parcel and the link uses parcel-help.training.example rather than a known portal.	INSPECT_CONTEXT +2; inspection path and time logged.
4 Branch	The interaction advances to an offline tracking page requesting card/UPI details	Chat-native preview plus offline safe browser/file viewer/call screen; every risky control remains selectable and scored.	Do not enter payment information or approve a collect request. Use Back/Close or safe preview only; no secret, payment, install or data release.	SAFE_PIVOT +3; risky open/reply -3; secret/payment/install/data release -8.
5 Verify	The learner opens Verify / More actions. Verification route: open the known courier app/site from the Trusted Directory and search the tracking number	Three-dot action sheet and independent Trusted Directory overlay; in-message numbers are never treated as trusted.	Verify independently: open the known courier app/site from the Trusted Directory and search the tracking number Then use the platform report/block path or the unit reporting route.	TRUSTED_VERIFY +3; report-only without checking +1; verification through message +0.
6 Resolve	Final expected resolution: close the page; report/block the sender; retain the synthetic tracking evidence	Outcome card plus 250-character rationale box, warning-sign chips, event summary and Return to dashboard.	Complete the resolution and return to the dashboard. Add a one-line reason without sensitive data.	RESOLVE_CORRECT +2; contradictory unsafe final -4; scenario capped 0-10.

End-state The fake checkout records no data and returns to a reported chat.	Concise learner feedback Small fees are used to lower caution. Verify an expected parcel in the official service, never through the message link.
--	--

Known Sports Meet Group

Platform WhatsApp	Difficulty Easy	Disposition Legitimate	Attack / case family Legitimate group invitation	Primary trigger Familiarity FICTIONAL MILITARY CONTEXT
----------------------	--------------------	---------------------------	---	---

Stage	Learner flow + synthetic content	UI to build	Expected safe behavior	Scoring event
1 Event	Dashboard notification: 'Recreation Coord: Unit Falcon sports meet group is ready. Please confirm attendance in the poll.' The WhatsApp badge increments and the toast routes into the scenario.	Dashboard toast, WhatsApp-style tile, unread badge, timestamp and synthetic sender preview.	Notice the source and time; open the full item before acting. Do not reply from the preview.	NOTIFY_SEEN +0; open latency and route logged.
2 Open	Open the new group thread from a saved coordinator. Context presented: A saved recreation coordinator creates the announced weekend sports group; no sensitive data or external link is requested.	Chat list, unread pill, thread header, bubbles, delivery ticks and prior-message history.	Read the full thread/message and prior context before choosing any action.	ITEM_OPEN +0; premature reply/action -1; dwell time logged.
3 Inspect	Open details and examine creator identity, known number, group participants and prior announcement	Contact/group info sheet with full number, mutual groups, join date, media and report controls.	Check this decision signal: The number matches the local directory, the event was expected, and the poll stays inside the app.	INSPECT_CONTEXT +2; inspection path and time logged.
4 Branch	The interaction advances to an in-app attendance poll with Yes/No options	Chat-native preview plus offline safe browser/file viewer/call screen; every risky control remains selectable and scored.	Use the normal in-app path only after the details match the known context. Do not switch to an untrusted channel.	CORRECT_USE +3; needless reject/ignore -2; unsafe external action -4.
5 Verify	The learner opens Verify / More actions. Verification route: compare the coordinator number with the local Trusted Directory	Three-dot action sheet and independent Trusted Directory overlay; in-message numbers are never treated as trusted.	Verify independently: compare the coordinator number with the local Trusted Directory. If it matches, continue; do not report or block a legitimate sender.	TRUSTED_VERIFY +3; false report/block -4; verification through message +0.
6 Resolve	Final expected resolution: answer the in-app poll and keep the group; do not report or block	Outcome card, concise feedback, warning-sign chips, event summary and Return to dashboard.	Complete the resolution and return to the dashboard.	RESOLVE_CORRECT +2; contradictory unsafe final -4; scenario capped 0-10.

End-state Poll choice is saved; group remains available as legitimate background traffic.	Concise learner feedback Not every new group is hostile. Match sender, context and requested action, then proceed without oversharing.
--	---

W04

Friend on a New Number

Platform WhatsApp	Difficulty Easy	Disposition Malicious	Attack / case family Known-contact impersonation / emergency payment	Primary trigger Empathy + urgency
Stage	Learner flow + synthetic content	UI to build	Expected safe behavior	Scoring event
1 Event	Dashboard notification: 'Riya (new number): Phone broke. Please send INR 8,000 for the clinic before 20:00.' The WhatsApp badge increments and the toast routes into the scenario.	Dashboard toast, WhatsApp-style tile, unread badge, timestamp and synthetic sender preview.	Notice the source and time; open the full item before acting. Do not reply from the preview.	NOTIFY_SEEN +0; open latency and route logged.
2 Open	Open the chat with a familiar profile photo but no history. Context presented: An unsaved number uses a friend's name and says their phone was damaged.	Chat list, unread pill, thread header, bubbles, delivery ticks and prior-message history.	Read the full thread/message and prior context before choosing any action.	ITEM_OPEN +0; premature reply/action -1; dwell time logged.
3 Inspect	Open details and examine number, account age, mutual groups and writing style	Contact/group info sheet with full number, mutual groups, join date, media and report controls.	Check this decision signal: The number is new, there is no shared history, and the payment request is urgent and unusual.	INSPECT_CONTEXT +2; inspection path and time logged.
4 Branch	The interaction advances to a UPI request card bearing an unrelated synthetic payee name	Chat-native preview plus offline safe browser/file viewer/call screen; every risky control remains selectable and scored.	Do not approve the payment or ask only in the same chat. Use Back/Close or safe preview only; no secret, payment, install or data release.	SAFE_PIVOT +3; risky open/reply -3; secret/payment/install/data release -8.
5 Verify	The learner opens Verify / More actions. Verification route: call the saved old number or another known family contact	Three-dot action sheet and independent Trusted Directory overlay; in-message numbers are never treated as trusted.	Verify independently: call the saved old number or another known family contact Then use the platform report/block path or the unit reporting route.	TRUSTED_VERIFY +3; report-only without checking +1; verification through message +0.
6 Resolve	Final expected resolution: decline the request; report/block the clone after the known friend confirms impersonation	Outcome card, concise feedback, warning-sign chips, event summary and Return to dashboard.	Complete the resolution and return to the dashboard.	RESOLVE_CORRECT +2; contradictory unsafe final -4; scenario capped 0-10.
End-state Payment remains unexecuted; the verified friend call reveals the clone.		Concise learner feedback A photo and name are easy to copy. Verify a new-number emergency through a contact route you already trust.		

W05

KYC Suspension Warning

Platform WhatsApp	Difficulty Easy	Disposition Malicious	Attack / case family Bank impersonation / credential phishing	Primary trigger Fear + urgency
----------------------	--------------------	--------------------------	--	-----------------------------------

Stage	Learner flow + synthetic content	UI to build	Expected safe behavior	Scoring event
1 Event	Dashboard notification: 'NationalPay KYC: Your wallet will be blocked in 30 minutes. Update now.' The WhatsApp badge increments and the toast routes into the scenario.	Dashboard toast, WhatsApp-style tile, unread badge, timestamp and synthetic sender preview.	Notice the source and time; open the full item before acting. Do not reply from the preview.	NOTIFY_SEEN +0; open latency and route logged.
2 Open	Open the business chat and warning card. Context presented: A logo-bearing account threatens immediate wallet suspension unless KYC is updated.	Chat list, unread pill, thread header, bubbles, delivery ticks and prior-message history.	Read the full thread/message and prior context before choosing any action.	ITEM_OPEN +0; premature reply/action -1; dwell time logged.
3 Inspect	Open details and examine full number, business verification state and target domain	Contact/group info sheet with full number, mutual groups, join date, media and report controls.	Check this decision signal: The account is unverified, uses a countdown, and routes outside the known banking app.	INSPECT_CONTEXT +2; inspection path and time logged.
4 Branch	The interaction advances to a synthetic KYC form asking for account, PIN and OTP	Chat-native preview plus offline safe browser/file viewer/call screen; every risky control remains selectable and scored.	Do not submit account credentials, PIN, OTP or identity document. Use Back/Close or safe preview only; no secret, payment, install or data release.	SAFE_PIVOT +3; risky open/reply -3; secret/payment/install/data release -8.
5 Verify	The learner opens Verify / More actions. Verification route: open the known banking app directly or call the number printed on the simulated card	Three-dot action sheet and independent Trusted Directory overlay; in-message numbers are never treated as trusted.	Verify independently: open the known banking app directly or call the number printed on the simulated card Then use the platform report/block path or the unit reporting route.	TRUSTED_VERIFY +3; report-only without checking +1; verification through message +0.
6 Resolve	Final expected resolution: close the form; report/block the sender; verify account status independently	Outcome card, concise feedback, warning-sign chips, event summary and Return to dashboard.	Complete the resolution and return to the dashboard.	RESOLVE_CORRECT +2; contradictory unsafe final -4; scenario capped 0-10.

End-state The official-app mock shows no KYC issue; suspicious chat is quarantined.	Concise learner feedback Banks do not need your PIN or OTP in chat. Open the official app yourself and verify before taking action.
--	--

W06

Unit Clerk ID Photo Request

Platform WhatsApp	Difficulty Easy	Disposition Malicious	Attack / case family Military impersonation / information collection	Primary trigger Authority FICTIONAL MILITARY CONTEXT
----------------------	--------------------	--------------------------	---	---

Stage	Learner flow + synthetic content	UI to build	Expected safe behavior	Scoring event
1 Event	Dashboard notification: 'Unit Clerk: Send front/back service ID photo now for today's database audit.' The WhatsApp badge increments and the toast routes into the scenario.	Dashboard toast, WhatsApp-style tile, unread badge, timestamp and synthetic sender preview.	Notice the source and time; open the full item before acting. Do not reply from the preview.	NOTIFY_SEEN +0; open latency and route logged.
2 Open	Open the unsaved chat and attached 'audit notice' image. Context presented: An unknown account uses a generic crest and claims a personnel database update is due immediately.	Chat list, unread pill, thread header, bubbles, delivery ticks and prior-message history.	Read the full thread/message and prior context before choosing any action.	ITEM_OPEN +0; premature reply/action -1; dwell time logged.
3 Inspect	Open details and examine number, missing mutual group, generic crest and request for ID imagery	Contact/group info sheet with full number, mutual groups, join date, media and report controls.	Check this decision signal: The request bypasses the approved administrative channel and asks for sensitive identity material in chat.	INSPECT_CONTEXT +2; inspection path and time logged.
4 Branch	The interaction advances to a media composer preloaded with a synthetic service-card image	Chat-native preview plus offline safe browser/file viewer/call screen; every risky control remains selectable and scored.	Do not send an ID image, roster data or personal document. Use Back/Close or safe preview only; no secret, payment, install or data release.	SAFE_PIVOT +3; risky open/reply -3; secret/payment/install/data release -8.
5 Verify	The learner opens Verify / More actions. Verification route: contact the unit clerk through the approved internal directory or in person	Three-dot action sheet and independent Trusted Directory overlay; in-message numbers are never treated as trusted.	Verify independently: contact the unit clerk through the approved internal directory or in person Then use the platform report/block path or the unit reporting route.	TRUSTED_VERIFY +3; report-only without checking +1; verification through message +0.
6 Resolve	Final expected resolution: cancel the upload; report the impersonation via unit procedure; block the account	Outcome card plus 250-character rationale box, warning-sign chips, event summary and Return to dashboard.	Complete the resolution and return to the dashboard. Add a one-line reason without sensitive data.	RESOLVE_CORRECT +2; contradictory unsafe final -4; scenario capped 0-10.

End-state No image leaves the device; the event is marked as protected-information refusal.	Concise learner feedback Rank or authority claims do not replace procedure. Never send service documents to an unverified chat account.
--	--

Expected Family Document

Platform WhatsApp	Difficulty Easy	Disposition Legitimate	Attack / case family Legitimate document exchange	Primary trigger Familiarity
----------------------	--------------------	---------------------------	--	--------------------------------

Stage	Learner flow + synthetic content	UI to build	Expected safe behavior	Scoring event
1 Event	Dashboard notification: 'Asha: Here is the invitation PDF you asked for. No form - just check the date.' The WhatsApp badge increments and the toast routes into the scenario.	Dashboard toast, WhatsApp-style tile, unread badge, timestamp and synthetic sender preview.	Notice the source and time; open the full item before acting. Do not reply from the preview.	NOTIFY_SEEN +0; open latency and route logged.
2 Open	Open the saved-contact thread with visible request history. Context presented: A saved family contact sends the event invitation PDF the learner requested earlier in the same thread.	Chat list, unread pill, thread header, bubbles, delivery ticks and prior-message history.	Read the full thread/message and prior context before choosing any action.	ITEM_OPEN +0; premature reply/action -1; dwell time logged.
3 Inspect	Open details and examine known number, matching conversation and PDF type/size	Contact/group info sheet with full number, mutual groups, join date, media and report controls.	Check this decision signal: The file is expected, the sender matches the saved contact, and the preview requests no sign-in or installation.	INSPECT_CONTEXT +2; inspection path and time logged.
4 Branch	The interaction advances to the inert PDF preview showing only event details	Chat-native preview plus offline safe browser/file viewer/call screen; every risky control remains selectable and scored.	Use the normal in-app path only after the details match the known context. Do not switch to an untrusted channel.	CORRECT_USE +3; needless reject/ignore -2; unsafe external action -4.
5 Verify	The learner opens Verify / More actions. Verification route: use the existing thread context; optional known-number call if anything differs	Three-dot action sheet and independent Trusted Directory overlay; in-message numbers are never treated as trusted.	Verify independently: use the existing thread context; optional known-number call if anything differs. If it matches, continue; do not report or block a legitimate sender.	TRUSTED_VERIFY +3; false report/block -4; verification through message +0.
6 Resolve	Final expected resolution: preview the PDF and retain it; do not report or block the sender	Outcome card, concise feedback, warning-sign chips, event summary and Return to dashboard.	Complete the resolution and return to the dashboard.	RESOLVE_CORRECT +2; contradictory unsafe final -4; scenario capped 0-10.

End-state Viewer closes normally and the chat is marked read.	Concise learner feedback Context matters. An expected inert document from a verified contact can be handled normally after inspection.
--	---

Festival Reward QR

Platform WhatsApp	Difficulty Easy	Disposition Malicious	Attack / case family Prize scam / QR phishing	Primary trigger Greed + scarcity
----------------------	--------------------	--------------------------	--	-------------------------------------

Stage	Learner flow + synthetic content	UI to build	Expected safe behavior	Scoring event
1 Event	Dashboard notification: 'Forwarded many times: Scan to claim a INR 5,000 festival voucher - 12 left.' The WhatsApp badge increments and the toast routes into the scenario.	Dashboard toast, WhatsApp-style tile, unread badge, timestamp and synthetic sender preview.	Notice the source and time; open the full item before acting. Do not reply from the preview.	NOTIFY_SEEN +0; open latency and route logged.
2 Open	Open the forwarded message in a community chat. Context presented: A forwarded message promises a time-limited shopping voucher to the first 500 scanners.	Chat list, unread pill, thread header, bubbles, delivery ticks and prior-message history.	Read the full thread/message and prior context before choosing any action.	ITEM_OPEN +0; premature reply/action -1; dwell time logged.
3 Inspect	Open details and examine forwarded label, unknown origin, expiry language and QR target	Contact/group info sheet with full number, mutual groups, join date, media and report controls.	Check this decision signal: The reward is unsolicited, scarce, and the QR hides a synthetic credential/payment site.	INSPECT_CONTEXT +2; inspection path and time logged.
4 Branch	The interaction advances to the local QR inspector and then a claim form	Chat-native preview plus offline safe browser/file viewer/call screen; every risky control remains selectable and scored.	Do not open the target, enter login/payment details or forward the message. Use Back/Close or safe preview only; no secret, payment, install or data release.	SAFE_PIVOT +3; risky open/reply -3; secret/payment/install/data release -8.
5 Verify	The learner opens Verify / More actions. Verification route: check the retailer's known app/site from the Trusted Directory	Three-dot action sheet and independent Trusted Directory overlay; in-message numbers are never treated as trusted.	Verify independently: check the retailer's known app/site from the Trusted Directory Then use the platform report/block path or the unit reporting route.	TRUSTED_VERIFY +3; report-only without checking +1; verification through message +0.
6 Resolve	Final expected resolution: close the QR flow; report the message; do not forward it	Outcome card, concise feedback, warning-sign chips, event summary and Return to dashboard.	Complete the resolution and return to the dashboard.	RESOLVE_CORRECT +2; contradictory unsafe final -4; scenario capped 0-10.
End-state The claim is rejected locally and the forwarded item is flagged as deceptive.		Concise learner feedback QR codes are links with less visible context. Inspect the destination and verify the offer independently.		

Compromised Colleague Gift Cards

Platform WhatsApp	Difficulty Medium	Disposition Malicious	Attack / case family Compromised-contact fraud	Primary trigger Authority + urgency FICTIONAL MILITARY CONTEXT
----------------------	----------------------	--------------------------	---	---

Stage	Learner flow + synthetic content	UI to build	Expected safe behavior	Scoring event
1 Event	Dashboard notification: 'Maj. Arin: Can't talk. Buy four gift cards for visitors and send the codes in 10 minutes.' The WhatsApp badge increments and the toast routes into the scenario.	Dashboard toast, WhatsApp-style tile, unread badge, timestamp and synthetic sender preview.	Notice the source and time; open the full item before acting. Do not reply from the preview.	NOTIFY_SEEN +0; open latency and route logged.
2 Open	Open the saved-contact thread with normal history. Context presented: A saved colleague's genuine account sends an out-of-character request while claiming to be in a meeting.	Chat list, unread pill, thread header, bubbles, delivery ticks and prior-message history.	Read the full thread/message and prior context before choosing any action.	ITEM_OPEN +0; premature reply/action -1; dwell time logged.
3 Inspect	Open details and examine message style, unusual payment method, secrecy and inability to call	Contact/group info sheet with full number, mutual groups, join date, media and report controls.	Check this decision signal: A genuine account can be compromised; gift-card codes and refusal of voice confirmation are strong warning signs.	INSPECT_CONTEXT +2; inspection path and time logged.
4 Branch	The interaction advances to a gift-card purchase mock followed by an image/code composer	Chat-native preview plus offline safe browser/file viewer/call screen; every risky control remains selectable and scored.	Do not buy cards, send codes or keep the request secret. Use Back/Close or safe preview only; no secret, payment, install or data release.	SAFE_PIVOT +3; risky open/reply -3; secret/payment/install/data release -8.
5 Verify	The learner opens Verify / More actions. Verification route: call the colleague through the known directory or confirm with the duty office	Three-dot action sheet and independent Trusted Directory overlay; in-message numbers are never treated as trusted.	Verify independently: call the colleague through the known directory or confirm with the duty office Then use the platform report/block path or the unit reporting route.	TRUSTED_VERIFY +3; report-only without checking +1; verification through message +0.
6 Resolve	Final expected resolution: stop the transaction; report the compromised-account message and alert the verified colleague	Outcome card, concise feedback, warning-sign chips, event summary and Return to dashboard.	Complete the resolution and return to the dashboard.	RESOLVE_CORRECT +2; contradictory unsafe final -4; scenario capped 0-10.

End-state Known-channel verification shows the colleague did not send the request.	Concise learner feedback Trust the person, not an unusual message from their account. Verify high-impact requests out of band.
---	---

Survey Device-Link QR

Platform WhatsApp	Difficulty Medium	Disposition Malicious	Attack / case family Linked-device takeover / QR deception	Primary trigger Convenience + authority
----------------------	----------------------	--------------------------	---	--

Stage	Learner flow + synthetic content	UI to build	Expected safe behavior	Scoring event
1 Event	Dashboard notification: 'WhatsApp Survey Desk: Scan this QR on Linked Devices to verify your feedback account.' The WhatsApp badge increments and the toast routes into the scenario.	Dashboard toast, WhatsApp-style tile, unread badge, timestamp and synthetic sender preview.	Notice the source and time; open the full item before acting. Do not reply from the preview.	NOTIFY_SEEN +0; open latency and route logged.
2 Open	Open the support chat and QR image. Context presented: A fake support account offers a service survey and says scanning a QR will validate participation.	Chat list, unread pill, thread header, bubbles, delivery ticks and prior-message history.	Read the full thread/message and prior context before choosing any action.	ITEM_OPEN +0; premature reply/action -1; dwell time logged.
3 Inspect	Open details and examine unsaved sender, instruction to open Linked Devices and QR purpose	Contact/group info sheet with full number, mutual groups, join date, media and report controls.	Check this decision signal: Linked-device QR codes authorize another device; surveys do not need account linking.	INSPECT_CONTEXT +2; inspection path and time logged.
4 Branch	The interaction advances to a faithful local Linked Devices screen with a pending link confirmation	Chat-native preview plus offline safe browser/file viewer/call screen; every risky control remains selectable and scored.	Do not scan/approve the device link or share a linking code. Use Back/Close or safe preview only; no secret, payment, install or data release.	SAFE_PIVOT +3; risky open/reply -3; secret/payment/install/data release -8.
5 Verify	The learner opens Verify / More actions. Verification route: open Settings > Linked Devices independently and compare the request origin	Three-dot action sheet and independent Trusted Directory overlay; in-message numbers are never treated as trusted.	Verify independently: open Settings > Linked Devices independently and compare the request origin Then use the platform report/block path or the unit reporting route.	TRUSTED_VERIFY +3; report-only without checking +1; verification through message +0.
6 Resolve	Final expected resolution: cancel linking; report/block the sender; review and remove unknown linked devices	Outcome card plus 250-character rationale box, warning-sign chips, event summary and Return to dashboard.	Complete the resolution and return to the dashboard. Add a one-line reason without sensitive data.	RESOLVE_CORRECT +2; contradictory unsafe final -4; scenario capped 0-10.

End-state Pending device is rejected and the mock account remains under learner control.	Concise learner feedback A device-link QR is an account-access request, not ordinary verification. Cancel unexpected links and review devices.
---	---

Expected Welfare Appointment

Platform WhatsApp	Difficulty Medium	Disposition Legitimate	Attack / case family Legitimate appointment confirmation	Primary trigger Authority + routine
----------------------	----------------------	---------------------------	---	--

Stage	Learner flow + synthetic content	UI to build	Expected safe behavior	Scoring event
1 Event	Dashboard notification: 'Welfare Office: Your requested appointment is confirmed for 10:30. Reply C to confirm.' The WhatsApp badge increments and the toast routes into the scenario.	Dashboard toast, WhatsApp-style tile, unread badge, timestamp and synthetic sender preview.	Notice the source and time; open the full item before acting. Do not reply from the preview.	NOTIFY_SEEN +0; open latency and route logged.
2 Open	Open the verified business chat with prior reference number. Context presented: The learner initiated a welfare-office appointment in the local portal; the saved office account confirms a time.	Chat list, unread pill, thread header, bubbles, delivery ticks and prior-message history.	Read the full thread/message and prior context before choosing any action.	ITEM_OPEN +0; premature reply/action -1; dwell time logged.
3 Inspect	Open details and examine saved number, matching request ID, time and minimal reply	Contact/group info sheet with full number, mutual groups, join date, media and report controls.	Check this decision signal: The request is expected, contains no external link, and asks only for a low-risk confirmation.	INSPECT_CONTEXT +2; inspection path and time logged.
4 Branch	The interaction advances to an in-chat quick reply with Confirm/Reschedule	Chat-native preview plus offline safe browser/file viewer/call screen; every risky control remains selectable and scored.	Use the normal in-app path only after the details match the known context. Do not switch to an untrusted channel.	CORRECT_USE +3; needless reject/ignore -2; unsafe external action -4.
5 Verify	The learner opens Verify / More actions. Verification route: match the reference in the local appointment portal or Trusted Directory	Three-dot action sheet and independent Trusted Directory overlay; in-message numbers are never treated as trusted.	Verify independently: match the reference in the local appointment portal or Trusted Directory. If it matches, continue; do not report or block a legitimate sender.	TRUSTED_VERIFY +3; false report/block -4; verification through message +0.
6 Resolve	Final expected resolution: send the in-app confirmation; retain the chat; do not report it	Outcome card plus 250-character rationale box, warning-sign chips, event summary and Return to dashboard.	Complete the resolution and return to the dashboard. Add a one-line reason without sensitive data.	RESOLVE_CORRECT +2; contradictory unsafe final -4; scenario capped 0-10.

End-state Appointment is marked Confirmed and no other data is requested.	Concise learner feedback Legitimate communications align with an action you initiated and use a verifiable, limited request.
--	---

Digital Arrest Escalation

Platform WhatsApp	Difficulty Medium	Disposition Malicious	Attack / case family Government impersonation / digital arrest	Primary trigger Fear + authority + isolation
----------------------	----------------------	--------------------------	---	---

Stage	Learner flow + synthetic content	UI to build	Expected safe behavior	Scoring event
1 Event	Dashboard notification: 'Investigation Desk: Your ID is linked to a seized parcel. Join video verification now.' The WhatsApp badge increments and the toast routes into the scenario.	Dashboard toast, WhatsApp-style tile, unread badge, timestamp and synthetic sender preview.	Notice the source and time; open the full item before acting. Do not reply from the preview.	NOTIFY_SEEN +0; open latency and route logged.
2 Open	Open the chat followed by an incoming video-call screen. Context presented: An unknown caller claims a parcel linked to the learner contains contraband and demands a video call.	Chat list, unread pill, thread header, bubbles, delivery ticks and prior-message history.	Read the full thread/message and prior context before choosing any action.	ITEM_OPEN +0; premature reply/action -1; dwell time logged.
3 Inspect	Open details and examine unknown country code, fabricated case PDF and demand for secrecy	Contact/group info sheet with full number, mutual groups, join date, media and report controls.	Check this decision signal: There is no lawful 'digital arrest'; agencies do not settle allegations or demand money by WhatsApp video.	INSPECT_CONTEXT +2; inspection path and time logged.
4 Branch	The interaction advances to a synthetic video call with a uniformed avatar, countdown and 'security deposit' demand	Chat-native preview plus offline safe browser/file viewer/call screen; every risky control remains selectable and scored.	Do not stay isolated, share identity/bank data or attempt payment. Use Back/Close or safe preview only; no secret, payment, install or data release.	SAFE_PIVOT +3; risky open/reply -3; secret/payment/install/data release -8.
5 Verify	The learner opens Verify / More actions. Verification route: end the call and use a known official number/unit security route; never the supplied case contact	Three-dot action sheet and independent Trusted Directory overlay; in-message numbers are never treated as trusted.	Verify independently: end the call and use a known official number/unit security route; never the supplied case contact Then use the platform report/block path or the unit reporting route.	TRUSTED_VERIFY +3; report-only without checking +1; verification through message +0.
6 Resolve	Final expected resolution: terminate; preserve evidence; report/block; follow unit and official cybercrime reporting procedures	Outcome card plus 250-character rationale box, warning-sign chips, event summary and Return to dashboard.	Complete the resolution and return to the dashboard. Add a one-line reason without sensitive data.	RESOLVE_CORRECT +2; contradictory unsafe final -4; scenario capped 0-10.

End-state Call ends; no payment occurs; evidence card is stored in the simulated report queue.	Concise learner feedback Threats, secrecy and payment demands are coercion. End the call, verify independently and report promptly.
---	--

Guaranteed IPO Group

Platform WhatsApp	Difficulty Medium	Disposition Malicious	Attack / case family Investment-group fraud	Primary trigger Greed + social proof
----------------------	----------------------	--------------------------	--	---

Stage	Learner flow + synthetic content	UI to build	Expected safe behavior	Scoring event
1 Event	Dashboard notification: 'Alpha Wealth VIP: Guaranteed IPO allotment. Deposit today for 18% weekly returns.' The WhatsApp badge increments and the toast routes into the scenario.	Dashboard toast, WhatsApp-style tile, unread badge, timestamp and synthetic sender preview.	Notice the source and time; open the full item before acting. Do not reply from the preview.	NOTIFY_SEEN +0; open latency and route logged.
2 Open	Open the newly joined investment group. Context presented: The learner is added to a group showing fabricated profits and a supposed adviser offering guaranteed allotments.	Chat list, unread pill, thread header, bubbles, delivery ticks and prior-message history.	Read the full thread/message and prior context before choosing any action.	ITEM_OPEN +0; premature reply/action -1; dwell time logged.
3 Inspect	Open details and examine who added the learner, admin numbers, repetitive testimonials and profit claims	Contact/group info sheet with full number, mutual groups, join date, media and report controls.	Check this decision signal: Guaranteed returns, private deposits and unsolicited group additions are incompatible with regulated advice.	INSPECT_CONTEXT +2; inspection path and time logged.
4 Branch	The interaction advances to a fake trading-app page showing a small bonus and Deposit button	Chat-native preview plus offline safe browser/file viewer/call screen; every risky control remains selectable and scored.	Do not install an APK, deposit funds or share bank details. Use Back/Close or safe preview only; no secret, payment, install or data release.	SAFE_PIVOT +3; risky open/reply -3; secret/payment/install/data release -8.
5 Verify	The learner opens Verify / More actions. Verification route: check adviser registration and the broker through independently known official sources	Three-dot action sheet and independent Trusted Directory overlay; in-message numbers are never treated as trusted.	Verify independently: check adviser registration and the broker through independently known official sources Then use the platform report/block path or the unit reporting route.	TRUSTED_VERIFY +3; report-only without checking +1; verification through message +0.
6 Resolve	Final expected resolution: leave/report the group; block admins; do not install or deposit	Outcome card, concise feedback, warning-sign chips, event summary and Return to dashboard.	Complete the resolution and return to the dashboard.	RESOLVE_CORRECT +2; contradictory unsafe final -4; scenario capped 0-10.

End-state Group disappears from inbox and synthetic deposit remains zero.	Concise learner feedback Fabricated profits and early bonuses build trust. Verify registration and never fund an unsolicited social-media scheme.
--	--

Movement Order APK

Platform WhatsApp	Difficulty Medium	Disposition Malicious	Attack / case family Military spearphishing / malicious app	Primary trigger Authority + urgency FICTIONAL MILITARY CONTEXT
----------------------	----------------------	--------------------------	--	---

Stage	Learner flow + synthetic content	UI to build	Expected safe behavior	Scoring event
1 Event	Dashboard notification: 'HQ Alpha Ops: Revised movement order attached. Install viewer before 18:00.' The WhatsApp badge increments and the toast routes into the scenario.	Dashboard toast, WhatsApp-style tile, unread badge, timestamp and synthetic sender preview.	Notice the source and time; open the full item before acting. Do not reply from the preview.	NOTIFY_SEEN +0; open latency and route logged.
2 Open	Open the unknown chat with file chip MoveOrder_Viewer.apk. Context presented: A number using a senior-sounding name sends an Android package labelled as a revised movement order.	Chat list, unread pill, thread header, bubbles, delivery ticks and prior-message history.	Read the full thread/message and prior context before choosing any action.	ITEM_OPEN +0; premature reply/action -1; dwell time logged.
3 Inspect	Open details and examine file extension, unsaved number, missing official reference and install request	Contact/group info sheet with full number, mutual groups, join date, media and report controls.	Check this decision signal: A movement order would not require installing an unknown app from a chat account.	INSPECT_CONTEXT +2; inspection path and time logged.
4 Branch	The interaction advances to a simulated Android install-permission screen requesting SMS, files and accessibility	Chat-native preview plus offline safe browser/file viewer/call screen; every risky control remains selectable and scored.	Do not install the APK or grant any permission. Use Back/Close or safe preview only; no secret, payment, install or data release.	SAFE_PIVOT +3; risky open/reply -3; secret/payment/install/data release -8.
5 Verify	The learner opens Verify / More actions. Verification route: contact the operations staff through the approved internal channel and check the document system	Three-dot action sheet and independent Trusted Directory overlay; in-message numbers are never treated as trusted.	Verify independently: contact the operations staff through the approved internal channel and check the document system Then use the platform report/block path or the unit reporting route.	TRUSTED_VERIFY +3; report-only without checking +1; verification through message +0.
6 Resolve	Final expected resolution: cancel installation; report via unit cyber/security route; block the sender	Outcome card, concise feedback, warning-sign chips, event summary and Return to dashboard.	Complete the resolution and return to the dashboard.	RESOLVE_CORRECT +2; contradictory unsafe final -4; scenario capped 0-10.

End-state
Installer is closed before permission grant; the inert file is quarantined locally.

Concise learner feedback
Treat unexpected APKs as high risk. Confirm orders in the approved system and never install a chat-delivered viewer.

Senior's Urgent Voice Note

Platform WhatsApp	Difficulty Medium	Disposition Malicious	Attack / case family Synthetic-media impersonation / data request	Primary trigger Authority + familiarity FICTIONAL MILITARY CONTEXT
Stage	Learner flow + synthetic content	UI to build	Expected safe behavior	Scoring event
1 Event	Dashboard notification: 'Col. Dev (new account): Voice note - Send today's access phrase here; official phone is unavailable.' The WhatsApp badge increments and the toast routes into the scenario.	Dashboard toast, WhatsApp-style tile, unread badge, timestamp and synthetic sender preview.	Notice the source and time; open the full item before acting. Do not reply from the preview.	NOTIFY_SEEN +0; open latency and route logged.
2 Open	Open the new-account thread and voice note. Context presented: A cloned profile sends a convincing synthetic voice note asking for a secure-room access detail.	Chat list, unread pill, thread header, bubbles, delivery ticks and prior-message history.	Read the full thread/message and prior context before choosing any action.	ITEM_OPEN +0; premature reply/action -1; dwell time logged.
3 Inspect	Open details and examine new number, profile creation date, request content and no shared history	Contact/group info sheet with full number, mutual groups, join date, media and report controls.	Check this decision signal: A familiar voice can be synthesized; protected access data must never move to personal chat.	INSPECT_CONTEXT +2; inspection path and time logged.
4 Branch	The interaction advances to a reply composer with quick chips for phrase/photo/document	Chat-native preview plus offline safe browser/file viewer/call screen; every risky control remains selectable and scored.	Do not send an access phrase, photo or protected procedure. Use Back/Close or safe preview only; no secret, payment, install or data release.	SAFE_PIVOT +3; risky open/reply -3; secret/payment/install/data release -8.
5 Verify	The learner opens Verify / More actions. Verification route: confirm via the established chain and approved communications channel	Three-dot action sheet and independent Trusted Directory overlay; in-message numbers are never treated as trusted.	Verify independently: confirm via the established chain and approved communications channel Then use the platform report/block path or the unit reporting route.	TRUSTED_VERIFY +3; report-only without checking +1; verification through message +0.
6 Resolve	Final expected resolution: send nothing; report the impersonation; preserve the synthetic voice-note evidence	Outcome card plus 250-character rationale box, warning-sign chips, event summary and Return to dashboard.	Complete the resolution and return to the dashboard. Add a one-line reason without sensitive data.	RESOLVE_CORRECT +2; contradictory unsafe final -4; scenario capped 0-10.
End-state Voice note is tagged as unverified synthetic media and the disclosure path closes.		Concise learner feedback Voice similarity is not identity proof. Follow the approved channel and protect operational access information.		

W16

Verified Vehicle-Pool Change

Platform WhatsApp	Difficulty Medium	Disposition Legitimate	Attack / case family Legitimate operational administration	Primary trigger Authority + time pressure FICTIONAL MILITARY CONTEXT
Stage	Learner flow + synthetic content	UI to build	Expected safe behavior	Scoring event
1 Event	Dashboard notification: 'Transport Coord: Weather closure. Use Alternate Gate B at 07:15; acknowledge only.' The WhatsApp badge increments and the toast routes into the scenario.	Dashboard toast, WhatsApp-style tile, unread badge, timestamp and synthetic sender preview.	Notice the source and time; open the full item before acting. Do not reply from the preview.	NOTIFY_SEEN +0; open latency and route logged.
2 Open	Open the saved coordinator thread with earlier schedule. Context presented: A saved transport coordinator changes a routine pickup point to the already published alternate location.	Chat list, unread pill, thread header, bubbles, delivery ticks and prior-message history.	Read the full thread/message and prior context before choosing any action.	ITEM_OPEN +0; premature reply/action -1; dwell time logged.
3 Inspect	Open details and examine known number, matching contingency note and limited acknowledgement	Contact/group info sheet with full number, mutual groups, join date, media and report controls.	Check this decision signal: The alternate location is already listed in the synthetic plan and no sensitive information is requested.	INSPECT_CONTEXT +2; inspection path and time logged.
4 Branch	The interaction advances to an in-chat Acknowledge button and read receipt	Chat-native preview plus offline safe browser/file viewer/call screen; every risky control remains selectable and scored.	Use the normal in-app path only after the details match the known context. Do not switch to an untrusted channel.	CORRECT_USE +3; needless reject/ignore -2; unsafe external action -4.
5 Verify	The learner opens Verify / More actions. Verification route: compare the update with the local movement board/Trusted Directory	Three-dot action sheet and independent Trusted Directory overlay; in-message numbers are never treated as trusted.	Verify independently: compare the update with the local movement board/Trusted Directory If it matches, continue; do not report or block a legitimate sender.	TRUSTED_VERIFY +3; false report/block -4; verification through message +0.
6 Resolve	Final expected resolution: acknowledge the verified change without adding sensitive details; do not report	Outcome card, concise feedback, warning-sign chips, event summary and Return to dashboard.	Complete the resolution and return to the dashboard.	RESOLVE_CORRECT +2; contradictory unsafe final -4; scenario capped 0-10.
End-state Acknowledgement is recorded; no route or roster information is exposed.		Concise learner feedback A time-sensitive message can be legitimate. Verify against an established plan and respond with the minimum necessary.		

W17

Part-Time Rating Tasks

Platform WhatsApp	Difficulty Medium	Disposition Malicious	Attack / case family Task/job scam	Primary trigger Greed + commitment
----------------------	----------------------	--------------------------	---------------------------------------	---------------------------------------

Stage	Learner flow + synthetic content	UI to build	Expected safe behavior	Scoring event
1 Event	Dashboard notification: 'Recruiter Mia: Earn INR 3,000 daily rating products. First task pays instantly.' The WhatsApp badge increments and the toast routes into the scenario.	Dashboard toast, WhatsApp-style tile, unread badge, timestamp and synthetic sender preview.	Notice the source and time; open the full item before acting. Do not reply from the preview.	NOTIFY_SEEN +0; open latency and route logged.
2 Open	Open the unsolicited recruiter chat. Context presented: A recruiter offers quick pay for rating products, then displays small synthetic earnings.	Chat list, unread pill, thread header, bubbles, delivery ticks and prior-message history.	Read the full thread/message and prior context before choosing any action.	ITEM_OPEN +0; premature reply/action -1; dwell time logged.
3 Inspect	Open details and examine unknown number, unrealistic pay, generic company name and move-to-payment pressure	Contact/group info sheet with full number, mutual groups, join date, media and report controls.	Check this decision signal: Unexpected easy-income offers often escalate from small rewards to deposits and withdrawal fees.	INSPECT_CONTEXT +2; inspection path and time logged.
4 Branch	The interaction advances to a task dashboard showing a bonus, then a 'recharge to unlock' demand	Chat-native preview plus offline safe browser/file viewer/call screen; every risky control remains selectable and scored.	Do not deposit/recharge, share bank details or recruit others. Use Back/Close or safe preview only; no secret, payment, install or data release.	SAFE_PIVOT +3; risky open/reply -3; secret/payment/install/data release -8.
5 Verify	The learner opens Verify / More actions. Verification route: look up the employer through an independently found corporate site and known vacancy channel	Three-dot action sheet and independent Trusted Directory overlay; in-message numbers are never treated as trusted.	Verify independently: look up the employer through an independently found corporate site and known vacancy channel. Then use the platform report/block path or the unit reporting route.	TRUSTED_VERIFY +3; report-only without checking +1; verification through message +0.
6 Resolve	Final expected resolution: stop tasks; report/block the recruiter; do not pay to earn	Outcome card, concise feedback, warning-sign chips, event summary and Return to dashboard.	Complete the resolution and return to the dashboard.	RESOLVE_CORRECT +2; contradictory unsafe final -4; scenario capped 0-10.

End-state Synthetic balance is exposed as non-withdrawable and no deposit is made.	Concise learner feedback Legitimate employers do not require deposits to release earnings. Stop when a task scheme asks you to pay.
---	--

Hijacked Group Admin Roster Link

Platform WhatsApp	Difficulty Hard	Disposition Malicious	Attack / case family Compromised admin / group spearphishing	Primary trigger Authority + routine FICTIONAL MILITARY CONTEXT
----------------------	--------------------	--------------------------	---	---

Stage	Learner flow + synthetic content	UI to build	Expected safe behavior	Scoring event
1 Event	Dashboard notification: 'Admin: Final roster correction closes in 15 minutes. Confirm your entry here.' The WhatsApp badge increments and the toast routes into the scenario.	Dashboard toast, WhatsApp-style tile, unread badge, timestamp and synthetic sender preview.	Notice the source and time; open the full item before acting. Do not reply from the preview.	NOTIFY_SEEN +0; open latency and route logged.
2 Open	Open the long-standing Unit Falcon group thread. Context presented: A real group admin account posts a roster-update link that conflicts subtly with prior process.	Chat list, unread pill, thread header, bubbles, delivery ticks and prior-message history.	Read the full thread/message and prior context before choosing any action.	ITEM_OPEN +0; premature reply/action -1; dwell time logged.
3 Inspect	Open details and examine admin's message history, changed tone, unusual link domain and other members' reactions	Contact/group info sheet with full number, mutual groups, join date, media and report controls.	Check this decision signal: A trusted account can be hijacked; the approved roster process never uses a public form.	INSPECT_CONTEXT +2; inspection path and time logged.
4 Branch	The interaction advances to a prefilled synthetic roster form asking service number, role and current location	Chat-native preview plus offline safe browser/file viewer/call screen; every risky control remains selectable and scored.	Do not submit personnel, role, location or contact data. Use Back/Close or safe preview only; no secret, payment, install or data release.	SAFE_PIVOT +3; risky open/reply -3; secret/payment/install/data release -8.
5 Verify	The learner opens Verify / More actions. Verification route: call the admin via known directory and check the approved roster system	Three-dot action sheet and independent Trusted Directory overlay; in-message numbers are never treated as trusted.	Verify independently: call the admin via known directory and check the approved roster system Then use the platform report/block path or the unit reporting route.	TRUSTED_VERIFY +3; report-only without checking +1; verification through message +0.
6 Resolve	Final expected resolution: do not submit; report the compromised post to group admins and unit security; warn without forwarding the link	Outcome card plus 250-character rationale box, warning-sign chips, event summary and Return to dashboard.	Complete the resolution and return to the dashboard. Add a one-line reason without sensitive data.	RESOLVE_CORRECT +2; contradictory unsafe final -4; scenario capped 0-10.

End-state The verified admin confirms takeover; the group post is locally marked removed.	Concise learner feedback Prior trust does not validate a changed process. Inspect links and verify sensitive requests out of band.
--	---

Commander Clone Requests Location

Platform WhatsApp	Difficulty Hard	Disposition Malicious	Attack / case family Military impersonation / location collection	Primary trigger Authority + secrecy FICTIONAL MILITARY CONTEXT
----------------------	--------------------	--------------------------	--	---

Stage	Learner flow + synthetic content	UI to build	Expected safe behavior	Scoring event
1 Event	Dashboard notification: 'Commander: For revised coordination, send live location now. Do not post in the group.' The WhatsApp badge increments and the toast routes into the scenario.	Dashboard toast, WhatsApp-style tile, unread badge, timestamp and synthetic sender preview.	Notice the source and time; open the full item before acting. Do not reply from the preview.	NOTIFY_SEEN +0; open latency and route logged.
2 Open	Open the direct chat from a near-identical account. Context presented: A clone closely matches a senior's photo and About text, and references a public event.	Chat list, unread pill, thread header, bubbles, delivery ticks and prior-message history.	Read the full thread/message and prior context before choosing any action.	ITEM_OPEN +0; premature reply/action -1; dwell time logged.
3 Inspect	Open details and examine exact number, account age, common groups and small name-character difference	Contact/group info sheet with full number, mutual groups, join date, media and report controls.	Check this decision signal: The account is new, lacks expected mutual groups, and requests live location outside procedure.	INSPECT_CONTEXT +2; inspection path and time logged.
4 Branch	The interaction advances to the live-location share sheet with 15-minute/1-hour options	Chat-native preview plus offline safe browser/file viewer/call screen; every risky control remains selectable and scored.	Do not share live/current location or explain the schedule. Use Back/Close or safe preview only; no secret, payment, install or data release.	SAFE_PIVOT +3; risky open/reply -3; secret/payment/install/data release -8.
5 Verify	The learner opens Verify / More actions. Verification route: contact the duty office or senior through an approved known route	Three-dot action sheet and independent Trusted Directory overlay; in-message numbers are never treated as trusted.	Verify independently: contact the duty office or senior through an approved known route Then use the platform report/block path or the unit reporting route.	TRUSTED_VERIFY +3; report-only without checking +1; verification through message +0.
6 Resolve	Final expected resolution: cancel location share; report the clone; notify unit security through policy	Outcome card, concise feedback, warning-sign chips, event summary and Return to dashboard.	Complete the resolution and return to the dashboard.	RESOLVE_CORRECT +2; contradictory unsafe final -4; scenario capped 0-10.

End-state Location permission remains off and the impersonating account is blocked.	Concise learner feedback Profile cloning can be exact. Compare account identity and never disclose location because a message claims seniority.
--	--

Supplier Bank-Detail Change

Platform WhatsApp	Difficulty Hard	Disposition Malicious	Attack / case family Procurement impersonation / payment diversion	Primary trigger Routine + urgency
----------------------	--------------------	--------------------------	---	--------------------------------------

Stage	Learner flow + synthetic content	UI to build	Expected safe behavior	Scoring event
1 Event	Dashboard notification: 'Northstar Supplies: Our bank is under audit. Use this new account for today's invoice.' The WhatsApp badge increments and the toast routes into the scenario.	Dashboard toast, WhatsApp-style tile, unread badge, timestamp and synthetic sender preview.	Notice the source and time; open the full item before acting. Do not reply from the preview.	NOTIFY_SEEN +0; open latency and route logged.
2 Open	Open the supplier chat with copied invoice references. Context presented: A known supplier logo account enters an existing project context and requests payment to a new beneficiary.	Chat list, unread pill, thread header, bubbles, delivery ticks and prior-message history.	Read the full thread/message and prior context before choosing any action.	ITEM_OPEN +0; premature reply/action -1; dwell time logged.
3 Inspect	Open details and examine new number, beneficiary mismatch and deviation from change-control process	Contact/group info sheet with full number, mutual groups, join date, media and report controls.	Check this decision signal: Accurate invoice details may be stolen; bank-detail changes require independent callback and approved workflow.	INSPECT_CONTEXT +2; inspection path and time logged.
4 Branch	The interaction advances to a synthetic invoice plus beneficiary-edit/payment screen	Chat-native preview plus offline safe browser/file viewer/call screen; every risky control remains selectable and scored.	Do not change stored bank details or approve payment from chat evidence. Use Back/Close or safe preview only; no secret, payment, install or data release.	SAFE_PIVOT +3; risky open/reply -3; secret/payment/install/data release -8.
5 Verify	The learner opens Verify / More actions. Verification route: call the supplier contact already on file and obtain dual approval through procurement workflow	Three-dot action sheet and independent Trusted Directory overlay; in-message numbers are never treated as trusted.	Verify independently: call the supplier contact already on file and obtain dual approval through procurement workflow Then use the platform report/block path or the unit reporting route.	TRUSTED_VERIFY +3; report-only without checking +1; verification through message +0.
6 Resolve	Final expected resolution: hold payment; report the impersonation; record the discrepancy for procurement/security	Outcome card plus 250-character rationale box, warning-sign chips, event summary and Return to dashboard.	Complete the resolution and return to the dashboard. Add a one-line reason without sensitive data.	RESOLVE_CORRECT +2; contradictory unsafe final -4; scenario capped 0-10.

End-state Beneficiary change is rejected and the legitimate supplier confirms no request.	Concise learner feedback Treat payment-detail changes as high-risk even when context is convincing. Use known contacts and dual control.
--	---

Verified Senior Requests Secure Follow-Up

Platform WhatsApp	Difficulty Hard	Disposition Legitimate	Attack / case family Legitimate minimal notification	Primary trigger Authority FICTIONAL MILITARY CONTEXT
----------------------	--------------------	---------------------------	---	---

Stage	Learner flow + synthetic content	UI to build	Expected safe behavior	Scoring event
1 Event	Dashboard notification: 'Col. Dev: Please review item REF-ALPHA-17 in the approved portal. No reply details here.' The WhatsApp badge increments and the toast routes into the scenario.	Dashboard toast, WhatsApp-style tile, unread badge, timestamp and synthetic sender preview.	Notice the source and time; open the full item before acting. Do not reply from the preview.	NOTIFY_SEEN +0; open latency and route logged.
2 Open	Open the established saved-contact thread. Context presented: A saved senior sends a brief personal-channel message that contains no task detail and directs the learner to the approved secure system.	Chat list, unread pill, thread header, bubbles, delivery ticks and prior-message history.	Read the full thread/message and prior context before choosing any action.	ITEM_OPEN +0; premature reply/action -1; dwell time logged.
3 Inspect	Open details and examine known number, matching directory record, minimal content and approved portal reference	Contact/group info sheet with full number, mutual groups, join date, media and report controls.	Check this decision signal: The message avoids operational detail and asks the learner to use the correct protected channel.	INSPECT_CONTEXT +2; inspection path and time logged.
4 Branch	The interaction advances to the local approved-portal launcher without an embedded login link	Chat-native preview plus offline safe browser/file viewer/call screen; every risky control remains selectable and scored.	Use the normal in-app path only after the details match the known context. Do not switch to an untrusted channel.	CORRECT_USE +3; needless reject/ignore -2; unsafe external action -4.
5 Verify	The learner opens Verify / More actions. Verification route: open the approved portal from the dashboard and compare reference REF-ALPHA-17	Three-dot action sheet and independent Trusted Directory overlay; in-message numbers are never treated as trusted.	Verify independently: open the approved portal from the dashboard and compare reference REF-ALPHA-17 If it matches, continue; do not report or block a legitimate sender.	TRUSTED_VERIFY +3; false report/block -4; verification through message +0.
6 Resolve	Final expected resolution: review the item in the approved mock portal; send only a minimal acknowledgement if required; do not report	Outcome card plus 250-character rationale box, warning-sign chips, event summary and Return to dashboard.	Complete the resolution and return to the dashboard. Add a one-line reason without sensitive data.	RESOLVE_CORRECT +2; contradictory unsafe final -4; scenario capped 0-10.

End-state The secure-portal task is opened and WhatsApp retains no sensitive follow-up.	Concise learner feedback A legitimate message can be brief and authoritative when it moves detail to the approved system. Verify the route, then proceed.
--	--

Long-Game Online Friendship

Platform WhatsApp	Difficulty Hard	Disposition Malicious	Attack / case family Relationship grooming / investment fraud	Primary trigger Trust + reciprocity
----------------------	--------------------	--------------------------	--	--

Stage	Learner flow + synthetic content	UI to build	Expected safe behavior	Scoring event
1 Event	Dashboard notification: 'Samira: My uncle's desk has a guaranteed window tonight. Start small so you can trust me.' The WhatsApp badge increments and the toast routes into the scenario.	Dashboard toast, WhatsApp-style tile, unread badge, timestamp and synthetic sender preview.	Notice the source and time; open the full item before acting. Do not reply from the preview.	NOTIFY_SEEN +0; open latency and route logged.
2 Open	Open the multi-week chat history. Context presented: A contact cultivated over several synthetic weeks now recommends a private crypto opportunity.	Chat list, unread pill, thread header, bubbles, delivery ticks and prior-message history.	Read the full thread/message and prior context before choosing any action.	ITEM_OPEN +0; premature reply/action -1; dwell time logged.
3 Inspect	Open details and examine rapid intimacy, inconsistent biography, investment pivot and guaranteed-return language	Contact/group info sheet with full number, mutual groups, join date, media and report controls.	Check this decision signal: Time and friendliness do not validate identity or investment claims; the relationship is being used to lower caution.	INSPECT_CONTEXT +2; inspection path and time logged.
4 Branch	The interaction advances to a polished fake exchange showing profit after a tiny trial deposit	Chat-native preview plus offline safe browser/file viewer/call screen; every risky control remains selectable and scored.	Do not deposit funds, upload ID or reveal financial information. Use Back/Close or safe preview only; no secret, payment, install or data release.	SAFE_PIVOT +3; risky open/reply -3; secret/payment/install/data release -8.
5 Verify	The learner opens Verify / More actions. Verification route: verify identity independently and research the platform/regulatory status outside the relationship	Three-dot action sheet and independent Trusted Directory overlay; in-message numbers are never treated as trusted.	Verify independently: verify identity independently and research the platform/regulatory status outside the relationship Then use the platform report/block path or the unit reporting route.	TRUSTED_VERIFY +3; report-only without checking +1; verification through message +0.
6 Resolve	Final expected resolution: do not invest; preserve and report the account; block after evidence capture	Outcome card, concise feedback, warning-sign chips, event summary and Return to dashboard.	Complete the resolution and return to the dashboard.	RESOLVE_CORRECT +2; contradictory unsafe final -4; scenario capped 0-10.

End-state Fake profit display is exposed and the payment route is closed.	Concise learner feedback Grooming can precede the financial request by weeks. Separate relationship trust from identity and investment verification.
--	---

Family Welfare Pretext

Platform WhatsApp	Difficulty Hard	Disposition Malicious	Attack / case family Military-family targeting / operational elicitation	Primary trigger Empathy + authority FICTIONAL MILITARY CONTEXT
----------------------	--------------------	--------------------------	---	---

Stage	Learner flow + synthetic content	UI to build	Expected safe behavior	Scoring event
1 Event	Dashboard notification: 'Forces Welfare Volunteer: We must route an emergency grant. Confirm unit, post and deployment dates.' The WhatsApp badge increments and the toast routes into the scenario.	Dashboard toast, WhatsApp-style tile, unread badge, timestamp and synthetic sender preview.	Notice the source and time; open the full item before acting. Do not reply from the preview.	NOTIFY_SEEN +0; open latency and route logged.
2 Open	Open the business-style chat with copied welfare imagery. Context presented: An account posing as a welfare volunteer says a family member needs help and asks where the learner is posted.	Chat list, unread pill, thread header, bubbles, delivery ticks and prior-message history.	Read the full thread/message and prior context before choosing any action.	ITEM_OPEN +0; premature reply/action -1; dwell time logged.
3 Inspect	Open details and examine unknown number, broad data request, urgency and lack of case reference	Contact/group info sheet with full number, mutual groups, join date, media and report controls.	Check this decision signal: The request combines family concern with operational and identity questions that a real process would already handle securely.	INSPECT_CONTEXT +2; inspection path and time logged.
4 Branch	The interaction advances to a synthetic grant form requesting unit, location, schedule, family and bank data	Chat-native preview plus offline safe browser/file viewer/call screen; every risky control remains selectable and scored.	Do not disclose posting, movement, family or bank information. Use Back/Close or safe preview only; no secret, payment, install or data release.	SAFE_PIVOT +3; risky open/reply -3; secret/payment/install/data release -8.
5 Verify	The learner opens Verify / More actions. Verification route: contact the known welfare office through the unit directory and check the family directly	Three-dot action sheet and independent Trusted Directory overlay; in-message numbers are never treated as trusted.	Verify independently: contact the known welfare office through the unit directory and check the family directly Then use the platform report/block path or the unit reporting route.	TRUSTED_VERIFY +3; report-only without checking +1; verification through message +0.
6 Resolve	Final expected resolution: submit nothing; report the impersonation through unit security; block the account	Outcome card plus 250-character rationale box, warning-sign chips, event summary and Return to dashboard.	Complete the resolution and return to the dashboard. Add a one-line reason without sensitive data.	RESOLVE_CORRECT +2; contradictory unsafe final -4; scenario capped 0-10.

End-state Form is discarded and the verified welfare office shows no case.	Concise learner feedback Attackers may target families to elicit service details. Verify welfare claims and disclose nothing in an unsolicited chat.
---	---

Remote Support Screen Share

Platform WhatsApp	Difficulty Hard	Disposition Malicious	Attack / case family Tech-support scam / remote access	Primary trigger Fear + helpfulness
----------------------	--------------------	--------------------------	---	---------------------------------------

Stage	Learner flow + synthetic content	UI to build	Expected safe behavior	Scoring event
1 Event	Dashboard notification: 'Mobile Security Desk: Critical infection detected. Install AssistNow and share screen.' The WhatsApp badge increments and the toast routes into the scenario.	Dashboard toast, WhatsApp-style tile, unread badge, timestamp and synthetic sender preview.	Notice the source and time; open the full item before acting. Do not reply from the preview.	NOTIFY_SEEN +0; open latency and route logged.
2 Open	Open the support chat and diagnostic image. Context presented: A support agent claims the learner's phone is spreading malware and offers to fix it immediately.	Chat list, unread pill, thread header, bubbles, delivery ticks and prior-message history.	Read the full thread/message and prior context before choosing any action.	ITEM_OPEN +0; premature reply/action -1; dwell time logged.
3 Inspect	Open details and examine unverified account, unsolicited diagnosis, APK link and remote-control request	Contact/group info sheet with full number, mutual groups, join date, media and report controls.	Check this decision signal: Legitimate support does not discover an infection by cold message or require an unknown remote-access app.	INSPECT_CONTEXT +2; inspection path and time logged.
4 Branch	The interaction advances to an install mock followed by accessibility and screen-share permission prompts	Chat-native preview plus offline safe browser/file viewer/call screen; every risky control remains selectable and scored.	Do not install the app, share screen or grant accessibility/SMS permission. Use Back/Close or safe preview only; no secret, payment, install or data release.	SAFE_PIVOT +3; risky open/reply -3; secret/payment/install/data release -8.
5 Verify	The learner opens Verify / More actions. Verification route: close chat and contact approved IT support using the local directory	Three-dot action sheet and independent Trusted Directory overlay; in-message numbers are never treated as trusted.	Verify independently: close chat and contact approved IT support using the local directory Then use the platform report/block path or the unit reporting route.	TRUSTED_VERIFY +3; report-only without checking +1; verification through message +0.
6 Resolve	Final expected resolution: cancel all permissions; report/block the account; request an approved device check if needed	Outcome card, concise feedback, warning-sign chips, event summary and Return to dashboard.	Complete the resolution and return to the dashboard.	RESOLVE_CORRECT +2; contradictory unsafe final -4; scenario capped 0-10.

End-state No app is installed and all simulated permissions remain denied.	Concise learner feedback Remote-access and accessibility permissions can expose everything on a device. Use only approved support channels.
---	--

Known Contact Sends a Linking Code

Platform WhatsApp	Difficulty Hard	Disposition Malicious	Attack / case family Compromised-contact device linking	Primary trigger Trust + reciprocity
----------------------	--------------------	--------------------------	--	--

Stage	Learner flow + synthetic content	UI to build	Expected safe behavior	Scoring event
1 Event	Dashboard notification: 'Neel: I'm testing the team desktop. Send the linking code you just got so I can finish setup.' The WhatsApp badge increments and the toast routes into the scenario.	Dashboard toast, WhatsApp-style tile, unread badge, timestamp and synthetic sender preview.	Notice the source and time; open the full item before acting. Do not reply from the preview.	NOTIFY_SEEN +0; open latency and route logged.
2 Open	Open the authentic-looking saved-contact thread. Context presented: A saved contact's compromised account asks the learner to help test a desktop login.	Chat list, unread pill, thread header, bubbles, delivery ticks and prior-message history.	Read the full thread/message and prior context before choosing any action.	ITEM_OPEN +0; premature reply/action -1; dwell time logged.
3 Inspect	Open details and examine request purpose, code warning, linked-device context and out-of-character behavior	Contact/group info sheet with full number, mutual groups, join date, media and report controls.	Check this decision signal: A linking code authorizes access to the learner's account; a colleague never needs it to test their own device.	INSPECT_CONTEXT +2; inspection path and time logged.
4 Branch	The interaction advances to a simulated device-link code and approval sheet	Chat-native preview plus offline safe browser/file viewer/call screen; every risky control remains selectable and scored.	Do not share the code or approve the unfamiliar device. Use Back/Close or safe preview only; no secret, payment, install or data release.	SAFE_PIVOT +3; risky open/reply -3; secret/payment/install/data release -8.
5 Verify	The learner opens Verify / More actions. Verification route: call the contact through a known alternate route and review Linked Devices	Three-dot action sheet and independent Trusted Directory overlay; in-message numbers are never treated as trusted.	Verify independently: call the contact through a known alternate route and review Linked Devices Then use the platform report/block path or the unit reporting route.	TRUSTED_VERIFY +3; report-only without checking +1; verification through message +0.
6 Resolve	Final expected resolution: deny linking; remove unknown devices; report the compromised message and alert the real contact	Outcome card plus 250-character rationale box, warning-sign chips, event summary and Return to dashboard.	Complete the resolution and return to the dashboard. Add a one-line reason without sensitive data.	RESOLVE_CORRECT +2; contradictory unsafe final -4; scenario capped 0-10.

End-state The account remains controlled by the learner and the compromised-contact warning is recorded.	Concise learner feedback Even a known account cannot justify sharing a linking code. Protect account-authorization prompts like passwords.
--	--

Scenario Bank: Instagram

Twenty-five six-stage scenarios for the simulated Instagram environment. Composition: 8 easy, 9 medium, 8 hard; 20 malicious/deceptive and 5 legitimate controls; 12 fictional military-context cases.

Implementation rule

All senders, messages, accounts, numbers, links, QR codes, files, calls and payment screens are synthetic. No scenario may resolve outside the local application. The learner can take unsafe-looking actions, but they only change local state and scoring.

ID	Scenario	Level	Case	Family	M	ID	Scenario	Level	Case	Family	M
I01	Flash Giveaway Winner	Easy	Malicious	Giveaway / credential-payment scam		I14	Commendation Page Requests Documents	Medium	Malicious	Military-themed impersonation / identity theft	Y
I02	Copyright Appeal Countdown	Easy	Malicious	Fake platform support / credential phishing		I15	You Are in This Video	Medium	Malicious	Compromised-contact link phishing	
I03	Published Blood-Donation Drive	Easy	Legitimate	Legitimate public announcement	Y	I16	Approved Photo Release Request	Medium	Legitimate	Legitimate public-affairs workflow	Y
I04	Cloned Friend in Distress	Easy	Malicious	Profile cloning / emergency payment		I17	Morphed-Photo Blackmail	Medium	Malicious	Image-based extortion	
I05	Friendly New Follower Questionnaire	Easy	Malicious	Social profiling / information elicitation	Y	I18	High-Fidelity Teammate Clone	Hard	Malicious	Profile cloning / location elicitation	Y
I06	Where Was This Exercise?	Easy	Malicious	Operational-information elicitation	Y	I19	Urgent Unit Incident Repost	Hard	Malicious	Disinformation / amplification lure	Y
I07	Known Friend Shares a Reel	Easy	Legitimate	Legitimate social sharing		I20	Researcher Asks Capability Questions	Hard	Malicious	Rapport-based elicitation / espionage pretext	Y
I08	Verification Badge Agent	Easy	Malicious	Fake verification service		I21	Post-Event Teammate Tag	Hard	Legitimate	Legitimate post-event sharing	Y
I09	Deepfake Trading Advertisement	Medium	Malicious	Investment fraud / synthetic endorsement		I22	Live Support Video Call	Hard	Malicious	Fake platform support / call coercion	
I10	Brand Collaboration Shipping Fee	Medium	Malicious	Influencer/brand impersonation		I23	Compromised Charity Influencer	Hard	Malicious	Compromised trusted account / donation diversion	
I11	Official Welfare Helpline Update	Medium	Legitimate	Legitimate official-account update	Y	I24	Institutional Trading App	Hard	Malicious	Fake regulated investment platform	
I12	Account Recovery Backup Code	Medium	Malicious	Account-recovery phishing		I25	Canteen Coupon Reel QR	Hard	Malicious	Military-themed QR phishing	Y
I13	Deployed Officer Romance Profile	Medium	Malicious	Romance scam / identity fabrication	Y						

Flash Giveaway Winner

Platform Instagram	Difficulty Easy	Disposition Malicious	Attack / case family Giveaway / credential-payment scam	Primary trigger Greed + scarcity
-----------------------	--------------------	--------------------------	--	-------------------------------------

Stage	Learner flow + synthetic content	UI to build	Expected safe behavior	Scoring event
1 Event	Dashboard notification: '@mega_rewards_help: You won! Claim in 10 minutes or we redraw.' The Instagram badge increments and the toast routes into the scenario.	Dashboard toast, Instagram-style tile, DM/activity badge, account avatar and synthetic preview.	Notice the source and time; open the full item before acting. Do not reply from the preview.	NOTIFY_SEEN +0; open latency and route logged.
2 Open	Open the Activity item and tagged giveaway post. Context presented: A newly created account tags the learner as a winner in a giveaway they never entered.	DM requests/inbox or activity/feed view with thread, post, story or reel context and timestamps.	Read the full thread/message and prior context before choosing any action.	ITEM_OPEN +0; premature reply/action -1; dwell time logged.
3 Inspect	Open details and examine exact handle, account age, follower ratio, comments and bio link	Profile sheet with exact handle, account age, username history, mutuals, follower ratios and report controls.	Check this decision signal: The account imitates a brand, disables comments and uses a look-alike handle and urgent claim link.	INSPECT_CONTEXT +2; inspection path and time logged.
4 Branch	The interaction advances to a fake prize page asking for social login and a small delivery fee	In-app profile/post/story view plus offline link browser, media composer or synthetic payment panel.	Do not enter credentials, payment data or share the post. Use Back/Close or safe preview only; no secret, payment, install or data release.	SAFE_PIVOT +3; risky open/reply -3; secret/payment/install/data release -8.
5 Verify	The learner opens Verify / More actions. Verification route: find the brand's official account independently and check its public promotion rules	DM action sheet with restrict/block/report and independent Trusted Directory or official-account lookup overlay.	Verify independently: find the brand's official account independently and check its public promotion rules. Then use the platform report/block path or the unit reporting route.	TRUSTED_VERIFY +3; report-only without checking +1; verification through message +0.
6 Resolve	Final expected resolution: close the claim; report the account/post as scam; block the account	Outcome card, concise feedback, warning-sign chips, event summary and Return to dashboard.	Complete the resolution and return to the dashboard.	RESOLVE_CORRECT +2; contradictory unsafe final -4; scenario capped 0-10.

End-state Claim flow closes and the fake account is removed from the local feed.	Concise learner feedback You cannot win a promotion you did not enter. Check the exact account and verify on the official page.
---	--

Copyright Appeal Countdown

Platform Instagram	Difficulty Easy	Disposition Malicious	Attack / case family Fake platform support / credential phishing	Primary trigger Fear + urgency
-----------------------	--------------------	--------------------------	---	-----------------------------------

Stage	Learner flow + synthetic content	UI to build	Expected safe behavior	Scoring event
1 Event	Dashboard notification: '@copyright_case_team: Appeal within 30 minutes or your account will be permanently removed.' The Instagram badge increments and the toast routes into the scenario.	Dashboard toast, Instagram-style tile, DM/activity badge, account avatar and synthetic preview.	Notice the source and time; open the full item before acting. Do not reply from the preview.	NOTIFY_SEEN +0; open latency and route logged.
2 Open	Open the DM request and account-warning message. Context presented: A DM claims the learner's profile will be deleted for copyright infringement.	DM requests/inbox or activity/feed view with thread, post, story or reel context and timestamps.	Read the full thread/message and prior context before choosing any action.	ITEM_OPEN +0; premature reply/action -1; dwell time logged.
3 Inspect	Open details and examine support handle, DM-request status, link domain and threat language	Profile sheet with exact handle, account age, username history, mutuals, follower ratios and report controls.	Check this decision signal: Platform enforcement is handled through in-app account status, not an unsolicited support DM.	INSPECT_CONTEXT +2; inspection path and time logged.
4 Branch	The interaction advances to an external-looking appeal login requesting username, password and backup code	In-app profile/post/story view plus offline link browser, media composer or synthetic payment panel.	Do not log in, upload ID or share a backup code. Use Back/Close or safe preview only; no secret, payment, install or data release.	SAFE_PIVOT +3; risky open/reply -3; secret/payment/install/data release -8.
5 Verify	The learner opens Verify / More actions. Verification route: open Settings > Account Status/Support directly inside the simulated app	DM action sheet with restrict/block/report and independent Trusted Directory or official-account lookup overlay.	Verify independently: open Settings > Account Status/Support directly inside the simulated app Then use the platform report/block path or the unit reporting route.	TRUSTED_VERIFY +3; report-only without checking +1; verification through message +0.
6 Resolve	Final expected resolution: close the link; report/block the fake support account; review official account status	Outcome card plus 250-character rationale box, warning-sign chips, event summary and Return to dashboard.	Complete the resolution and return to the dashboard. Add a one-line reason without sensitive data.	RESOLVE_CORRECT +2; contradictory unsafe final -4; scenario capped 0-10.

End-state Account Status shows no violation and the DM is marked as phishing.	Concise learner feedback Urgent support DMs are a common credential lure. Use the platform's own settings and never share recovery codes.
--	--

Published Blood-Donation Drive

Platform Instagram	Difficulty Easy	Disposition Legitimate	Attack / case family Legitimate public announcement	Primary trigger Empathy FICTIONAL MILITARY CONTEXT
-----------------------	--------------------	---------------------------	--	---

Stage	Learner flow + synthetic content	UI to build	Expected safe behavior	Scoring event
1 Event	Dashboard notification: '@unitfalcon_public: Voluntary blood donation, 05 Sep, Civic Hall. Details in approved poster.' The Instagram badge increments and the toast routes into the scenario.	Dashboard toast, Instagram-style tile, DM/activity badge, account avatar and synthetic preview.	Notice the source and time; open the full item before acting. Do not reply from the preview.	NOTIFY_SEEN +0; open latency and route logged.
2 Open	Open the Activity item and public post. Context presented: A verified fictional public-information account posts an already approved blood-donation drive with no external registration.	DM requests/inbox or activity/feed view with thread, post, story or reel context and timestamps.	Read the full thread/message and prior context before choosing any action.	ITEM_OPEN +0; premature reply/action -1; dwell time logged.
3 Inspect	Open details and examine verified badge context, exact handle, post history and approval label	Profile sheet with exact handle, account age, username history, mutuals, follower ratios and report controls.	Check this decision signal: The account matches the local official-account list and the post contains only publicly releasable information.	INSPECT_CONTEXT +2; inspection path and time logged.
4 Branch	The interaction advances to the in-app poster viewer and Save/Share controls	In-app profile/post/story view plus offline link browser, media composer or synthetic payment panel.	Use the normal in-app path only after the details match the known context. Do not switch to an untrusted channel.	CORRECT_USE +3; needless reject/ignore -2; unsafe external action -4.
5 Verify	The learner opens Verify / More actions. Verification route: compare the handle with the local official-account directory	DM action sheet with restrict/block/report and independent Trusted Directory or official-account lookup overlay.	Verify independently: compare the handle with the local official-account directory. If it matches, continue; do not report or block a legitimate sender.	TRUSTED_VERIFY +3; false report/block -4; verification through message +0.
6 Resolve	Final expected resolution: save or like the post; share only if the approved-public marker is present; do not report	Outcome card, concise feedback, warning-sign chips, event summary and Return to dashboard.	Complete the resolution and return to the dashboard.	RESOLVE_CORRECT +2; contradictory unsafe final -4; scenario capped 0-10.

End-state Post remains in feed and the legitimate action is logged.	Concise learner feedback A verified public post with matching official history may be used normally. Keep any response within released information.
--	--

Cloned Friend in Distress

Platform Instagram	Difficulty Easy	Disposition Malicious	Attack / case family Profile cloning / emergency payment	Primary trigger Empathy + urgency
-----------------------	--------------------	--------------------------	---	--------------------------------------

Stage	Learner flow + synthetic content	UI to build	Expected safe behavior	Scoring event
1 Event	Dashboard notification: '@riya.kapoor_2: Lost wallet and phone. Please send travel money before the last bus.' The Instagram badge increments and the toast routes into the scenario.	Dashboard toast, Instagram-style tile, DM/activity badge, account avatar and synthetic preview.	Notice the source and time; open the full item before acting. Do not reply from the preview.	NOTIFY_SEEN +0; open latency and route logged.
2 Open	Open the DM request and cloned profile. Context presented: A near-identical account follows the learner and sends a direct message asking for travel money.	DM requests/inbox or activity/feed view with thread, post, story or reel context and timestamps.	Read the full thread/message and prior context before choosing any action.	ITEM_OPEN +0; premature reply/action -1; dwell time logged.
3 Inspect	Open details and examine extra character in handle, recent posts, follower overlap and account age	Profile sheet with exact handle, account age, username history, mutuals, follower ratios and report controls.	Check this decision signal: The account is new and copies old photos but lacks the friend's normal interactions.	INSPECT_CONTEXT +2; inspection path and time logged.
4 Branch	The interaction advances to a payment-handle card with a third-party synthetic name	In-app profile/post/story view plus offline link browser, media composer or synthetic payment panel.	Do not send money or verify only by DM. Use Back/Close or safe preview only; no secret, payment, install or data release.	SAFE_PIVOT +3; risky open/reply -3; secret/payment/install/data release -8.
5 Verify	The learner opens Verify / More actions. Verification route: call the friend using the number already saved or ask a known mutual through a separate channel	DM action sheet with restrict/block/report and independent Trusted Directory or official-account lookup overlay.	Verify independently: call the friend using the number already saved or ask a known mutual through a separate channel Then use the platform report/block path or the unit reporting route.	TRUSTED_VERIFY +3; report-only without checking +1; verification through message +0.
6 Resolve	Final expected resolution: decline; report the clone for impersonation; block after independent confirmation	Outcome card, concise feedback, warning-sign chips, event summary and Return to dashboard.	Complete the resolution and return to the dashboard.	RESOLVE_CORRECT +2; contradictory unsafe final -4; scenario capped 0-10.

End-state Verified friend confirms the clone; no payment is attempted.	Concise learner feedback Copied photos and mutual followers do not prove identity. Use an existing contact route for emergencies.
---	--

Friendly New Follower Questionnaire

Platform Instagram	Difficulty Easy	Disposition Malicious	Attack / case family Social profiling / information elicitation	Primary trigger Flattery + curiosity FICTIONAL MILITARY CONTEXT
-----------------------	--------------------	--------------------------	--	--

Stage	Learner flow + synthetic content	UI to build	Expected safe behavior	Scoring event
1 Event	Dashboard notification: '@trail_fan_87: Great training! Which city, unit and daily route do you use?' The Instagram badge increments and the toast routes into the scenario.	Dashboard toast, Instagram-style tile, DM/activity badge, account avatar and synthetic preview.	Notice the source and time; open the full item before acting. Do not reply from the preview.	NOTIFY_SEEN +0; open latency and route logged.
2 Open	Open the DM request and follower profile. Context presented: A new follower compliments the learner's fitness posts and asks a sequence of personal questions.	DM requests/inbox or activity/feed view with thread, post, story or reel context and timestamps.	Read the full thread/message and prior context before choosing any action.	ITEM_OPEN +0; premature reply/action -1; dwell time logged.
3 Inspect	Open details and examine account age, sparse original content, broad following and escalating questions	Profile sheet with exact handle, account age, username history, mutuals, follower ratios and report controls.	Check this decision signal: The questions combine location, affiliation and routine details useful for targeting.	INSPECT_CONTEXT +2; inspection path and time logged.
4 Branch	The interaction advances to a quick-reply panel offering city/unit/route answers	In-app profile/post/story view plus offline link browser, media composer or synthetic payment panel.	Do not reveal workplace, location, schedule or relationship data. Use Back/Close or safe preview only; no secret, payment, install or data release.	SAFE_PIVOT +3; risky open/reply -3; secret/payment/install/data release -8.
5 Verify	The learner opens Verify / More actions. Verification route: review the profile and, if identity is claimed, verify through a known mutual outside the DM	DM action sheet with restrict/block/report and independent Trusted Directory or official-account lookup overlay.	Verify independently: review the profile and, if identity is claimed, verify through a known mutual outside the DM Then use the platform report/block path or the unit reporting route.	TRUSTED_VERIFY +3; report-only without checking +1; verification through message +0.
6 Resolve	Final expected resolution: do not answer; restrict/report the account; review profile privacy	Outcome card, concise feedback, warning-sign chips, event summary and Return to dashboard.	Complete the resolution and return to the dashboard.	RESOLVE_CORRECT +2; contradictory unsafe final -4; scenario capped 0-10.

End-state DM request is restricted and no personal detail is released.	Concise learner feedback Friendly conversation can be elicitation. Share only what an unknown follower genuinely needs to know.
---	--

Where Was This Exercise?

Platform Instagram	Difficulty Easy	Disposition Malicious	Attack / case family Operational-information elicitation	Primary trigger Pride + social validation FICTIONAL MILITARY CONTEXT
-----------------------	--------------------	--------------------------	---	---

Stage	Learner flow + synthetic content	UI to build	Expected safe behavior	Scoring event
1 Event	Dashboard notification: '@defence_fan_archive: Impressive! Which base and what dates was this taken? DM me the route.' The Instagram badge increments and the toast routes into the scenario.	Dashboard toast, Instagram-style tile, DM/activity badge, account avatar and synthetic preview.	Notice the source and time; open the full item before acting. Do not reply from the preview.	NOTIFY_SEEN +0; open latency and route logged.
2 Open	Open the comment thread and commenter's profile. Context presented: A commenter praises a generic training photo and asks for location and timing details.	DM requests/inbox or activity/feed view with thread, post, story or reel context and timestamps.	Read the full thread/message and prior context before choosing any action.	ITEM_OPEN +0; premature reply/action -1; dwell time logged.
3 Inspect	Open details and examine unknown identity, military-themed reposts and specific location/schedule questions	Profile sheet with exact handle, account age, username history, mutuals, follower ratios and report controls.	Check this decision signal: Public enthusiasm does not create a need to know; the request seeks operational context.	INSPECT_CONTEXT +2; inspection path and time logged.
4 Branch	The interaction advances to a reply composer and location-tag selector	In-app profile/post/story view plus offline link browser, media composer or synthetic payment panel.	Do not identify a base, route, schedule, capability or participant. Use Back/Close or safe preview only; no secret, payment, install or data release.	SAFE_PIVOT +3; risky open/reply -3; secret/payment/install/data release -8.
5 Verify	The learner opens Verify / More actions. Verification route: check the post's approved-release note and consult the unit public-information route	DM action sheet with restrict/block/report and independent Trusted Directory or official-account lookup overlay.	Verify independently: check the post's approved-release note and consult the unit public-information route Then use the platform report/block path or the unit reporting route.	TRUSTED_VERIFY +3; report-only without checking +1; verification through message +0.
6 Resolve	Final expected resolution: do not disclose details; hide/report the eliciting comment if policy requires	Outcome card plus 250-character rationale box, warning-sign chips, event summary and Return to dashboard.	Complete the resolution and return to the dashboard. Add a one-line reason without sensitive data.	RESOLVE_CORRECT +2; contradictory unsafe final -4; scenario capped 0-10.

End-state No reply or geotag is added; the comment is routed to moderation.	Concise learner feedback Small details can combine into an operational picture. Do not answer location, schedule or capability questions.
--	--

Known Friend Shares a Reel

Platform Instagram	Difficulty Easy	Disposition Legitimate	Attack / case family Legitimate social sharing	Primary trigger Familiarity
-----------------------	--------------------	---------------------------	---	--------------------------------

Stage	Learner flow + synthetic content	UI to build	Expected safe behavior	Scoring event
1 Event	Dashboard notification: '@neel.verma: This is the recipe we discussed yesterday.' The Instagram badge increments and the toast routes into the scenario.	Dashboard toast, Instagram-style tile, DM/activity badge, account avatar and synthetic preview.	Notice the source and time; open the full item before acting. Do not reply from the preview.	NOTIFY_SEEN +0; open latency and route logged.
2 Open	Open the established DM thread and shared reel. Context presented: A long-standing friend shares a harmless public cooking reel without a link or request.	DM requests/inbox or activity/feed view with thread, post, story or reel context and timestamps.	Read the full thread/message and prior context before choosing any action.	ITEM_OPEN +0; premature reply/action -1; dwell time logged.
3 Inspect	Open details and examine exact handle, long message history, public source and absence of external action	Profile sheet with exact handle, account age, username history, mutuals, follower ratios and report controls.	Check this decision signal: The context matches the prior conversation and the reel stays within the app.	INSPECT_CONTEXT +2; inspection path and time logged.
4 Branch	The interaction advances to the in-app reel player with Like/Save/Reply	In-app profile/post/story view plus offline link browser, media composer or synthetic payment panel.	Use the normal in-app path only after the details match the known context. Do not switch to an untrusted channel.	CORRECT_USE +3; needless reject/ignore -2; unsafe external action -4.
5 Verify	The learner opens Verify / More actions. Verification route: use the existing thread context; no extra verification is required unless the content differs	DM action sheet with restrict/block/report and independent Trusted Directory or official-account lookup overlay.	Verify independently: use the existing thread context; no extra verification is required unless the content differs. If it matches, continue; do not report or block a legitimate sender.	TRUSTED_VERIFY +3; false report/block -4; verification through message +0.
6 Resolve	Final expected resolution: view/save or reply normally; do not report or block	Outcome card, concise feedback, warning-sign chips, event summary and Return to dashboard.	Complete the resolution and return to the dashboard.	RESOLVE_CORRECT +2; contradictory unsafe final -4; scenario capped 0-10.

End-state Reel closes normally and the message is marked read.	Concise learner feedback Good security includes normal use of verified, expected content. Do not create false positives without evidence.
---	--

Verification Badge Agent

Platform Instagram	Difficulty Easy	Disposition Malicious	Attack / case family Fake verification service	Primary trigger Status + scarcity
-----------------------	--------------------	--------------------------	---	--------------------------------------

Stage	Learner flow + synthetic content	UI to build	Expected safe behavior	Scoring event
1 Event	Dashboard notification: '@badge_priority_agent: Your profile is pre-approved. Pay today for guaranteed verification.' The Instagram badge increments and the toast routes into the scenario.	Dashboard toast, Instagram-style tile, DM/activity badge, account avatar and synthetic preview.	Notice the source and time; open the full item before acting. Do not reply from the preview.	NOTIFY_SEEN +0; open latency and route logged.
2 Open	Open the DM request and agent profile. Context presented: A DM account offers a guaranteed blue badge through a private form and fee.	DM requests/inbox or activity/feed view with thread, post, story or reel context and timestamps.	Read the full thread/message and prior context before choosing any action.	ITEM_OPEN +0; premature reply/action -1; dwell time logged.
3 Inspect	Open details and examine third-party claim, recent account, guaranteed outcome and payment request	Profile sheet with exact handle, account age, username history, mutuals, follower ratios and report controls.	Check this decision signal: A private agent cannot guarantee platform verification; official options are available through in-app settings.	INSPECT_CONTEXT +2; inspection path and time logged.
4 Branch	The interaction advances to a synthetic badge application requesting password, ID and payment	In-app profile/post/story view plus offline link browser, media composer or synthetic payment panel.	Do not submit credentials/ID or pay the agent. Use Back/Close or safe preview only; no secret, payment, install or data release.	SAFE_PIVOT +3; risky open/reply -3; secret/payment/install/data release -8.
5 Verify	The learner opens Verify / More actions. Verification route: open the platform's own verification settings and Help Center locally	DM action sheet with restrict/block/report and independent Trusted Directory or official-account lookup overlay.	Verify independently: open the platform's own verification settings and Help Center locally Then use the platform report/block path or the unit reporting route.	TRUSTED_VERIFY +3; report-only without checking +1; verification through message +0.
6 Resolve	Final expected resolution: close; report/block the agent; use only official in-app verification if desired	Outcome card, concise feedback, warning-sign chips, event summary and Return to dashboard.	Complete the resolution and return to the dashboard.	RESOLVE_CORRECT +2; contradictory unsafe final -4; scenario capped 0-10.

End-state Fake application is discarded and account remains secure.	Concise learner feedback Verification is not sold through unsolicited DMs. Use only the platform's in-app process.
--	---

Deepfake Trading Advertisement

Platform Instagram	Difficulty Medium	Disposition Malicious	Attack / case family Investment fraud / synthetic endorsement	Primary trigger Greed + authority
-----------------------	----------------------	--------------------------	--	--------------------------------------

Stage	Learner flow + synthetic content	UI to build	Expected safe behavior	Scoring event
1 Event	Dashboard notification: 'Sponsored: Exclusive AI trading window - join the private group before midnight.' The Instagram badge increments and the toast routes into the scenario.	Dashboard toast, Instagram-style tile, DM/activity badge, account avatar and synthetic preview.	Notice the source and time; open the full item before acting. Do not reply from the preview.	NOTIFY_SEEN +0; open latency and route logged.
2 Open	Open the sponsored reel and advertiser profile. Context presented: A sponsored reel shows a synthetic public figure promising guaranteed AI-trading returns.	DM requests/inbox or activity/feed view with thread, post, story or reel context and timestamps.	Read the full thread/message and prior context before choosing any action.	ITEM_OPEN +0; premature reply/action -1; dwell time logged.
3 Inspect	Open details and examine paid-ad label, advertiser history, altered lip sync, promised returns and destination	Profile sheet with exact handle, account age, username history, mutuals, follower ratios and report controls.	Check this decision signal: A polished or familiar face does not prove endorsement; guaranteed returns and private groups are warning signs.	INSPECT_CONTEXT +2; inspection path and time logged.
4 Branch	The interaction advances to an offline ad landing page that moves the learner to a fake WhatsApp group and trading app	In-app profile/post/story view plus offline link browser, media composer or synthetic payment panel.	Do not join, install, deposit or upload identity documents. Use Back/Close or safe preview only; no secret, payment, install or data release.	SAFE_PIVOT +3; risky open/reply -3; secret/payment/install/data release -8.
5 Verify	The learner opens Verify / More actions. Verification route: check the investment adviser and platform through independently known regulator/official sources	DM action sheet with restrict/block/report and independent Trusted Directory or official-account lookup overlay.	Verify independently: check the investment adviser and platform through independently known regulator/official sources Then use the platform report/block path or the unit reporting route.	TRUSTED_VERIFY +3; report-only without checking +1; verification through message +0.
6 Resolve	Final expected resolution: close and report the ad/account; do not join, install or deposit	Outcome card plus 250-character rationale box, warning-sign chips, event summary and Return to dashboard.	Complete the resolution and return to the dashboard. Add a one-line reason without sensitive data.	RESOLVE_CORRECT +2; contradictory unsafe final -4; scenario capped 0-10.

End-state Ad is removed locally and the synthetic portfolio remains empty.	Concise learner feedback Synthetic media and ads can manufacture authority. Verify registration and never trust guaranteed social-media returns.
---	---

Brand Collaboration Shipping Fee

Platform	Difficulty	Disposition	Attack / case family	Primary trigger
Instagram	Medium	Malicious	Influencer/brand impersonation	Flattery + reciprocity

Stage	Learner flow + synthetic content	UI to build	Expected safe behavior	Scoring event
1 Event	Dashboard notification: '@peakgear_collabs: Selected ambassador! Free kit - pay only INR 199 shipping.' The Instagram badge increments and the toast routes into the scenario.	Dashboard toast, Instagram-style tile, DM/activity badge, account avatar and synthetic preview.	Notice the source and time; open the full item before acting. Do not reply from the preview.	NOTIFY_SEEN +0; open latency and route logged.
2 Open	Open the DM and brand-look-alike profile. Context presented: A supposed sports brand offers a free kit but asks the learner to pay shipping through a bio link.	DM requests/inbox or activity/feed view with thread, post, story or reel context and timestamps.	Read the full thread/message and prior context before choosing any action.	ITEM_OPEN +0; premature reply/action -1; dwell time logged.
3 Inspect	Open details and examine handle spelling, account age, copied posts, private payment link and pressure	Profile sheet with exact handle, account age, username history, mutuals, follower ratios and report controls.	Check this decision signal: Unsolicited selection, cloned branding and upfront fees contradict a normal documented collaboration.	INSPECT_CONTEXT +2; inspection path and time logged.
4 Branch	The interaction advances to a fake creator-contract page requesting address, card and social password	In-app profile/post/story view plus offline link browser, media composer or synthetic payment panel.	Do not pay, enter credentials or provide unnecessary personal data. Use Back/Close or safe preview only; no secret, payment, install or data release.	SAFE_PIVOT +3; risky open/reply -3; secret/payment/install/data release -8.
5 Verify	The learner opens Verify / More actions. Verification route: contact the brand through its separately found official site/account	DM action sheet with restrict/block/report and independent Trusted Directory or official-account lookup overlay.	Verify independently: contact the brand through its separately found official site/account Then use the platform report/block path or the unit reporting route.	TRUSTED_VERIFY +3; report-only without checking +1; verification through message +0.
6 Resolve	Final expected resolution: decline; report the impersonating account and link; block it	Outcome card, concise feedback, warning-sign chips, event summary and Return to dashboard.	Complete the resolution and return to the dashboard.	RESOLVE_CORRECT +2; contradictory unsafe final -4; scenario capped 0-10.

End-state No shipping fee or data submission occurs.	Concise learner feedback Flattery can lower caution. Verify the company independently and reject upfront-fee collaborations.
---	---

Official Welfare Helpline Update

Platform Instagram	Difficulty Medium	Disposition Legitimate	Attack / case family Legitimate official-account update	Primary trigger Authority + care FICTIONAL MILITARY CONTEXT
-----------------------	----------------------	---------------------------	--	--

Stage	Learner flow + synthetic content	UI to build	Expected safe behavior	Scoring event
1 Event	Dashboard notification: '@forces_welfare_official: Helpline extension updated. Use the contact in the approved directory.' The Instagram badge increments and the toast routes into the scenario.	Dashboard toast, Instagram-style tile, DM/activity badge, account avatar and synthetic preview.	Notice the source and time; open the full item before acting. Do not reply from the preview.	NOTIFY_SEEN +0; open latency and route logged.
2 Open	Open the official post and profile. Context presented: A verified fictional welfare account posts a helpline change already listed in the approved directory.	DM requests/inbox or activity/feed view with thread, post, story or reel context and timestamps.	Read the full thread/message and prior context before choosing any action.	ITEM_OPEN +0; premature reply/action -1; dwell time logged.
3 Inspect	Open details and examine exact handle, verified status, consistent history and directory match	Profile sheet with exact handle, account age, username history, mutuals, follower ratios and report controls.	Check this decision signal: The post directs users to an independently maintained directory and requests no private response.	INSPECT_CONTEXT +2; inspection path and time logged.
4 Branch	The interaction advances to the post details and local directory comparison panel	In-app profile/post/story view plus offline link browser, media composer or synthetic payment panel.	Use the normal in-app path only after the details match the known context. Do not switch to an untrusted channel.	CORRECT_USE +3; needless reject/ignore -2; unsafe external action -4.
5 Verify	The learner opens Verify / More actions. Verification route: compare the account and extension with the Trusted Directory	DM action sheet with restrict/block/report and independent Trusted Directory or official-account lookup overlay.	Verify independently: compare the account and extension with the Trusted Directory. If it matches, continue; do not report or block a legitimate sender.	TRUSTED_VERIFY +3; false report/block -4; verification through message +0.
6 Resolve	Final expected resolution: save the verified update; do not report/block; do not post personal case details	Outcome card, concise feedback, warning-sign chips, event summary and Return to dashboard.	Complete the resolution and return to the dashboard.	RESOLVE_CORRECT +2; contradictory unsafe final -4; scenario capped 0-10.

End-state Directory match is confirmed and the post remains saved.	Concise learner feedback Official updates should be cross-checked with an approved directory. Keep personal cases out of public comments.
---	--

Account Recovery Backup Code

Platform Instagram	Difficulty Medium	Disposition Malicious	Attack / case family Account-recovery phishing	Primary trigger Fear + authority
-----------------------	----------------------	--------------------------	---	-------------------------------------

Stage	Learner flow + synthetic content	UI to build	Expected safe behavior	Scoring event
1 Event	Dashboard notification: '@meta_recovery_case: We stopped a hacker. Send one backup code to secure your account.' The Instagram badge increments and the toast routes into the scenario.	Dashboard toast, Instagram-style tile, DM/activity badge, account avatar and synthetic preview.	Notice the source and time; open the full item before acting. Do not reply from the preview.	NOTIFY_SEEN +0; open latency and route logged.
2 Open	Open the DM request and recovery profile. Context presented: A support-like account claims to have recovered the learner's profile and asks for a backup code to finish.	DM requests/inbox or activity/feed view with thread, post, story or reel context and timestamps.	Read the full thread/message and prior context before choosing any action.	ITEM_OPEN +0; premature reply/action -1; dwell time logged.
3 Inspect	Open details and examine unofficial handle, request for a secret, no in-app case and suspicious link	Profile sheet with exact handle, account age, username history, mutuals, follower ratios and report controls.	Check this decision signal: Backup codes grant account access; legitimate support does not ask for them in DMs.	INSPECT_CONTEXT +2; inspection path and time logged.
4 Branch	The interaction advances to a reply composer and fake security-check page	In-app profile/post/story view plus offline link browser, media composer or synthetic payment panel.	Do not send a backup code, password or recovery link. Use Back/Close or safe preview only; no secret, payment, install or data release.	SAFE_PIVOT +3; risky open/reply -3; secret/payment/install/data release -8.
5 Verify	The learner opens Verify / More actions. Verification route: open Security Checkup/Password and security directly from Settings	DM action sheet with restrict/block/report and independent Trusted Directory or official-account lookup overlay.	Verify independently: open Security Checkup/Password and security directly from Settings Then use the platform report/block path or the unit reporting route.	TRUSTED_VERIFY +3; report-only without checking +1; verification through message +0.
6 Resolve	Final expected resolution: send nothing; report/block the fake support account; review sessions and enable strong MFA	Outcome card, concise feedback, warning-sign chips, event summary and Return to dashboard.	Complete the resolution and return to the dashboard.	RESOLVE_CORRECT +2; contradictory unsafe final -4; scenario capped 0-10.

End-state No code is revealed and the account-security mock shows controlled sessions.	Concise learner feedback Recovery codes are secrets. Start recovery yourself through the platform, never through an inbound DM.
---	--

Deployed Officer Romance Profile

Platform Instagram	Difficulty Medium	Disposition Malicious	Attack / case family Romance scam / identity fabrication	Primary trigger Trust + empathy FICTIONAL MILITARY CONTEXT
-----------------------	----------------------	--------------------------	---	---

Stage	Learner flow + synthetic content	UI to build	Expected safe behavior	Scoring event
1 Event	Dashboard notification: '@captain_aarav_global: My baggage is held. Please pay the release fee; I will repay you tomorrow.' The Instagram badge increments and the toast routes into the scenario.	Dashboard toast, Instagram-style tile, DM/activity badge, account avatar and synthetic preview.	Notice the source and time; open the full item before acting. Do not reply from the preview.	NOTIFY_SEEN +0; open latency and route logged.
2 Open	Open the multi-day DM and profile. Context presented: A profile claiming to be a deployed officer quickly builds intimacy and then requests emergency customs money.	DM requests/inbox or activity/feed view with thread, post, story or reel context and timestamps.	Read the full thread/message and prior context before choosing any action.	ITEM_OPEN +0; premature reply/action -1; dwell time logged.
3 Inspect	Open details and examine stolen-looking photos, inconsistent locations, rapid intimacy and money request	Profile sheet with exact handle, account age, username history, mutuals, follower ratios and report controls.	Check this decision signal: Military status is being used as credibility; the relationship cannot validate identity or financial need.	INSPECT_CONTEXT +2; inspection path and time logged.
4 Branch	The interaction advances to a customs-payment mock with crypto/gift-card choices	In-app profile/post/story view plus offline link browser, media composer or synthetic payment panel.	Do not send money, gift cards, identity documents or intimate media. Use Back/Close or safe preview only; no secret, payment, install or data release.	SAFE_PIVOT +3; risky open/reply -3; secret/payment/install/data release -8.
5 Verify	The learner opens Verify / More actions. Verification route: verify identity independently; reverse-image/search tools may be represented locally for training	DM action sheet with restrict/block/report and independent Trusted Directory or official-account lookup overlay.	Verify independently: verify identity independently; reverse-image/search tools may be represented locally for training. Then use the platform report/block path or the unit reporting route.	TRUSTED_VERIFY +3; report-only without checking +1; verification through message +0.
6 Resolve	Final expected resolution: do not pay; preserve evidence; report/block the account	Outcome card plus 250-character rationale box, warning-sign chips, event summary and Return to dashboard.	Complete the resolution and return to the dashboard. Add a one-line reason without sensitive data.	RESOLVE_CORRECT +2; contradictory unsafe final -4; scenario capped 0-10.

End-state Fake customs case fails verification and the payment path closes.	Concise learner feedback Uniform photos and emotional stories are not identity proof. Never finance an online-only relationship under pressure.
--	--

Commendation Page Requests Documents

Platform Instagram	Difficulty Medium	Disposition Malicious	Attack / case family Military-themed impersonation / identity theft	Primary trigger Pride + authority FICTIONAL MILITARY CONTEXT
Stage	Learner flow + synthetic content	UI to build	Expected safe behavior	Scoring event
1 Event	Dashboard notification: '@honour_roll_india: Send service card and posting proof to verify your feature today.' The Instagram badge increments and the toast routes into the scenario.	Dashboard toast, Instagram-style tile, DM/activity badge, account avatar and synthetic preview.	Notice the source and time; open the full item before acting. Do not reply from the preview.	NOTIFY_SEEN +0; open latency and route logged.
2 Open	Open the DM request and fan page. Context presented: A fan page says the learner is shortlisted for a public commendation feature and requests service documents.	DM requests/inbox or activity/feed view with thread, post, story or reel context and timestamps.	Read the full thread/message and prior context before choosing any action.	ITEM_OPEN +0; premature reply/action -1; dwell time logged.
3 Inspect	Open details and examine non-official status, copied emblems, public bio and document request	Profile sheet with exact handle, account age, username history, mutuals, follower ratios and report controls.	Check this decision signal: A social-media feature has no legitimate need for service identity documents or posting proof.	INSPECT_CONTEXT +2; inspection path and time logged.
4 Branch	The interaction advances to a media uploader accepting synthetic ID and posting-order files	In-app profile/post/story view plus offline link browser, media composer or synthetic payment panel.	Do not upload identity, posting or family documents. Use Back/Close or safe preview only; no secret, payment, install or data release.	SAFE_PIVOT +3; risky open/reply -3; secret/payment/install/data release -8.
5 Verify	The learner opens Verify / More actions. Verification route: check with the approved public-information/administrative office through known channels	DM action sheet with restrict/block/report and independent Trusted Directory or official-account lookup overlay.	Verify independently: check with the approved public-information/administrative office through known channels Then use the platform report/block path or the unit reporting route.	TRUSTED_VERIFY +3; report-only without checking +1; verification through message +0.
6 Resolve	Final expected resolution: upload nothing; report the impersonation/data solicitation; block the page	Outcome card, concise feedback, warning-sign chips, event summary and Return to dashboard.	Complete the resolution and return to the dashboard.	RESOLVE_CORRECT +2; contradictory unsafe final -4; scenario capped 0-10.
End-state Uploader is cleared and the account is added to the local report queue.		Concise learner feedback Pride and recognition can be used as bait. Protect service documents and verify through official channels.		

You Are in This Video

Platform Instagram	Difficulty Medium	Disposition Malicious	Attack / case family Compromised-contact link phishing	Primary trigger Curiosity + embarrassment
-----------------------	----------------------	--------------------------	---	--

Stage	Learner flow + synthetic content	UI to build	Expected safe behavior	Scoring event
1 Event	Dashboard notification: '@knownfriend: Is this you in the video?? I can't believe it.' The Instagram badge increments and the toast routes into the scenario.	Dashboard toast, Instagram-style tile, DM/activity badge, account avatar and synthetic preview.	Notice the source and time; open the full item before acting. Do not reply from the preview.	NOTIFY_SEEN +0; open latency and route logged.
2 Open	Open the existing DM thread and video thumbnail. Context presented: A known account sends a short DM saying the learner appears in a shocking video.	DM requests/inbox or activity/feed view with thread, post, story or reel context and timestamps.	Read the full thread/message and prior context before choosing any action.	ITEM_OPEN +0; premature reply/action -1; dwell time logged.
3 Inspect	Open details and examine changed message style, external target, generic thumbnail and unusual timing	Profile sheet with exact handle, account age, username history, mutuals, follower ratios and report controls.	Check this decision signal: A real contact can be compromised; the lure creates curiosity and embarrassment to force a click.	INSPECT_CONTEXT +2; inspection path and time logged.
4 Branch	The interaction advances to a fake Instagram login page before the 'video'	In-app profile/post/story view plus offline link browser, media composer or synthetic payment panel.	Do not enter username/password or approve a login prompt. Use Back/Close or safe preview only; no secret, payment, install or data release.	SAFE_PIVOT +3; risky open/reply -3; secret/payment/install/data release -8.
5 Verify	The learner opens Verify / More actions. Verification route: call/message the friend through another known route and review login activity	DM action sheet with restrict/block/report and independent Trusted Directory or official-account lookup overlay.	Verify independently: call/message the friend through another known route and review login activity Then use the platform report/block path or the unit reporting route.	TRUSTED_VERIFY +3; report-only without checking +1; verification through message +0.
6 Resolve	Final expected resolution: close the page; report the suspicious DM; alert the verified friend	Outcome card, concise feedback, warning-sign chips, event summary and Return to dashboard.	Complete the resolution and return to the dashboard.	RESOLVE_CORRECT +2; contradictory unsafe final -4; scenario capped 0-10.

End-state Known friend confirms compromise; learner credentials remain untouched.	Concise learner feedback Unexpected emotion-driven links from known accounts still require verification. Do not re-login from a DM link.
--	---

Approved Photo Release Request

Platform Instagram	Difficulty Medium	Disposition Legitimate	Attack / case family Legitimate public-affairs workflow	Primary trigger Authority + pride FICTIONAL MILITARY CONTEXT
-----------------------	----------------------	---------------------------	--	---

Stage	Learner flow + synthetic content	UI to build	Expected safe behavior	Scoring event
1 Event	Dashboard notification: '@unitfalcon_public: Approved image PF-204 is ready. Confirm your consent in the in-app card.' The Instagram badge increments and the toast routes into the scenario.	Dashboard toast, Instagram-style tile, DM/activity badge, account avatar and synthetic preview.	Notice the source and time; open the full item before acting. Do not reply from the preview.	NOTIFY_SEEN +0; open latency and route logged.
2 Open	Open the established admin DM and tagged draft. Context presented: A known public-information admin asks the learner to approve a previously reviewed, non-sensitive event photo.	DM requests/inbox or activity/feed view with thread, post, story or reel context and timestamps.	Read the full thread/message and prior context before choosing any action.	ITEM_OPEN +0; premature reply/action -1; dwell time logged.
3 Inspect	Open details and examine known admin handle, local approval ID, image status and consent scope	Profile sheet with exact handle, account age, username history, mutuals, follower ratios and report controls.	Check this decision signal: The request matches the synthetic release register and asks only for in-app consent, not operational data.	INSPECT_CONTEXT +2; inspection path and time logged.
4 Branch	The interaction advances to a consent card showing the approved image, scope and Confirm/Decline	In-app profile/post/story view plus offline link browser, media composer or synthetic payment panel.	Use the normal in-app path only after the details match the known context. Do not switch to an untrusted channel.	CORRECT_USE +3; needless reject/ignore -2; unsafe external action -4.
5 Verify	The learner opens Verify / More actions. Verification route: compare image ID PF-204 with the local public-release register	DM action sheet with restrict/block/report and independent Trusted Directory or official-account lookup overlay.	Verify independently: compare image ID PF-204 with the local public-release register. If it matches, continue; do not report or block a legitimate sender.	TRUSTED_VERIFY +3; false report/block -4; verification through message +0.
6 Resolve	Final expected resolution: confirm or decline the matching consent card; do not report the verified admin	Outcome card plus 250-character rationale box, warning-sign chips, event summary and Return to dashboard.	Complete the resolution and return to the dashboard. Add a one-line reason without sensitive data.	RESOLVE_CORRECT +2; contradictory unsafe final -4; scenario capped 0-10.

End-state Consent decision is stored against the synthetic approved image only.	Concise learner feedback A legitimate publication request is specific, verifiable and limited. Confirm the exact approved asset and scope.
--	---

Morphed-Photo Blackmail

Platform Instagram	Difficulty Medium	Disposition Malicious	Attack / case family Image-based extortion	Primary trigger Fear + shame + isolation
-----------------------	----------------------	--------------------------	---	---

Stage	Learner flow + synthetic content	UI to build	Expected safe behavior	Scoring event
1 Event	Dashboard notification: '@private_case_404: Pay tonight or this edited image goes to everyone you follow.' The Instagram badge increments and the toast routes into the scenario.	Dashboard toast, Instagram-style tile, DM/activity badge, account avatar and synthetic preview.	Notice the source and time; open the full item before acting. Do not reply from the preview.	NOTIFY_SEEN +0; open latency and route logged.
2 Open	Open the DM request with safety-blurred image. Context presented: An account sends a blurred synthetic composite and threatens to post it unless paid.	DM requests/inbox or activity/feed view with thread, post, story or reel context and timestamps.	Read the full thread/message and prior context before choosing any action.	ITEM_OPEN +0; premature reply/action -1; dwell time logged.
3 Inspect	Open details and examine unknown account, extortion demand, countdown and crypto payment handle	Profile sheet with exact handle, account age, username history, mutuals, follower ratios and report controls.	Check this decision signal: Paying or negotiating does not guarantee removal and may increase demands; evidence and support matter.	INSPECT_CONTEXT +2; inspection path and time logged.
4 Branch	The interaction advances to a payment panel and threatening follow-up timer	In-app profile/post/story view plus offline link browser, media composer or synthetic payment panel.	Do not pay, send more images, negotiate alone or delete all evidence. Use Back/Close or safe preview only; no secret, payment, install or data release.	SAFE_PIVOT +3; risky open/reply -3; secret/payment/install/data release -8.
5 Verify	The learner opens Verify / More actions. Verification route: use the platform report path and approved unit/law-enforcement support route	DM action sheet with restrict/block/report and independent Trusted Directory or official-account lookup overlay.	Verify independently: use the platform report path and approved unit/law-enforcement support route Then use the platform report/block path or the unit reporting route.	TRUSTED_VERIFY +3; report-only without checking +1; verification through message +0.
6 Resolve	Final expected resolution: do not pay or respond; preserve evidence; report/block; seek approved support promptly	Outcome card plus 250-character rationale box, warning-sign chips, event summary and Return to dashboard.	Complete the resolution and return to the dashboard. Add a one-line reason without sensitive data.	RESOLVE_CORRECT +2; contradictory unsafe final -4; scenario capped 0-10.

End-state Threat is contained, evidence is stored locally and support options are displayed.	Concise learner feedback You are not at fault. Do not pay or comply; preserve evidence, report the account and seek trusted support.
---	---

High-Fidelity Teammate Clone

Platform Instagram	Difficulty Hard	Disposition Malicious	Attack / case family Profile cloning / location elicitation	Primary trigger Familiarity + urgency FICTIONAL MILITARY CONTEXT
-----------------------	--------------------	--------------------------	--	---

Stage	Learner flow + synthetic content	UI to build	Expected safe behavior	Scoring event
1 Event	Dashboard notification: '@arjun.k_singh: New private account. Send tomorrow's assembly point so I don't miss it.' The Instagram badge increments and the toast routes into the scenario.	Dashboard toast, Instagram-style tile, DM/activity badge, account avatar and synthetic preview.	Notice the source and time; open the full item before acting. Do not reply from the preview.	NOTIFY_SEEN +0; open latency and route logged.
2 Open	Open the DM and highly copied profile. Context presented: A clone has bought followers, copied recent posts and follows many mutuals before asking for a meetup location.	DM requests/inbox or activity/feed view with thread, post, story or reel context and timestamps.	Read the full thread/message and prior context before choosing any action.	ITEM_OPEN +0; premature reply/action -1; dwell time logged.
3 Inspect	Open details and examine username history, creation date, mutual timing, copied captions and private request	Profile sheet with exact handle, account age, username history, mutuals, follower ratios and report controls.	Check this decision signal: Follower count and mutuals can be manufactured; a new account still cannot receive protected schedule/location details.	INSPECT_CONTEXT +2; inspection path and time logged.
4 Branch	The interaction advances to a map/location reply card	In-app profile/post/story view plus offline link browser, media composer or synthetic payment panel.	Do not send assembly point, live location, schedule or roster detail. Use Back/Close or safe preview only; no secret, payment, install or data release.	SAFE_PIVOT +3; risky open/reply -3; secret/payment/install/data release -8.
5 Verify	The learner opens Verify / More actions. Verification route: contact the teammate through the previously known account/number and check the approved schedule channel	DM action sheet with restrict/block/report and independent Trusted Directory or official-account lookup overlay.	Verify independently: contact the teammate through the previously known account/number and check the approved schedule channel. Then use the platform report/block path or the unit reporting route.	TRUSTED_VERIFY +3; report-only without checking +1; verification through message +0.
6 Resolve	Final expected resolution: send nothing; report the clone; notify the real teammate and unit security	Outcome card, concise feedback, warning-sign chips, event summary and Return to dashboard.	Complete the resolution and return to the dashboard.	RESOLVE_CORRECT +2; contradictory unsafe final -4; scenario capped 0-10.

End-state

Clone is confirmed despite strong social proof; location remains protected.

Concise learner feedback

High-quality clones exploit social proof. Account history and an independent known contact matter more than follower counts.

Urgent Unit Incident Report

Platform Instagram	Difficulty Hard	Disposition Malicious	Attack / case family Disinformation / amplification lure	Primary trigger Fear + duty FICTIONAL MILITARY CONTEXT
-----------------------	--------------------	--------------------------	---	---

Stage	Learner flow + synthetic content	UI to build	Expected safe behavior	Scoring event
1 Event	Dashboard notification: '@breaking_defence_now: URGENT incident at Unit Falcon - repost before it is deleted.' The Instagram badge increments and the toast routes into the scenario.	Dashboard toast, Instagram-style tile, DM/activity badge, account avatar and synthetic preview.	Notice the source and time; open the full item before acting. Do not reply from the preview.	NOTIFY_SEEN +0; open latency and route logged.
2 Open	Open the viral post and reshare tray. Context presented: A dramatic post falsely claims an incident involving fictional Unit Falcon and asks everyone to repost immediately.	DM requests/inbox or activity/feed view with thread, post, story or reel context and timestamps.	Read the full thread/message and prior context before choosing any action.	ITEM_OPEN +0; premature reply/action -1; dwell time logged.
3 Inspect	Open details and examine source history, absent official confirmation, recycled image and urgency to amplify	Profile sheet with exact handle, account age, username history, mutuals, follower ratios and report controls.	Check this decision signal: Unverified crisis content can expose, misinform or amplify manipulation; speed is not a substitute for confirmation.	INSPECT_CONTEXT +2; inspection path and time logged.
4 Branch	The interaction advances to a reshare composer with Add location/Tag personnel options	In-app profile/post/story view plus offline link browser, media composer or synthetic payment panel.	Do not repost, speculate, tag personnel or add location. Use Back/Close or safe preview only; no secret, payment, install or data release.	SAFE_PIVOT +3; risky open/reply -3; secret/payment/install/data release -8.
5 Verify	The learner opens Verify / More actions. Verification route: check approved official statements and alert the unit public-information/security route	DM action sheet with restrict/block/report and independent Trusted Directory or official-account lookup overlay.	Verify independently: check approved official statements and alert the unit public-information/security route. Then use the platform report/block path or the unit reporting route.	TRUSTED_VERIFY +3; report-only without checking +1; verification through message +0.
6 Resolve	Final expected resolution: do not repost; report misinformation/impersonation if applicable; preserve link for review	Outcome card plus 250-character rationale box, warning-sign chips, event summary and Return to dashboard.	Complete the resolution and return to the dashboard. Add a one-line reason without sensitive data.	RESOLVE_CORRECT +2; contradictory unsafe final -4; scenario capped 0-10.

End-state The viral post is held from sharing and routed to local moderation.	Concise learner feedback Pause before amplifying crisis claims. Verify through official channels and never add operational context.
--	--

Researcher Asks Capability Questions

Platform Instagram	Difficulty Hard	Disposition Malicious	Attack / case family Rapport-based elicitation / espionage pretext	Primary trigger Expert status + flattery FICTIONAL MILITARY CONTEXT
Stage	Learner flow + synthetic content	UI to build	Expected safe behavior	Scoring event
1 Event	Dashboard notification: '@defence_research_lab: Your experience is valuable. Which system fails most often in field conditions?' The Instagram badge increments and the toast routes into the scenario.	Dashboard toast, Instagram-style tile, DM/activity badge, account avatar and synthetic preview.	Notice the source and time; open the full item before acting. Do not reply from the preview.	NOTIFY_SEEN +0; open latency and route logged.
2 Open	Open the long-running DM and researcher profile. Context presented: A credible-looking researcher has interacted normally for weeks, then asks about equipment limitations.	DM requests/inbox or activity/feed view with thread, post, story or reel context and timestamps.	Read the full thread/message and prior context before choosing any action.	ITEM_OPEN +0; premature reply/action -1; dwell time logged.
3 Inspect	Open details and examine institution mismatch, unverifiable publications, narrow capability questions and gradual escalation	Profile sheet with exact handle, account age, username history, mutuals, follower ratios and report controls.	Check this decision signal: A plausible professional identity does not create authorization to discuss capabilities or limitations.	INSPECT_CONTEXT +2; inspection path and time logged.
4 Branch	The interaction advances to a structured interview form requesting equipment, readiness and routine details	In-app profile/post/story view plus offline link browser, media composer or synthetic payment panel.	Do not answer, correct public speculation with nonpublic facts, or upload photos. Use Back/Close or safe preview only; no secret, payment, install or data release.	SAFE_PIVOT +3; risky open/reply -3; secret/payment/install/data release -8.
5 Verify	The learner opens Verify / More actions. Verification route: route the request to the approved public-information/security contact for authorization	DM action sheet with restrict/block/report and independent Trusted Directory or official-account lookup overlay.	Verify independently: route the request to the approved public-information/security contact for authorization Then use the platform report/block path or the unit reporting route.	TRUSTED_VERIFY +3; report-only without checking +1; verification through message +0.
6 Resolve	Final expected resolution: decline to discuss; report the elicitation attempt internally; restrict/block per policy	Outcome card plus 250-character rationale box, warning-sign chips, event summary and Return to dashboard.	Complete the resolution and return to the dashboard. Add a one-line reason without sensitive data.	RESOLVE_CORRECT +2; contradictory unsafe final -4; scenario capped 0-10.
End-state No capability data is submitted and the account is flagged for review.		Concise learner feedback Elicitation often feels like professional conversation. Need-to-know and release authorization still apply.		

Post-Event Teammate Tag

Platform Instagram	Difficulty Hard	Disposition Legitimate	Attack / case family Legitimate post-event sharing	Primary trigger Familiarity + pride FICTIONAL MILITARY CONTEXT
Stage	Learner flow + synthetic content	UI to build	Expected safe behavior	Scoring event
1 Event	Dashboard notification: '@arjun.k.singh: Public-release photo PF-311 is up. May I tag you?' The Instagram badge increments and the toast routes into the scenario.	Dashboard toast, Instagram-style tile, DM/activity badge, account avatar and synthetic preview.	Notice the source and time; open the full item before acting. Do not reply from the preview.	NOTIFY_SEEN +0; open latency and route logged.
2 Open	Open the established DM and published post. Context presented: A known teammate asks to tag the learner in an approved photo after the event has concluded and the image is marked public.	DM requests/inbox or activity/feed view with thread, post, story or reel context and timestamps.	Read the full thread/message and prior context before choosing any action.	ITEM_OPEN +0; premature reply/action -1; dwell time logged.
3 Inspect	Open details and examine exact handle, long history, public-release ID and absence of future schedule/location	Profile sheet with exact handle, account age, username history, mutuals, follower ratios and report controls.	Check this decision signal: The image and event are already approved for public release; the request is limited to a consent choice.	INSPECT_CONTEXT +2; inspection path and time logged.
4 Branch	The interaction advances to the tag-review card with Approve/Decline and privacy audience	In-app profile/post/story view plus offline link browser, media composer or synthetic payment panel.	Use the normal in-app path only after the details match the known context. Do not switch to an untrusted channel.	CORRECT_USE +3; needless reject/ignore -2; unsafe external action -4.
5 Verify	The learner opens Verify / More actions. Verification route: compare PF-311 with the local release register and privacy preferences	DM action sheet with restrict/block/report and independent Trusted Directory or official-account lookup overlay.	Verify independently: compare PF-311 with the local release register and privacy preferences. If it matches, continue; do not report or block a legitimate sender.	TRUSTED_VERIFY +3; false report/block -4; verification through message +0.
6 Resolve	Final expected resolution: approve or decline the verified tag; do not report/block; add no sensitive caption	Outcome card, concise feedback, warning-sign chips, event summary and Return to dashboard.	Complete the resolution and return to the dashboard.	RESOLVE_CORRECT +2; contradictory unsafe final -4; scenario capped 0-10.
End-state Tag preference is applied only to the approved post.		Concise learner feedback After verification, legitimate social use should remain possible. Control audience and avoid adding extra detail.		

Live Support Video Call

Platform Instagram	Difficulty Hard	Disposition Malicious	Attack / case family Fake platform support / call coercion	Primary trigger Authority + fear
-----------------------	--------------------	--------------------------	---	-------------------------------------

Stage	Learner flow + synthetic content	UI to build	Expected safe behavior	Scoring event
1 Event	Dashboard notification: '@security_live_case: Accept our video verification now to prevent account removal.' The Instagram badge increments and the toast routes into the scenario.	Dashboard toast, Instagram-style tile, DM/activity badge, account avatar and synthetic preview.	Notice the source and time; open the full item before acting. Do not reply from the preview.	NOTIFY_SEEN +0; open latency and route logged.
2 Open	Open the DM request and incoming call screen. Context presented: A fake support account initiates a video call and claims the profile will be disabled unless identity is shown on camera.	DM requests/inbox or activity/feed view with thread, post, story or reel context and timestamps.	Read the full thread/message and prior context before choosing any action.	ITEM_OPEN +0; premature reply/action -1; dwell time logged.
3 Inspect	Open details and examine unofficial handle, unsolicited call, secrecy and absence of in-app case	Profile sheet with exact handle, account age, username history, mutuals, follower ratios and report controls.	Check this decision signal: Support does not require an unsolicited DM video call, screen share or spoken recovery code.	INSPECT_CONTEXT +2; inspection path and time logged.
4 Branch	The interaction advances to a synthetic call requesting face scan, screen share and backup code	In-app profile/post/story view plus offline link browser, media composer or synthetic payment panel.	Do not accept continued coercion, show ID, share screen or speak a code. Use Back/Close or safe preview only; no secret, payment, install or data release.	SAFE_PIVOT +3; risky open/reply -3; secret/payment/install/data release -8.
5 Verify	The learner opens Verify / More actions. Verification route: end the call and open Security/Support directly in app settings	DM action sheet with restrict/block/report and independent Trusted Directory or official-account lookup overlay.	Verify independently: end the call and open Security/Support directly in app settings Then use the platform report/block path or the unit reporting route.	TRUSTED_VERIFY +3; report-only without checking +1; verification through message +0.
6 Resolve	Final expected resolution: decline/end; report/block the support impersonator; review account security	Outcome card, concise feedback, warning-sign chips, event summary and Return to dashboard.	Complete the resolution and return to the dashboard.	RESOLVE_CORRECT +2; contradictory unsafe final -4; scenario capped 0-10.

End-state Call ends before any permission or code is shared.	Concise learner feedback A video call is not proof of platform authority. Start support from the app and protect identity and recovery secrets.
---	--

Compromised Charity Influencer

Platform Instagram	Difficulty Hard	Disposition Malicious	Attack / case family Compromised trusted account / donation diversion	Primary trigger Empathy + social proof
-----------------------	--------------------	--------------------------	--	---

Stage	Learner flow + synthetic content	UI to build	Expected safe behavior	Scoring event
1 Event	Dashboard notification: '@carewithmaya: Emergency surgery fund - crypto only for the next two hours.' The Instagram badge increments and the toast routes into the scenario.	Dashboard toast, Instagram-style tile, DM/activity badge, account avatar and synthetic preview.	Notice the source and time; open the full item before acting. Do not reply from the preview.	NOTIFY_SEEN +0; open latency and route logged.
2 Open	Open the story, profile and recent post history. Context presented: A known charity creator's account posts a sudden crypto-only emergency fundraiser after takeover.	DM requests/inbox or activity/feed view with thread, post, story or reel context and timestamps.	Read the full thread/message and prior context before choosing any action.	ITEM_OPEN +0; premature reply/action -1; dwell time logged.
3 Inspect	Open details and examine changed beneficiary, crypto-only method, disabled comments and abrupt content shift	Profile sheet with exact handle, account age, username history, mutuals, follower ratios and report controls.	Check this decision signal: A real account can be compromised; urgency and a changed payment route need independent confirmation.	INSPECT_CONTEXT +2; inspection path and time logged.
4 Branch	The interaction advances to a crypto payment screen and share-to-story button	In-app profile/post/story view plus offline link browser, media composer or synthetic payment panel.	Do not send funds or amplify before verification. Use Back/Close or safe preview only; no secret, payment, install or data release.	SAFE_PIVOT +3; risky open/reply -3; secret/payment/install/data release -8.
5 Verify	The learner opens Verify / More actions. Verification route: use the charity's separately known website/contact and compare beneficiary details	DM action sheet with restrict/block/report and independent Trusted Directory or official-account lookup overlay.	Verify independently: use the charity's separately known website/contact and compare beneficiary details Then use the platform report/block path or the unit reporting route.	TRUSTED_VERIFY +3; report-only without checking +1; verification through message +0.
6 Resolve	Final expected resolution: do not donate/share; report the compromised story; notify the legitimate organization	Outcome card, concise feedback, warning-sign chips, event summary and Return to dashboard.	Complete the resolution and return to the dashboard.	RESOLVE_CORRECT +2; contradictory unsafe final -4; scenario capped 0-10.

End-state Donation is held and the verified charity confirms account compromise.	Concise learner feedback Verify the beneficiary, not just the account name. Compromised trusted accounts can redirect genuine goodwill.
---	--

Institutional Trading App

Platform Instagram	Difficulty Hard	Disposition Malicious	Attack / case family Fake regulated investment platform	Primary trigger Authority + greed
-----------------------	--------------------	--------------------------	--	--------------------------------------

Stage	Learner flow + synthetic content	UI to build	Expected safe behavior	Scoring event
1 Event	Dashboard notification: 'Sponsored: Institutional account access for service professionals - confirmed IPO allotment.' The Instagram badge increments and the toast routes into the scenario.	Dashboard toast, Instagram-style tile, DM/activity badge, account avatar and synthetic preview.	Notice the source and time; open the full item before acting. Do not reply from the preview.	NOTIFY_SEEN +0; open latency and route logged.
2 Open	Open the carousel, advertiser profile and comments. Context presented: A polished sponsored carousel claims special institutional access and shows fabricated regulator marks.	DM requests/inbox or activity/feed view with thread, post, story or reel context and timestamps.	Read the full thread/message and prior context before choosing any action.	ITEM_OPEN +0; premature reply/action -1; dwell time logged.
3 Inspect	Open details and examine misused marks, unverifiable registration, scripted comments and APK/download route	Profile sheet with exact handle, account age, username history, mutuals, follower ratios and report controls.	Check this decision signal: Official-looking marks and testimonials can be fabricated; special guaranteed access is implausible.	INSPECT_CONTEXT +2; inspection path and time logged.
4 Branch	The interaction advances to a fake app store/app dashboard with initial profit and withdrawal lock	In-app profile/post/story view plus offline link browser, media composer or synthetic payment panel.	Do not install, upload KYC, deposit or pay withdrawal tax. Use Back/Close or safe preview only; no secret, payment, install or data release.	SAFE_PIVOT +3; risky open/reply -3; secret/payment/install/data release -8.
5 Verify	The learner opens Verify / More actions. Verification route: independently verify the entity/adviser and use only an approved store/broker	DM action sheet with restrict/block/report and independent Trusted Directory or official-account lookup overlay.	Verify independently: independently verify the entity/adviser and use only an approved store/broker Then use the platform report/block path or the unit reporting route.	TRUSTED_VERIFY +3; report-only without checking +1; verification through message +0.
6 Resolve	Final expected resolution: report the ad/account; do not install, deposit or upload documents	Outcome card plus 250-character rationale box, warning-sign chips, event summary and Return to dashboard.	Complete the resolution and return to the dashboard. Add a one-line reason without sensitive data.	RESOLVE_CORRECT +2; contradictory unsafe final -4; scenario capped 0-10.

End-state The fake app remains inert and no identity/payment data is entered.	Concise learner feedback Regulatory logos are not proof. Verify registration independently and distrust guaranteed allocation or withdrawal fees.
--	--

Canteen Coupon Reel QR

Platform Instagram	Difficulty Hard	Disposition Malicious	Attack / case family Military-themed QR phishing	Primary trigger Familiarity + scarcity FICTIONAL MILITARY CONTEXT
-----------------------	--------------------	--------------------------	---	--

Stage	Learner flow + synthetic content	UI to build	Expected safe behavior	Scoring event
1 Event	Dashboard notification: '@falcon_family_deals: Scan for the first 200 service-family coupon packs.' The Instagram badge increments and the toast routes into the scenario.	Dashboard toast, Instagram-style tile, DM/activity badge, account avatar and synthetic preview.	Notice the source and time; open the full item before acting. Do not reply from the preview.	NOTIFY_SEEN +0; open latency and route logged.
2 Open	Open the reel and community account. Context presented: A convincing community reel offers limited canteen coupons and shows a QR code over copied imagery.	DM requests/inbox or activity/feed view with thread, post, story or reel context and timestamps.	Read the full thread/message and prior context before choosing any action.	ITEM_OPEN +0; premature reply/action -1; dwell time logged.
3 Inspect	Open details and examine unofficial handle, copied posts, limited-quantity pressure and hidden QR destination	Profile sheet with exact handle, account age, username history, mutuals, follower ratios and report controls.	Check this decision signal: A community theme and copied photos do not authorize collection of service or payment data.	INSPECT_CONTEXT +2; inspection path and time logged.
4 Branch	The interaction advances to the QR inspector and a synthetic eligibility form	In-app profile/post/story view plus offline link browser, media composer or synthetic payment panel.	Do not open the target, enter service number/family details or pay an activation fee. Use Back/Close or safe preview only; no secret, payment, install or data release.	SAFE_PIVOT +3; risky open/reply -3; secret/payment/install/data release -8.
5 Verify	The learner opens Verify / More actions. Verification route: check the known canteen/welfare notice route and official directory	DM action sheet with restrict/block/report and independent Trusted Directory or official-account lookup overlay.	Verify independently: check the known canteen/welfare notice route and official directory. Then use the platform report/block path or the unit reporting route.	TRUSTED_VERIFY +3; report-only without checking +1; verification through message +0.
6 Resolve	Final expected resolution: close; report the account/reel; do not enter data or share the coupon	Outcome card plus 250-character rationale box, warning-sign chips, event summary and Return to dashboard.	Complete the resolution and return to the dashboard. Add a one-line reason without sensitive data.	RESOLVE_CORRECT +2; contradictory unsafe final -4; scenario capped 0-10.

End-state QR flow is blocked locally and the community account is reported.	Concise learner feedback Military-themed familiarity can disguise phishing. Inspect the QR and verify benefits through official channels.
--	--

Scenario Bank: Email

Twenty-five six-stage scenarios for the simulated Email environment. Composition: 8 easy, 9 medium, 8 hard; 20 malicious/deceptive and 5 legitimate controls; 8 fictional military-context cases.

Implementation rule

All senders, messages, accounts, numbers, links, QR codes, files, calls and payment screens are synthetic. No scenario may resolve outside the local application. The learner can take unsafe-looking actions, but they only change local state and scoring.

ID	Scenario	Level	Case	Family	M	ID	Scenario	Level	Case	Family	M
E01	Password Expires Today	Easy	Malicious	Credential phishing		E14	Revised Movement Order	Medium	Malicious	Military spearphishing / attachment	Y
E02	Invoice Spreadsheet Macro	Easy	Malicious	Malicious attachment		E15	OAuth Consent for Mail Review	Medium	Malicious	Consent phishing / cloud-app access	
E03	Authenticated Internal Newsletter	Easy	Legitimate	Legitimate internal communication		E16	Signed Maintenance Notice	Medium	Legitimate	Legitimate IT maintenance	
E04	Customs Parcel Hold	Easy	Malicious	Delivery impersonation / fee phishing		E17	Invoice Callback Trap	Medium	Malicious	Callback phishing / tech-support fraud	
E05	Mandatory HR Policy Login	Easy	Malicious	HR impersonation / credential phishing		E18	Hijacked Reply-Chain Invoice	Hard	Malicious	Thread hijack / payment diversion	
E06	Adjutant Roster Request	Easy	Malicious	Military display-name spoofing / data request	Y	E19	Academic Interview on Readiness	Hard	Malicious	Military elicitation / research pretext	Y
E07	Expected Training Calendar Invite	Easy	Legitimate	Legitimate calendar invitation	Y	E20	Legal Notice and Secrecy Order	Hard	Malicious	Legal/government impersonation / extortion	
E08	Instant Tax Refund	Easy	Malicious	Government impersonation / refund phishing		E21	Verified Vendor Master Change	Hard	Legitimate	Legitimate high-risk business change	
E09	Executive Gift-Card Request	Medium	Malicious	Business email compromise	Y	E22	Senior Voice Memo Transfer	Hard	Malicious	Synthetic voice / executive impersonation	Y
E10	Vendor Changes Bank Details	Medium	Malicious	Invoice/payment diversion		E23	DLP Alert HTML Attachment	Hard	Malicious	Security-tool impersonation / HTML smuggling	
E11	Leave Approval in Known Portal	Medium	Legitimate	Legitimate workflow notification		E24	QR Code in Policy PDF	Hard	Malicious	QR phishing / credential theft	
E12	Shared Document Sign-In	Medium	Malicious	Cloud-document credential phishing	Y	E25	Payroll Direct-Deposit Redirect	Hard	Malicious	HR/business email compromise / payroll fraud	Y
E13	Password-Protected ZIP	Medium	Malicious	Archive-delivered malware							

E01

Password Expires Today

Platform Email	Difficulty Easy	Disposition Malicious	Attack / case family Credential phishing	Primary trigger Urgency + authority
-------------------	--------------------	--------------------------	---	--

Stage	Learner flow + synthetic content	UI to build	Expected safe behavior	Scoring event
1 Event	Dashboard notification: 'IT Service Desk: Password expires today - retain access by validating now.' The Email badge increments and the toast routes into the scenario.	Dashboard toast, mail tile, unread counter, subject preview and received time.	Notice the source and time; open the full item before acting. Do not reply from the preview.	NOTIFY_SEEN +0; open latency and route logged.
2 Open	Open the unread IT-themed email. Context presented: A message using IT branding says the mailbox password expires today.	Inbox and message pane with folders, thread history, attachment chips, reply controls and warning banners.	Read the full thread/message and prior context before choosing any action.	ITEM_OPEN +0; premature reply/action -1; dwell time logged.
3 Inspect	Open details and examine full From/Reply-To, authentication summary and link target	Expanded sender and message-details sheet: display name, full address, reply-to, authentication summary and link target.	Check this decision signal: The display name looks official but the sender and reply-to use unrelated reserved domains.	INSPECT_CONTEXT +2; inspection path and time logged.
4 Branch	The interaction advances to a synthetic sign-in page that requests username, password and OTP	Offline safe browser, attachment preview, QR inspector, OAuth consent mock or callback panel; no host execution/network.	Do not enter credentials or approve an unexpected sign-in. Use Back/Close or safe preview only; no secret, payment, install or data release.	SAFE_PIVOT +3; risky open/reply -3; secret/payment/install/data release -8.
5 Verify	The learner opens Verify / More actions. Verification route: open the known account/security portal directly from the Trusted Directory	More-actions menu with Report phishing plus independent directory, approved portal and known-vendor-contact overlay.	Verify independently: open the known account/security portal directly from the Trusted Directory Then use the platform report/block path or the unit reporting route.	TRUSTED_VERIFY +3; report-only without checking +1; verification through message +0.
6 Resolve	Final expected resolution: close the page; report phishing; verify account status in the official portal	Outcome card, concise feedback, warning-sign chips, event summary and Return to dashboard.	Complete the resolution and return to the dashboard.	RESOLVE_CORRECT +2; contradictory unsafe final -4; scenario capped 0-10.

End-state Official portal shows no expiry; message moves to the simulated phishing folder.	Concise learner feedback A familiar logo is not sender proof. Inspect the full address and go directly to the approved account portal.
---	---

Invoice Spreadsheet Macro

Platform Email	Difficulty Easy	Disposition Malicious	Attack / case family Malicious attachment	Primary trigger Routine + urgency
-------------------	--------------------	--------------------------	--	--------------------------------------

Stage	Learner flow + synthetic content	UI to build	Expected safe behavior	Scoring event
1 Event	Dashboard notification: 'Accounts Notice: Overdue invoice - enable content to view payment lines.' The Email badge increments and the toast routes into the scenario.	Dashboard toast, mail tile, unread counter, subject preview and received time.	Notice the source and time; open the full item before acting. Do not reply from the preview.	NOTIFY_SEEN +0; open latency and route logged.
2 Open	Open the inbox message with Invoice_8841.xlsm. Context presented: An unknown supplier sends an overdue invoice as a macro-enabled spreadsheet.	Inbox and message pane with folders, thread history, attachment chips, reply controls and warning banners.	Read the full thread/message and prior context before choosing any action.	ITEM_OPEN +0; premature reply/action -1; dwell time logged.
3 Inspect	Open details and examine sender domain, unexpected supplier, file extension and Enable Content instruction	Expanded sender and message-details sheet: display name, full address, reply-to, authentication summary and link target.	Check this decision signal: A macro-enabled file from an unknown sender is not needed to view an invoice and may execute code.	INSPECT_CONTEXT +2; inspection path and time logged.
4 Branch	The interaction advances to an inert spreadsheet preview followed by an Enable Content prompt	Offline safe browser, attachment preview, QR inspector, OAuth consent mock or callback panel; no host execution/network.	Do not enable macros, run content or upload the file elsewhere. Use Back/Close or safe preview only; no secret, payment, install or data release.	SAFE_PIVOT +3; risky open/reply -3; secret/payment/install/data release -8.
5 Verify	The learner opens Verify / More actions. Verification route: check the supplier in the approved vendor system and call the known finance contact	More-actions menu with Report phishing plus independent directory, approved portal and known-vendor-contact overlay.	Verify independently: check the supplier in the approved vendor system and call the known finance contact Then use the platform report/block path or the unit reporting route.	TRUSTED_VERIFY +3; report-only without checking +1; verification through message +0.
6 Resolve	Final expected resolution: do not enable; report phishing; quarantine the attachment in the simulation	Outcome card plus 250-character rationale box, warning-sign chips, event summary and Return to dashboard.	Complete the resolution and return to the dashboard. Add a one-line reason without sensitive data.	RESOLVE_CORRECT +2; contradictory unsafe final -4; scenario capped 0-10.

End-state Attachment remains inert and the message is quarantined.	Concise learner feedback Treat unexpected macro-enabled documents as high risk. Verify the invoice and use a safe preview process.
---	---

Authenticated Internal Newsletter

Platform Email	Difficulty Easy	Disposition Legitimate	Attack / case family Legitimate internal communication	Primary trigger Routine
-------------------	--------------------	---------------------------	---	----------------------------

Stage	Learner flow + synthetic content	UI to build	Expected safe behavior	Scoring event
1 Event	Dashboard notification: 'Learning Office: September safety newsletter - read-only edition.' The Email badge increments and the toast routes into the scenario.	Dashboard toast, mail tile, unread counter, subject preview and received time.	Notice the source and time; open the full item before acting. Do not reply from the preview.	NOTIFY_SEEN +0; open latency and route logged.
2 Open	Open the unread newsletter. Context presented: The monthly training newsletter arrives from the expected authenticated internal domain with no action request.	Inbox and message pane with folders, thread history, attachment chips, reply controls and warning banners.	Read the full thread/message and prior context before choosing any action.	ITEM_OPEN +0; premature reply/action -1; dwell time logged.
3 Inspect	Open details and examine full sender, authentication summary, prior monthly thread and absence of attachments/login requests	Expanded sender and message-details sheet: display name, full address, reply-to, authentication summary and link target.	Check this decision signal: The message matches cadence and domain, passes the simulated authentication checks, and asks for no sensitive action.	INSPECT_CONTEXT +2; inspection path and time logged.
4 Branch	The interaction advances to the in-message newsletter reader with Archive/Mark unread	Offline safe browser, attachment preview, QR inspector, OAuth consent mock or callback panel; no host execution/network.	Use the normal in-app path only after the details match the known context. Do not switch to an untrusted channel.	CORRECT_USE +3; needless reject/ignore -2; unsafe external action -4.
5 Verify	The learner opens Verify / More actions. Verification route: compare sender and issue number with the local internal directory/archive	More-actions menu with Report phishing plus independent directory, approved portal and known-vendor-contact overlay.	Verify independently: compare sender and issue number with the local internal directory/archive. If it matches, continue; do not report or block a legitimate sender.	TRUSTED_VERIFY +3; false report/block -4; verification through message +0.
6 Resolve	Final expected resolution: read/archive normally; do not report or block	Outcome card, concise feedback, warning-sign chips, event summary and Return to dashboard.	Complete the resolution and return to the dashboard.	RESOLVE_CORRECT +2; contradictory unsafe final -4; scenario capped 0-10.

End-state Newsletter is marked read and archived if selected.	Concise learner feedback Routine authenticated mail without unusual requests can be handled normally after a proportionate check.
--	--

E04

Customs Parcel Hold

Platform Email	Difficulty Easy	Disposition Malicious	Attack / case family Delivery impersonation / fee phishing	Primary trigger Fear + curiosity
-------------------	--------------------	--------------------------	---	-------------------------------------

Stage	Learner flow + synthetic content	UI to build	Expected safe behavior	Scoring event
1 Event	Dashboard notification: 'RapidShip Customs: Parcel RS-441 held. Pay a small clearance fee today.' The Email badge increments and the toast routes into the scenario.	Dashboard toast, mail tile, unread counter, subject preview and received time.	Notice the source and time; open the full item before acting. Do not reply from the preview.	NOTIFY_SEEN +0; open latency and route logged.
2 Open	Open the delivery email and tracking button. Context presented: A courier-themed email claims a parcel is held for missing customs payment.	Inbox and message pane with folders, thread history, attachment chips, reply controls and warning banners.	Read the full thread/message and prior context before choosing any action.	ITEM_OPEN +0; premature reply/action -1; dwell time logged.
3 Inspect	Open details and examine sender domain, unsolicited tracking number, link target and payment urgency	Expanded sender and message-details sheet: display name, full address, reply-to, authentication summary and link target.	Check this decision signal: The parcel is unexpected and the button leads to a look-alike reserved domain.	INSPECT_CONTEXT +2; inspection path and time logged.
4 Branch	The interaction advances to a fake tracking page requesting card/UPI data	Offline safe browser, attachment preview, QR inspector, OAuth consent mock or callback panel; no host execution/network.	Do not enter payment information or identity documents. Use Back/Close or safe preview only; no secret, payment, install or data release.	SAFE_PIVOT +3; risky open/reply -3; secret/payment/install/data release -8.
5 Verify	The learner opens Verify / More actions. Verification route: open the known courier site/app independently and search the number	More-actions menu with Report phishing plus independent directory, approved portal and known-vendor-contact overlay.	Verify independently: open the known courier site/app independently and search the number Then use the platform report/block path or the unit reporting route.	TRUSTED_VERIFY +3; report-only without checking +1; verification through message +0.
6 Resolve	Final expected resolution: close; report phishing; retain the message as evidence	Outcome card, concise feedback, warning-sign chips, event summary and Return to dashboard.	Complete the resolution and return to the dashboard.	RESOLVE_CORRECT +2; contradictory unsafe final -4; scenario capped 0-10.

End-state Known courier mock reports no such parcel; message is quarantined.	Concise learner feedback Unexpected parcel fees are common lures. Verify tracking in the official service before paying anything.
---	--

Mandatory HR Policy Login

Platform Email	Difficulty Easy	Disposition Malicious	Attack / case family HR impersonation / credential phishing	Primary trigger Authority + compliance
-------------------	--------------------	--------------------------	--	---

Stage	Learner flow + synthetic content	UI to build	Expected safe behavior	Scoring event
1 Event	Dashboard notification: 'People Office: Mandatory policy acknowledgement due in 60 minutes.' The Email badge increments and the toast routes into the scenario.	Dashboard toast, mail tile, unread counter, subject preview and received time.	Notice the source and time; open the full item before acting. Do not reply from the preview.	NOTIFY_SEEN +0; open latency and route logged.
2 Open	Open the HR-themed email. Context presented: A message says pay access will be suspended unless a policy is acknowledged through a login button.	Inbox and message pane with folders, thread history, attachment chips, reply controls and warning banners.	Read the full thread/message and prior context before choosing any action.	ITEM_OPEN +0; premature reply/action -1; dwell time logged.
3 Inspect	Open details and examine sender domain, reply-to, generic greeting, countdown and destination	Expanded sender and message-details sheet: display name, full address, reply-to, authentication summary and link target.	Check this decision signal: The action is high-pressure, uses a look-alike domain and bypasses the approved HR portal.	INSPECT_CONTEXT +2; inspection path and time logged.
4 Branch	The interaction advances to a cloned HR login and acknowledgement screen	Offline safe browser, attachment preview, QR inspector, OAuth consent mock or callback panel; no host execution/network.	Do not enter password, OTP or payroll information. Use Back/Close or safe preview only; no secret, payment, install or data release.	SAFE_PIVOT +3; risky open/reply -3; secret/payment/install/data release -8.
5 Verify	The learner opens Verify / More actions. Verification route: open the approved HR portal from a bookmark/directory and check assigned tasks	More-actions menu with Report phishing plus independent directory, approved portal and known-vendor-contact overlay.	Verify independently: open the approved HR portal from a bookmark/directory and check assigned tasks Then use the platform report/block path or the unit reporting route.	TRUSTED_VERIFY +3; report-only without checking +1; verification through message +0.
6 Resolve	Final expected resolution: close; report phishing; take no action in the message	Outcome card, concise feedback, warning-sign chips, event summary and Return to dashboard.	Complete the resolution and return to the dashboard.	RESOLVE_CORRECT +2; contradictory unsafe final -4; scenario capped 0-10.

End-state Approved portal shows no task and the phish is reported.	Concise learner feedback Compliance language can be weaponized. Start from the known HR portal rather than a message link.
---	---

Adjutant Roster Request

Platform Email	Difficulty Easy	Disposition Malicious	Attack / case family Military display-name spoofing / data request	Primary trigger Authority FICTIONAL MILITARY CONTEXT
-------------------	--------------------	--------------------------	---	---

Stage	Learner flow + synthetic content	UI to build	Expected safe behavior	Scoring event
1 Event	Dashboard notification: 'Unit Adjutant: Send the latest personnel roster before the commander's brief.' The Email badge increments and the toast routes into the scenario.	Dashboard toast, mail tile, unread counter, subject preview and received time.	Notice the source and time; open the full item before acting. Do not reply from the preview.	NOTIFY_SEEN +0; open latency and route logged.
2 Open	Open the authority-themed email. Context presented: A display name resembling the unit adjutant asks for the current personnel roster in spreadsheet form.	Inbox and message pane with folders, thread history, attachment chips, reply controls and warning banners.	Read the full thread/message and prior context before choosing any action.	ITEM_OPEN +0; premature reply/action -1; dwell time logged.
3 Inspect	Open details and examine full sender address, reply-to, external banner and data classification cue	Expanded sender and message-details sheet: display name, full address, reply-to, authentication summary and link target.	Check this decision signal: The external address does not match the approved domain and the requested roster is protected.	INSPECT_CONTEXT +2; inspection path and time logged.
4 Branch	The interaction advances to a reply composer with a synthetic roster attachment chip	Offline safe browser, attachment preview, QR inspector, OAuth consent mock or callback panel; no host execution/network.	Do not attach or summarize roster/personnel information. Use Back/Close or safe preview only; no secret, payment, install or data release.	SAFE_PIVOT +3; risky open/reply -3; secret/payment/install/data release -8.
5 Verify	The learner opens Verify / More actions. Verification route: contact the adjutant through the approved internal directory and document system	More-actions menu with Report phishing plus independent directory, approved portal and known-vendor-contact overlay.	Verify independently: contact the adjutant through the approved internal directory and document system Then use the platform report/block path or the unit reporting route.	TRUSTED_VERIFY +3; report-only without checking +1; verification through message +0.
6 Resolve	Final expected resolution: cancel the reply; report the spoof through unit security; do not attach data	Outcome card plus 250-character rationale box, warning-sign chips, event summary and Return to dashboard.	Complete the resolution and return to the dashboard. Add a one-line reason without sensitive data.	RESOLVE_CORRECT +2; contradictory unsafe final -4; scenario capped 0-10.

End-state

No roster is attached and the spoof is logged for review.

Concise learner feedback

Display names can be copied. Verify the full address and keep personnel data in approved systems.

Expected Training Calendar Invite

Platform Email	Difficulty Easy	Disposition Legitimate	Attack / case family Legitimate calendar invitation	Primary trigger Routine + authority FICTIONAL MILITARY CONTEXT
-------------------	--------------------	---------------------------	--	---

Stage	Learner flow + synthetic content	UI to build	Expected safe behavior	Scoring event
1 Event	Dashboard notification: 'Training Office: Invite - Social Engineering Lab, 04 Sep, Training Room C.' The Email badge increments and the toast routes into the scenario.	Dashboard toast, mail tile, unread counter, subject preview and received time.	Notice the source and time; open the full item before acting. Do not reply from the preview.	NOTIFY_SEEN +0; open latency and route logged.
2 Open	Open the calendar invitation in the known thread. Context presented: A known training officer sends the calendar invite announced in the morning briefing.	Inbox and message pane with folders, thread history, attachment chips, reply controls and warning banners.	Read the full thread/message and prior context before choosing any action.	ITEM_OPEN +0; premature reply/action -1; dwell time logged.
3 Inspect	Open details and examine organizer address, expected time/location, attendee list and absence of external login	Expanded sender and message-details sheet: display name, full address, reply-to, authentication summary and link target.	Check this decision signal: The invitation matches the prior announcement and organizer directory entry.	INSPECT_CONTEXT +2; inspection path and time logged.
4 Branch	The interaction advances to the in-app calendar card with Accept/Tentative/Decline	Offline safe browser, attachment preview, QR inspector, OAuth consent mock or callback panel; no host execution/network.	Use the normal in-app path only after the details match the known context. Do not switch to an untrusted channel.	CORRECT_USE +3; needless reject/ignore -2; unsafe external action -4.
5 Verify	The learner opens Verify / More actions. Verification route: compare the organizer with the Trusted Directory and the local course schedule	More-actions menu with Report phishing plus independent directory, approved portal and known-vendor-contact overlay.	Verify independently: compare the organizer with the Trusted Directory and the local course schedule. If it matches, continue; do not report or block a legitimate sender.	TRUSTED_VERIFY +3; false report/block -4; verification through message +0.
6 Resolve	Final expected resolution: accept/tentative/decline normally; do not report the sender	Outcome card, concise feedback, warning-sign chips, event summary and Return to dashboard.	Complete the resolution and return to the dashboard.	RESOLVE_CORRECT +2; contradictory unsafe final -4; scenario capped 0-10.

End-state Calendar response is stored locally and invite remains legitimate.	Concise learner feedback Expected invitations from verified organizers should be handled normally. Check details without creating a false alarm.
---	---

Instant Tax Refund

Platform Email	Difficulty Easy	Disposition Malicious	Attack / case family Government impersonation / refund phishing	Primary trigger Greed + urgency
-------------------	--------------------	--------------------------	--	------------------------------------

Stage	Learner flow + synthetic content	UI to build	Expected safe behavior	Scoring event
1 Event	Dashboard notification: 'Revenue Refund Centre: INR 7,840 refund expires today - complete release.' The Email badge increments and the toast routes into the scenario.	Dashboard toast, mail tile, unread counter, subject preview and received time.	Notice the source and time; open the full item before acting. Do not reply from the preview.	NOTIFY_SEEN +0; open latency and route logged.
2 Open	Open the refund email. Context presented: A tax-themed email promises a refund but asks for card and identity details through a button.	Inbox and message pane with folders, thread history, attachment chips, reply controls and warning banners.	Read the full thread/message and prior context before choosing any action.	ITEM_OPEN +0; premature reply/action -1; dwell time logged.
3 Inspect	Open details and examine sender domain, generic reference, urgency and link destination	Expanded sender and message-details sheet: display name, full address, reply-to, authentication summary and link target.	Check this decision signal: Unexpected refunds and expiry pressure do not justify submitting financial/identity data to a message link.	INSPECT_CONTEXT +2; inspection path and time logged.
4 Branch	The interaction advances to a fake refund form requesting PAN-like ID, card and OTP placeholders	Offline safe browser, attachment preview, QR inspector, OAuth consent mock or callback panel; no host execution/network.	Do not enter identity, account, card or OTP data. Use Back/Close or safe preview only; no secret, payment, install or data release.	SAFE_PIVOT +3; risky open/reply -3; secret/payment/install/data release -8.
5 Verify	The learner opens Verify / More actions. Verification route: open the relevant official portal using a known address and check filed-return status	More-actions menu with Report phishing plus independent directory, approved portal and known-vendor-contact overlay.	Verify independently: open the relevant official portal using a known address and check filed-return status Then use the platform report/block path or the unit reporting route.	TRUSTED_VERIFY +3; report-only without checking +1; verification through message +0.
6 Resolve	Final expected resolution: close; report phishing; do not submit or reply	Outcome card, concise feedback, warning-sign chips, event summary and Return to dashboard.	Complete the resolution and return to the dashboard.	RESOLVE_CORRECT +2; contradictory unsafe final -4; scenario capped 0-10.

End-state Official portal mock shows no refund case and the email is quarantined.	Concise learner feedback Refunds do not require secret codes through unsolicited mail. Check status in the official portal you open yourself.
--	--

Executive Gift-Card Request

Platform Email	Difficulty Medium	Disposition Malicious	Attack / case family Business email compromise	Primary trigger Authority + urgency + secrecy FICTIONAL MILITARY CONTEXT
-------------------	----------------------	--------------------------	---	---

Stage	Learner flow + synthetic content	UI to build	Expected safe behavior	Scoring event
1 Event	Dashboard notification: 'From: Col. Dev - Need six gift cards for visitors. Keep this confidential.' The Email badge increments and the toast routes into the scenario.	Dashboard toast, mail tile, unread counter, subject preview and received time.	Notice the source and time; open the full item before acting. Do not reply from the preview.	NOTIFY_SEEN +0; open latency and route logged.
2 Open	Open the short executive-style email. Context presented: A senior's display name appears on a personal email asking for gift cards while claiming to be in a meeting.	Inbox and message pane with folders, thread history, attachment chips, reply controls and warning banners.	Read the full thread/message and prior context before choosing any action.	ITEM_OPEN +0; premature reply/action -1; dwell time logged.
3 Inspect	Open details and examine full sender, reply-to, unusual channel, secrecy and payment method	Expanded sender and message-details sheet: display name, full address, reply-to, authentication summary and link target.	Check this decision signal: The personal domain and gift-card request contradict normal procurement controls.	INSPECT_CONTEXT +2; inspection path and time logged.
4 Branch	The interaction advances to a reply/purchase mock asking for gift-card images and codes	Offline safe browser, attachment preview, QR inspector, OAuth consent mock or callback panel; no host execution/network.	Do not buy cards, send codes or conceal the request. Use Back/Close or safe preview only; no secret, payment, install or data release.	SAFE_PIVOT +3; risky open/reply -3; secret/payment/install/data release -8.
5 Verify	The learner opens Verify / More actions. Verification route: call the senior/duty office through the known directory and check procurement authorization	More-actions menu with Report phishing plus independent directory, approved portal and known-vendor-contact overlay.	Verify independently: call the senior/duty office through the known directory and check procurement authorization Then use the platform report/block path or the unit reporting route.	TRUSTED_VERIFY +3; report-only without checking +1; verification through message +0.
6 Resolve	Final expected resolution: do not purchase; report the impersonation; notify the verified senior/security route	Outcome card, concise feedback, warning-sign chips, event summary and Return to dashboard.	Complete the resolution and return to the dashboard.	RESOLVE_CORRECT +2; contradictory unsafe final -4; scenario capped 0-10.

End-state Senior denies the request and the email is flagged as BEC.	Concise learner feedback Authority plus secrecy is a warning sign. Verify unusual financial requests with a known contact and approved workflow.
---	---

Vendor Changes Bank Details

Platform Email	Difficulty Medium	Disposition Malicious	Attack / case family Invoice/payment diversion	Primary trigger Routine + urgency
-------------------	----------------------	--------------------------	---	--------------------------------------

Stage	Learner flow + synthetic content	UI to build	Expected safe behavior	Scoring event
1 Event	Dashboard notification: 'Northstar Supplies: Banking migration - use the attached new beneficiary for invoice NS-104.' The Email badge increments and the toast routes into the scenario.	Dashboard toast, mail tile, unread counter, subject preview and received time.	Notice the source and time; open the full item before acting. Do not reply from the preview.	NOTIFY_SEEN +0; open latency and route logged.
2 Open	Open the vendor email and invoice thread. Context presented: A look-alike vendor domain replies with a real project reference and new beneficiary account.	Inbox and message pane with folders, thread history, attachment chips, reply controls and warning banners.	Read the full thread/message and prior context before choosing any action.	ITEM_OPEN +0; premature reply/action -1; dwell time logged.
3 Inspect	Open details and examine one-character domain difference, reply-to, changed beneficiary and approval gap	Expanded sender and message-details sheet: display name, full address, reply-to, authentication summary and link target.	Check this decision signal: Stolen context can make fraud convincing; beneficiary changes require independent callback and dual control.	INSPECT_CONTEXT +2; inspection path and time logged.
4 Branch	The interaction advances to an invoice preview and vendor-master edit screen	Offline safe browser, attachment preview, QR inspector, OAuth consent mock or callback panel; no host execution/network.	Do not change bank details or approve payment from the email alone. Use Back/Close or safe preview only; no secret, payment, install or data release.	SAFE_PIVOT +3; risky open/reply -3; secret/payment/install/data release -8.
5 Verify	The learner opens Verify / More actions. Verification route: call the known vendor contact on file and use the approved change-control process	More-actions menu with Report phishing plus independent directory, approved portal and known-vendor-contact overlay.	Verify independently: call the known vendor contact on file and use the approved change-control process Then use the platform report/block path or the unit reporting route.	TRUSTED_VERIFY +3; report-only without checking +1; verification through message +0.
6 Resolve	Final expected resolution: hold payment; report the look-alike sender; record the attempted change	Outcome card plus 250-character rationale box, warning-sign chips, event summary and Return to dashboard.	Complete the resolution and return to the dashboard. Add a one-line reason without sensitive data.	RESOLVE_CORRECT +2; contradictory unsafe final -4; scenario capped 0-10.

End-state Beneficiary update is rejected and the real vendor confirms no change.	Concise learner feedback Accurate context is not enough. Independently verify all payment-detail changes and apply dual approval.
---	--

Leave Approval in Known Portal

Platform Email	Difficulty Medium	Disposition Legitimate	Attack / case family Legitimate workflow notification	Primary trigger Authority + anticipation
-------------------	----------------------	---------------------------	--	---

Stage	Learner flow + synthetic content	UI to build	Expected safe behavior	Scoring event
1 Event	Dashboard notification: 'People Portal: Request LV-204 status updated. View it from your portal dashboard.' The Email badge increments and the toast routes into the scenario.	Dashboard toast, mail tile, unread counter, subject preview and received time.	Notice the source and time; open the full item before acting. Do not reply from the preview.	NOTIFY_SEEN +0; open latency and route logged.
2 Open	Open the existing leave-request thread. Context presented: The learner recently submitted a leave request; an authenticated notification says the decision is available in the approved portal.	Inbox and message pane with folders, thread history, attachment chips, reply controls and warning banners.	Read the full thread/message and prior context before choosing any action.	ITEM_OPEN +0; premature reply/action -1; dwell time logged.
3 Inspect	Open details and examine request ID, authenticated sender, no embedded login link and matching timeline	Expanded sender and message-details sheet: display name, full address, reply-to, authentication summary and link target.	Check this decision signal: The notification refers to an action the learner initiated and directs them to the known portal rather than collecting data.	INSPECT_CONTEXT +2; inspection path and time logged.
4 Branch	The interaction advances to the dashboard's approved-portal launcher and read-only leave status	Offline safe browser, attachment preview, QR inspector, OAuth consent mock or callback panel; no host execution/network.	Use the normal in-app path only after the details match the known context. Do not switch to an untrusted channel.	CORRECT_USE +3; needless reject/ignore -2; unsafe external action -4.
5 Verify	The learner opens Verify / More actions. Verification route: open the known HR portal from the dashboard and match request LV-204	More-actions menu with Report phishing plus independent directory, approved portal and known-vendor-contact overlay.	Verify independently: open the known HR portal from the dashboard and match request LV-204 If it matches, continue; do not report or block a legitimate sender.	TRUSTED_VERIFY +3; false report/block -4; verification through message +0.
6 Resolve	Final expected resolution: view the result in the portal; archive the email; do not report	Outcome card, concise feedback, warning-sign chips, event summary and Return to dashboard.	Complete the resolution and return to the dashboard.	RESOLVE_CORRECT +2; contradictory unsafe final -4; scenario capped 0-10.

End-state Leave status matches and the email is archived normally.	Concise learner feedback Legitimate status mail is specific, expected and verifiable in a portal you open independently.
---	---

Shared Document Sign-In

Platform Email	Difficulty Medium	Disposition Malicious	Attack / case family Cloud-document credential phishing	Primary trigger Curiosity + collaboration FICTIONAL MILITARY CONTEXT
-------------------	----------------------	--------------------------	--	---

Stage	Learner flow + synthetic content	UI to build	Expected safe behavior	Scoring event
1 Event	Dashboard notification: 'Docs Share: 'Updated Deployment Photos' was shared with you.' The Email badge increments and the toast routes into the scenario.	Dashboard toast, mail tile, unread counter, subject preview and received time.	Notice the source and time; open the full item before acting. Do not reply from the preview.	NOTIFY_SEEN +0; open latency and route logged.
2 Open	Open the document-share email. Context presented: An external collaborator shares a document with a generic title and prompts a fresh sign-in.	Inbox and message pane with folders, thread history, attachment chips, reply controls and warning banners.	Read the full thread/message and prior context before choosing any action.	ITEM_OPEN +0; premature reply/action -1; dwell time logged.
3 Inspect	Open details and examine sender identity, unexpected title, external banner, target domain and access scope	Expanded sender and message-details sheet: display name, full address, reply-to, authentication summary and link target.	Check this decision signal: The share is unexpected and the sign-in target is not the approved collaboration domain.	INSPECT_CONTEXT +2; inspection path and time logged.
4 Branch	The interaction advances to a cloned cloud-login page followed by an MFA approval prompt	Offline safe browser, attachment preview, QR inspector, OAuth consent mock or callback panel; no host execution/network.	Do not enter credentials or approve the sign-in. Use Back/Close or safe preview only; no secret, payment, install or data release.	SAFE_PIVOT +3; risky open/reply -3; secret/payment/install/data release -8.
5 Verify	The learner opens Verify / More actions. Verification route: contact the supposed sender by known channel and open the approved collaboration portal directly	More-actions menu with Report phishing plus independent directory, approved portal and known-vendor-contact overlay.	Verify independently: contact the supposed sender by known channel and open the approved collaboration portal directly Then use the platform report/block path or the unit reporting route.	TRUSTED_VERIFY +3; report-only without checking +1; verification through message +0.
6 Resolve	Final expected resolution: close; report phishing; do not request access through the fake page	Outcome card, concise feedback, warning-sign chips, event summary and Return to dashboard.	Complete the resolution and return to the dashboard.	RESOLVE_CORRECT +2; contradictory unsafe final -4; scenario capped 0-10.

End-state

Sender denies the share and credentials remain protected.

Concise learner feedback

Document-sharing lures exploit collaboration habits. Verify the share and sign in only from the known service.

Password-Protected ZIP

Platform Email	Difficulty Medium	Disposition Malicious	Attack / case family Archive-delivered malware	Primary trigger Curiosity + routine
-------------------	----------------------	--------------------------	---	--

Stage	Learner flow + synthetic content	UI to build	Expected safe behavior	Scoring event
1 Event	Dashboard notification: 'Case Documents: Confidential scan attached. Password: 2468.' The Email badge increments and the toast routes into the scenario.	Dashboard toast, mail tile, unread counter, subject preview and received time.	Notice the source and time; open the full item before acting. Do not reply from the preview.	NOTIFY_SEEN +0; open latency and route logged.
2 Open	Open the external email and CaseFiles.zip chip. Context presented: An external sender provides a password-protected archive and places the password in the message to bypass inspection.	Inbox and message pane with folders, thread history, attachment chips, reply controls and warning banners.	Read the full thread/message and prior context before choosing any action.	ITEM_OPEN +0; premature reply/action -1; dwell time logged.
3 Inspect	Open details and examine sender identity, unexpected case, archive type and separate password	Expanded sender and message-details sheet: display name, full address, reply-to, authentication summary and link target.	Check this decision signal: An unsolicited encrypted archive prevents normal inspection and the case context is not expected.	INSPECT_CONTEXT +2; inspection path and time logged.
4 Branch	The interaction advances to an inert archive viewer with a simulated executable inside	Offline safe browser, attachment preview, QR inspector, OAuth consent mock or callback panel; no host execution/network.	Do not extract/run the file or disable protection. Use Back/Close or safe preview only; no secret, payment, install or data release.	SAFE_PIVOT +3; risky open/reply -3; secret/payment/install/data release -8.
5 Verify	The learner opens Verify / More actions. Verification route: verify the sender/case through the approved records system and known contact	More-actions menu with Report phishing plus independent directory, approved portal and known-vendor-contact overlay.	Verify independently: verify the sender/case through the approved records system and known contact Then use the platform report/block path or the unit reporting route.	TRUSTED_VERIFY +3; report-only without checking +1; verification through message +0.
6 Resolve	Final expected resolution: do not extract; report phishing; quarantine the archive	Outcome card, concise feedback, warning-sign chips, event summary and Return to dashboard.	Complete the resolution and return to the dashboard.	RESOLVE_CORRECT +2; contradictory unsafe final -4; scenario capped 0-10.

End-state Archive stays unopened and the email is quarantined.	Concise learner feedback Password-protected archives can conceal unsafe files. Verify the business need before any extraction.
---	---

Revised Movement Order

Platform Email	Difficulty Medium	Disposition Malicious	Attack / case family Military spearphishing / attachment	Primary trigger Authority + urgency FICTIONAL MILITARY CONTEXT
-------------------	----------------------	--------------------------	---	---

Stage	Learner flow + synthetic content	UI to build	Expected safe behavior	Scoring event
1 Event	Dashboard notification: 'HQ Alpha Movements: Urgent revision MOV-77 - open attached order now.' The Email badge increments and the toast routes into the scenario.	Dashboard toast, mail tile, unread counter, subject preview and received time.	Notice the source and time; open the full item before acting. Do not reply from the preview.	NOTIFY_SEEN +0; open latency and route logged.
2 Open	Open the priority email and PDF attachment. Context presented: A look-alike HQ address sends a revised movement order shortly before a fictional exercise.	Inbox and message pane with folders, thread history, attachment chips, reply controls and warning banners.	Read the full thread/message and prior context before choosing any action.	ITEM_OPEN +0; premature reply/action -1; dwell time logged.
3 Inspect	Open details and examine subtle domain change, reply-to, classification mismatch and unexpected revision process	Expanded sender and message-details sheet: display name, full address, reply-to, authentication summary and link target.	Check this decision signal: Premise alignment raises difficulty, but the sender and distribution route do not match the approved system.	INSPECT_CONTEXT +2; inspection path and time logged.
4 Branch	The interaction advances to a PDF preview containing a QR to 'decrypt' the order	Offline safe browser, attachment preview, QR inspector, OAuth consent mock or callback panel; no host execution/network.	Do not scan the QR, enter service credentials or disclose schedule details. Use Back/Close or safe preview only; no secret, payment, install or data release.	SAFE_PIVOT +3; risky open/reply -3; secret/payment/install/data release -8.
5 Verify	The learner opens Verify / More actions. Verification route: check MOV-77 in the approved orders system and call movement staff through the directory	More-actions menu with Report phishing plus independent directory, approved portal and known-vendor-contact overlay.	Verify independently: check MOV-77 in the approved orders system and call movement staff through the directory Then use the platform report/block path or the unit reporting route.	TRUSTED_VERIFY +3; report-only without checking +1; verification through message +0.
6 Resolve	Final expected resolution: do not use the QR; report the spearphish; preserve the email for unit security	Outcome card plus 250-character rationale box, warning-sign chips, event summary and Return to dashboard.	Complete the resolution and return to the dashboard. Add a one-line reason without sensitive data.	RESOLVE_CORRECT +2; contradictory unsafe final -4; scenario capped 0-10.

End-state Approved system shows no revision and the attachment remains inert.	Concise learner feedback Time-relevant military themes can be tailored from public information. Verify orders only in approved channels.
--	---

OAuth Consent for Mail Review

Platform Email	Difficulty Medium	Disposition Malicious	Attack / case family Consent phishing / cloud-app access	Primary trigger Convenience + authority
-------------------	----------------------	--------------------------	---	--

Stage	Learner flow + synthetic content	UI to build	Expected safe behavior	Scoring event
1 Event	Dashboard notification: 'Security Upgrade: Approve MailSafe Analyzer to complete mandatory protection.' The Email badge increments and the toast routes into the scenario.	Dashboard toast, mail tile, unread counter, subject preview and received time.	Notice the source and time; open the full item before acting. Do not reply from the preview.	NOTIFY_SEEN +0; open latency and route logged.
2 Open	Open the security-themed email and consent button. Context presented: A message asks the learner to authorize an app that will supposedly scan the inbox for threats.	Inbox and message pane with folders, thread history, attachment chips, reply controls and warning banners.	Read the full thread/message and prior context before choosing any action.	ITEM_OPEN +0; premature reply/action -1; dwell time logged.
3 Inspect	Open details and examine publisher status, broad permissions, sender and absence of approved change notice	Expanded sender and message-details sheet: display name, full address, reply-to, authentication summary and link target.	Check this decision signal: The app requests read/send mailbox access and is not an approved publisher.	INSPECT_CONTEXT +2; inspection path and time logged.
4 Branch	The interaction advances to a synthetic OAuth consent screen listing Mail.Read, Mail.Send and Contacts permissions	Offline safe browser, attachment preview, QR inspector, OAuth consent mock or callback panel; no host execution/network.	Do not grant consent or approve broad access. Use Back/Close or safe preview only; no secret, payment, install or data release.	SAFE_PIVOT +3; risky open/reply -3; secret/payment/install/data release -8.
5 Verify	The learner opens Verify / More actions. Verification route: check the approved application catalogue and contact IT through the known directory	More-actions menu with Report phishing plus independent directory, approved portal and known-vendor-contact overlay.	Verify independently: check the approved application catalogue and contact IT through the known directory Then use the platform report/block path or the unit reporting route.	TRUSTED_VERIFY +3; report-only without checking +1; verification through message +0.
6 Resolve	Final expected resolution: deny consent; report phishing; review/remove unapproved app grants	Outcome card, concise feedback, warning-sign chips, event summary and Return to dashboard.	Complete the resolution and return to the dashboard.	RESOLVE_CORRECT +2; contradictory unsafe final -4; scenario capped 0-10.

End-state Consent is denied and no mailbox permission is created.	Concise learner feedback A consent screen can grant access without asking for a password. Read permissions and verify the app publisher.
--	---

Signed Maintenance Notice

Platform Email	Difficulty Medium	Disposition Legitimate	Attack / case family Legitimate IT maintenance	Primary trigger Authority + routine
-------------------	----------------------	---------------------------	---	--

Stage	Learner flow + synthetic content	UI to build	Expected safe behavior	Scoring event
1 Event	Dashboard notification: 'IT Operations: Planned mail maintenance 22:00-22:30; no action required.' The Email badge increments and the toast routes into the scenario.	Dashboard toast, mail tile, unread counter, subject preview and received time.	Notice the source and time; open the full item before acting. Do not reply from the preview.	NOTIFY_SEEN +0; open latency and route logged.
2 Open	Open the maintenance email. Context presented: An authenticated, digitally signed notice announces planned downtime and asks for no credentials.	Inbox and message pane with folders, thread history, attachment chips, reply controls and warning banners.	Read the full thread/message and prior context before choosing any action.	ITEM_OPEN +0; premature reply/action -1; dwell time logged.
3 Inspect	Open details and examine signature status, internal sender, maintenance calendar and no-action wording	Expanded sender and message-details sheet: display name, full address, reply-to, authentication summary and link target.	Check this decision signal: The signed sender and local change calendar match; the message does not ask for a link, file or secret.	INSPECT_CONTEXT +2; inspection path and time logged.
4 Branch	The interaction advances to the in-message maintenance detail and Add reminder control	Offline safe browser, attachment preview, QR inspector, OAuth consent mock or callback panel; no host execution/network.	Use the normal in-app path only after the details match the known context. Do not switch to an untrusted channel.	CORRECT_USE +3; needless reject/ignore -2; unsafe external action -4.
5 Verify	The learner opens Verify / More actions. Verification route: compare change ID CHG-118 with the local IT status board	More-actions menu with Report phishing plus independent directory, approved portal and known-vendor-contact overlay.	Verify independently: compare change ID CHG-118 with the local IT status board. If it matches, continue; do not report or block a legitimate sender.	TRUSTED_VERIFY +3; false report/block -4; verification through message +0.
6 Resolve	Final expected resolution: add a reminder/archive normally; do not report or block	Outcome card, concise feedback, warning-sign chips, event summary and Return to dashboard.	Complete the resolution and return to the dashboard.	RESOLVE_CORRECT +2; contradictory unsafe final -4; scenario capped 0-10.

End-state
Maintenance event is added to the local calendar.

Concise learner feedback
A verified no-action notice is legitimate. Use proportionate checks and avoid unnecessary escalation.

Invoice Callback Trap

Platform Email	Difficulty Medium	Disposition Malicious	Attack / case family Callback phishing / tech-support fraud	Primary trigger Fear + urgency
-------------------	----------------------	--------------------------	--	-----------------------------------

Stage	Learner flow + synthetic content	UI to build	Expected safe behavior	Scoring event
1 Event	Dashboard notification: 'Subscription Billing: INR 32,900 renewal processed. Call within 30 minutes to cancel.' The Email badge increments and the toast routes into the scenario.	Dashboard toast, mail tile, unread counter, subject preview and received time.	Notice the source and time; open the full item before acting. Do not reply from the preview.	NOTIFY_SEEN +0; open latency and route logged.
2 Open	Open the invoice email. Context presented: A renewal invoice says the learner will be charged unless they call a supplied number immediately.	Inbox and message pane with folders, thread history, attachment chips, reply controls and warning banners.	Read the full thread/message and prior context before choosing any action.	ITEM_OPEN +0; premature reply/action -1; dwell time logged.
3 Inspect	Open details and examine unknown sender, no known subscription, supplied callback number and urgency	Expanded sender and message-details sheet: display name, full address, reply-to, authentication summary and link target.	Check this decision signal: The goal is to move the learner to a scam operator who can request remote access or payment details.	INSPECT_CONTEXT +2; inspection path and time logged.
4 Branch	The interaction advances to a call-confirmation panel leading to a synthetic support script asking for remote access	Offline safe browser, attachment preview, QR inspector, OAuth consent mock or callback panel; no host execution/network.	Do not call the supplied number, share screen or install support software. Use Back/Close or safe preview only; no secret, payment, install or data release.	SAFE_PIVOT +3; risky open/reply -3; secret/payment/install/data release -8.
5 Verify	The learner opens Verify / More actions. Verification route: check statements/subscriptions directly and use a known vendor contact if needed	More-actions menu with Report phishing plus independent directory, approved portal and known-vendor-contact overlay.	Verify independently: check statements/subscriptions directly and use a known vendor contact if needed Then use the platform report/block path or the unit reporting route.	TRUSTED_VERIFY +3; report-only without checking +1; verification through message +0.
6 Resolve	Final expected resolution: do not call; report phishing; monitor the simulated account independently	Outcome card plus 250-character rationale box, warning-sign chips, event summary and Return to dashboard.	Complete the resolution and return to the dashboard. Add a one-line reason without sensitive data.	RESOLVE_CORRECT +2; contradictory unsafe final -4; scenario capped 0-10.

End-state Statement shows no charge; callback path is closed.	Concise learner feedback A shocking invoice can be bait for a phone scam. Verify the charge independently and do not call numbers in the message.
--	--

Hijacked Reply-Chain Invoice

Platform Email	Difficulty Hard	Disposition Malicious	Attack / case family Thread hijack / payment diversion	Primary trigger Trust + routine
-------------------	--------------------	--------------------------	---	------------------------------------

Stage	Learner flow + synthetic content	UI to build	Expected safe behavior	Scoring event
1 Event	Dashboard notification: 'Re: NS-104 - Please use our recovery account for this month's settlement.' The Email badge increments and the toast routes into the scenario.	Dashboard toast, mail tile, unread counter, subject preview and received time.	Notice the source and time; open the full item before acting. Do not reply from the preview.	NOTIFY_SEEN +0; open latency and route logged.
2 Open	Open the authentic-looking reply chain. Context presented: A compromised mailbox inserts a realistic message into an established invoice thread and changes payment details.	Inbox and message pane with folders, thread history, attachment chips, reply controls and warning banners.	Read the full thread/message and prior context before choosing any action.	ITEM_OPEN +0; premature reply/action -1; dwell time logged.
3 Inspect	Open details and examine new reply-to, changed writing style, beneficiary mismatch and unusual exception	Expanded sender and message-details sheet: display name, full address, reply-to, authentication summary and link target.	Check this decision signal: A genuine thread and prior attachments can be abused after compromise; payment changes still need independent confirmation.	INSPECT_CONTEXT +2; inspection path and time logged.
4 Branch	The interaction advances to the existing invoice and vendor-master payment screen	Offline safe browser, attachment preview, QR inspector, OAuth consent mock or callback panel; no host execution/network.	Do not update beneficiary or approve payment based on the thread. Use Back/Close or safe preview only; no secret, payment, install or data release.	SAFE_PIVOT +3; risky open/reply -3; secret/payment/install/data release -8.
5 Verify	The learner opens Verify / More actions. Verification route: call the vendor using the pre-existing master-data contact and obtain dual approval	More-actions menu with Report phishing plus independent directory, approved portal and known-vendor-contact overlay.	Verify independently: call the vendor using the pre-existing master-data contact and obtain dual approval Then use the platform report/block path or the unit reporting route.	TRUSTED_VERIFY +3; report-only without checking +1; verification through message +0.
6 Resolve	Final expected resolution: hold payment; report the suspicious reply; alert vendor/security through known routes	Outcome card plus 250-character rationale box, warning-sign chips, event summary and Return to dashboard.	Complete the resolution and return to the dashboard. Add a one-line reason without sensitive data.	RESOLVE_CORRECT +2; contradictory unsafe final -4; scenario capped 0-10.

End-state Vendor confirms mailbox compromise; payment remains held.	Concise learner feedback Thread history is context, not authentication. Independently verify financial changes every time.
--	---

Academic Interview on Readiness

Platform Email	Difficulty Hard	Disposition Malicious	Attack / case family Military elicitation / research pretext	Primary trigger Expert status + flattery FICTIONAL MILITARY CONTEXT
-------------------	--------------------	--------------------------	---	--

Stage	Learner flow + synthetic content	UI to build	Expected safe behavior	Scoring event
1 Event	Dashboard notification: 'Dr. Mira Sen: Your field experience can improve our readiness study. Questionnaire attached.' The Email badge increments and the toast routes into the scenario.	Dashboard toast, mail tile, unread counter, subject preview and received time.	Notice the source and time; open the full item before acting. Do not reply from the preview.	NOTIFY_SEEN +0; open latency and route logged.
2 Open	Open the formal interview request. Context presented: A polished academic request seeks an interview and attaches questions about readiness and equipment gaps.	Inbox and message pane with folders, thread history, attachment chips, reply controls and warning banners.	Read the full thread/message and prior context before choosing any action.	ITEM_OPEN +0; premature reply/action -1; dwell time logged.
3 Inspect	Open details and examine institution domain mismatch, unverifiable publication, narrow operational questions and distribution list	Expanded sender and message-details sheet: display name, full address, reply-to, authentication summary and link target.	Check this decision signal: Professional tone and public credentials do not authorize disclosure of protected capability information.	INSPECT_CONTEXT +2; inspection path and time logged.
4 Branch	The interaction advances to an inert questionnaire requesting systems, limitations, locations and routines	Offline safe browser, attachment preview, QR inspector, OAuth consent mock or callback panel; no host execution/network.	Do not answer, correct assumptions with nonpublic facts, or forward internally without review. Use Back/Close or safe preview only; no secret, payment, install or data release.	SAFE_PIVOT +3; risky open/reply -3; secret/payment/install/data release -8.
5 Verify	The learner opens Verify / More actions. Verification route: route the inquiry to approved public-information/security staff for authorization	More-actions menu with Report phishing plus independent directory, approved portal and known-vendor-contact overlay.	Verify independently: route the inquiry to approved public-information/security staff for authorization Then use the platform report/block path or the unit reporting route.	TRUSTED_VERIFY +3; report-only without checking +1; verification through message +0.
6 Resolve	Final expected resolution: do not answer; report the elicitation attempt internally; retain evidence	Outcome card plus 250-character rationale box, warning-sign chips, event summary and Return to dashboard.	Complete the resolution and return to the dashboard. Add a one-line reason without sensitive data.	RESOLVE_CORRECT +2; contradictory unsafe final -4; scenario capped 0-10.

End-state No questionnaire data is submitted and the request is routed for review.	Concise learner feedback Elicitation may look scholarly. Authorization and need-to-know determine what can be discussed.
---	---

Legal Notice and Secrecy Order

Platform Email	Difficulty Hard	Disposition Malicious	Attack / case family Legal/government impersonation / extortion	Primary trigger Fear + authority + isolation
-------------------	--------------------	--------------------------	--	---

Stage	Learner flow + synthetic content	UI to build	Expected safe behavior	Scoring event
1 Event	Dashboard notification: 'National Inquiry Office: Confidential summons - pay verification bond before 17:00.' The Email badge increments and the toast routes into the scenario.	Dashboard toast, mail tile, unread counter, subject preview and received time.	Notice the source and time; open the full item before acting. Do not reply from the preview.	NOTIFY_SEEN +0; open latency and route logged.
2 Open	Open the high-priority legal-themed email. Context presented: An official-looking notice alleges criminal involvement, forbids discussion and requests a refundable bond.	Inbox and message pane with folders, thread history, attachment chips, reply controls and warning banners.	Read the full thread/message and prior context before choosing any action.	ITEM_OPEN +0; premature reply/action -1; dwell time logged.
3 Inspect	Open details and examine sender domain, fabricated seal, secrecy demand, payment route and case lookup	Expanded sender and message-details sheet: display name, full address, reply-to, authentication summary and link target.	Check this decision signal: A legal-looking PDF and confidentiality language do not validate a demand for immediate payment.	INSPECT_CONTEXT +2; inspection path and time logged.
4 Branch	The interaction advances to a synthetic warrant PDF and bond-payment portal	Offline safe browser, attachment preview, QR inspector, OAuth consent mock or callback panel; no host execution/network.	Do not pay, upload ID/bank statements or remain isolated. Use Back/Close or safe preview only; no secret, payment, install or data release.	SAFE_PIVOT +3; risky open/reply -3; secret/payment/install/data release -8.
5 Verify	The learner opens Verify / More actions. Verification route: verify with the relevant authority through an independently known official route and inform unit/legal support	More-actions menu with Report phishing plus independent directory, approved portal and known-vendor-contact overlay.	Verify independently: verify with the relevant authority through an independently known official route and inform unit/legal support Then use the platform report/block path or the unit reporting route.	TRUSTED_VERIFY +3; report-only without checking +1; verification through message +0.
6 Resolve	Final expected resolution: do not pay or reply; preserve and report the impersonation through approved channels	Outcome card, concise feedback, warning-sign chips, event summary and Return to dashboard.	Complete the resolution and return to the dashboard.	RESOLVE_CORRECT +2; contradictory unsafe final -4; scenario capped 0-10.

End-state Case number fails independent verification and the payment screen closes.	Concise learner feedback Threats, secrecy and payment demands are coercive signals. Verify legal contact independently and seek support.
--	---

Verified Vendor Master Change

Platform Email	Difficulty Hard	Disposition Legitimate	Attack / case family Legitimate high-risk business change	Primary trigger Routine + authority
-------------------	--------------------	---------------------------	--	--

Stage	Learner flow + synthetic content	UI to build	Expected safe behavior	Scoring event
1 Event	Dashboard notification: 'Northstar Supplies: Signed beneficiary-change case VC-209 is available in the vendor portal.' The Email badge increments and the toast routes into the scenario.	Dashboard toast, mail tile, unread counter, subject preview and received time.	Notice the source and time; open the full item before acting. Do not reply from the preview.	NOTIFY_SEEN +0; open latency and route logged.
2 Open	Open the established vendor thread. Context presented: A real vendor initiates a bank-detail change through the approved signed form and expects independent callback and dual approval.	Inbox and message pane with folders, thread history, attachment chips, reply controls and warning banners.	Read the full thread/message and prior context before choosing any action.	ITEM_OPEN +0; premature reply/action -1; dwell time logged.
3 Inspect	Open details and examine authenticated sender, signed form hash, portal case ID and explicit callback instruction	Expanded sender and message-details sheet: display name, full address, reply-to, authentication summary and link target.	Check this decision signal: The request follows the approved high-risk process and invites independent verification; it is not safe to accept without those controls.	INSPECT_CONTEXT +2; inspection path and time logged.
4 Branch	The interaction advances to the approved vendor portal case with side-by-side old/new details and Hold/Verify	Offline safe browser, attachment preview, QR inspector, OAuth consent mock or callback panel; no host execution/network.	Use the normal in-app path only after the details match the known context. Do not switch to an untrusted channel.	CORRECT_USE +3; needless reject/ignore -2; unsafe external action -4.
5 Verify	The learner opens Verify / More actions. Verification route: call the known vendor contact on file and obtain the required second approver	More-actions menu with Report phishing plus independent directory, approved portal and known-vendor-contact overlay.	Verify independently: call the known vendor contact on file and obtain the required second approver If it matches, continue; do not report or block a legitimate sender.	TRUSTED_VERIFY +3; false report/block -4; verification through message +0.
6 Resolve	Final expected resolution: after both checks match, approve in the vendor portal; retain audit evidence; do not report the legitimate sender	Outcome card plus 250-character rationale box, warning-sign chips, event summary and Return to dashboard.	Complete the resolution and return to the dashboard. Add a one-line reason without sensitive data.	RESOLVE_CORRECT +2; contradictory unsafe final -4; scenario capped 0-10.

End-state Dual approval completes VC-209 and an audit record is written.	Concise learner feedback Legitimate high-impact changes still require controls. Verification and dual approval enable safe completion without false rejection.
---	---

Senior Voice Memo Transfer

Platform Email	Difficulty Hard	Disposition Malicious	Attack / case family Synthetic voice / executive impersonation	Primary trigger Authority + urgency FICTIONAL MILITARY CONTEXT
-------------------	--------------------	--------------------------	---	---

Stage	Learner flow + synthetic content	UI to build	Expected safe behavior	Scoring event
1 Event	Dashboard notification: 'Col. Dev: Voice memo - process the welfare transfer now; do not call during the briefing.' The Email badge increments and the toast routes into the scenario.	Dashboard toast, mail tile, unread counter, subject preview and received time.	Notice the source and time; open the full item before acting. Do not reply from the preview.	NOTIFY_SEEN +0; open latency and route logged.
2 Open	Open the short email and audio attachment. Context presented: An external email contains a convincing voice memo directing a confidential transfer before a meeting.	Inbox and message pane with folders, thread history, attachment chips, reply controls and warning banners.	Read the full thread/message and prior context before choosing any action.	ITEM_OPEN +0; premature reply/action -1; dwell time logged.
3 Inspect	Open details and examine external sender, request outside role, secrecy, payment urgency and absence of written approval	Expanded sender and message-details sheet: display name, full address, reply-to, authentication summary and link target.	Check this decision signal: Voice resemblance can be synthesized and cannot replace procurement authorization.	INSPECT_CONTEXT +2; inspection path and time logged.
4 Branch	The interaction advances to an audio player with transfer instructions and a payment mock	Offline safe browser, attachment preview, QR inspector, OAuth consent mock or callback panel; no host execution/network.	Do not initiate payment, keep secret or rely on voice identity. Use Back/Close or safe preview only; no secret, payment, install or data release.	SAFE_PIVOT +3; risky open/reply -3; secret/payment/install/data release -8.
5 Verify	The learner opens Verify / More actions. Verification route: call the senior/duty office through known contact and check written authorization	More-actions menu with Report phishing plus independent directory, approved portal and known-vendor-contact overlay.	Verify independently: call the senior/duty office through known contact and check written authorization Then use the platform report/block path or the unit reporting route.	TRUSTED_VERIFY +3; report-only without checking +1; verification through message +0.
6 Resolve	Final expected resolution: do not transfer; report the impersonation; preserve the audio/email evidence	Outcome card plus 250-character rationale box, warning-sign chips, event summary and Return to dashboard.	Complete the resolution and return to the dashboard. Add a one-line reason without sensitive data.	RESOLVE_CORRECT +2; contradictory unsafe final -4; scenario capped 0-10.

End-state Senior denies the request and the synthetic media is flagged.	Concise learner feedback A familiar voice is not authorization. Apply the same independent verification and financial controls.
--	--

DLP Alert HTML Attachment

Platform Email	Difficulty Hard	Disposition Malicious	Attack / case family Security-tool impersonation / HTML smuggling	Primary trigger Fear + compliance
-------------------	--------------------	--------------------------	--	--------------------------------------

Stage	Learner flow + synthetic content	UI to build	Expected safe behavior	Scoring event
1 Event	Dashboard notification: 'Data Protection Monitor: Potential exfiltration detected - open SecurityReport.html.' The Email badge increments and the toast routes into the scenario.	Dashboard toast, mail tile, unread counter, subject preview and received time.	Notice the source and time; open the full item before acting. Do not reply from the preview.	NOTIFY_SEEN +0; open latency and route logged.
2 Open	Open the security alert email. Context presented: A DLP-themed email claims a policy violation and attaches an HTML report for local review.	Inbox and message pane with folders, thread history, attachment chips, reply controls and warning banners.	Read the full thread/message and prior context before choosing any action.	ITEM_OPEN +0; premature reply/action -1; dwell time logged.
3 Inspect	Open details and examine sender/authentication, unusual HTML attachment, threat language and no matching console alert	Expanded sender and message-details sheet: display name, full address, reply-to, authentication summary and link target.	Check this decision signal: An HTML attachment can present a fake login or trigger unsafe content; the approved DLP console should hold real alerts.	INSPECT_CONTEXT +2; inspection path and time logged.
4 Branch	The interaction advances to an inert local HTML page that renders a credential prompt and download button	Offline safe browser, attachment preview, QR inspector, OAuth consent mock or callback panel; no host execution/network.	Do not enter credentials or launch the downloaded file. Use Back/Close or safe preview only; no secret, payment, install or data release.	SAFE_PIVOT +3; risky open/reply -3; secret/payment/install/data release -8.
5 Verify	The learner opens Verify / More actions. Verification route: open the approved security console directly and contact IT/security via known route	More-actions menu with Report phishing plus independent directory, approved portal and known-vendor-contact overlay.	Verify independently: open the approved security console directly and contact IT/security via known route Then use the platform report/block path or the unit reporting route.	TRUSTED_VERIFY +3; report-only without checking +1; verification through message +0.
6 Resolve	Final expected resolution: close/quarantine the attachment; report phishing; verify console status	Outcome card, concise feedback, warning-sign chips, event summary and Return to dashboard.	Complete the resolution and return to the dashboard.	RESOLVE_CORRECT +2; contradictory unsafe final -4; scenario capped 0-10.

End-state Approved console shows no alert; HTML file remains inert.	Concise learner feedback Security alerts can be impersonated. Inspect file types and verify in the real console before acting.
--	---

QR Code in Policy PDF

Platform Email	Difficulty Hard	Disposition Malicious	Attack / case family QR phishing / credential theft	Primary trigger Authority + convenience
-------------------	--------------------	--------------------------	--	--

Stage	Learner flow + synthetic content	UI to build	Expected safe behavior	Scoring event
1 Event	Dashboard notification: 'Compliance Office: Mobile acknowledgement required - scan the QR in attached policy.' The Email badge increments and the toast routes into the scenario.	Dashboard toast, mail tile, unread counter, subject preview and received time.	Notice the source and time; open the full item before acting. Do not reply from the preview.	NOTIFY_SEEN +0; open latency and route logged.
2 Open	Open the policy email and PDF. Context presented: An otherwise polished policy email attaches a PDF that says scanning a QR is the only way to acknowledge.	Inbox and message pane with folders, thread history, attachment chips, reply controls and warning banners.	Read the full thread/message and prior context before choosing any action.	ITEM_OPEN +0; premature reply/action -1; dwell time logged.
3 Inspect	Open details and examine sender/reply-to, unexpected mobile-only method, QR destination and reference mismatch	Expanded sender and message-details sheet: display name, full address, reply-to, authentication summary and link target.	Check this decision signal: The QR hides a look-alike login route and the process is absent from the approved compliance portal.	INSPECT_CONTEXT +2; inspection path and time logged.
4 Branch	The interaction advances to the PDF QR inspector and synthetic mobile sign-in	Offline safe browser, attachment preview, QR inspector, OAuth consent mock or callback panel; no host execution/network.	Do not open the QR target or enter credentials/OTP. Use Back/Close or safe preview only; no secret, payment, install or data release.	SAFE_PIVOT +3; risky open/reply -3; secret/payment/install/data release -8.
5 Verify	The learner opens Verify / More actions. Verification route: check assigned policies directly in the approved portal and contact Compliance through the directory	More-actions menu with Report phishing plus independent directory, approved portal and known-vendor-contact overlay.	Verify independently: check assigned policies directly in the approved portal and contact Compliance through the directory. Then use the platform report/block path or the unit reporting route.	TRUSTED_VERIFY +3; report-only without checking +1; verification through message +0.
6 Resolve	Final expected resolution: do not use the QR; report phishing; close the attachment	Outcome card plus 250-character rationale box, warning-sign chips, event summary and Return to dashboard.	Complete the resolution and return to the dashboard. Add a one-line reason without sensitive data.	RESOLVE_CORRECT +2; contradictory unsafe final -4; scenario capped 0-10.

End-state Portal shows no policy task and the QR is marked unsafe.	Concise learner feedback QR codes bypass visible-link checks. Inspect the destination and verify the process in the official portal.
---	---

Payroll Direct-Deposit Redirect

Platform Email	Difficulty Hard	Disposition Malicious	Attack / case family HR/business email compromise / payroll fraud	Primary trigger Authority + routine FICTIONAL MILITARY CONTEXT
-------------------	--------------------	--------------------------	--	---

Stage	Learner flow + synthetic content	UI to build	Expected safe behavior	Scoring event
1 Event	Dashboard notification: 'Re: Allowance correction - use the new account before today's payroll cutoff.' The Email badge increments and the toast routes into the scenario.	Dashboard toast, mail tile, unread counter, subject preview and received time.	Notice the source and time; open the full item before acting. Do not reply from the preview.	NOTIFY_SEEN +0; open latency and route logged.
2 Open	Open the realistic HR reply chain. Context presented: A compromised-looking manager thread asks payroll to redirect a service member's allowance using an attached form.	Inbox and message pane with folders, thread history, attachment chips, reply controls and warning banners.	Read the full thread/message and prior context before choosing any action.	ITEM_OPEN +0; premature reply/action -1; dwell time logged.
3 Inspect	Open details and examine role mismatch, changed beneficiary, urgent cutoff, altered reply-to and missing case ID	Expanded sender and message-details sheet: display name, full address, reply-to, authentication summary and link target.	Check this decision signal: Copied HR context cannot authorize a bank change; the request bypasses the employee-initiated workflow and dual approval.	INSPECT_CONTEXT +2; inspection path and time logged.
4 Branch	The interaction advances to a prefilled payroll change form and Approve button	Offline safe browser, attachment preview, QR inspector, OAuth consent mock or callback panel; no host execution/network.	Do not alter bank details or approve without employee verification. Use Back/Close or safe preview only; no secret, payment, install or data release.	SAFE_PIVOT +3; risky open/reply -3; secret/payment/install/data release -8.
5 Verify	The learner opens Verify / More actions. Verification route: verify with the employee and HR through known channels and require the approved portal workflow	More-actions menu with Report phishing plus independent directory, approved portal and known-vendor-contact overlay.	Verify independently: verify with the employee and HR through known channels and require the approved portal workflow Then use the platform report/block path or the unit reporting route.	TRUSTED_VERIFY +3; report-only without checking +1; verification through message +0.
6 Resolve	Final expected resolution: hold the change; report the compromised thread; preserve evidence	Outcome card plus 250-character rationale box, warning-sign chips, event summary and Return to dashboard.	Complete the resolution and return to the dashboard. Add a one-line reason without sensitive data.	RESOLVE_CORRECT +2; contradictory unsafe final -4; scenario capped 0-10.

End-state Payroll remains unchanged and the legitimate manager is alerted.	Concise learner feedback Payroll diversion can hide in real threads. Require employee initiation, known-channel verification and dual control.
---	---

Scenario Bank: SMS

Twenty-five six-stage scenarios for the simulated SMS environment. Composition: 8 easy, 9 medium, 8 hard; 20 malicious/deceptive and 5 legitimate controls; 5 fictional military-context cases.

Implementation rule

All senders, messages, accounts, numbers, links, QR codes, files, calls and payment screens are synthetic. No scenario may resolve outside the local application. The learner can take unsafe-looking actions, but they only change local state and scoring.

ID	Scenario	Level	Case	Family	M	ID	Scenario	Level	Case	Family	M
S01	Bank KYC Suspension	Easy	Malicious	Smishing / bank impersonation		S14	Emergency Recall Location Link	Medium	Malicious	Military smishing / location collection	Y
S02	Electricity Disconnect Tonight	Easy	Malicious	Utility impersonation / callback scam		S15	Canteen Subsidy MMS QR	Medium	Malicious	Military-themed QR smishing	Y
S03	Matching Debit Alert	Easy	Legitimate	Legitimate transaction alert		S16	Learner-Initiated Login Code	Medium	Legitimate	Legitimate OTP / security code	
S04	Unpaid E-Challan Link	Easy	Malicious	Government-service smishing		S17	New-Phone Family Emergency	Medium	Malicious	Known-person impersonation / emergency payment	
S05	Parcel Address Fee	Easy	Malicious	Parcel smishing / payment phishing		S18	Bank Header Thread Hijack	Hard	Malicious	Sender-ID spoofing / callback phishing	
S06	Service-Number Confirmation	Easy	Malicious	Military impersonation / identity collection	Y	S19	Network Survey Requests IMEI	Hard	Malicious	Military-targeted technical pretext / device profiling	Y
S07	Expected Recharge Confirmation	Easy	Legitimate	Legitimate service receipt		S20	Parcel Text Plus Callback	Hard	Malicious	Multi-stage parcel / callback / remote access scam	
S08	Lottery Claim Text	Easy	Malicious	Prize/advance-fee scam		S21	Matching New-Login Alert	Hard	Legitimate	Legitimate security alert	
S09	Wrong Number Becomes an Investment Pitch	Medium	Malicious	Wrong-number grooming / investment fraud		S22	Synthetic Voice-Mail Link	Hard	Malicious	Voice phishing / link lure	Y
S10	eSIM Upgrade OTP	Medium	Malicious	SIM-swap / OTP theft		S23	UPI Refund Collect Request	Hard	Malicious	Payment-request reversal scam	
S11	Expected Clinic Reminder	Medium	Legitimate	Legitimate appointment reminder		S24	Fake Cybercrime Case Fee	Hard	Malicious	Government/I4C impersonation / digital arrest	
S12	Income-Tax Refund Form	Medium	Malicious	Government impersonation / refund smishing		S25	FASTag Update APK	Hard	Malicious	Road-toll impersonation / malicious app	
S13	Rating-Task Recruiter	Medium	Malicious	Task/job scam							

S01

Bank KYC Suspension

Platform SMS	Difficulty Easy	Disposition Malicious	Attack / case family Smishing / bank impersonation	Primary trigger Fear + urgency
-----------------	--------------------	--------------------------	---	-----------------------------------

Stage	Learner flow + synthetic content	UI to build	Expected safe behavior	Scoring event
1 Event	Dashboard notification: 'KYC overdue. Account blocks in 30 min. Update: bank-verify.training.example' The SMS badge increments and the toast routes into the scenario.	Dashboard toast, SMS tile, unread badge, sender/header preview and received time.	Notice the source and time; open the full item before acting. Do not reply from the preview.	NOTIFY_SEEN +0; open latency and route logged.
2 Open	Open the unread bank-themed conversation. Context presented: A text from an ordinary mobile number says the learner's bank account will be blocked unless KYC is updated.	Native-style conversation list and thread with sender header/number, timestamps and link/MMS preview.	Read the full thread/message and prior context before choosing any action.	ITEM_OPEN +0; premature reply/action -1; dwell time logged.
3 Inspect	Open details and examine full number/header, prior thread, shortened/look-alike link and countdown	Conversation details sheet showing full number/header, prior thread, SIM label and report-junk controls.	Check this decision signal: The message is unsolicited, uses pressure and asks the learner to leave the official banking app.	INSPECT_CONTEXT +2; inspection path and time logged.
4 Branch	The interaction advances to a fake mobile KYC page requesting account, PIN and OTP	Offline safe browser, call-confirmation sheet, MMS/QR inspector or synthetic payment request panel.	Do not enter credentials, PIN, OTP or ID imagery. Use Back/Close or safe preview only; no secret, payment, install or data release.	SAFE_PIVOT +3; risky open/reply -3; secret/payment/install/data release -8.
5 Verify	The learner opens Verify / More actions. Verification route: open the known banking app directly or call the card's known number	Conversation action sheet with block/report junk plus independent official-app, statement or known-number verification overlay.	Verify independently: open the known banking app directly or call the card's known number Then use the platform report/block path or the unit reporting route.	TRUSTED_VERIFY +3; report-only without checking +1; verification through message +0.
6 Resolve	Final expected resolution: close; report junk/block; verify account status independently	Outcome card, concise feedback, warning-sign chips, event summary and Return to dashboard.	Complete the resolution and return to the dashboard.	RESOLVE_CORRECT +2; contradictory unsafe final -4; scenario capped 0-10.

End-state Official app shows no block; sender is reported as junk.	Concise learner feedback Banks do not need your PIN or OTP by text. Open the official app yourself and verify.
---	---

Electricity Disconnect Tonight

Platform SMS	Difficulty Easy	Disposition Malicious	Attack / case family Utility impersonation / callback scam	Primary trigger Fear + urgency
-----------------	--------------------	--------------------------	---	-----------------------------------

Stage	Learner flow + synthetic content	UI to build	Expected safe behavior	Scoring event
1 Event	Dashboard notification: 'Power will disconnect 21:30 for unpaid bill. Call 00000 12002 now.' The SMS badge increments and the toast routes into the scenario.	Dashboard toast, SMS tile, unread badge, sender/header preview and received time.	Notice the source and time; open the full item before acting. Do not reply from the preview.	NOTIFY_SEEN +0; open latency and route logged.
2 Open	Open the utility-themed thread. Context presented: A text threatens power disconnection and supplies a personal mobile number for immediate payment.	Native-style conversation list and thread with sender header/number, timestamps and link/MMS preview.	Read the full thread/message and prior context before choosing any action.	ITEM_OPEN +0; premature reply/action -1; dwell time logged.
3 Inspect	Open details and examine sender number, absent customer reference, supplied callback and late-hour pressure	Conversation details sheet showing full number/header, prior thread, SIM label and report-junk controls.	Check this decision signal: A genuine utility notice should match the account and be verifiable in the official portal; the personal callback is suspicious.	INSPECT_CONTEXT +2; inspection path and time logged.
4 Branch	The interaction advances to a call-confirmation sheet leading to a synthetic operator asking for remote access/payment	Offline safe browser, call-confirmation sheet, MMS/QR inspector or synthetic payment request panel.	Do not call the supplied number, share screen or pay. Use Back/Close or safe preview only; no secret, payment, install or data release.	SAFE_PIVOT +3; risky open/reply -3; secret/payment/install/data release -8.
5 Verify	The learner opens Verify / More actions. Verification route: check the known utility app/bill or call the official number from the bill	Conversation action sheet with block/report junk plus independent official-app, statement or known-number verification overlay.	Verify independently: check the known utility app/bill or call the official number from the bill. Then use the platform report/block path or the unit reporting route.	TRUSTED_VERIFY +3; report-only without checking +1; verification through message +0.
6 Resolve	Final expected resolution: do not call; report junk/block; verify the account independently	Outcome card, concise feedback, warning-sign chips, event summary and Return to dashboard.	Complete the resolution and return to the dashboard.	RESOLVE_CORRECT +2; contradictory unsafe final -4; scenario capped 0-10.

End-state

Official bill mock shows paid status and the fake number is blocked.

Concise learner feedback

Disconnection threats create panic. Verify bills through the utility channel you already know.

Matching Debit Alert

Platform SMS	Difficulty Easy	Disposition Legitimate	Attack / case family Legitimate transaction alert	Primary trigger Routine
-----------------	--------------------	---------------------------	--	----------------------------

Stage	Learner flow + synthetic content	UI to build	Expected safe behavior	Scoring event
1 Event	Dashboard notification: 'ALERT: INR 840 debited at TRAINING MART, card xx1042. No action needed.' The SMS badge increments and the toast routes into the scenario.	Dashboard toast, SMS tile, unread badge, sender/header preview and received time.	Notice the source and time; open the full item before acting. Do not reply from the preview.	NOTIFY_SEEN +0; open latency and route logged.
2 Open	Open the established bank-alert thread. Context presented: A no-link bank alert matches the synthetic purchase the learner completed moments earlier.	Native-style conversation list and thread with sender header/number, timestamps and link/MMS preview.	Read the full thread/message and prior context before choosing any action.	ITEM_OPEN +0; premature reply/action -1; dwell time logged.
3 Inspect	Open details and examine registered header, amount, masked card, timestamp and absence of links/callback	Conversation details sheet showing full number/header, prior thread, SIM label and report-junk controls.	Check this decision signal: The alert matches the learner's simulated transaction and contains no request for secrets or action.	INSPECT_CONTEXT +2; inspection path and time logged.
4 Branch	The interaction advances to the in-app transaction comparison card with Mark reviewed	Offline safe browser, call-confirmation sheet, MMS/QR inspector or synthetic payment request panel.	Use the normal in-app path only after the details match the known context. Do not switch to an untrusted channel.	CORRECT_USE +3; needless reject/ignore -2; unsafe external action -4.
5 Verify	The learner opens Verify / More actions. Verification route: compare with the known banking-app transaction list	Conversation action sheet with block/report junk plus independent official-app, statement or known-number verification overlay.	Verify independently: compare with the known banking-app transaction list If it matches, continue; do not report or block a legitimate sender.	TRUSTED_VERIFY +3; false report/block -4; verification through message +0.
6 Resolve	Final expected resolution: mark reviewed/archive; do not report or block	Outcome card, concise feedback, warning-sign chips, event summary and Return to dashboard.	Complete the resolution and return to the dashboard.	RESOLVE_CORRECT +2; contradictory unsafe final -4; scenario capped 0-10.

End-state

Transaction match is confirmed and the alert remains in the legitimate thread.

Concise learner feedback

A matching no-action alert is useful security information. Verify it against the account and avoid a false report.

Unpaid E-Challan Link

Platform SMS	Difficulty Easy	Disposition Malicious	Attack / case family Government-service smishing	Primary trigger Fear + urgency
-----------------	--------------------	--------------------------	---	-----------------------------------

Stage	Learner flow + synthetic content	UI to build	Expected safe behavior	Scoring event
1 Event	Dashboard notification: 'E-CHALLAN pending INR 500. Pay today to avoid court: challan-pay.training.example' The SMS badge increments and the toast routes into the scenario.	Dashboard toast, SMS tile, unread badge, sender/header preview and received time.	Notice the source and time; open the full item before acting. Do not reply from the preview.	NOTIFY_SEEN +0; open latency and route logged.
2 Open	Open the new challan conversation. Context presented: A text claims an unpaid traffic fine will increase today and contains a look-alike payment link.	Native-style conversation list and thread with sender header/number, timestamps and link/MMS preview.	Read the full thread/message and prior context before choosing any action.	ITEM_OPEN +0; premature reply/action -1; dwell time logged.
3 Inspect	Open details and examine sender/header, vehicle/reference mismatch, link target and consequence language	Conversation details sheet showing full number/header, prior thread, SIM label and report-junk controls.	Check this decision signal: The learner has no matching case and the domain is not the known government portal.	INSPECT_CONTEXT +2; inspection path and time logged.
4 Branch	The interaction advances to a fake challan page requesting vehicle, card/UPI and OTP	Offline safe browser, call-confirmation sheet, MMS/QR inspector or synthetic payment request panel.	Do not pay or enter vehicle/financial/OTP data. Use Back/Close or safe preview only; no secret, payment, install or data release.	SAFE_PIVOT +3; risky open/reply -3; secret/payment/install/data release -8.
5 Verify	The learner opens Verify / More actions. Verification route: open the official challan portal/app independently and search a known vehicle/reference	Conversation action sheet with block/report junk plus independent official-app, statement or known-number verification overlay.	Verify independently: open the official challan portal/app independently and search a known vehicle/reference Then use the platform report/block path or the unit reporting route.	TRUSTED_VERIFY +3; report-only without checking +1; verification through message +0.
6 Resolve	Final expected resolution: close; report junk/block; preserve the message	Outcome card plus 250-character rationale box, warning-sign chips, event summary and Return to dashboard.	Complete the resolution and return to the dashboard. Add a one-line reason without sensitive data.	RESOLVE_CORRECT +2; contradictory unsafe final -4; scenario capped 0-10.

End-state Official portal mock finds no fine and the sender is blocked.	Concise learner feedback Verify fines in the official portal you open yourself. Do not pay from an unsolicited text link.
--	--

S05

Parcel Address Fee

Platform SMS	Difficulty Easy	Disposition Malicious	Attack / case family Parcel smishing / payment phishing	Primary trigger Curiosity + urgency
-----------------	--------------------	--------------------------	--	--

Stage	Learner flow + synthetic content	UI to build	Expected safe behavior	Scoring event
1 Event	Dashboard notification: 'Parcel paused: confirm address and pay INR 20 within 6 hours.' The SMS badge increments and the toast routes into the scenario.	Dashboard toast, SMS tile, unread badge, sender/header preview and received time.	Notice the source and time; open the full item before acting. Do not reply from the preview.	NOTIFY_SEEN +0; open latency and route logged.
2 Open	Open the package text thread. Context presented: A text says a delivery address is incomplete and asks for a small redelivery fee.	Native-style conversation list and thread with sender header/number, timestamps and link/MMS preview.	Read the full thread/message and prior context before choosing any action.	ITEM_OPEN +0; premature reply/action -1; dwell time logged.
3 Inspect	Open details and examine unknown sender, unexpected parcel, shortened link and small-fee request	Conversation details sheet showing full number/header, prior thread, SIM label and report-junk controls.	Check this decision signal: The link and fee are inconsistent with a parcel the learner cannot identify.	INSPECT_CONTEXT +2; inspection path and time logged.
4 Branch	The interaction advances to a synthetic address form followed by card/UPI fields	Offline safe browser, call-confirmation sheet, MMS/QR inspector or synthetic payment request panel.	Do not enter home address, card details or approve payment. Use Back/Close or safe preview only; no secret, payment, install or data release.	SAFE_PIVOT +3; risky open/reply -3; secret/payment/install/data release -8.
5 Verify	The learner opens Verify / More actions. Verification route: check the known courier app/site with independently held tracking information	Conversation action sheet with block/report junk plus independent official-app, statement or known-number verification overlay.	Verify independently: check the known courier app/site with independently held tracking information Then use the platform report/block path or the unit reporting route.	TRUSTED_VERIFY +3; report-only without checking +1; verification through message +0.
6 Resolve	Final expected resolution: close; report junk/block; do not reply	Outcome card, concise feedback, warning-sign chips, event summary and Return to dashboard.	Complete the resolution and return to the dashboard.	RESOLVE_CORRECT +2; contradictory unsafe final -4; scenario capped 0-10.

End-state No address/payment data is entered and the sender is blocked.	Concise learner feedback Small delivery fees are designed to seem harmless. Verify the parcel independently before sharing data.
--	---

Service-Number Confirmation

Platform SMS	Difficulty Easy	Disposition Malicious	Attack / case family Military impersonation / identity collection	Primary trigger Authority FICTIONAL MILITARY CONTEXT
-----------------	--------------------	--------------------------	--	---

Stage	Learner flow + synthetic content	UI to build	Expected safe behavior	Scoring event
1 Event	Dashboard notification: 'Unit Records: Reply SERVICE NO + DOB to keep your personnel file active.' The SMS badge increments and the toast routes into the scenario.	Dashboard toast, SMS tile, unread badge, sender/header preview and received time.	Notice the source and time; open the full item before acting. Do not reply from the preview.	NOTIFY_SEEN +0; open latency and route logged.
2 Open	Open the unsaved administrative-looking thread. Context presented: An unknown number claims to be the unit clerk and asks the learner to reply with a service number and date of birth.	Native-style conversation list and thread with sender header/number, timestamps and link/MMS preview.	Read the full thread/message and prior context before choosing any action.	ITEM_OPEN +0; premature reply/action -1; dwell time logged.
3 Inspect	Open details and examine full number, generic sender, absent case reference and sensitive data request	Conversation details sheet showing full number/header, prior thread, SIM label and report-junk controls.	Check this decision signal: A personal SMS number is not the approved personnel-record channel and the data request is excessive.	INSPECT_CONTEXT +2; inspection path and time logged.
4 Branch	The interaction advances to a quick-reply composer with synthetic identity chips	Offline safe browser, call-confirmation sheet, MMS/QR inspector or synthetic payment request panel.	Do not send service number, date of birth or document photo. Use Back/Close or safe preview only; no secret, payment, install or data release.	SAFE_PIVOT +3; risky open/reply -3; secret/payment/install/data release -8.
5 Verify	The learner opens Verify / More actions. Verification route: contact the unit clerk through the approved directory/in person	Conversation action sheet with block/report junk plus independent official-app, statement or known-number verification overlay.	Verify independently: contact the unit clerk through the approved directory/in person Then use the platform report/block path or the unit reporting route.	TRUSTED_VERIFY +3; report-only without checking +1; verification through message +0.
6 Resolve	Final expected resolution: do not reply; report through unit security; block the number	Outcome card plus 250-character rationale box, warning-sign chips, event summary and Return to dashboard.	Complete the resolution and return to the dashboard. Add a one-line reason without sensitive data.	RESOLVE_CORRECT +2; contradictory unsafe final -4; scenario capped 0-10.

End-state No identity data is sent and the sender is blocked.	Concise learner feedback Authority claims do not replace the approved records process. Never send service identity data by unsolicited SMS.
--	--

S07

Expected Recharge Confirmation

Platform SMS	Difficulty Easy	Disposition Legitimate	Attack / case family Legitimate service receipt	Primary trigger Routine
Stage	Learner flow + synthetic content	UI to build	Expected safe behavior	Scoring event
1 Event	Dashboard notification: 'Recharge of INR 299 successful for xx7710. Validity 28 days. No action required.' The SMS badge increments and the toast routes into the scenario.	Dashboard toast, SMS tile, unread badge, sender/header preview and received time.	Notice the source and time; open the full item before acting. Do not reply from the preview.	NOTIFY_SEEN +0; open latency and route logged.
2 Open	Open the established provider thread. Context presented: A registered telecom header confirms the exact recharge the learner initiated in the synthetic provider app.	Native-style conversation list and thread with sender header/number, timestamps and link/MMS preview.	Read the full thread/message and prior context before choosing any action.	ITEM_OPEN +0; premature reply/action -1; dwell time logged.
3 Inspect	Open details and examine registered header, masked number, amount, timing and no-action text	Conversation details sheet showing full number/header, prior thread, SIM label and report-junk controls.	Check this decision signal: The alert matches the learner-initiated transaction and asks for no link, reply or personal information.	INSPECT_CONTEXT +2; inspection path and time logged.
4 Branch	The interaction advances to the provider-app receipt comparison card	Offline safe browser, call-confirmation sheet, MMS/QR inspector or synthetic payment request panel.	Use the normal in-app path only after the details match the known context. Do not switch to an untrusted channel.	CORRECT_USE +3; needless reject/ignore -2; unsafe external action -4.
5 Verify	The learner opens Verify / More actions. Verification route: compare the transaction in the known provider app	Conversation action sheet with block/report junk plus independent official-app, statement or known-number verification overlay.	Verify independently: compare the transaction in the known provider app. If it matches, continue; do not report or block a legitimate sender.	TRUSTED_VERIFY +3; false report/block -4; verification through message +0.
6 Resolve	Final expected resolution: mark reviewed; retain/archive; do not report/block	Outcome card, concise feedback, warning-sign chips, event summary and Return to dashboard.	Complete the resolution and return to the dashboard.	RESOLVE_CORRECT +2; contradictory unsafe final -4; scenario capped 0-10.
End-state Recharge and SMS receipt match and remain stored locally.		Concise learner feedback Expected, matching receipts are legitimate. Verify the amount and account, then handle normally.		

Lottery Claim Text

Platform SMS	Difficulty Easy	Disposition Malicious	Attack / case family Prize/advance-fee scam	Primary trigger Greed + scarcity
-----------------	--------------------	--------------------------	--	-------------------------------------

Stage	Learner flow + synthetic content	UI to build	Expected safe behavior	Scoring event
1 Event	Dashboard notification: 'CONGRATS! You won INR 5 lakh. Pay INR 499 processing before midnight.' The SMS badge increments and the toast routes into the scenario.	Dashboard toast, SMS tile, unread badge, sender/header preview and received time.	Notice the source and time; open the full item before acting. Do not reply from the preview.	NOTIFY_SEEN +0; open latency and route logged.
2 Open	Open the unsolicited prize thread. Context presented: An unknown sender says the learner won a lottery they never entered and must pay a processing fee.	Native-style conversation list and thread with sender header/number, timestamps and link/MMS preview.	Read the full thread/message and prior context before choosing any action.	ITEM_OPEN +0; premature reply/action -1; dwell time logged.
3 Inspect	Open details and examine unknown number, no entry history, fee demand and urgent deadline	Conversation details sheet showing full number/header, prior thread, SIM label and report-junk controls.	Check this decision signal: A genuine prize cannot arise without entry and should not require payment to release winnings.	INSPECT_CONTEXT +2; inspection path and time logged.
4 Branch	The interaction advances to a claim form with identity and payment fields	Offline safe browser, call-confirmation sheet, MMS/QR inspector or synthetic payment request panel.	Do not pay the fee or submit identity/bank details. Use Back/Close or safe preview only; no secret, payment, install or data release.	SAFE_PIVOT +3; risky open/reply -3; secret/payment/install/data release -8.
5 Verify	The learner opens Verify / More actions. Verification route: verify any promotion through an independently found official organizer	Conversation action sheet with block/report junk plus independent official-app, statement or known-number verification overlay.	Verify independently: verify any promotion through an independently found official organizer Then use the platform report/block path or the unit reporting route.	TRUSTED_VERIFY +3; report-only without checking +1; verification through message +0.
6 Resolve	Final expected resolution: do not reply/pay; report junk/block	Outcome card, concise feedback, warning-sign chips, event summary and Return to dashboard.	Complete the resolution and return to the dashboard.	RESOLVE_CORRECT +2; contradictory unsafe final -4; scenario capped 0-10.

End-state Claim is discarded and sender is blocked.	Concise learner feedback Paying to receive an unexpected prize is a classic advance-fee scam. Report and disengage.
--	--

Wrong Number Becomes an Investment Pitch

Platform SMS	Difficulty Medium	Disposition Malicious	Attack / case family Wrong-number grooming / investment fraud	Primary trigger Curiosity + trust
-----------------	----------------------	--------------------------	--	--------------------------------------

Stage	Learner flow + synthetic content	UI to build	Expected safe behavior	Scoring event
1 Event	Dashboard notification: 'Sorry, is this Rohan? ... You seem kind. My analyst has a guaranteed trade tonight.' The SMS badge increments and the toast routes into the scenario.	Dashboard toast, SMS tile, unread badge, sender/header preview and received time.	Notice the source and time; open the full item before acting. Do not reply from the preview.	NOTIFY_SEEN +0; open latency and route logged.
2 Open	Open the multi-day wrong-number thread. Context presented: A polite wrong-number exchange develops over several synthetic days before pivoting to private investments.	Native-style conversation list and thread with sender header/number, timestamps and link/MMS preview.	Read the full thread/message and prior context before choosing any action.	ITEM_OPEN +0; premature reply/action -1; dwell time logged.
3 Inspect	Open details and examine unsolicited start, rapid rapport, lifestyle claims and investment pivot	Conversation details sheet showing full number/header, prior thread, SIM label and report-junk controls.	Check this decision signal: The accidental contact and relationship are engineered to establish trust before the financial request.	INSPECT_CONTEXT +2; inspection path and time logged.
4 Branch	The interaction advances to a fake trading dashboard showing a trial profit and Deposit button	Offline safe browser, call-confirmation sheet, MMS/QR inspector or synthetic payment request panel.	Do not deposit, upload identity or move to another app. Use Back/Close or safe preview only; no secret, payment, install or data release.	SAFE_PIVOT +3; risky open/reply -3; secret/payment/install/data release -8.
5 Verify	The learner opens Verify / More actions. Verification route: research the person/platform independently and check regulator/official sources	Conversation action sheet with block/report junk plus independent official-app, statement or known-number verification overlay.	Verify independently: research the person/platform independently and check regulator/official sources Then use the platform report/block path or the unit reporting route.	TRUSTED_VERIFY +3; report-only without checking +1; verification through message +0.
6 Resolve	Final expected resolution: stop responding; report junk/block; do not invest	Outcome card plus 250-character rationale box, warning-sign chips, event summary and Return to dashboard.	Complete the resolution and return to the dashboard. Add a one-line reason without sensitive data.	RESOLVE_CORRECT +2; contradictory unsafe final -4; scenario capped 0-10.

End-state Synthetic trial profit is exposed as fabricated; no deposit occurs.	Concise learner feedback A wrong-number chat can be the start of long-game grooming. End contact when it pivots to money.
--	--

eSIM Upgrade OTP

Platform SMS	Difficulty Medium	Disposition Malicious	Attack / case family SIM-swap / OTP theft	Primary trigger Authority + convenience
-----------------	----------------------	--------------------------	--	--

Stage	Learner flow + synthetic content	UI to build	Expected safe behavior	Scoring event
1 Event	Dashboard notification: 'SIM upgrade pending. Call 00000 31010 and quote the OTP sent next.' The SMS badge increments and the toast routes into the scenario.	Dashboard toast, SMS tile, unread badge, sender/header preview and received time.	Notice the source and time; open the full item before acting. Do not reply from the preview.	NOTIFY_SEEN +0; open latency and route logged.
2 Open	Open the telecom-themed thread. Context presented: A text claims a required eSIM upgrade and directs the learner to call a mobile number and share an OTP.	Native-style conversation list and thread with sender header/number, timestamps and link/MMS preview.	Read the full thread/message and prior context before choosing any action.	ITEM_OPEN +0; premature reply/action -1; dwell time logged.
3 Inspect	Open details and examine unregistered sender, call number, OTP instruction and account-takeover implications	Conversation details sheet showing full number/header, prior thread, SIM label and report-junk controls.	Check this decision signal: An OTP can authorize SIM/eSIM changes; it must never be relayed to an inbound contact.	INSPECT_CONTEXT +2; inspection path and time logged.
4 Branch	The interaction advances to a call-confirmation sheet and synthetic OTP message	Offline safe browser, call-confirmation sheet, MMS/QR inspector or synthetic payment request panel.	Do not call the supplied number or share the OTP. Use Back/Close or safe preview only; no secret, payment, install or data release.	SAFE_PIVOT +3; risky open/reply -3; secret/payment/install/data release -8.
5 Verify	The learner opens Verify / More actions. Verification route: open the known carrier app/store contact and check for a requested SIM change	Conversation action sheet with block/report junk plus independent official-app, statement or known-number verification overlay.	Verify independently: open the known carrier app/store contact and check for a requested SIM change Then use the platform report/block path or the unit reporting route.	TRUSTED_VERIFY +3; report-only without checking +1; verification through message +0.
6 Resolve	Final expected resolution: do not call/share; report junk/block; secure the carrier account	Outcome card, concise feedback, warning-sign chips, event summary and Return to dashboard.	Complete the resolution and return to the dashboard.	RESOLVE_CORRECT +2; contradictory unsafe final -4; scenario capped 0-10.

End-state No SIM change is approved and the suspicious number is blocked.	Concise learner feedback SIM-change OTPs protect control of your number. Never share them; contact the carrier through a known route.
--	--

Expected Clinic Reminder

Platform SMS	Difficulty Medium	Disposition Legitimate	Attack / case family Legitimate appointment reminder	Primary trigger Routine + care
-----------------	----------------------	---------------------------	---	-----------------------------------

Stage	Learner flow + synthetic content	UI to build	Expected safe behavior	Scoring event
1 Event	Dashboard notification: 'Training Clinic: Appointment 03 Sep 09:20. Reply 1 confirm, 2 reschedule.' The SMS badge increments and the toast routes into the scenario.	Dashboard toast, SMS tile, unread badge, sender/header preview and received time.	Notice the source and time; open the full item before acting. Do not reply from the preview.	NOTIFY_SEEN +0; open latency and route logged.
2 Open	Open the established clinic thread. Context presented: A registered clinic header reminds the learner of an appointment booked in the synthetic clinic portal.	Native-style conversation list and thread with sender header/number, timestamps and link/MMS preview.	Read the full thread/message and prior context before choosing any action.	ITEM_OPEN +0; premature reply/action -1; dwell time logged.
3 Inspect	Open details and examine registered header, matching date/reference and limited reply options	Conversation details sheet showing full number/header, prior thread, SIM label and report-junk controls.	Check this decision signal: The reminder matches an initiated booking and requests only a low-risk confirmation.	INSPECT_CONTEXT +2; inspection path and time logged.
4 Branch	The interaction advances to the SMS quick-reply choices and local appointment comparison	Offline safe browser, call-confirmation sheet, MMS/QR inspector or synthetic payment request panel.	Use the normal in-app path only after the details match the known context. Do not switch to an untrusted channel.	CORRECT_USE +3; needless reject/ignore -2; unsafe external action -4.
5 Verify	The learner opens Verify / More actions. Verification route: compare with the known clinic portal/Trusted Directory	Conversation action sheet with block/report junk plus independent official-app, statement or known-number verification overlay.	Verify independently: compare with the known clinic portal/Trusted Directory. If it matches, continue; do not report or block a legitimate sender.	TRUSTED_VERIFY +3; false report/block -4; verification through message +0.
6 Resolve	Final expected resolution: reply 1 or 2 as appropriate; retain the thread; do not report	Outcome card, concise feedback, warning-sign chips, event summary and Return to dashboard.	Complete the resolution and return to the dashboard.	RESOLVE_CORRECT +2; contradictory unsafe final -4; scenario capped 0-10.

End-state Appointment status updates locally and no health details are transmitted.	Concise learner feedback A specific expected reminder with limited action can be legitimate. Confirm the booking without oversharing.
--	--

Income-Tax Refund Form

Platform SMS	Difficulty Medium	Disposition Malicious	Attack / case family Government impersonation / refund smishing	Primary trigger Greed + authority
-----------------	----------------------	--------------------------	--	--------------------------------------

Stage	Learner flow + synthetic content	UI to build	Expected safe behavior	Scoring event
1 Event	Dashboard notification: 'Tax refund INR 12,480 approved. Confirm bank before 18:00: tx-rf.training.example' The SMS badge increments and the toast routes into the scenario.	Dashboard toast, SMS tile, unread badge, sender/header preview and received time.	Notice the source and time; open the full item before acting. Do not reply from the preview.	NOTIFY_SEEN +0; open latency and route logged.
2 Open	Open the tax-themed conversation. Context presented: A branded header promises a refund but uses a shortened link and requests bank credentials.	Native-style conversation list and thread with sender header/number, timestamps and link/MMS preview.	Read the full thread/message and prior context before choosing any action.	ITEM_OPEN +0; premature reply/action -1; dwell time logged.
3 Inspect	Open details and examine header anomalies, generic reference, target domain and urgency	Conversation details sheet showing full number/header, prior thread, SIM label and report-junk controls.	Check this decision signal: A tax refund should be verified in the official portal and does not require banking secrets by text.	INSPECT_CONTEXT +2; inspection path and time logged.
4 Branch	The interaction advances to a synthetic refund form asking identity, account, card and OTP	Offline safe browser, call-confirmation sheet, MMS/QR inspector or synthetic payment request panel.	Do not submit identity/financial secrets. Use Back/Close or safe preview only; no secret, payment, install or data release.	SAFE_PIVOT +3; risky open/reply -3; secret/payment/install/data release -8.
5 Verify	The learner opens Verify / More actions. Verification route: open the known tax portal directly and check account/refund status	Conversation action sheet with block/report junk plus independent official-app, statement or known-number verification overlay.	Verify independently: open the known tax portal directly and check account/refund status Then use the platform report/block path or the unit reporting route.	TRUSTED_VERIFY +3; report-only without checking +1; verification through message +0.
6 Resolve	Final expected resolution: close; report junk/block; do not submit	Outcome card, concise feedback, warning-sign chips, event summary and Return to dashboard.	Complete the resolution and return to the dashboard.	RESOLVE_CORRECT +2; contradictory unsafe final -4; scenario capped 0-10.

End-state Official portal mock shows no refund and the message is reported.	Concise learner feedback Unexpected refunds combine authority and reward. Verify directly in the official portal.
--	--

Rating-Task Recruiter

Platform SMS	Difficulty Medium	Disposition Malicious	Attack / case family Task/job scam	Primary trigger Greed + commitment
-----------------	----------------------	--------------------------	---------------------------------------	---------------------------------------

Stage	Learner flow + synthetic content	UI to build	Expected safe behavior	Scoring event
1 Event	Dashboard notification: 'Remote role: earn INR 4,000/day rating products. Reply YES for instant joining.' The SMS badge increments and the toast routes into the scenario.	Dashboard toast, SMS tile, unread badge, sender/header preview and received time.	Notice the source and time; open the full item before acting. Do not reply from the preview.	NOTIFY_SEEN +0; open latency and route logged.
2 Open	Open the new recruiter thread. Context presented: An unsolicited recruiter offers high pay for product ratings and quickly asks for a deposit to unlock tasks.	Native-style conversation list and thread with sender header/number, timestamps and link/MMS preview.	Read the full thread/message and prior context before choosing any action.	ITEM_OPEN +0; premature reply/action -1; dwell time logged.
3 Inspect	Open details and examine unexpected contact, unrealistic earnings, no interview and personal number	Conversation details sheet showing full number/header, prior thread, SIM label and report-junk controls.	Check this decision signal: Legitimate employers do not hire by random text or require payment to release work or wages.	INSPECT_CONTEXT +2; inspection path and time logged.
4 Branch	The interaction advances to a task dashboard showing bonus earnings followed by a recharge demand	Offline safe browser, call-confirmation sheet, MMS/QR inspector or synthetic payment request panel.	Do not reply with personal data, deposit or recruit others. Use Back/Close or safe preview only; no secret, payment, install or data release.	SAFE_PIVOT +3; risky open/reply -3; secret/payment/install/data release -8.
5 Verify	The learner opens Verify / More actions. Verification route: verify the employer through a separately found corporate site and known vacancy channel	Conversation action sheet with block/report junk plus independent official-app, statement or known-number verification overlay.	Verify independently: verify the employer through a separately found corporate site and known vacancy channel Then use the platform report/block path or the unit reporting route.	TRUSTED_VERIFY +3; report-only without checking +1; verification through message +0.
6 Resolve	Final expected resolution: stop; report junk/block; do not pay to earn	Outcome card, concise feedback, warning-sign chips, event summary and Return to dashboard.	Complete the resolution and return to the dashboard.	RESOLVE_CORRECT +2; contradictory unsafe final -4; scenario capped 0-10.

End-state Synthetic earnings are shown as fake and no deposit is made.	Concise learner feedback Unexpected easy-income offers often become deposit scams. Research the employer and never pay to work.
---	--

Emergency Recall Location Link

Platform SMS	Difficulty Medium	Disposition Malicious	Attack / case family Military smishing / location collection	Primary trigger Authority + urgency FICTIONAL MILITARY CONTEXT
Stage	Learner flow + synthetic content	UI to build	Expected safe behavior	Scoring event
1 Event	Dashboard notification: 'UNIT ALERT: Immediate recall. Confirm live location and ETA at recall.training.example.' The SMS badge increments and the toast routes into the scenario.	Dashboard toast, SMS tile, unread badge, sender/header preview and received time.	Notice the source and time; open the full item before acting. Do not reply from the preview.	NOTIFY_SEEN +0; open latency and route logged.
2 Open	Open the urgent administrative-looking thread. Context presented: A spoofed sender announces an emergency recall and asks the learner to confirm current location via a link.	Native-style conversation list and thread with sender header/number, timestamps and link/MMS preview.	Read the full thread/message and prior context before choosing any action.	ITEM_OPEN +0; premature reply/action -1; dwell time logged.
3 Inspect	Open details and examine sender/header, absent authentication code, public link and request for live location	Conversation details sheet showing full number/header, prior thread, SIM label and report-junk controls.	Check this decision signal: Recall and location reporting must use approved channels; a public SMS link cannot establish authority.	INSPECT_CONTEXT +2; inspection path and time logged.
4 Branch	The interaction advances to a synthetic map form asking location, route and service number	Offline safe browser, call-confirmation sheet, MMS/QR inspector or synthetic payment request panel.	Do not submit location, ETA, route or identity data. Use Back/Close or safe preview only; no secret, payment, install or data release.	SAFE_PIVOT +3; risky open/reply -3; secret/payment/install/data release -8.
5 Verify	The learner opens Verify / More actions. Verification route: contact the duty office through the approved directory and check the official recall channel	Conversation action sheet with block/report junk plus independent official-app, statement or known-number verification overlay.	Verify independently: contact the duty office through the approved directory and check the official recall channel Then use the platform report/block path or the unit reporting route.	TRUSTED_VERIFY +3; report-only without checking +1; verification through message +0.
6 Resolve	Final expected resolution: submit nothing; report through unit security; block the sender	Outcome card plus 250-character rationale box, warning-sign chips, event summary and Return to dashboard.	Complete the resolution and return to the dashboard. Add a one-line reason without sensitive data.	RESOLVE_CORRECT +2; contradictory unsafe final -4; scenario capped 0-10.
End-state No location is shared and the duty office confirms no recall.		Concise learner feedback Urgent military wording can be spoofed. Verify through the approved recall process before disclosing location.		

Canteen Subsidy MMS QR

Platform SMS	Difficulty Medium	Disposition Malicious	Attack / case family Military-themed QR smishing	Primary trigger Familiarity + scarcity FICTIONAL MILITARY CONTEXT
-----------------	----------------------	--------------------------	---	--

Stage	Learner flow + synthetic content	UI to build	Expected safe behavior	Scoring event
1 Event	Dashboard notification: 'Service family subsidy - scan today to activate INR 2,000 benefit.' The SMS badge increments and the toast routes into the scenario.	Dashboard toast, SMS tile, unread badge, sender/header preview and received time.	Notice the source and time; open the full item before acting. Do not reply from the preview.	NOTIFY_SEEN +0; open latency and route logged.
2 Open	Open the MMS thread and poster image. Context presented: An MMS image offers a limited canteen subsidy and hides the destination in a QR code.	Native-style conversation list and thread with sender header/number, timestamps and link/MMS preview.	Read the full thread/message and prior context before choosing any action.	ITEM_OPEN +0; premature reply/action -1; dwell time logged.
3 Inspect	Open details and examine unknown number, generic eligibility, expiry pressure and QR target	Conversation details sheet showing full number/header, prior thread, SIM label and report-junk controls.	Check this decision signal: Benefits are not activated by an unsolicited QR that requests service and payment data.	INSPECT_CONTEXT +2; inspection path and time logged.
4 Branch	The interaction advances to the QR inspector and synthetic eligibility form	Offline safe browser, call-confirmation sheet, MMS/QR inspector or synthetic payment request panel.	Do not open the target, enter service/family data or pay activation. Use Back/Close or safe preview only; no secret, payment, install or data release.	SAFE_PIVOT +3; risky open/reply -3; secret/payment/install/data release -8.
5 Verify	The learner opens Verify / More actions. Verification route: check the known canteen/welfare portal or directory	Conversation action sheet with block/report junk plus independent official-app, statement or known-number verification overlay.	Verify independently: check the known canteen/welfare portal or directory Then use the platform report/block path or the unit reporting route.	TRUSTED_VERIFY +3; report-only without checking +1; verification through message +0.
6 Resolve	Final expected resolution: close; report junk and unit-themed impersonation; do not forward	Outcome card, concise feedback, warning-sign chips, event summary and Return to dashboard.	Complete the resolution and return to the dashboard.	RESOLVE_CORRECT +2; contradictory unsafe final -4; scenario capped 0-10.

End-state QR target is blocked and no data is entered.	Concise learner feedback A familiar military theme can disguise a phishing route. Verify benefits in approved channels.
---	--

Learner-Initiated Login Code

Platform SMS	Difficulty Medium	Disposition Legitimate	Attack / case family Legitimate OTP / security code	Primary trigger Routine
-----------------	----------------------	---------------------------	--	----------------------------

Stage	Learner flow + synthetic content	UI to build	Expected safe behavior	Scoring event
1 Event	Dashboard notification: 'Your TRAINING PORTAL code is 482193. Do not share it. Expires in 5 minutes.' The SMS badge increments and the toast routes into the scenario.	Dashboard toast, SMS tile, unread badge, sender/header preview and received time.	Notice the source and time; open the full item before acting. Do not reply from the preview.	NOTIFY_SEEN +0; open latency and route logged.
2 Open	Open the established security-code thread. Context presented: The learner has just initiated a login in the synthetic official app and receives the matching one-time code.	Native-style conversation list and thread with sender header/number, timestamps and link/MMS preview.	Read the full thread/message and prior context before choosing any action.	ITEM_OPEN +0; premature reply/action -1; dwell time logged.
3 Inspect	Open details and examine service name, timing, no links, warning text and matching login session	Conversation details sheet showing full number/header, prior thread, SIM label and report-junk controls.	Check this decision signal: The code is expected and should be entered only into the session the learner initiated, never sent to another person.	INSPECT_CONTEXT +2; inspection path and time logged.
4 Branch	The interaction advances to the already-open official-app code field with matching session ID	Offline safe browser, call-confirmation sheet, MMS/QR inspector or synthetic payment request panel.	Use the normal in-app path only after the details match the known context. Do not switch to an untrusted channel.	CORRECT_USE +3; needless reject/ignore -2; unsafe external action -4.
5 Verify	The learner opens Verify / More actions. Verification route: compare the service/session in the official app and SMS; no outside contact is needed	Conversation action sheet with block/report junk plus independent official-app, statement or known-number verification overlay.	Verify independently: compare the service/session in the official app and SMS; no outside contact is needed If it matches, continue; do not report or block a legitimate sender.	TRUSTED_VERIFY +3; false report/block -4; verification through message +0.
6 Resolve	Final expected resolution: enter the code only in the matching official-app mock; retain no screenshot; do not report the SMS	Outcome card plus 250-character rationale box, warning-sign chips, event summary and Return to dashboard.	Complete the resolution and return to the dashboard. Add a one-line reason without sensitive data.	RESOLVE_CORRECT +2; contradictory unsafe final -4; scenario capped 0-10.

End-state Local login completes and the code expires; no other device is authorized.	Concise learner feedback An OTP can be legitimate when you initiated the matching action. Use it only in that session and never share it.
---	--

New-Phone Family Emergency

Platform SMS	Difficulty Medium	Disposition Malicious	Attack / case family Known-person impersonation / emergency payment	Primary trigger Empathy + urgency
-----------------	----------------------	--------------------------	--	--------------------------------------

Stage	Learner flow + synthetic content	UI to build	Expected safe behavior	Scoring event
1 Event	Dashboard notification: 'Mum, this is my new number. Phone broke. Please send INR 15,000 to the hospital now.' The SMS badge increments and the toast routes into the scenario.	Dashboard toast, SMS tile, unread badge, sender/header preview and received time.	Notice the source and time; open the full item before acting. Do not reply from the preview.	NOTIFY_SEEN +0; open latency and route logged.
2 Open	Open the unsaved emergency thread. Context presented: An unknown number claims to be a family member with a broken phone and requests immediate payment.	Native-style conversation list and thread with sender header/number, timestamps and link/MMS preview.	Read the full thread/message and prior context before choosing any action.	ITEM_OPEN +0; premature reply/action -1; dwell time logged.
3 Inspect	Open details and examine unknown number, generic relationship cue, urgent payment and third-party payee	Conversation details sheet showing full number/header, prior thread, SIM label and report-junk controls.	Check this decision signal: The relationship claim is unverified and the payment recipient does not match the supposed family member.	INSPECT_CONTEXT +2; inspection path and time logged.
4 Branch	The interaction advances to a payment request plus quick reply 'Done'	Offline safe browser, call-confirmation sheet, MMS/QR inspector or synthetic payment request panel.	Do not send money or verify only in the new-number thread. Use Back/Close or safe preview only; no secret, payment, install or data release.	SAFE_PIVOT +3; risky open/reply -3; secret/payment/install/data release -8.
5 Verify	The learner opens Verify / More actions. Verification route: call the family member's known old number or another trusted family contact	Conversation action sheet with block/report junk plus independent official-app, statement or known-number verification overlay.	Verify independently: call the family member's known old number or another trusted family contact Then use the platform report/block path or the unit reporting route.	TRUSTED_VERIFY +3; report-only without checking +1; verification through message +0.
6 Resolve	Final expected resolution: decline; report junk/block after impersonation is confirmed	Outcome card, concise feedback, warning-sign chips, event summary and Return to dashboard.	Complete the resolution and return to the dashboard.	RESOLVE_CORRECT +2; contradictory unsafe final -4; scenario capped 0-10.

End-state Known contact confirms no emergency; no payment occurs.	Concise learner feedback New-number emergencies demand independent verification using contact details you already trust.
--	---

Bank Header Thread Hijack

Platform SMS	Difficulty Hard	Disposition Malicious	Attack / case family Sender-ID spoofing / callback phishing	Primary trigger Trust + fear
-----------------	--------------------	--------------------------	--	---------------------------------

Stage	Learner flow + synthetic content	UI to build	Expected safe behavior	Scoring event
1 Event	Dashboard notification: 'SECURITY HOLD: Unusual transfer. Call 00000 41818 in 10 minutes to prevent account freeze.' The SMS badge increments and the toast routes into the scenario.	Dashboard toast, SMS tile, unread badge, sender/header preview and received time.	Notice the source and time; open the full item before acting. Do not reply from the preview.	NOTIFY_SEEN +0; open latency and route logged.
2 Open	Open the established-looking bank thread. Context presented: A malicious message appears inside a realistic existing bank-alert thread and asks the learner to call a number.	Native-style conversation list and thread with sender header/number, timestamps and link/MMS preview.	Read the full thread/message and prior context before choosing any action.	ITEM_OPEN +0; premature reply/action -1; dwell time logged.
3 Inspect	Open details and examine message wording, supplied number, absence of transaction detail and official-app status	Conversation details sheet showing full number/header, prior thread, SIM label and report-junk controls.	Check this decision signal: Thread placement or sender ID is not proof; the callback number is controlled by the message.	INSPECT_CONTEXT +2; inspection path and time logged.
4 Branch	The interaction advances to a call-confirmation sheet leading to a synthetic operator requesting card/PIN/OTP	Offline safe browser, call-confirmation sheet, MMS/QR inspector or synthetic payment request panel.	Do not call the number or disclose financial secrets. Use Back/Close or safe preview only; no secret, payment, install or data release.	SAFE_PIVOT +3; risky open/reply -3; secret/payment/install/data release -8.
5 Verify	The learner opens Verify / More actions. Verification route: open the known banking app and call the number printed on the simulated card	Conversation action sheet with block/report junk plus independent official-app, statement or known-number verification overlay.	Verify independently: open the known banking app and call the number printed on the simulated card Then use the platform report/block path or the unit reporting route.	TRUSTED_VERIFY +3; report-only without checking +1; verification through message +0.
6 Resolve	Final expected resolution: do not call the message number; report junk if confirmed; secure the account through known channels	Outcome card plus 250-character rationale box, warning-sign chips, event summary and Return to dashboard.	Complete the resolution and return to the dashboard. Add a one-line reason without sensitive data.	RESOLVE_CORRECT +2; contradictory unsafe final -4; scenario capped 0-10.

End-state Official app shows no hold and the fake callback is blocked.	Concise learner feedback Spoofed sender IDs can make texts appear in trusted threads. Verify alerts through the official app or known number.
---	--

Network Survey Requests IMEI

Platform SMS	Difficulty Hard	Disposition Malicious	Attack / case family Military-targeted technical pretext / device profiling	Primary trigger Authority + helpfulness FICTIONAL MILITARY CONTEXT
-----------------	--------------------	--------------------------	--	---

Stage	Learner flow + synthetic content	UI to build	Expected safe behavior	Scoring event
1 Event	Dashboard notification: 'Priority network survey for Unit Falcon area. Reply IMEI + location + device model.' The SMS badge increments and the toast routes into the scenario.	Dashboard toast, SMS tile, unread badge, sender/header preview and received time.	Notice the source and time; open the full item before acting. Do not reply from the preview.	NOTIFY_SEEN +0; open latency and route logged.
2 Open	Open the technical survey thread. Context presented: A telecom-style message says a coverage survey for a base requires IMEI, live location and device model.	Native-style conversation list and thread with sender header/number, timestamps and link/MMS preview.	Read the full thread/message and prior context before choosing any action.	ITEM_OPEN +0; premature reply/action -1; dwell time logged.
3 Inspect	Open details and examine unknown sender, targeted military reference, excessive device/location data and reply request	Conversation details sheet showing full number/header, prior thread, SIM label and report-junk controls.	Check this decision signal: A coverage survey does not justify sending unique device identifiers or protected location by SMS.	INSPECT_CONTEXT +2; inspection path and time logged.
4 Branch	The interaction advances to a structured reply form with IMEI, GPS and device fields	Offline safe browser, call-confirmation sheet, MMS/QR inspector or synthetic payment request panel.	Do not submit device identifiers, location or unit association. Use Back/Close or safe preview only; no secret, payment, install or data release.	SAFE_PIVOT +3; risky open/reply -3; secret/payment/install/data release -8.
5 Verify	The learner opens Verify / More actions. Verification route: contact approved communications/IT staff and the carrier through known channels	Conversation action sheet with block/report junk plus independent official-app, statement or known-number verification overlay.	Verify independently: contact approved communications/IT staff and the carrier through known channels Then use the platform report/block path or the unit reporting route.	TRUSTED_VERIFY +3; report-only without checking +1; verification through message +0.
6 Resolve	Final expected resolution: send nothing; report the targeted solicitation through unit security; block	Outcome card plus 250-character rationale box, warning-sign chips, event summary and Return to dashboard.	Complete the resolution and return to the dashboard. Add a one-line reason without sensitive data.	RESOLVE_CORRECT +2; contradictory unsafe final -4; scenario capped 0-10.

End-state No device/location data is released and the solicitation is logged.	Concise learner feedback Technical language can conceal reconnaissance. Protect device identifiers, location and unit association.
--	---

Parcel Text Plus Callback

Platform SMS	Difficulty Hard	Disposition Malicious	Attack / case family Multi-stage parcel / callback / remote access scam	Primary trigger Curiosity + urgency
-----------------	--------------------	--------------------------	--	--

Stage	Learner flow + synthetic content	UI to build	Expected safe behavior	Scoring event
1 Event	Dashboard notification: 'Parcel address failed. Later: Payment fraud detected - call support immediately.' The SMS badge increments and the toast routes into the scenario.	Dashboard toast, SMS tile, unread badge, sender/header preview and received time.	Notice the source and time; open the full item before acting. Do not reply from the preview.	NOTIFY_SEEN +0; open latency and route logged.
2 Open	Open the two-stage parcel thread. Context presented: A parcel text first requests address confirmation; a follow-up says fraud was detected and gives a support number.	Native-style conversation list and thread with sender header/number, timestamps and link/MMS preview.	Read the full thread/message and prior context before choosing any action.	ITEM_OPEN +0; premature reply/action -1; dwell time logged.
3 Inspect	Open details and examine unknown parcel, link/callback controlled by sender, escalating story and requested tools	Conversation details sheet showing full number/header, prior thread, SIM label and report-junk controls.	Check this decision signal: The escalation is designed to move the learner from a small task to a high-pressure support scam.	INSPECT_CONTEXT +2; inspection path and time logged.
4 Branch	The interaction advances to a call mock where 'support' asks for screen share and a remote-help app	Offline safe browser, call-confirmation sheet, MMS/QR inspector or synthetic payment request panel.	Do not call, share screen, install support software or disclose OTP. Use Back/Close or safe preview only; no secret, payment, install or data release.	SAFE_PIVOT +3; risky open/reply -3; secret/payment/install/data release -8.
5 Verify	The learner opens Verify / More actions. Verification route: check the known courier account and bank statement independently	Conversation action sheet with block/report junk plus independent official-app, statement or known-number verification overlay.	Verify independently: check the known courier account and bank statement independently Then use the platform report/block path or the unit reporting route.	TRUSTED_VERIFY +3; report-only without checking +1; verification through message +0.
6 Resolve	Final expected resolution: do not engage; report junk/block; contact approved support only if a real issue exists	Outcome card, concise feedback, warning-sign chips, event summary and Return to dashboard.	Complete the resolution and return to the dashboard.	RESOLVE_CORRECT +2; contradictory unsafe final -4; scenario capped 0-10.

End-state Both parcel and fraud claims fail verification; permissions remain denied.	Concise learner feedback Multi-stage scams change the story after engagement. Stop, reset and verify each claim independently.
---	---

S21

Matching New-Login Alert

Platform SMS	Difficulty Hard	Disposition Legitimate	Attack / case family Legitimate security alert	Primary trigger Fear + routine
-----------------	--------------------	---------------------------	---	-----------------------------------

Stage	Learner flow + synthetic content	UI to build	Expected safe behavior	Scoring event
1 Event	Dashboard notification: 'TRAINING PORTAL login on DEV-204 at 14:22. If this was you, no action is needed.' The SMS badge increments and the toast routes into the scenario.	Dashboard toast, SMS tile, unread badge, sender/header preview and received time.	Notice the source and time; open the full item before acting. Do not reply from the preview.	NOTIFY_SEEN +0; open latency and route logged.
2 Open	Open the established security-alert thread. Context presented: A registered security alert matches a login the learner just completed on a synthetic issued device.	Native-style conversation list and thread with sender header/number, timestamps and link/MMS preview.	Read the full thread/message and prior context before choosing any action.	ITEM_OPEN +0; premature reply/action -1; dwell time logged.
3 Inspect	Open details and examine device ID, exact time, no link/callback and matching active session	Conversation details sheet showing full number/header, prior thread, SIM label and report-junk controls.	Check this decision signal: The alert matches the learner's action and gives a clear no-action state without requesting secrets.	INSPECT_CONTEXT +2; inspection path and time logged.
4 Branch	The interaction advances to the official-app session list showing DEV-204 and End session	Offline safe browser, call-confirmation sheet, MMS/QR inspector or synthetic payment request panel.	Use the normal in-app path only after the details match the known context. Do not switch to an untrusted channel.	CORRECT_USE +3; needless reject/ignore -2; unsafe external action -4.
5 Verify	The learner opens Verify / More actions. Verification route: compare with the session list opened directly in the official app	Conversation action sheet with block/report junk plus independent official-app, statement or known-number verification overlay.	Verify independently: compare with the session list opened directly in the official app. If it matches, continue; do not report or block a legitimate sender.	TRUSTED_VERIFY +3; false report/block -4; verification through message +0.
6 Resolve	Final expected resolution: mark reviewed and keep the session if recognized; do not report/block	Outcome card plus 250-character rationale box, warning-sign chips, event summary and Return to dashboard.	Complete the resolution and return to the dashboard. Add a one-line reason without sensitive data.	RESOLVE_CORRECT +2; contradictory unsafe final -4; scenario capped 0-10.

End-state Recognized session remains active and the alert is marked reviewed.	Concise learner feedback A matching no-action security alert is legitimate. Verify in the account, then avoid an unnecessary incident report.
--	--

S22

Synthetic Voice-Mail Link

Platform SMS	Difficulty Hard	Disposition Malicious	Attack / case family Voice phishing / link lure	Primary trigger Authority + curiosity FICTIONAL MILITARY CONTEXT
-----------------	--------------------	--------------------------	--	---

Stage	Learner flow + synthetic content	UI to build	Expected safe behavior	Scoring event
1 Event	Dashboard notification: 'Secure Voice: Col. Dev left 1 urgent message. Listen before 18:00.' The SMS badge increments and the toast routes into the scenario.	Dashboard toast, SMS tile, unread badge, sender/header preview and received time.	Notice the source and time; open the full item before acting. Do not reply from the preview.	NOTIFY_SEEN +0; open latency and route logged.
2 Open	Open the voice-notification thread. Context presented: A text claims a senior left a secure voice message accessible only through a short link.	Native-style conversation list and thread with sender header/number, timestamps and link/MMS preview.	Read the full thread/message and prior context before choosing any action.	ITEM_OPEN +0; premature reply/action -1; dwell time logged.
3 Inspect	Open details and examine unknown service, link target, sender identity and artificial expiry	Conversation details sheet showing full number/header, prior thread, SIM label and report-junk controls.	Check this decision signal: An unapproved voice service and link cannot authenticate the caller or justify a new login.	INSPECT_CONTEXT +2; inspection path and time logged.
4 Branch	The interaction advances to a fake voice portal that asks for mail credentials, then plays a synthetic instruction	Offline safe browser, call-confirmation sheet, MMS/QR inspector or synthetic payment request panel.	Do not enter credentials or act on the voice instruction. Use Back/Close or safe preview only; no secret, payment, install or data release.	SAFE_PIVOT +3; risky open/reply -3; secret/payment/install/data release -8.
5 Verify	The learner opens Verify / More actions. Verification route: contact the senior/duty office through known channels and check approved messaging systems	Conversation action sheet with block/report junk plus independent official-app, statement or known-number verification overlay.	Verify independently: contact the senior/duty office through known channels and check approved messaging systems Then use the platform report/block path or the unit reporting route.	TRUSTED_VERIFY +3; report-only without checking +1; verification through message +0.
6 Resolve	Final expected resolution: close; report junk and impersonation; do not act on the audio	Outcome card, concise feedback, warning-sign chips, event summary and Return to dashboard.	Complete the resolution and return to the dashboard.	RESOLVE_CORRECT +2; contradictory unsafe final -4; scenario capped 0-10.

End-state Senior confirms no message; credentials and actions remain protected.	Concise learner feedback A voice recording can be fabricated. Verify the sender and use approved systems before acting.
--	--

UPI Refund Collect Request

Platform SMS	Difficulty Hard	Disposition Malicious	Attack / case family Payment-request reversal scam	Primary trigger Greed + confusion
-----------------	--------------------	--------------------------	---	--------------------------------------

Stage	Learner flow + synthetic content	UI to build	Expected safe behavior	Scoring event
1 Event	Dashboard notification: 'Refund INR 2,499 ready. Accept collect request and enter UPI PIN to receive.' The SMS badge increments and the toast routes into the scenario.	Dashboard toast, SMS tile, unread badge, sender/header preview and received time.	Notice the source and time; open the full item before acting. Do not reply from the preview.	NOTIFY_SEEN +0; open latency and route logged.
2 Open	Open the merchant text and payment notification. Context presented: A merchant-themed text says a refund requires accepting a UPI collect request and entering the payment PIN.	Native-style conversation list and thread with sender header/number, timestamps and link/MMS preview.	Read the full thread/message and prior context before choosing any action.	ITEM_OPEN +0; premature reply/action -1; dwell time logged.
3 Inspect	Open details and examine unrecognized order, collect direction, payee name and request for payment PIN	Conversation details sheet showing full number/header, prior thread, SIM label and report-junk controls.	Check this decision signal: A collect request sends money; receiving a refund does not require authorizing a debit with a PIN.	INSPECT_CONTEXT +2; inspection path and time logged.
4 Branch	The interaction advances to a synthetic UPI collect screen clearly showing PAY and amount	Offline safe browser, call-confirmation sheet, MMS/QR inspector or synthetic payment request panel.	Do not approve the collect request or enter the payment PIN. Use Back/Close or safe preview only; no secret, payment, install or data release.	SAFE_PIVOT +3; risky open/reply -3; secret/payment/install/data release -8.
5 Verify	The learner opens Verify / More actions. Verification route: check the original merchant order/refund in the official app and bank statement	Conversation action sheet with block/report junk plus independent official-app, statement or known-number verification overlay.	Verify independently: check the original merchant order/refund in the official app and bank statement Then use the platform report/block path or the unit reporting route.	TRUSTED_VERIFY +3; report-only without checking +1; verification through message +0.
6 Resolve	Final expected resolution: decline the collect request; report junk/block; contact the merchant through known support if needed	Outcome card plus 250-character rationale box, warning-sign chips, event summary and Return to dashboard.	Complete the resolution and return to the dashboard. Add a one-line reason without sensitive data.	RESOLVE_CORRECT +2; contradictory unsafe final -4; scenario capped 0-10.

End-state Collect request is declined and account balance is unchanged.	Concise learner feedback Read the payment direction, not the story. A refund should not require approving a collect request or entering a PIN.
--	---

Fake Cybercrime Case Fee

Platform SMS	Difficulty Hard	Disposition Malicious	Attack / case family Government/I4C impersonation / digital arrest	Primary trigger Fear + authority
-----------------	--------------------	--------------------------	---	-------------------------------------

Stage	Learner flow + synthetic content	UI to build	Expected safe behavior	Scoring event
1 Event	Dashboard notification: 'CYBER CASE NOTICE: Pay verification fee to avoid warrant. Case closes today.' The SMS badge increments and the toast routes into the scenario.	Dashboard toast, SMS tile, unread badge, sender/header preview and received time.	Notice the source and time; open the full item before acting. Do not reply from the preview.	NOTIFY_SEEN +0; open latency and route logged.
2 Open	Open the government-themed thread. Context presented: A text claims a cybercrime complaint names the learner and demands a case-clearance fee.	Native-style conversation list and thread with sender header/number, timestamps and link/MMS preview.	Read the full thread/message and prior context before choosing any action.	ITEM_OPEN +0; premature reply/action -1; dwell time logged.
3 Inspect	Open details and examine sender/header, payment demand, secrecy, case link and official reporting guidance	Conversation details sheet showing full number/header, prior thread, SIM label and report-junk controls.	Check this decision signal: Cybercrime authorities do not clear warrants through an SMS payment; the pressure and fee are fraudulent.	INSPECT_CONTEXT +2; inspection path and time logged.
4 Branch	The interaction advances to a fake case portal and payment timer	Offline safe browser, call-confirmation sheet, MMS/QR inspector or synthetic payment request panel.	Do not pay, upload identity/bank data or call the supplied officer. Use Back/Close or safe preview only; no secret, payment, install or data release.	SAFE_PIVOT +3; risky open/reply -3; secret/payment/install/data release -8.
5 Verify	The learner opens Verify / More actions. Verification route: use independently known official/unit legal/security contacts and the official portal only	Conversation action sheet with block/report junk plus independent official-app, statement or known-number verification overlay.	Verify independently: use independently known official/unit legal/security contacts and the official portal only Then use the platform report/block path or the unit reporting route.	TRUSTED_VERIFY +3; report-only without checking +1; verification through message +0.
6 Resolve	Final expected resolution: do not pay/reply; preserve; report/block through approved channels	Outcome card, concise feedback, warning-sign chips, event summary and Return to dashboard.	Complete the resolution and return to the dashboard.	RESOLVE_CORRECT +2; contradictory unsafe final -4; scenario capped 0-10.

End-state Case number fails verification and payment stays at zero.	Concise learner feedback No legitimate case is settled by instant text payment. Verify through official contacts and report impersonation.
--	---

FASTag Update APK

Platform SMS	Difficulty Hard	Disposition Malicious	Attack / case family Road-toll impersonation / malicious app	Primary trigger Convenience + urgency
-----------------	--------------------	--------------------------	---	--

Stage	Learner flow + synthetic content	UI to build	Expected safe behavior	Scoring event
1 Event	Dashboard notification: 'FASTag KYC expiring. Install verification app now to avoid deactivation.' The SMS badge increments and the toast routes into the scenario.	Dashboard toast, SMS tile, unread badge, sender/header preview and received time.	Notice the source and time; open the full item before acting. Do not reply from the preview.	NOTIFY_SEEN +0; open latency and route logged.
2 Open	Open the toll-service thread and APK link. Context presented: A text says a toll tag will stop working unless an attached Android app is installed for verification.	Native-style conversation list and thread with sender header/number, timestamps and link/MMS preview.	Read the full thread/message and prior context before choosing any action.	ITEM_OPEN +0; premature reply/action -1; dwell time logged.
3 Inspect	Open details and examine unregistered sender, APK delivery, broad permission need and short deadline	Conversation details sheet showing full number/header, prior thread, SIM label and report-junk controls.	Check this decision signal: Financial/toll KYC should be completed through the official bank/app; an SMS-delivered APK is unsafe.	INSPECT_CONTEXT +2; inspection path and time logged.
4 Branch	The interaction advances to a simulated APK installer requesting SMS, accessibility and screen-capture permissions	Offline safe browser, call-confirmation sheet, MMS/QR inspector or synthetic payment request panel.	Do not install or grant any permission. Use Back/Close or safe preview only; no secret, payment, install or data release.	SAFE_PIVOT +3; risky open/reply -3; secret/payment/install/data release -8.
5 Verify	The learner opens Verify / More actions. Verification route: open the known issuer/bank app or call its known support number	Conversation action sheet with block/report junk plus independent official-app, statement or known-number verification overlay.	Verify independently: open the known issuer/bank app or call its known support number Then use the platform report/block path or the unit reporting route.	TRUSTED_VERIFY +3; report-only without checking +1; verification through message +0.
6 Resolve	Final expected resolution: cancel installation; report junk/block; verify tag status independently	Outcome card plus 250-character rationale box, warning-sign chips, event summary and Return to dashboard.	Complete the resolution and return to the dashboard. Add a one-line reason without sensitive data.	RESOLVE_CORRECT +2; contradictory unsafe final -4; scenario capped 0-10.

End-state No app is installed and the official mock shows the tag active.	Concise learner feedback Never install financial-service apps from message links. Use the official store or issuer app and deny unexpected permissions.
--	--

7. Results, Feedback and Progress Comparison

Results element	Requirement
Score	Large 0-100 total plus 10 scenario points. Avoid pass/fail labels unless the instructor configures a local policy.
Behavior breakdown	Platform, attack family, trigger and action-stage results; distinguish missed threat from false positive.
Path replay	Compact timeline of inspect, branch, verify and resolve events; never replay or display real user secrets.
Feedback	For each case: disposition, observed cues, safe response, likely impact and one habit. Keep blame-free language.
Progress	Compare current and previous attempts only when mode/content version are comparable; show trend and exposure count.
Remediation	Recommend 2-3 targeted practice scenarios from weak families; do not diagnose personality or emotional state.
Exit	Save completed attempt, Return to dashboard, Print/export if authorized, and Logout for the next learner.

Recommended feedback voice
State what the learner did, why it mattered, and what to do next. Example: 'You checked the profile but used the number supplied in the message. Verify with a number already held in the trusted directory, then report the impersonating account.'

8. Authoritative Research Basis

Accessed 02 September 2026. These sources inform the learning model, threat patterns and safe-response guidance; local military policy and approved unit reporting procedures always take precedence.

#	Source	#	Source
1	NIST SP 800-50 Rev. 1 - Building a Cybersecurity and Privacy Learning Program (2024) Open official source	10	I4C - Fake stock-market investment websites/apps advisory (22 April 2024) Open official source
2	NIST TN 2276 - NIST Phish Scale User Guide (2023) Open official source	11	I4C - Fake CAPTCHA-filling jobs advisory (08 April 2025) Open official source
3	CISA - Secure Our World: Recognize and Report Phishing Open official source	12	I4C - WhatsApp Web account-renting scam advisory (15 October 2025) Open official source
4	Google - Avoid and report phishing emails Open official source	13	National Cyber Crime Reporting Portal - Report Suspect and 1930 guidance Open official source
5	Meta/WhatsApp - New WhatsApp Tools and Tips to Beat Messaging Scams (2025) Open official source	14	CERT-In - Cybersecurity awareness booklets Open official source
6	WhatsApp Help Center - Security codes on linked devices Open official source	15	RBI - BE(A)WARE: QR-code scam modus operandi and precautions Open official source
7	Instagram Help Center - Login, recovery and hacked-account guidance Open official source	16	FTC - What are the signs of a scam? (2025) Open official source
8	I4C - Cybercrime advisories index Open official source	17	NSA - Keeping Safe on Social Media Open official source
9	I4C - Advisory on Digital Arrest (06 March 2025) Open official source	18	U.S. Army - Social Media Safety and geotagging Open official source

Indian incident reporting note
For actual civilian financial cyber fraud in India, current official guidance points to immediate reporting via 1930 or cybercrime.gov.in. Inside this application, the first learner action should follow the approved unit reporting chain; the simulation must not transmit a real report.

Appendix A - Scenario Content Authoring Schema

Field	Rule
identity	Stable ID, title, version, platform, owner, review date and active flag.
classification	Difficulty, disposition, attack/case family, primary trigger, military-context flag and legitimate-control flag.
synthetic content	Generated sender, message/thread, reserved link, inert asset IDs and prior context. No copied live victim/adversary content.
six stages	Notification, open/read, inspect, branch, verify/report, resolve/feedback. Each defines UI, choices, next states and events.
scoring	Stable event codes, point delta, per-scenario cap, critical-risk flag and expected final outcome.
feedback	Disposition, warning/confirming signs, impact, preferred action and prevention habit.
quality	Content reviewer, technical reviewer, instructional reviewer, safety check, accessibility check and pilot status.

Definition of done for each new scenario
A fresh learner can complete the safe path; every risky path remains locally contained; the disposition is supported by observable evidence; verification does not leak the answer; points sum correctly; copy is fictional; and feedback teaches one transferable habit.

END OF SPECIFICATION
100 scenarios | 4 simulated platforms | 600 interaction stages