

Lobster Profile Documentation

Generated: 2025-09-15 16:52
Source: Profile-01_PL_AGAT_RHD_OrderInterface_OrderImport_RHDPoland.xml

Workflow

[Open full-size workflow diagram](#)

Detailed Steps

- 1. Trigger**
Event-based HTTP POST to `AGAT/Order` with `application/xml` payload.
- 2. Parse XML**
Read and validate structure.
- 3. Validate Data**
Check required fields and formats.
- 4. Map Fields**
Apply mapping rules (89 pairs).
- 5. Forward / Handoff**
On success, hand off to
`02\_PL\_AGAT\_RHD\_OrderInterface\_StatusResponse\_RHDPoland`.
- 6. Error Handling**
On error, route to `02\_PL\_AGAT\_RHD\_OrderInterface\_StatusResponse\_RHDPoland`.

Profile Purpose

Overview
This profile receives POST requests at AGAT/Order.

Input Data

- Where the data comes from
Requests are sent to the endpoint `AGAT/Order`.
- How the data is sent
The system expects an HTTP POST request with the format application/xml.
- What must be included
Each request contains a single order message that follows the agreed XML structure and includes the required fields (for example: order number, customer, items, quantities, and dates).

Mapping

Source Structure	Target Structure	Description	How it's calculated
OrderNumber	OrderNumber	Unique customer order number	set display column(a,b,c) - linked field - constant '1'

Source Structure	Target Structure	Description	How it's calculated
			• constant
Remark	Remark	Remark on order level	1:1
AmountValue-2	AmountValue#2	The value of an amount with two decimal digits. An point (".") has to be used as decimal separator, comma is not allowed.	1:1
AmountValue-3	AmountValue#3	The value of an amount with two decimal digits. An point (".") has to be used as decimal separator, comma is not allowed.	1:1
FreightTerm	FreightTerm	Specify the freight terms for this order	1:1
Salutation-1	Salutation#1	Salutation towards person or company	1:1
ServiceType	ServiceType	Type of service.	1:1
SequenceNumber	SequenceNumber	If the order is updated the system can verify via the sequence number, that all previous updates have been received. Provided by sender.	1:1
Street	Street	Street	1:1
DesiredDate	DesiredDate	Desired date for delivery/ pickup at customers address.	1:1
ReturnOrder-1_choice_1_val	ReturnOrder#1_choice_1_val	Goods should be picked up at customers home and returned to RHD location.	1:1
AmountValue-1	AmountValue#1	The value of an amount	1:1

Source Structure	Target Structure	Description	How it's calculated
		with two decimal digits. An point (".") has to be used as decimal separator, comma is not allowed.	
Fax-1	Fax#1	Fax number for contacting the person/ company	1:1
PostalCode-1	PostalCode#1	Postal code	1:1
LocationCode	LocationCode	Code of the location.	1:1
PackageQuantity	PackageQuantity	Number of Packages per one Article	1:1
Volume	Volume	Volume of the complete order in cbm	1:1
SenderAbbreviation	SenderAbbreviation	Abbreviation of the sender. This must map to a sender (organisational unit of the client) as listed in the master data at RHD.	1:1
Country	Country	Country of address; ISO-2-Alpha-Country-Code according to ISO 3166	1:1
TransmissionCommand	TransmissionCommand	Specify if the order should be created, updated or canceled	set display column(a,b,c) • linked field • constant '2' • constant
LocationType-2	LocationType#2	The type of the location.	1:1
LocationType-1	LocationType#1	The type of the location.	1:1
HouseNumber	HouseNumber	House number	1:1
Street-1	Street#1	Street	1:1
ArticleWeight	ArticleWeight	Weight of one article within order in kg	1:1
Salutation	Salutation	Salutation towards	1:1

Source Structure	Target Structure	Description	How it's calculated
		person or company	
HouseNumber-1	HouseNumber#1	House number	1:1
ItemBarcode_val	ItemBarcode_val	The unique barcode number of a package of this position. One position can consist of multiple packages. Please specify every barcode.	1:1
Phone3-1	Phone3#1	Additional phone number 3 for contacting the person/ company	1:1
OrderNumber2	OrderNumber2	Additional customer order number	1:1
MessageDate	MessageDate	Date and time of this message	1:1
OrderNumber3	OrderNumber3	Additional customer order number	1:1
FirstName	FirstName	Persons first name	1:1
City-1	City#1	City	1:1
EMail	EMail	Address for contacting the person/ company via email	1:1
AmountValue	AmountValue	The value of an amount with two decimal digits. An point (".") has to be used as decimal separator, comma is not allowed.	1:1
ServiceOnly-1_choice_1_val	ServiceOnly#1_choice_1_val	The order is only about service as furniture assembly or other. No goods will be transported.	1:1
AttributeKey	AttributeKey		1:1

Source Structure	Target Structure	Description	How it's calculated
		The key or description of the attribute.	
Country-1	Country#1	Country of address; ISO-2-Alpha-Country-Code according to ISO 3166	1:1
LatestTime	LatestTime	Latest time for delivery/ pickup at customers address.	1:1
OrderInterfaceVersion_attr	OrderInterfaceVersion_attr		1:1
OrderCreation	OrderCreation	Date and time when the order was placed	1:1
AmountCurrency-2	AmountCurrency#2	Currency of the amount as ISO 4217 three alpha code.	1:1
AttributeValue	AttributeValue	The value/ content of the attribute.	1:1
AmountCurrency-3	AmountCurrency#3	Currency of the amount as ISO 4217 three alpha code.	1:1
Remark-1	Remark#1	Remark on order level	1:1
AmountCurrency-1	AmountCurrency#1	Currency of the amount as ISO 4217 three alpha code.	1:1
Remark-2	Remark#2	Remark on order level	1:1
Name	Name	Persons last name or company name	replace chars(a, list b, list c) - linked field - constant 'ç,ó,ą,ś,ł,ż,ż,ć,ń,Ę,Ó,Ą,Ś,Ł,Ż,Ż,Ć,Ń' - constant 'e,o,a,s,l,z,z,c,n,E,O,A,S,L,Z,Z,C,N'
AdditionalAddressLine-1	AdditionalAddressLine#1	Additional address information	1:1
CustomerNumber	CustomerNumber	Customer number	1:1

Source Structure	Target Structure	Description	How it's calculated
ArticleNumber	ArticleNumber	Number of the article. Usually something like EAN.	1:1
TransportType	TransportType	Type of service	1:1
Client	Client	Abbreviation of the client. This must map to a client as listed in the master data at RHD.	1:1
Phone2-1	Phone2#1	Additional phone number 2 for contacting the person/ company	1:1
City	City	City	1:1
PositionNumber	PositionNumber	Number of the order position	1:1
Weight	Weight	Weight of the complete order in kg	1:1
ArticleDescription	ArticleDescription	Description of the article as it should be printed on the documents.	1:1
PostalCode	PostalCode	Postal code	1:1
InjectionBordereau	InjectionBordereau	The bordereau number or equivalent information for identification of the transport of the goods to the RHD location.	1:1
AdditionalAddressLine	AdditionalAddressLine	Additional address information	1:1
Phone1	Phone1	Phone number 1 for contacting the person/ company	1:1
Phone3	Phone3	Additional phone number 3 for contacting the	1:1

Source Structure	Target Structure	Description	How it's calculated
		person/ company	
Phone2	Phone2	Additional phone number 2 for contacting the person/ company	1:1
Floor-1	Floor#1	Floor information of this address	1:1
FirstName-1	FirstName#1	Persons first name	1:1
Quality	Quality	Stock Type	1:1
LocationCode-1	LocationCode#1	Code of the location.	1:1
FixedDate	FixedDate	Fixed date for delivery/ pickup at customers address already agreed with the customer.	1:1
LocationCode-2	LocationCode#2	Code of the location.	1:1
Phone1-1	Phone1#1	Phone number 1 for contacting the person/ company	1:1
Floor	Floor	Floor information of this address	1:1
InjectionDate	InjectionDate	Date when the goods will be delivered to the RHD location.	1:1
ReferenceOrderNumber	ReferenceOrderNumber	If this order is linked to another order, you can transmit the refernced order number.	1:1
Title	Title	Title of person	1:1
Quantity	Quantity	Quantity of the transport position	1:1
Quantity-1	Quantity#1	Quantity of the transport position	1:1

Source Structure	Target Structure	Description	How it's calculated
Title-1	Title#1	Title of person	1:1
ArticleVolume	ArticleVolume	Volume of one article within order in cbm	1:1
PositionNumber-1	PositionNumber#1	Number of the order position	1:1
EMail-1	EMail#1	Address for contacting the person/ company via email	1:1
AmountCurrency	AmountCurrency	Currency of the amount as ISO 4217 three alpha code.	1:1
EarliestTime	EarliestTime	Earliest time for delivery/ pickup at customers address.	1:1
Name-1	Name#1	Persons last name or company name	replace chars(a, list b, list c) - linked field - constant 'ę,ó,ą,ś,ł,ż,ż,ć,ń,Ę,Ó,Ą,Ś,Ł,Ż,Ż,Ć,Ń' - constant 'e,o,a,s,l,z,z,c,n,E,O,A,S,L,Z,Z,C,N'
Fax	Fax	Fax number for contacting the person/ company	1:1
LocationType	LocationType	The type of the location.	1:1
Hold	Hold	Specify if the order should be held. If set to true, the order will be held in the RHD hub until it's released by setting hold=TRUE.	1:1
MessageId	MessageId	Unique message id, for example the sequence number of the senders system or a timestamp	1:1

Output Data

Success Profile
02_PL_AGAT_RHD_OrderInterface_StatusResponse_RHDPoland
Error Profile
02_PL_AGAT_RHD_OrderInterface_StatusResponse_RHDPoland

Trigger

Profile Type
HTTP

Profile Metadata

Profile Name
01_PL_AGAT_RHD_OrderInterface_OrderImport_RHDPoland
Version
3