

Address APIs User - Guide

FOR NATIONAL ADDRESS DATA API'S PROJECT

National Address integration APIs, June 08 2023



SPL | Saudi Post

Tel + 966-11-2897711

Fax + 966-11-2897711

2929 Rayhanah Bint Zaid - Al Arid
Dist. Riyadh 13337 - 8118

<http://www.splonline.com.sa>
abugmi@splonline.com.sa

Contents

Introduction.....	3
National Address Integration Services (APIs)	3
Address APIs	3
National Address By Short Address:	4

Introduction

This document explains the National Address (NA) APIs and the way it can be consumed by National Address clients. The NA APIs creation mainly derived from our agreement and understanding of the business process and the required data needed to be exchange in order to satisfy the business need for all parties involved in this project.

In this document:

MUST means that the requirement is an absolute mandatory requirement.

MUST NOT means that the requirement absolutely prohibited.

SHOULD means that if the requirement cannot be fulfilled out-of-the-box, some other means of fulfilling the requirement should be devised, e.g. by customization or by integrating with another product that can fulfill the functionality.

MAY means that the requirement is optional.

National Address Integration Services (APIs)

Address APIs

Service Description

National Address By Short Address:

Full National Address By Geocode allows a user to find the detailed National Address including Short Address for a given Geocode. You can decide to use Json or XML as an output format in addition to language of your choice from Arabic or English.

Service URLs

Production Environment:

<https://apina.address.gov.sa/NationalAddress/NationalAddressByShortAddress/NationalAddressByShortAddress?format=json&language=E&page=1&encode=utf8&shortaddress=RRRD3005>

Service Methods

National Address By Short Address *Method(GET)*

Input Parameters

Parameter Name	Mandatory	Data Type	Description
shortaddress	Mandatory	String	Short Address Value. Shall contain 4 alphabetic characters then 4 numeric characters. (the system will automatically ignore case). Example value: RRRD3005
page	Optional	Number	By default each request returns a maximum number of 10 results. If there are a large number of results, in such a case, this page number must be passed along to get the next set of results. Default value is 1.

language	Optional (‘A’ or ‘E’)	String	It is an optional input. Our API can provide response in Arabic or English with Arabic being the default language.
format	Optional (‘json’ or ‘xml’)	String	It’s an optional input. We currently support output for API’s in two formats Json and XML. You will be required to specify in which format you need response, default is Json.
encode	Optional (‘utf8’ or ‘windows1256’)	String	By default response is in windows-1256. Pass "utf8" as input parameter to get utf-8 charset.

Sample Request:

<https://apina.address.gov.sa/NationalAddress/NationalAddressByShortAddress/NationalAddressByShortAddress?format=json&language=E&page=1&encode=utf8&shortaddress=RRRD3005>

Output Parameters

Parameter Name	Mandatory	Data Type	Description
totalSearchResult	Mandatory	String	By default, each search request returns a set of 10 results. In case of multiple results, this attribute will describe the total number of results, so that the developer can pass the page number to get the next set of results accordingly.
Addresses	Mandatory	Object	
BuildingNumber	Mandatory	String	Four digit number which is unique to a building.
Street	Mandatory	String	Name of the street on which building is. Example king abdul aziz road.

District	Mandatory	String	Name of the district in which address falls. Example al amal.
City	Mandatory	String	Name of the city in which address falls. Example Riyadh.
PostCode	Mandatory	String	Four digits numerical Post code / Zip Code.
AdditionalNumber	Mandatory	String	Four digit number.
success	Mandatory	Boolean	This represents success or failure of the request itself (true/false)
statusdescription	Mandatory	String	This provides a description of the current status, validation messages or error messages, if any.

Sample Response 1 (Success case):

```
{
  "Addresses": [
    {
      "BuildingNumber": "3005",
      "PostCode": "13342",
      "AdditionalNumber": "7221",
      "Street": "Sulayman Ibn Murad",
      "District": "Al Arid Dist.",
      "City": "RIYADH"
    }
  ],
  "totalSearchResults": "1",
  "success": true,
  "statusdescription": "SUCCESS"
}
```

Sample Response 2 (Failure case):

```
{
  "Addresses": [],
  "totalSearchResults": "0",
  "success": true,
  "statusdescription": "Invalid Short Address, please try again."
}
```

Error Handling

HTTP Status Code	Scenario	Error Code
400	The short address field is empty when it is required.	
400	Invalid short address format. The required format is XXXXYYYY, where 'X' represents an English letter and 'Y' represents a digit.	
400	The entered short address does not exist in the system.	
401	Access denied due to invalid subscription key.	
403	Total limit for calls under your subscription has been reached.	
404	The endpoint or resource your application is trying to reach doesn't exist.	
500	There was an error on the server while processing the request.	
503	Service unavailable.	