# Baseline Text Sample



SwiftPDF baseline sample — sample-text.pdf

This document is generated deterministically for regression testing.
It contains three paragraphs of plain Latin text laid out on A4 pages.
The engine must preserve this text, its order and its position exactly.

Section 1 — Purpose. The sample exercises structural operations such as merge, split, rotate, watermark and page numbering without any raster content, so output diffs isolate layout behaviour only.

Section 2 — Method. Every baseline run uses identical options and inputs. Results are compared by page geometry, extracted text hash and size.

Section 3 — Footer marker 1/3. End of deterministic content.

# Baseline Text Sample



SwiftPDF baseline sample — sample-text.pdf

This document is generated deterministically for regression testing.
It contains three paragraphs of plain Latin text laid out on A4 pages.
The engine must preserve this text, its order and its position exactly.

Section 1 — Purpose. The sample exercises structural operations such as merge, split, rotate, watermark and page numbering without any raster content, so output diffs isolate layout behaviour only.

Section 2 — Method. Every baseline run uses identical options and inputs. Results are compared by page geometry, extracted text hash and size.

Section 3 — Footer marker 2/3. End of deterministic content.

# Baseline Text Sample



SwiftPDF baseline sample — sample-text.pdf

This document is generated deterministically for regression testing.
It contains three paragraphs of plain Latin text laid out on A4 pages.
The engine must preserve this text, its order and its position exactly.

Section 1 — Purpose. The sample exercises structural operations such as merge, split, rotate, watermark and page numbering without any raster content, so output diffs isolate layout behaviour only.

Section 2 — Method. Every baseline run uses identical options and inputs. Results are compared by page geometry, extracted text hash and size.

Section 3 — Footer marker 3/3. End of deterministic content.

# Baseline Second Sample



SwiftPDF baseline sample — sample-second.pdf

This document is generated deterministically for regression testing.
It contains three paragraphs of plain Latin text laid out on A4 pages.
The engine must preserve this text, its order and its position exactly.

Section 1 — Purpose. The sample exercises structural operations such as merge, split, rotate, watermark and page numbering without any raster content, so output diffs isolate layout behaviour only.

Section 2 — Method. Every baseline run uses identical options and inputs. Results are compared by page geometry, extracted text hash and size.

Section 3 — Footer marker 1/2. End of deterministic content.

# Baseline Second Sample



SwiftPDF baseline sample — sample-second.pdf

This document is generated deterministically for regression testing.
It contains three paragraphs of plain Latin text laid out on A4 pages.
The engine must preserve this text, its order and its position exactly.

Section 1 — Purpose. The sample exercises structural operations such as merge, split, rotate, watermark and page numbering without any raster content, so output diffs isolate layout behaviour only.

Section 2 — Method. Every baseline run uses identical options and inputs. Results are compared by page geometry, extracted text hash and size.

Section 3 — Footer marker 2/2. End of deterministic content.