

Evidencia (tarea semana 3)

Jorge Javier Araya Navarro <jorge@esavara.cr>

Lo presente es la tarea de la semana 3, a presentar en la semana 4.

Provisto esta configuración de Terraform:

```
resource "aws_vpc" "lab-JORGE_JAVIER_ARAYA_NAVARRO" {
  cidr_block = "10.0.0.0/16"
}
```

Ejecuto terraform init, terraform plan y luego terraform apply:

```
laboratorio-cenfotec-terraform/tareas/semana 3 on master (c02bedf) [!?] via default via impure (nix-shell)
  terraform init
Initializing the backend...
Initializing provider plugins...
- Finding latest version of hashicorp/aws...
- Installing hashicorp/aws v6.37.0...
- Installed hashicorp/aws v6.37.0 (signed by HashiCorp)
Terraform has created a lock file .terraform.lock.hcl to record the provider
selections it made above. Include this file in your version control repository
so that Terraform can guarantee to make the same selections by default when
you run "terraform init" in the future.
```

Terraform has been successfully initialized!

You may now begin working with Terraform. Try running "terraform plan" to see any changes that are required for your infrastructure. All Terraform commands should now work.

If you ever set or change modules or backend configuration for Terraform, rerun this command to reinitialize your working directory. If you forget, other commands will detect it and remind you to do so if necessary.

```
laboratorio-cenfotec-terraform/tareas/semana 3 on master (c02bedf) [!?] via default via impure (nix-shell)
  terraform plan
```

Terraform used the selected providers to generate the following execution plan. Resource actions are indicated with the following symbols:

- + create

Terraform will perform the following actions:

```
# aws_vpc.lab-JORGE_JAVIER_ARAYA_NAVARRO will be created
+ resource "aws_vpc" "lab-JORGE_JAVIER_ARAYA_NAVARRO" {
+   arn                               = (known after apply)
+   cidr_block                        = "10.0.0.0/16"
+   default_network_acl_id           = (known after apply)
+   default_route_table_id           = (known after apply)
+   default_security_group_id        = (known after apply)
+   dhcp_options_id                  = (known after apply)
+   enable_dns_hostnames              = (known after apply)
+   enable_dns_support                = true
```

```

+ enable_network_address_usage_metrics = (known after apply)
+ id                                   = (known after apply)
+ instance_tenancy                     = "default"
+ ipv6_association_id                  = (known after apply)
+ ipv6_cidr_block                       = (known after apply)
+ ipv6_cidr_block_network_border_group = (known after apply)
+ main_route_table_id                  = (known after apply)
+ owner_id                             = (known after apply)
+ region                              = "us-east-2"
+ tags_all                             = (known after apply)
}

```

Plan: 1 to add, 0 to change, 0 to destroy.

Note: You didn't use the `-out` option to save this plan, so Terraform can't guarantee to take exactly these actions.

laboratorio-cenfotec-terraform/tareas/semana 3 on master (c02bedf) [!?] via default via impure (nix-shell) terraform apply

Terraform used the selected providers to generate the following execution plan. Resource actions are indicated with the following symbols:
+ create

Terraform will perform the following actions:

```

# aws_vpc.lab-JORGE_JAVIER_ARAYA_NAVARRO will be created
+ resource "aws_vpc" "lab-JORGE_JAVIER_ARAYA_NAVARRO" {
+   arn                                   = (known after apply)
+   cidr_block                           = "10.0.0.0/16"
+   default_network_acl_id               = (known after apply)
+   default_route_table_id               = (known after apply)
+   default_security_group_id            = (known after apply)
+   dhcp_options_id                      = (known after apply)
+   enable_dns_hostnames                  = (known after apply)
+   enable_dns_support                    = true
+   enable_network_address_usage_metrics = (known after apply)
+   id                                    = (known after apply)
+   instance_tenancy                     = "default"
+   ipv6_association_id                  = (known after apply)
+   ipv6_cidr_block                       = (known after apply)
+   ipv6_cidr_block_network_border_group = (known after apply)
+   main_route_table_id                  = (known after apply)
+   owner_id                             = (known after apply)
+   region                              = "us-east-2"
+   tags_all                             = (known after apply)
}

```

Plan: 1 to add, 0 to change, 0 to destroy.

Do you want to perform these actions?

Terraform will perform the actions described above.

Only 'yes' will be accepted to approve.

Enter a value: yes

aws_vpc.lab-JORGE_JAVIER_ARAYA_NAVARRO: Creating...

aws_vpc.lab-JORGE_JAVIER_ARAYA_NAVARRO: Creation complete after 2s [id=vpc-02f5720343033d1e3]

Apply complete! Resources: 1 added, 0 changed, 0 destroyed.

¡El recurso VPC ha sido creado de manera exitosa en Amazon Web Services!

Inmediatamente se borra el recurso con terraform destroy:

```
laboratorio-cenfotec-terraform/tareas/semana 3 on master (c02bedf) [!?] via default via impure (nix-shell)
terraform destroy
aws_vpc.lab-JORGE_JAVIER_ARAYA_NAVARRO: Refreshing state... [id=vpc-02f5720343033d1e3]
```

Terraform used the selected providers to generate the following execution plan. Resource actions are indicated with the following symbols:

- destroy

Terraform will perform the following actions:

```
# aws_vpc.lab-JORGE_JAVIER_ARAYA_NAVARRO will be destroyed
- resource "aws_vpc" "lab-JORGE_JAVIER_ARAYA_NAVARRO" {
  - arn                                = "arn:aws:ec2:us-east-2:367816904393:vpc/vpc-02f5720343033d1e3"
  - assign_generated_ipv6_cidr_block   = false -> null
  - cidr_block                         = "10.0.0.0/16" -> null
  - default_network_acl_id            = "acl-0226e8e7699e603ca" -> null
  - default_route_table_id            = "rtb-03569f911bba8a214" -> null
  - default_security_group_id         = "sg-04ea5fa60a6aa9db8" -> null
  - dhcp_options_id                   = "dopt-069c12649ebed9d9a" -> null
  - enable_dns_hostnames               = false -> null
  - enable_dns_support                = true -> null
  - enable_network_address_usage_metrics = false -> null
  - id                                = "vpc-02f5720343033d1e3" -> null
  - instance_tenancy                  = "default" -> null
  - ipv6_netmask_length                = 0 -> null
  - main_route_table_id               = "rtb-03569f911bba8a214" -> null
  - owner_id                          = "367816904393" -> null
  - region                            = "us-east-2" -> null
  - tags                              = {} -> null
  - tags_all                          = {} -> null
  # (4 unchanged attributes hidden)
}
```

Plan: 0 to add, 0 to change, 1 to destroy.

Do you really want to destroy all resources?

Terraform will destroy all your managed infrastructure, as shown above.

There is no undo. Only 'yes' will be accepted to confirm.

Enter a value: yes

```
aws_vpc.lab-JORGE_JAVIER_ARAYA_NAVARRO: Destroying... [id=vpc-02f5720343033d1e3]
aws_vpc.lab-JORGE_JAVIER_ARAYA_NAVARRO: Destruction complete after 1s
```

Destroy complete! Resources: 1 destroyed.