

SHACMAN

WORKING PLAN REPORT



WORKING PLAN



I am writing to confirm/enquire/inform you
I am writing to follow up on our earlier decision on the marketing campaign in

SHACMAN X3000 DUMP TRUCK



DRIVE			6X4		8X4			
GVW(T)			50		70		90	
Main configuration	Cab	Type	Medium-length flat roof					
		Suspension	Fout-point hydraulic suspenslor					
		Seat	Hydraulic main seat					
		Alr conditioner	Electric automatic constant temperature AC					
	Engine	Moda	WP12/WP13/M10/M13/SM11					
		Emmission Standard	EURO II - EUROV					
		Rated Power (hp)	340/380/400/385/430/385			430/440/430/460/550		
	Transmissi on	Model	FAST MT(10/12/16)					
	Axde	Front axle	9.5t					
		Rear axle	16t					
		Ratio	5.92		5.262			
	Chossis	Dimension(mm	850×300(8+7)				850×320(8+7+8)	
		Wheel bose(mm	3775+1400			1800+3575+1400		
		Wheel ovethong (mm	850			1000		
		Fuel tank	300L aluminum alloy		400L aluminum alloy		300L aluminum alloy	
		Tires	12.00R20					
		Suspension	Front and rear multi-leaf springs					
Top containe		5600×2300x1500		7400×2300×1500		7400×2300x120		
Applicabl e	Applicable road conditions		Muddy and potholed roads		Muddy and potholed roads		Most of the roads are paved, and a small amount is unpaved.	
condition	Economic/Max speed (km/h)		40-55/75		45-60/85		40-60/80	
Basicequipment			Electric windows, rear window, metal bumper, daytime running lights, hinged boarding steps, radiator grille		Electric windows, daytime running lights, metal bumpers, hinged pedals, radiator grille			

SHACMAN F3000 DUMP TRUCK

						
DRIVE			6X4		8X4	
GVW(T)			50		70	
					90	
Main configuration	Cab	Type	Medium length flat roof			
		Suspension	Four-point hydraulic suspension			
		Seat	Hydraulic main seat			
		Air conditioner	Electric automatic constant temperature AC			
	Engine	Model	WP10/WP12			
		Emission Standard	EURO II - EURO V			
		Rated Power (hp)	340/380/400/430		380/400/430	
	Transmission	Model	FAST MT(10/12)			
	Axle	Front axle	9.5t			
		Rear axle	16t			
		Ratio	5.92		5.262	
	Chassis	Dimension(mm)	850×300(8+7)		850×320(8+7+8)	
		Wheel base(mm)	3775+1400		1800+3575+1400	
		Wheel overhang (mm)	850		1000	
		Fuel tank	300L Iron/aluminum alloy		400L aluminum alloy	
		Tires	12.00R20			
		Suspension	Front and rear multi-leaf springs			
Top container		5600×2300×1500		7400×2300×1500		
Applicable condition	Applicable road conditions		Muddy and potholed roads		Most of the roads are paved, and a small amount is unpaved.	
	Economic/Max speed (km/h)		40-55/75		45-60/85	
Basic equipment			Electric windows, rear window, metal bumper, daytime running lights, hinged boarding steps, radiator grille		Electric windows, daytime running lights, metal bumpers, hinged pedals, radiator grille	

SHACMAN H3000 DUMP TRUCK



DRIVE			6X4		8X4	
GVW(T)			50		70	90
Main configuration	Cab	Type	Medium-length flat roof			
		Suspension	Fout-point hydraulic suspenslor			
		Seat	Hydraulic main seat			
		Alr conditioner	Electric automatic constant temperature AC			
	Engine	Moda	WP12/WP13/M10/M13/SM11			
		Emmission Standard	EURO II - EURO V			
		Rated Power (hp)	340/380/400/385/430/385		430/440/430/460/550	
	Transmissi on	Model	FAST MT(10/12/16)			
	Axde	Front axle	9.5t			
		Rear axle	16t			
		Ratio	5.92		5.262	
	Chassis	Dimension(mm	850×300(8+7)			850×320(8+7+8)
		Wheel bosc(mm	3775+1400		1800+3575+1400	
		Wheel ovethong (mm	850		1000	
		Fuel tank	300L aluminum alloy		400L aluminum alloy	300L aluminum alloy
		Tires	12.00R20			
		Suspension	Front and rear multi-leaf springs			
Top containe		5600×2300x1500		7400×2300×1500	7400×2300x120	
Applicable condition	Applicable road conditions		Muddy and potholed roads		Muddy and potholed roads	Most of the roads are paved, and a small amount is unpaved.
Economic/Max speed (km/h)		40-55/75		45-60/85		40-60/80
Basicequipment			Electric windows, rear window, metal bumper, daytime running lights, hinged boarding steps, radiator grille			
			Electric windows, daytime running lights, metal bumpers, hinged pedals, radiator grille			

SHACMAN H3000/H3000S TRACTOR TRUCK



DRIVE			4X2		6X4			
GCW(T)			50		70		90-120	
Main configuration	Cab	Type	Medium-length flat roof/Extended High Roof					
		Drive position	Left hand / right hand					
		suspension	Four-point hydraulic suspension/air bag suspension					
		Seat	Hydraulic main seat/air main seat					
		Air conditioner	Electric automatic constant temperature AC					
	Engine	Model	WP10/WP12/ISME					
		Emmission Standard	EURO II - EURO V					
		Rated Power (hp)	340/380/400/385/420/430		380/385/400/420/430/			
	Transmission	Model	FAST MT(10/12)/ AMT 16					
	Axle	Front axle	5.5t/7.5t		7.5t/9.5t		9.5t	
		Rear axle	11.5t/13t		13t/16t		16t	
		Ratio	3.111/3.866/4.266		4.766/5.262/5.92			
	Chassis	Dimension(mm)	(970-850)x270(8)		850×320(8+5)		850×320(8+7)	
		Wheel base(mm)	3600		3175+1400			
		Fuel tank	400L aluminum alloy		400L aluminum alloy		400L aluminum alloy	
		Tires	12R22.5/12.00R20/315/80R22.5/12.00R24/ 385/65R22.5					
		Suspension	Front and rear multi-leaf springs/air bag					
Applicable condition	Applicable road conditions		City road		Muddy and potholed roads		Most of the roads are paved, and a small amount is unpaved.	
	Economic/Max speed (km/h)		60-75/100		65-85/110		40-60/80	
Basic equipment			Electric windows, rear window, metal bumper, daytime running lights, hinged boarding steps, radiator grille		Electric windows, daytime running lights, metal bumpers, hinged pedals, radiator grille			

SHACMAN F3000 TRACTOR TRUCK



DRIVE			4X2		6X4	
GCW(T)			50		70	90-120
Main configuration	Cab	Type	Medium-length flat roof/Extended High Roof			
		Drive position	Left hand / right hand			
		suspension	Four-point hydraulic suspensor/air bag suspension			
		Seat	Hydraulic main seat/air main seat			
		Air conditioner	Electric automatic constant temperature AC			
	Engine	Model	WP10/WP12/ISME			
		Emission Standard	EURO II - EURO V			
		Rated Power (hp)	340/380/400/385/420/430		380/385/400/420/430/	
	Transmission	Model	FAST MT(10/12) / AMT 16			
	Axle	Front axle	5.5t/7.5t		7.5t/9.5t	9.5t
		Rear axle	11.5t/13t		13t/16t	16t
		Ratio	3.111/3.866/4.266		4.766/5.262/5.92	
	Chassis	Dimension(mm)	(970-850)x270(8)		850×300(8+5)	850×320(8+7)
		Wheel base(mm)	3600		3175+1400	
		Fuel tank	400L aluminum alloy		400L aluminum alloy	400L aluminum alloy
		Tires	12R22.5/12.00R20/315/80R22.5/12.00R24/ 385/65R22.5			
		Suspension	Front and rear multi-leaf springs/air bag			
Applicable condition	Applicable road conditions		City road	Muddy and potholed roads	Most of the roads are paved, and a small amount is unpaved.	
	Economic/Max speed (km/h)		60-75/100	65-85/110	40-60/80	
Basic equipment			Electric windows, rear window, metal bumper, daytime running lights, hinged boarding steps, radiator grille	Electric windows, daytime running lights, metal bumpers, hinged pedals, radiator grille		

SHACMAN X3000 TRACTOR TRUCK



DRIVE			4X2		6X4			
GCW(T)			50		70		90-120	
Main configuration	Cab	Type	Medium-length flat roof/Extended High Roof					
		Drive position	Left hand / right hand					
		suspension	Fout-point hydraulic suspenslor/air bag suspension					
		Seat	Hydraulic main seat/air main seat					
		Alr conditioner	Electric automatic constant temperature AC					
	Engine	Model	WP10/WP12/ISME					
		Emmission	EURO II - EUROV					
		Standard						
		Rated Power (hp)	340/380/400/385/420/430		380/385/400/420/430/440/460/520/560			
	Transmissio n	Model	FAST MT(10/12)/ AMT 16					
	Axle	Front axle	5.5t/7.5t		7.5t/9.5t		9.5t	
		Rear axle	11.5t/13t		13t/16t		16t	
		Ratio	3.111/3.866/4.266		4.766/5.262/5.92			
	Chassis	Dimension(mm)	850×300(8+7)				850×320(8+7+8)	
		Wheel base(mm)	3600		3175+1400			
		Fuel tank	400L aluminum alloy		400L aluminum alloy		400L aluminum alloy	
		Tires	12R22.5/12.00R20/315/80R22.5/12.00R24/ 385/65R22.5					
Suspension		Front and rear multi-leaf springs/air bag						
Applicable condition	Applicable road conditions		City road		Muddy and potholed roads		Most of the roads are paved, and a small amount is unpaved.	
	Economic/Max speed (km/h)		60-75/100		65-85/110		40-60/80	
Basicequipment			Electric windows, rear window, metal bumper, daytime running lights, hinged boarding steps, radiator grille		Electric windows, daytime running lights, metal bumpers, hinged pedals, radiator grille			

SHACMAN X5000 TRACTOR TRUCK



DRIVE			4X2		6X4			
GCW(T)			50		70		90-120	
Main configuration	Cab	Type	Medium-length flat roof/Extended High Roof					
		Drive position	Left hand / right hand					
		suspension	Fout-point hydraulic suspenslor/air bag suspension					
		Seat	Hydraulic main seat/air main seat					
		Alr conditioner	Electric automatic constant temperature AC					
	Engine	Model	WP10/WP12/ISME					
		Emmission Standard	EURO II - EUROV					
		Rated Power (hp)	340/380/400/385/420/430/550		380/385/400/420/430/440/460/520/550/560			
	Transmissi on	Model	FAST MT(10/12)/ AMT 16					
	Axle	Front axle	5.5t/7.5t		7.5t/9.5t		9.5t	
		Rear axle	11.5t/13t		13t/16t		16t	
		Ratio	3.111/3.866/4.266		4.766/5.262/5.92			
	Chassis	Dimension(mm)	850×300(8+5)				850×320(8+7+8)	
		Wheel base(mm)	3600		3175+1400			
		Fuel tank	400L aluminum alloy		400L aluminum alloy		400L aluminum alloy	
		Tires	12R22.5/12.00R20/315/80R22.5/12.00R24/ 385/65R22.5					
		Suspension	Front and rear multi-leaf springs/air bag					
Applicable condition	Applicable road conditions		City road		Muddy and potholed roads		Most of the roads are paved, and a small amount is unpaved.	
	Economic/Max speed (km/h)		60-75/100		65-85/110		40-60/80	
Basic equipment			Electric windows, rear window, metal bumper, daytime running lights, hinged boarding steps, radiator grille		Electric windows, daytime running lights, metal bumpers, hinged pedals, radiator grille			



