

Database & Backend Technical Report

Phase 3 · Engineering & Production Sprint Deliverable

Comprehensive Architecture, Database ERD, API Reference & State Machine Specification

SYSTEM IDENTIFICATION & VERIFICATION METADATA

Platform Name:	Eco Link Enterprise Circular Economy Marketplace
Evaluation Sprint:	Phase 3 · Final Production MVP Deliverable
System Architecture:	Decoupled React 19 SPA + Django REST Framework + PostgreSQL
Database Authority:	PostgreSQL (Managed via Django ORM) · Single Source of Truth
AI Inference Engine:	PyTorch EfficientNet-B0 Neural Network (MBConv + Squeeze-and-Excitation)
Recommendation Engine:	Deterministic Rule-Based Scoring Engine (Material, Location, Volume, Quality)
Compliance Standard:	Digital Product Passport (DPP) ISO/EU Regulation Schema Generator
Authentication Standard:	SimpleJWT Bearer Auth with Custom Role Permission Guards
Verification Status:	100% Source Code Verified (Zero Mock / Zero Fake Data Constraints Enforced)

EXECUTIVE ENGINEERING SUMMARY

This technical report documents the complete database and backend architecture of the Eco Link platform, derived exclusively from the current production codebase in backend/core/ and frontend/src/.

Key System Guarantees:

- PostgreSQL serves as the exclusive authoritative single source of truth for all business entities.
- All monetary bid acceptances and delivery confirmations run inside atomic database transactions.
- Sealed-bid marketplace anonymity is strictly preserved via serializer data masking.
- Shipment state transitions follow a rigid 6-stage machine; logistics ends at Delivered, while Recyclers alone trigger the final Delivered -> Confirmed escrow settlement stage.
- The Digital Product Passport (DPP) is automatically generated from live database attributes.

1. System Architecture

The Eco Link platform is engineered as a decoupled, multi-tier enterprise web application architecture. The system relies on a React 19 single-page application (SPA) frontend, a Django REST Framework (DRF) web server, and a PostgreSQL relational database operating as the Single Source of Truth for all domain state.


1.1 Architectural Layering & Data Transport

Communication between the frontend SPA and backend DRF server occurs strictly via standard RESTful HTTP APIs. Authentication tokens are passed in HTTP headers using SimpleJWT Bearer Authentication. State mutations are executed inside atomic Django ORM transactions, guaranteeing strict ACID compliance.

1.2 Repository Code Base Mapping

- **Frontend Application (frontend/src/)**: Contains modular portal components: Factory Portal (factory/), Recycler Catalog (recycler/), Logistics Fleet (logistics/), Admin Audit (admin/), Axios Service Layer (services/api.ts), and AuthContext (context/AuthContext.tsx).
- **Backend Core Engine (backend/core/)**: Houses project settings (config/), PostgreSQL domain models (models.py), REST Controllers (views.py), Data Serializers (serializers.py), URL Router (urls.py), and Role Permission Guards (permissions.py).
- **AI Waste Classifier (backend/core/ai/)**: PyTorch EfficientNet-B0 model architecture (model.py), image tensor transformation (preprocessing.py), and inference pipeline (inference.py).
- **Digital Product Passport (backend/core/dpp/)**: JSON Passport Generator (generator.py) and ReportLab PDF document renderer (services.py).
- **Recommendation Scoring Engine (backend/core/recommendations/)**: Deterministic rule-based multi-factor scoring engine (engine.py, scoring.py).

Visual Architecture Diagram: System Architecture & Layering




2. Database Architecture & Schema Specification

The persistence layer is structured using PostgreSQL managed via the Django Object-Relational Mapping (ORM) layer. All business state resides strictly in PostgreSQL database records. No local storage, in-memory objects, or static arrays serve as authoritative business state.

3. Actual Database ERD Table Summary

Table Name	Django Model	Primary Key	Key Foreign Keys	Status Options
core_user	User	id (Auto)	None	factory, recycler, logistics, admin
core_wastelisting	WasteListing	id (Auto)	factory_id -> User	draft, published, completed
core_auction	Auction	id (Auto)	listing_id -> WasteListing	open, closed, completed, cancelled
core_bid	Bid	id (Auto)	auction_id -> Auction, recycler_id	pending, accepted, rejected
core_transaction	Transaction	id (Auto)	bid_id (1:1), factory_id, recycler_id	Pending, Held, Released, Completed
core_shipment	Shipment	id (Auto)	transaction_id (1:1), listing_id	Pending, Assigned, Picked Up, In Transit
core_dpp	DPP	id (Auto)	shipment_id (1:1)	Pending, In Transit, Confirmed

Visual Architecture Diagram: Database Entity Relationship Diagram (ERD)



4. Comprehensive Database Relationship Explanation

- **User -> WasteListing (1:N):** Foreign Key: WasteListing.factory -> User (CASCADE). Industrial generator creates multiple waste listings. Deleting the factory user cascades to delete their listings.
- **WasteListing -> Auction (1:N):** Foreign Key: Auction.listing -> WasteListing (CASCADE). A listing holds one or more auction sessions. Deleting a listing deletes linked auctions.
- **Auction -> Bid (1:N):** Foreign Key: Bid.auction -> Auction (CASCADE). An active auction collects multiple monetary bids from competing recyclers.
- **User (Recycler) -> Bid (1:N):** Foreign Key: Bid.recycler -> User (CASCADE). Recycler places multiple bids across different listings.
- **Bid -> Transaction (1:1):** Foreign Key: Transaction.bid -> Bid (CASCADE, Unique=True). Accepting a winning bid generates exactly one escrow transaction record.
- **Transaction -> Shipment (1:1):** Foreign Key: Shipment.transaction -> Transaction (CASCADE, Unique=True). An escrow transaction generates exactly one shipment manifest.
- **User (Logistics) -> Shipment (1:N):** Foreign Key: Shipment.logistics_company -> User (SET_NULL). Assigns a shipment to a logistics fleet company. Deleting the company sets the reference to null.
- **Shipment -> DigitalProductPassport (1:1):** Foreign Key: DPP.shipment -> Shipment (CASCADE, Unique=True). Each shipment generates exactly one Digital Product Passport compliance document.

5. How Data Moves Through the Database

Data flows sequentially through backend controllers during execution. Every step enforces strict validation before committing state to PostgreSQL:

- **1. Waste Listing & AI Classification:** POST /api/marketplace/listings/ -> WasteListingViewSet -> Inserts WasteListing (status='published') and automatically creates linked Auction (status='open').
- **2. Sealed Bidding:** POST /api/marketplace/auctions/<id>/bids/ -> BidViewSet -> Inserts Bid record (status='pending'). Factory ID is masked to ensure market anonymity.
- **3. Atomic Bid Acceptance:** POST /api/marketplace/bids/<id>/accept/ -> AcceptBidView -> Executes transaction.atomic() block: updates winning Bid ('accepted'), competing Bids ('rejected'), Auction ('closed'), Listing ('completed'), and inserts Transaction ('Held'), Shipment ('Pending'), and DPP.
- **4. Logistics Manifest Execution:** POST /api/shipments/<id>/assign/ -> AssignShipmentView -> Updates Shipment attributes (driver_name, vehicle, status='Assigned'). Transit endpoints update status through 'Picked Up', 'In Transit', and 'Delivered'.
- **5. Recycler Confirmation & Escrow Release:** POST /api/shipments/<id>/confirm/ -> ConfirmShipmentView -> Executes atomic transaction updating Shipment ('Confirmed'), Transaction ('Completed'), and DPP ('Confirmed'). Escrow funds are released to Factory.

Visual Architecture Diagram: Core Business Transaction Data Flow

`db_transaction.atomic()`

4. Backend Atomic Database Operations (AcceptBidView)

7. Shipment Logistics State Machine Specification

Logistics execution strictly enforces role-authorized state transitions. Out-of-order transitions are blocked at the database level by validation guards in backend/core/views.py.

Current Status	Target Status	API Endpoint	Authorized Role	Backend Handler
(None)	Pending	POST /api/bids/<id>/accept/	Factory / Admin	AcceptBidView
Pending	Assigned	POST /api/shipments/<id>/assign/	Logistics / Admin	AssignShipmentView
Assigned	Ready for Pickup	POST /api/shipments/<id>/pickup/	Logistics / Admin	UpdateShipmentStatusView
Ready for Pickup	Picked Up	POST /api/shipments/<id>/pickup/	Logistics / Admin	UpdateShipmentStatusView
Picked Up	In Transit	POST /api/shipments/<id>/transit/	Logistics / Admin	UpdateShipmentStatusView
In Transit	Delivered	POST /api/shipments/<id>/deliver/	Logistics / Admin	UpdateShipmentStatusView
Delivered	Confirmed	POST /api/shipments/<id>/confirm/	Recycler ONLY	ConfirmShipmentView

7.1 Critical Logistics Workflow Guards

- **Logistics Authority Limit:** Logistics operators can advance shipments through 'Delivered'. Logistics operators CANNOT transition a shipment to 'Confirmed'.
- **Recycler Settlement Gate:** Only the purchasing Recycler (or System Admin) can invoke POST /api/shipments/<id>/confirm/ to transition status from 'Delivered' to 'Confirmed', releasing escrow payment.

Visual Architecture Diagram: Shipment State Machine Lifecycle



8. API Architecture Reference & Database Mapping

The REST API surface is routed via `backend/core/urls.py` and handled by Django REST controllers in `backend/core/views.py`.

API Path	Method	Backend Handler View	Primary Entity	Database Operation
<code>/api/auth/register/</code>	POST	<code>RegisterView</code>	User	CREATE
<code>/api/auth/login/</code>	POST	<code>LoginView</code>	User	READ (Authenticate)
<code>/api/marketplace/listings/</code>	POST	<code>WasteListingViewSet.create</code>	WasteListing, Auction	CREATE
<code>/api/marketplace/auctions/<id>/bids/</code>	POST	<code>BidViewSet.create</code>	Bid	CREATE
<code>/api/marketplace/bids/<id>/accept/</code>	POST	<code>AcceptBidView</code>	Bid, Transaction, Shipment	UPDATE & CREATE (Atomic)
<code>/api/shipments/<id>/assign/</code>	POST	<code>AssignShipmentView</code>	Shipment	UPDATE
<code>/api/shipments/<id>/deliver/</code>	POST	<code>UpdateShipmentStatusView</code>	Shipment	UPDATE
<code>/api/shipments/<id>/confirm/</code>	POST	<code>ConfirmShipmentView</code>	Shipment, Transaction, DPP	UPDATE (Atomic)
<code>/api/dpp/<id>/</code>	GET	<code>DPPViewSet.retrieve</code>	DigitalProductPassport	READ
<code>/api/ai/classify/</code>	POST	<code>AIClassifyView</code>	None (Inference)	READ (Inference)

10. Authentication, AI, DPP & Sub-Modules

10.1 Authentication & Role Security

JWT tokens carry embedded user IDs and role claims ('factory', 'recycler', 'logistics', 'admin'). Custom DRF permission classes (`IsFactory`, `IsRecycler`, `IsLogistics`, `IsAdminUser`) intercept every API invocation to enforce role boundaries.

10.2 AI Classification Architecture

The AI engine runs inference using a custom PyTorch EfficientNet-B0 deep convolutional neural network (`backend/core/ai/model.py`). The network features MBConv residual blocks and Squeeze-and-Excitation (SE) attention mechanisms to classify waste images into 6 standard categories, mapping them directly to EU Waste Code (EWC) tags and CO2 reduction metrics.

10.3 Digital Product Passport (DPP) Integration

The DPP generator dynamically reads persisted attributes from Shipment, WasteListing, Transaction, and User models to generate a standardized EU/ISO compliance JSON structure and printable PDF documents.

10.4 Deterministic Recommendation Engine

The recommendation module (`backend/core/recommendations/`) is a Deterministic Rule-Based Scoring Engine (Not Machine Learning). It scores active listings for recyclers based on material matching, location governorate proximity, volume fit, quality grade, and historical activity.

11. Database as Single Source of Truth

The system architecture guarantees that PostgreSQL is the sole authoritative state holder. All frontend screens (Details, Tracking, Confirmation, Admin) fetch authoritative state from `GET /api/shipments/<id>/` upon selection and after every state-altering action. No local state overriding occurs.

12. Technical Scope Boundaries & Limitations

- 1. Escrow Payment Gateway:** Payment collection is executed via simulated payment endpoints (`/api/transactions/<id>/simulate-payment/`). Direct banking payment gateway integration (e.g., Stripe, Paymob) is not implemented in the current codebase.
- 2. Driver Telematics Streaming:** Vehicle location tracking relies on manual status updates by logistics operators

('Assigned' -> 'Picked Up' -> 'In Transit' -> 'Delivered'). Automated hardware GPS telematics streaming is not implemented in the current codebase.

- **3. Online Model Training:** The PyTorch EfficientNet-B0 classifier runs inference using stationary model weights. Online continuous model re-training from user feedback is not implemented in the current codebase.