

LATIN approach for fatigue damage computation

Shadi Alameddin, Mainak Bhattacharyya, Amelie Fau,
Udo Nackenhorst, David Néron and Pierre Ladevèze

06.03.2017

Non-linear mechanical behaviour such as (visco)plasticity or damage is generally tackled with time incremental methods where the time domain is subdivided into incremental steps. Then a numerical scheme is carried out consequently for each time step. In contrast, in LARge Time INcrement (LATIN) method [1], an approximation of the total time history process is sought directly. This is done by an iterative sequence of two steps: tackling the global linear mechanical equilibrium equation on one side, and on the other one the local history process is determined. The global stage can benefit from model reduction techniques such as the proper generalised decomposition (PGD), in order to obtain a substantial reduction of the computational cost. Moreover, for parametric problems, efficient reduced models can easily be derived.

The LATIN method has been well established to compute several types of problems including material non-linearities [2] but has not been extended to unilateral damage law which leads to a non-linear state equation. An extension of the method is then introduced herein to tackle this issue and then to benefit from a promising numerical framework for fatigue damage computation.

[1] P. Ladevèze, *Nonlinear computational structural mechanics: new approaches and non-incremental methods of calculation*. New York, NY: Springer New York, 1999.

[2] P. Ladevèze, “On reduced models in nonlinear solid mechanics,” *European Journal of Mechanics - A/Solids*, vol. 60, pp. 227 - 237, 2016.

This abstract was submitted to damage and fracture mechanics section, organised by Martin Hofmann (Dresden) and Andreas Ricoeur (Kassel) within the 88th Annual meeting of GAMM (Gesellschaft für Angewandte Mathematik und Mechanik - Internal Association for Applied Mathematics and Mechanics), March 6-10, 2017, Weimar, Germany.