


# Large time increment approach for fatigue damage computations

S. Alameddini<sup>†</sup>, M. Bhattacharyya<sup>†</sup>, A. Fau<sup>†</sup>,  
U. Nackenhorst<sup>†</sup>, D. Néron<sup>‡</sup>, P. Ladevèze<sup>‡</sup>

<sup>†</sup> IBNM, Leibniz Universität Hannover

<sup>‡</sup> LMT, ENS Cachan, CNRS, Université Paris Saclay

15. March 2017




DFG  
IRTG-1627

Deutsche  
Forschungsgemeinschaft


# Fatigue damage

■ Cyclic loading



# Fatigue damage

## ■ Cyclic loading




## ■ Damage



Image by alegri / 4freephotos.com

# Fatigue damage

■ Cyclic loading




■ Damage




Image by alegri / 4freephotos.com

# Fatigue damage

## ■ Cyclic loading




## ■ Damage



# Fatigue damage


## ■ Cyclic loading



- Virtual experiments
- Continuum damage model
- Millions of cycles
- Computationally expensive

# Fatigue damage

## ■ Cyclic loading



- Virtual experiments
- Continuum damage model
- Millions of cycles
- Computationally expensive

Model order reduction (MOR) techniques

# Model order reduction (MOR)

- Proper orthogonal decomposition (POD)  
*a posteriori* approach [Antoulas 2005; Quarteroni, Manzoni, Negri 2016]



# Model order reduction (MOR)

- Proper orthogonal decomposition (POD)  
*a posteriori* approach [Antoulas 2005; Quarteroni, Manzoni, Negri 2016]
- Proper generalised decomposition (PGD)  
*a priori* approach [Ladeveze 1985, 1999; Chinesta, Ladevèze 2014]

$$\varepsilon^p(x, t) \approx \sum_{i=1}^n \bar{\varepsilon}_i^p(x) \lambda_i(t)$$

# Model order reduction (MOR)

- Proper orthogonal decomposition (POD)  
*a posteriori* approach [Antoulas 2005; Quarteroni, Manzoni, Negri 2016]
- Proper generalised decomposition (PGD)  
*a priori* approach [Ladeveze 1985, 1999; Chinesta, Ladev ze 2014]

$$\varepsilon^p(x, t) \approx \sum_{i=1}^n \bar{\varepsilon}_i^p(x) \lambda_i(t)$$

- Intrusive method
- Integrals over the generalised coordinates

# Model order reduction (MOR)

- Proper orthogonal decomposition (POD)  
*a posteriori* approach [Antoulas 2005; Quarteroni, Manzoni, Negri 2016]
- Proper generalised decomposition (PGD)  
*a priori* approach [Ladeveze 1985, 1999; Chinesta, Ladev ze 2014]

$$\varepsilon^P(x, t) \approx \sum_{i=1}^n \bar{\varepsilon}_i^P(x) \lambda_i(t)$$

- Intrusive method
- Integrals over the generalised coordinates

Need for a convenient framework to utilise PGD

# Large time increment (LATIN) method

- At each iteration
  - An approximation on the **whole time-space domain** is obtained.
  - The balance equation is solved as a **linear** problem.

# Large time increment (LATIN) method

- At each iteration
  - An approximation on the **whole time-space domain** is obtained.
  - The balance equation is solved as a **linear** problem.


# The LATIN framework

## ■ Assumptions

- Free energy function  $\psi$   
**State equations**
- Dissipation potential  $\phi$   
**Evolution equations**
- Here: no dynamic effects

## ■ Linear initialisation

$$\varepsilon = \varepsilon^e$$




# The LATIN framework

- **Non-linear step**
- The evolution equations


$$\text{e.g. } \dot{X} = -\frac{\partial \phi}{\partial Y}$$

- **Local in space** (cheap)





# The LATIN framework

- Linear step
  - The equilibrium equation
- $$\text{div}(\boldsymbol{\sigma}) = \mathbf{0}$$
- Global in space
  - Convenient to apply PGD









# The LATIN iterative scheme





# The LATIN iterative scheme





# The LATIN iterative scheme





# The LATIN iterative scheme




# The LATIN iterative scheme



# The LATIN iterative scheme



# The LATIN iterative scheme



Established for viscoplasticity, contact and large deformations problems [Surveys: Ladevèze 1999, Chinesta 2014]

# LATIN with isotropic damage

## ■ State equation

e.g.  $\sigma = E (1 - D) \varepsilon^e$

Evolution equations  $\Gamma$




# LATIN with isotropic damage

- State equation

e.g.  $\sigma = E (1 - D) \varepsilon^e$

- Nonlinear  $\mathcal{A}$



# LATIN with isotropic damage


- State equation

e.g.  $\sigma = E (1 - D) \varepsilon^e$

- Nonlinear  $\mathcal{A}$

## Workaround

- Solve  $\sigma = E (1 - D) \varepsilon^e$   
in the **local step**



# LATIN with isotropic damage

- State equation

e.g.  $\sigma = E (1 - D) \varepsilon^e$

- Nonlinear  $\mathcal{A}$


## Workaround

- Solve  $\sigma = E (1 - D) \varepsilon^e$

in the **local step**

- Linear  $\mathcal{A}$

- Use **PGD** for the global step



# PGD

$$\varepsilon^P(x, t) \approx \sum_{i=1}^n \lambda_i(t) \bar{\varepsilon}_i^P(x)$$

Initialise  $\lambda_i(t)$

**while**  $err > tol$  **do**

$\int_t \bullet dt$	$\rightarrow$	the space function $\bar{\varepsilon}_i^P(x)$
$\int_{\Omega} \bullet d\Omega$	$\rightarrow$	the time function $\lambda_i(t)$

**end**

**Algorithm:** PGD enrichment step

# PGD

$$\varepsilon^P(x, t) \approx \sum_{i=1}^n \lambda_i(t) \bar{\varepsilon}_i^P(x)$$

Initialise  $\lambda_i(t)$

**while**  $err > tol$  **do**

$\int_t \bullet dt$	$\rightarrow$	the space function $\bar{\varepsilon}_i^P(x)$
$\int_{\Omega} \bullet d\Omega$	$\rightarrow$	the time function $\lambda_i(t)$

**end**

**Algorithm:** PGD enrichment step


- Auto. generation of the best pairs by a greedy algorithm
- No a priori assumption on the reduced order basis

# Numerical example

- Modified "standard" Chaboche Marquis constitutive model  
(Cr-Mo steel at 580°C, Unilateral damage) [Chaboche 1993; Cognard 1993]



$$\psi = \frac{1}{2} E (\varepsilon^e)^2 + \underbrace{\frac{1}{2} C (\alpha)^2}_{\text{hardening}}$$




$$\phi = \phi^p$$

$$\phi^p = \frac{k}{n+1} \langle f^p \rangle_+^{n+1} \quad f^p = |\sigma - \beta| + \frac{a}{C} \beta^2 - \sigma_y$$

# Numerical example

- Modified "standard" Chaboche Marquis constitutive model  
(Cr-Mo steel at 580°C, Unilateral damage) [Chaboche 1993; Cognard 1993]




$$\phi = \phi^p$$

$$\phi^p = \frac{k}{n+1} \langle f^p \rangle_+^{n+1} \quad f^p = |\sigma - \beta| + \frac{a}{C} \beta^2 - \sigma_y$$

# Numerical example

- Modified "standard" Chaboche Marquis constitutive model  
(Cr-Mo steel at 580°C, Unilateral damage) [Chaboche 1993; Cognard 1993]




$$\phi = \phi^p + \phi^d$$

$$\phi^p = \frac{k}{n+1} \langle f^p \rangle_+^{n+1} \quad f^p = |\sigma - \beta| + \frac{a}{C} \beta^2 - \sigma_y$$



# Numerical example

- Modified "standard" Chaboche Marquis constitutive model  
(Cr-Mo steel at 580°C, Unilateral damage) [Chaboche 1993; Cognard 1993]





$$\phi = \phi^p + \phi^d$$

$$\phi^p = \frac{k}{n+1} \langle f^p \rangle_+^{n+1} \quad f^p = |\sigma - \beta| + \frac{a}{C} \beta^2 - \sigma_y$$



$$\phi^d = \frac{k_d}{n_d+1} \langle f^d \rangle_+^{n_d+1} \quad f^d = Y - Y_0$$

# The convergence behaviour



Damage evolution at convergence


# The plastic strain evolution using PGD



$$\dot{\varepsilon}^p(x, t) \approx \sum_{i=1}^3 \dot{\lambda}_i(t) \varepsilon_i^p(x)$$


# Conclusion and current research

- A LATIN-based model reduction approach for the simulation of cycling damage [Mainak Bhattacharyya, IRTG 2<sup>nd</sup> cohort]
  - Crack closure effect
  - Non-proportional loading
- Two-time scale approach (*in progress*)



# Conclusion and current research


- A LATIN-based model reduction approach for the simulation of cycling damage [Mainak Bhattacharyya, IRTG 2<sup>nd</sup> cohort]
  - Crack closure effect
  - Non-proportional loading
- Two-time scale approach (*in progress*)




## Current objectives

- Extend the two-time scale to consider  
Different amplitudes, frequencies and random loadings

# Milestone plan



# Milestone plan



Thank you for your attention!

## ■ Time comparison

D. Néron et al, Time-space PGD for the rapid solution of 3D nonlinear parametrized problems in the many-query context, *IJNME*, 2015.



## ■ LATIN convergence conditions

Ladeveze 1999 [p84]

## ■ PGD existence and convergence

Ladeveze 1999 [p119]

## ■ PGD for solving PDE

A. Nouy. A priori model reduction through proper generalized decomposition for solving time-dependent partial differential equations. *Computer Methods In Applied Mechanics and Engineering*, 199(23- 24):1603–1626, 2010.

Antonio Falco