The Publishing API: guide for developers and AI agents

For: a developer building software against it, or an AI agent that schedules posts. Base address: `https://publish.dhakakacchi.com`

An agent can also read the short plain-text version at `GET /llms.txt` and the machine-readable contract at `GET /openapi.json` (interactive page: `/docs`). Neither needs a key. Every rule a post must meet is one document, `GET /v1/spec` (section 5c). AI agents can also connect over **MCP** at `/mcp/` with the same key (section 5f).

1. What it does, in one minute



Posts made here and posts typed in the Google Sheet use the **same engine** (checks, approval, schedule, retries, "never post twice"). They are shown together, sorted by date, in the Sheet's **Calendar** tab (`source` says `agent` for yours). The Sheet never edits or cancels API posts.

2. Get a key

Only the owner can create keys, in their own terminal (the key is shown once, so never send it in chat or email):

```
dk api key-create content-agent --right draft
```

Right	May do
`read`	look at platforms and posts
`draft`	also upload files, validate, create **drafts**, cancel drafts
`approve`	also publish directly (`"approve": true`) and approve drafts

Give an agent the `draft` right. Then every post waits for a human. Use `approve` only for software you fully trust. The owner stops a key at once with `dk api key-revoke content-agent`.

Send the key on **every** `/v1` call:

```
Authorization: Bearer dkp_xxxxxxxxxxxxxxx
```

Set it once in your shell for the examples below (do not paste real keys into scripts that get shared):

```
API=https://publish.dhakakacchi.com
read -rs "KEY?Paste key, press Enter: "; export KEY      # zsh. In bash: read -rs -p "Key: "
KEY; export KEY
```

3. Step by step, with real requests

Step 1: Learn what is possible

```
curl -s -H "Authorization: Bearer $KEY" $API/v1/platforms
```

You get every connected platform with its **formats, caption limits, file types, extra options, and connected accounts**. This is the source of truth and is always current. Do this first, and again whenever a post is refused. One platform: `GET /v1/platforms/instagram`.

Current platforms: `facebook`, `instagram`, `threads`, `youtube`, `tiktok`. `mode` says what happens: `live` = published for real, `assisted` = handed to the owner on Telegram to post by hand (TikTok).

Step 2: Upload each file once

```
curl -s -H "Authorization: Bearer $KEY" -X POST -T ./reel.mp4 "$API/v1/media?filename=reel.mp4"
# -> {"media_id":"3de909cc-...","filename":"reel.mp4","size":8123456,"sha256":"a782..."}
```

Or let the server download a **public https** link:

```
curl -s -H "Authorization: Bearer $KEY" -H "Content-Type: application/json" -X POST
$API/v1/media \
  -d '{"url":"https://example.com/reel.mp4","filename":"reel.mp4"}'
```

Keep the `media_id`. The extension in `filename` matters (it says what the file is). Allowed types: `.jpg .jpeg .png .mp4 .mov .m4v .webm .avi .mkv` (each platform accepts only some, checked in step 3).

Limits: 512 MB per file; each key may keep 5 GB on the server at once (`413 quota_exceeded`); uploads pause with `507 storage_full` when the server disk is nearly full. Files are **deleted a week after their posts are finished**. A post that still names a deleted file is refused with `media_expired`: upload again and use the new id.

Step 3: Check the post (creates nothing)

```
curl -s -H "Authorization: Bearer $KEY" -H "Content-Type: application/json" -X POST
$API/v1/posts/validate -d '{
  "post_key": "eid-2026-reel-1",
  "variants": [
    {"platform": "instagram", "format": "reel", "caption": "Slow-cooked for Eid.",
     "media": ["3de909cc-..."], "slot": "2026-12-20T19:30:00+01:00",
     "options": {"share_to_feed": true}}
  ]
}'
# -> {"valid": true}   or   {"valid": false, "problems": [...], "examples": {...}}
```

Step 4: Create it

Same body, to `POST /v1/posts`. The answer is `201`:

```
{"post_key": "eid-2026-reel-1", "summary": "awaiting_approval", "created_by": "content-agent",
 "variants": [{"variant_id": "...", "platform": "instagram", "account": "Dhaka Kacchi",
"format": "reel",
               "state": "awaiting_approval", "status": "draft", "slot": "2026-12-
20T18:30:00+00:00",
               "handed_over": false}]}
```

The owner is told on Telegram and approves in the Sheet (Calendar tab, tick `approve`).

Step 5: Follow it

```
curl -s -H "Authorization: Bearer $KEY" $API/v1/posts/eid-2026-reel-1
curl -s -H "Authorization: Bearer $KEY" $API/v1/posts          # all API posts, newest first
```

Poll gently (once a minute is plenty), or use a webhook (section 5b). Per variant, `state` is one of:

state	Meaning
`awaiting_approval`	A draft waiting for the owner
`scheduled`	Approved, waiting for the slot
`publishing`	Going out now
`checking`	The outcome is uncertain; the server is verifying with the platform. **Do not resend.**
`published`	Live; `live_url` is set (TikTok `handed_over: true`: the owner posts it by hand)
`failed` / `expired`	It did not go out (`error` explains)
`invalid`	Refused by the platform's rules at approval
`cancelled`	Cancelled

Step 6: Cancel (optional)

```
curl -s -H "Authorization: Bearer $KEY" -X DELETE $API/v1/posts/eid-2026-reel-1
```

Cancels everything that has not gone out. A variant already publishing or published is left and reported as `409`. To **change** a post: cancel it and send a new post with a **new** `post_key`.

4. The post body, field by field

```
{
  "post_key": "eid-2026-reel-1",
  "label": "Eid reel",
  "approve": false,
  "variants": [
    {
      "platform": "instagram",
      "format": "reel",
      "caption": "Slow-cooked for Eid.",
      "media": ["<media_id>"],
      "slot": "2026-12-20T19:30:00+01:00",
      "account": "Dhaka Kacchi",
      "options": {"share_to_feed": true}
    }
  ]
}
```

Field	Rules
`post_key`	**Your own unique id**, 1 to 80 characters: letters, digits and `. _ : -`, starting with a letter or digit. See "Repeating safely".
`label`	Optional internal name. Never published.
`approve`	`false` (default) creates drafts. `true` needs a key with the `approve` right.
`variants`	1 to 20 entries. **One variant = one post on one platform account.** Send several to post the same idea to several platforms.
`platform`, `format`	From `GET /v1/platforms`.
`caption`	The text. Limits are per platform. Some formats have none (YouTube, Instagram story).
`media`	The `media_id`s from step 2, in display order.
`slot`	ISO 8601 **with** an offset: `2026-12-20T19:30:00+01:00` or `...Z`. A time without an offset is **refused** (ambiguous). At least a minute ahead, at most a year.
`account`	Needed only if the platform has more than one connected account.
`options`	The format's extra fields (see below). **Anything platform-specific goes here, not at the top.**

Unknown fields are **refused** (so a typo is caught, not silently ignored). Only one variant per platform and account in a request.

5. Ready-to-send examples for every platform

Each is one variant. Put it inside `"variants": [ ... ]`. Replace `MEDIA_ID` with a real id and pick a future `slot`.

Instagram

```
{"platform":"instagram","format":"feed","caption":"Fresh out of the pot.","media":
["MEDIA_ID"],"slot":"2026-12-20T19:30:00+01:00"}
{"platform":"instagram","format":"carousel","caption":"Three plates.","media":
["MEDIA_ID","MEDIA_ID"],"slot":"2026-12-20T19:30:00+01:00"}
{"platform":"instagram","format":"reel","caption":"Slow-cooked.","media":
["MEDIA_ID"],"slot":"2026-12-20T19:30:00+01:00","options":{"share_to_feed":true}}
{"platform":"instagram","format":"story","media":["MEDIA_ID"],"slot":"2026-12-
20T19:30:00+01:00"}
```

Facebook

```
{"platform":"facebook","format":"post","caption":"Open today from noon.","slot":"2026-12-
20T19:30:00+01:00"}
{"platform":"facebook","format":"photo","caption":"Today's platter.","media":
["MEDIA_ID"],"slot":"2026-12-20T19:30:00+01:00"}
{"platform":"facebook","format":"video","caption":"Watch the dum opening.","media":
["MEDIA_ID"],"slot":"2026-12-20T19:30:00+01:00"}
```

Threads

```
{"platform":"threads","format":"text","caption":"Biryani o'clock.","slot":"2026-12-
20T19:30:00+01:00"}
{"platform":"threads","format":"image","caption":"Look at this.","media":
["MEDIA_ID"],"slot":"2026-12-20T19:30:00+01:00"}
{"platform":"threads","format":"video","caption":"Watch.","media":["MEDIA_ID"],"slot":"2026-12-
20T19:30:00+01:00"}
```

YouTube (no `caption`: use the options)

```
{"platform":"youtube","format":"video","media":["MEDIA_ID"],"slot":"2026-12-20T19:30:00+01:00",
 "options":{"title":"Dum biryani in 40 seconds","description":"How we open the
pot.","made_for_kids":"no"}}
```

TikTok (handed to the owner on Telegram at the slot; `privacy_level` is always required)

```
{"platform":"tiktok","format":"video","caption":"Biryani.","media":["MEDIA_ID"],"slot":"2026-
12-20T19:30:00+01:00",
 "options":{"privacy_level":"public"}}
```

One idea, three platforms, one request

```
{
  "post_key": "eid-2026-1",
  "variants": [
    {"platform":"instagram","format":"reel","caption":"Slow-cooked for Eid.","media":
["MEDIA_ID"],"slot":"2026-12-20T19:30:00+01:00","options":{"share_to_feed":true}},
    {"platform":"youtube","format":"video","media":["MEDIA_ID"],"slot":"2026-12-
20T20:00:00+01:00","options":{"title":"Dum biryani in 40 seconds","made_for_kids":"no"}},
    {"platform":"tiktok","format":"video","caption":"Slow-cooked for Eid.","media":
["MEDIA_ID"],"slot":"2026-12-20T19:30:00+01:00","options":{"privacy_level":"public"}}
  ]
}
```

Cheat sheet (the live, authoritative numbers are in `GET /v1/platforms`)

Platform / format	Files	Caption	Options (* = required)
instagram `feed`	1 JPEG	optional, 2,200	none
instagram `carousel`	2 to 10 JPEG	optional, 2,200	none
instagram `reel`	1 `.mp4` / `.mov`	optional, 2,200	`share_to_feed`, `cover_at_s`
instagram `story`	1 photo or video	none	none
facebook `post`	none	**required**, 63,206	`link`, `delivery` (`direct` / `native`)
facebook `photo`	1 to 10, `.jpg/.png`, 10 MB each	optional	none
facebook `video`	1, up to 1 GB	optional	`delivery`
threads `text`	none	**required**, 500	`reply_control`
threads `image` / `video`	1	optional, 500	`reply_control`
youtube `video`	1	none	`title`, *`made_for_kids`* (yes / no), `description`, `tags`, `category`, `visibility_after_publish`, `delivery`
tiktok `video`	1 `.mp4/.mov/.webm`	optional, 2,200	`privacy_level`* (`public` / `friends` / `followers` / `only_me`), `allow_comments`, `allow_duet`, `allow_stitch`, `commercial_disclosure`

`delivery: "native"` makes Facebook or YouTube hold the post and publish it themselves (the slot must be at least 10 minutes ahead). Default `direct` = this server publishes at the slot.

5b. Webhooks: let the server call you (instead of polling)

Instead of asking "is it published yet?" every minute, give us an address and **we send you a message when a post changes state**. It is optional; polling still works.

1. Register an address (a `draft` key; the address must be `https` and a public host):

```
curl -s -H "Authorization: Bearer $KEY" -H "Content-Type: application/json" -X POST
$API/v1/webhooks \
  -d '{"url": "https://agent.example.com/dk-hooks", "events": ["post.published",
"post.failed"]}'
# -> {"id": "...", "url": "...", "events": [...], "active": true, "secret": "whsec_...",
"note": "Save the secret now..."}
```

Save the `secret` now: it signs every message and is never shown again (leave `events` out to get all of them). A key may have 3 webhooks. List yours with `GET /v1/webhooks`, remove one with `DELETE /v1/webhooks/{endpoint_id}`.

2. Test it (sends one signed message right now and tells you what your server answered):

```
curl -s -H "Authorization: Bearer $KEY" -X POST $API/v1/webhooks/ENDPOINT_ID/ping
# -> {"delivered": true, "http_status": 200}
```

3. What you receive: `POST` to your address with a JSON body

```
{
  "id": "evt_5f0c..._4",
  "type": "post.published",
  "created_at": "2026-12-20T18:30:12+00:00",
  "data": {
    "post_key": "eid-2026-reel-1", "variant_id": "5f0c...", "platform": "instagram",
    "account": "Dhaka Kacchi", "format": "reel", "state": "published", "status": "published",
    "slot": "2026-12-20T18:30:00+00:00", "live_url": "https://www.instagram.com/p/...",
    "handed_over": false, "reason": "published"
  }
}
```

Event	When
`post.approved`	The owner approved it (it is scheduled)
`post.published`	It is live. `data.live_url` is set (TikTok: `handed_over: true`, the owner posts it by hand)
`post.failed`	It did not go out. `data.reason` says why
`post.expired`	It missed its slot and was too late to publish safely
`post.needs_check`	The outcome is uncertain and the server is verifying it. **Do not resend the post**
`post.cancelled`	Cancelled by you, or **rejected by the owner** in the Sheet (`data.reason` says which)
`post.invalid`	The platform's rules refused it at approval
`ping`	A test message from the ping call

Headers: `X-DK-Event` (the type), `X-DK-Event-Id` (the same as `id`, **identical on every retry**), `X-DK-Delivery`, `X-DK-Signature`.

4. Verify the signature, always. Anyone can post to your address; only we know the secret. `X-DK-Signature` looks like `t=1766255412,v1=<hex>`, where `v1` is the HMAC-SHA256, keyed with your secret, of the text `"<t>.<raw request body>"`. Use the **raw bytes** you received (not re-encoded JSON), compare in constant time, and refuse a timestamp older than 5 minutes (a replayed message).

```
import hashlib, hmac, time


def valid(secret: str, header: str, raw_body: bytes) -> bool:
    parts = dict(p.split("=", 1) for p in header.split(","))
    t = int(parts["t"])
    if abs(time.time() - t) > 300:
        return False
    expected = hmac.new(secret.encode(), f"{t}.".encode() + raw_body,
hashlib.sha256).hexdigest()
    return hmac.compare_digest(expected, parts["v1"])
```

```
import { createHmac, timingSafeEqual } from "node:crypto";

export function valid(secret, header, rawBody /* Buffer */) {
  const parts = Object.fromEntries(header.split(",").map((p) => p.split("=")));
  if (Math.abs(Date.now() / 1000 - Number(parts.t)) > 300) return false;
  const expected = createHmac("sha256",
secret).update(`${parts.t}.`).update(rawBody).digest("hex");
  return expected.length === parts.v1.length && timingSafeEqual(Buffer.from(expected),
Buffer.from(parts.v1));
}
```

5. Answer fast, and expect repeats.

- Reply with any `2xx` quickly (do the real work afterwards). Anything else, a timeout or no connection counts as a failure.
- Failed messages are retried after **1 min, 5 min, 30 min, 2 h, 6 h, 24 h**; after the 7th failure we give up and the owner is told on Telegram. The post itself is never affected.
- Delivery is **at least once**: you may get the same message twice. Remember `id` and ignore a repeat.
- Order is not guaranteed (a retry can arrive after a newer event). If unsure, read `GET /v1/posts/{post_key}`.
- Answer `410 Gone` and we switch that webhook off. Redirects are not followed.
- See what happened to each message with `GET /v1/webhooks/{endpoint_id}/deliveries` (`status` is `pending`, `delivered` or `dead`, with `attempts`, `http_status` and `error`).
- Only messages after you registered are sent (no history). Revoking the key stops them.

The owner can list every registered webhook with `dk api webhooks` and switch one off with `dk api webhook-disable ID`.

5c. Build to the contract: `GET /v1/spec`

One document holds every rule a post must meet, built from the same code that checks posts, so it is never out of date. Read it **before making content**: a media maker learns the file types, how many files and the largest size; a writer learns the caption and option limits; code learns the timing and how each platform is published.

```
curl -s "$API/v1/spec?platform=instagram&format=reel" -H "Authorization: Bearer $KEY"
# -> {"spec_version": "3f1c...", "post": {...rules for every post...}, "upload": {...},
"states": {...},
#     "platforms": {"instagram": {"mode": "live", "route": {...}, "accounts": [...], "timing":
{...},
#       "quotas": [...], "formats": {"reel": {"media": {"min": 1, "max": 1, "types": [".mp4",
".mov"]},
#         "caption": {...}, "options": {...}, "example": {...}, "json_schema": {...}}}}}}
```

- Leave out `platform` and `format` for everything. A `read` key is enough.
- `spec_version` changes when any rule, account or setting does. It is also the `ETag`: send `If-None-Match: "<spec_version>"` and you get `304` when nothing changed, so a client can cache it.
- `media.max_bytes` is checked when you submit: a bigger file is refused at once with `file_too_large`, not at the slot.
- `json_schema` lets code check a variant offline. The API's own check (`dry_run` or `/v1/posts/validate`) stays the authority: a few rules, such as a link counting as 23 characters, only the platform's check knows.
- `states` says what every state means and what a client should do in it.
- `dk api spec [--platform ... --format ...]` prints the same document from a terminal.

5d. Many posts at once: `POST /v1/posts/batch`

```
curl -s "$API/v1/posts/batch" -H "Authorization: Bearer $KEY" -H "Content-Type:
application/json" \
  -d '{"dry_run": true, "posts": [ {"post_key": "wk42-reel", "variants": [...]}, {"post_key":
"wk42-text", "variants": [...]} ]}'
# -> {"dry_run": true, "spec_version": "...", "ok": 1, "failed": 1,
#     "results": [{"post_key": "wk42-reel", "ok": true}, {"post_key": "wk42-text", "ok": false,
"problems": [...], "examples": {...}}]}
```

- Up to 20 posts, each exactly like `POST /v1/posts` and each **on its own**: one bad post never stops the others.
- `dry_run: true` checks everything and creates nothing. Then send the same batch without it.
- Sending the same batch again is safe: existing posts come back with `"replayed": true`.
- A batch **always creates drafts**, whatever the key may do. A person approves them in the Calendar.
- A `media` entry may be a `media_id` or a public `https://` link; the server downloads each link once per batch.

5e. Where publishing stands: `GET /v1/overview` and `GET /v1/calendar`

Both cover **every** post, the Google Sheet's too. A `read` key is enough; nothing can be changed through them.

```
curl -s "$API/v1/overview?days_back=7&days_ahead=14" -H "Authorization: Bearer $KEY"
# -> {"pipeline": {"total": 28, "by_state": {"awaiting_approval": {...}, "scheduled":
{"instagram": 9, ...}}},
#     "published": {"total": 44, "by_platform": {...}}, "problems": [...], "next": [...5
slots...],
#     "awaiting_approval": [...], "plan_ends": "2026-10-15T14:30:00+00:00", "note": "Nothing is
scheduled after ..."}
curl -s "$API/v1/calendar?state=published&platform=instagram&limit=20" -H "Authorization:
Bearer $KEY"
# -> {"total": 12, "limit": 20, "posts": [{"post_key", "platform", "account", "format",
"state", "slot", "source",
#                                         "by", "text", "live_url", "error"}, ...]}
```

`/v1/calendar` filters: `state`, `platform`, `source` (`sheet` or `api`), `from` and `to` (ISO 8601 with an offset) and `limit` (at most 200). `state=published` is the history, newest first, with live links. Posts are by slot otherwise. `GET /v1/posts/{post_key}` also shows a Sheet post (reading only: it cannot be cancelled here).

5f. Connect an AI agent over MCP

The same API, for agents that speak MCP (Claude Code, Claude Desktop, Cursor, LangChain, the OpenAI Agents SDK): `https://publish.dhakakacchi.com/mcp/` with the header `Authorization: Bearer <key>`. Same keys, same rights.

Tool	Right	What it does
`publishing_overview`	read	`GET /v1/overview`
`list_posts`	read	`GET /v1/calendar`
`get_post`	read	`GET /v1/posts/{post_key}`
`publishing_spec`	read	`GET /v1/spec`
`submit_posts`	draft	`POST /v1/posts/batch` (always drafts)
`cancel_post`	draft	`DELETE /v1/posts/{post_key}`

- Resources: `dkp://spec` (the whole contract) and `dkp://guide` (`/llms.txt`). Prompt: `publish_posts`.
- There is **no approve tool**, whatever the key may do over HTTP. A person approves in the Calendar or on the review page (section 5g).
- Files never travel through MCP: code uploads them with `POST /v1/media`, or a post names a public https link.
- `dk api mcp-config --client claude-code` (or `claude-desktop`, `cursor`, `langchain`, `openai-agents`) prints the settings to paste. The key appears only as the variable `DK_PUBLISH_KEY`, which you set yourself.
- The owner switches MCP on with `"mcp": {"enabled": true}` in `dk.json`. `"disabled_tools": "submit_posts"` switches a tool off.

5g. The owner's daily review page: watch the videos, approve in two minutes

For the owner, in plain words. Agent builders: the last list says what the page shows of your drafts.

The Calendar tab shows text only. The **review page** shows the same drafts with the video playing, so you can approve a whole day at once without guessing what the video looks like. It is a normal web page you open on your phone.

How you open it

1. Every morning at 08:00 the Telegram message has a line **"Review today's posts"** when agent drafts for today wait for you. Tap the link. (No drafts waiting, no line.)
2. The link signs you in on that phone for 12 hours and then shows the page without the secret part in the address. It works for 24 hours. After that it says so, and you use the next morning's link.
3. Need a link at another time? On the server run `dk review link` (the runbook `docs/runbooks/review-page.md` has the exact command). The Calendar tab also has a **`watch`** column: tap it on an agent's row to open that day. It works if you signed in with the morning link in the last 12 hours.

What you see: the day (use *Earlier*, *Today*, *Later* or the date box for other days), one block per **idea**, the video or photos once per idea, and under it each platform with its caption, format, time (Berlin), the extra settings (for example the YouTube title or the TikTok privacy) and which agent made it.

What you tap

- **Approve all N for this day** at the top: approves every post shown that is still waiting.
- **Approve this idea / Reject this idea**: all platforms of that idea.
- **Approve / Reject** under one platform's caption: that platform only.

An approved post goes into the normal schedule, exactly as if you had ticked `approve` in the Calendar. A rejected post is cancelled, and the agent has to send a new one. A post whose time has already passed, or that a platform's rules refused, has no approve button, only reject. If something changed meanwhile (you approved it in the Sheet a minute ago), the page says "left alone" and changes nothing. Nothing is ever published by looking at the page.

If it says "sign-in needed" or "expired": open the newest Telegram link, or run `dk review link`. If it says "too many wrong attempts", wait ten minutes. If you think a link leaked, run `dk review init --base-url <your API address> --rotate` on your Mac and `make deploy-secrets`: every older link stops working.

The page exists only when it is set up (a secret and the API's address in `dk.json`; see the runbook). Without that it does not exist at all, the Telegram line is missing and the Calendar's `watch` column stays empty.

For agent builders

- Agents have no access to the page and never need approval rights; the page records the owner as the decider.
- One `post_key` = one idea; put one variant per platform in it. The page groups by `post_key` and shows the key's name (`by`), the caption, `options`, the slot and each distinct file once.
- Files are shown from the upload for a week after the post is done (ADR 0021). A removed file shows its name instead.
- Make `post_key`s readable (for example `2026w42-ig-tue1700-s1`): they are the headings the owner sees.

6. When something is wrong: errors that teach

Every failure is JSON (`application/problem+json`). A validation failure lists **every** problem at once:

```
{
  "status": 422, "title": "The request has problems",
  "problems": [
    {"path": "variants[0].caption", "code": "too_long", "limit": 2200, "actual": 2410,
     "message": "Caption is 2,410 characters; Instagram allows 2,200."},
    {"path": "variants[1].options.privacy_level", "code": "not_allowed",
     "allowed": ["public", "friends", "followers", "only_me"], "message": "..."}
  ],
  "examples": {"variants[0]": {"platform": "instagram", "format": "reel", "media":
["MEDIA_ID"], "slot": "..."}}
}
```

How to react (an agent can do this automatically): read each problem's `path`, fix that field using `limit`, `allowed` or `expected`, copy the shape from `examples`, send again. Nothing was created by a refused request.

HTTP	Meaning
200 / 201	OK / created
401	No key or a wrong key
403	The key lacks the needed right
404	Unknown post
409	Conflict: `post_key_taken`, or a post that cannot be cancelled/approved now
413	`quota_exceeded`: this key's upload space is full
422	The request has problems (listed)
507	`storage_full`: server disk nearly full, uploads paused; tell the owner

Problem `code`s: `invalid`, `invalid_post_key`, `required`, `too_many`, `too_long`, `not_allowed`, `unknown_platform`, `unknown_format`, `unknown_option`, `unknown_field`, `unknown_account`, `account_required`, `unknown_media`, `media_expired`, `media_rejected` (see `expected`), `invalid_slot`, `slot_in_past`, `slot_too_far`, `duplicate_variant`, `post_key_taken`, `unsupported_type`, `too_large`, `file_too_large` (a file over the format's `max_bytes`), `empty`, `webhooks_off`, `filename_required`, `bad_url`, `fetch_failed`, `storage_full`, `quota_exceeded`.

7. Repeating safely (important for agents)

`post_key` is the idempotency key.

- The connection dropped and you do not know if the post was created? **Send exactly the same request again.** You get the existing post back (`200`, header `Idempotent-Replay: true`). It is never created twice.
- The **same `post_key` with different content** is `409 post_key_taken`. To change a post, cancel it and use a new key.
- **Never retry** a post whose state is `checking`: the server is already verifying it with the platform.

- Use stable keys, for example `<campaign>-<platform>-<date>`, so a restarted agent does not create duplicates.

8. Code examples

Python

```
import os, requests

API = "https://publish.dhakakacchi.com"
H = {"Authorization": f"Bearer {os.environ['DK_KEY']}"}  # never hard-code the key

with open("reel.mp4", "rb") as f:  # 1. upload
    media = requests.post(
        f"{API}/v1/media", params={"filename": "reel.mp4"}, headers=H, data=f
    ).json()["media_id"]

post = {  # 2. describe the post
    "post_key": "eid-2026-reel-1",
    "variants": [
        {
            "platform": "instagram",
            "format": "reel",
            "caption": "Slow-cooked for Eid.",
            "media": [media],
            "slot": "2026-12-20T19:30:00+01:00",
            "options": {"share_to_feed": True},
        }
    ],
}
check = requests.post(f"{API}/v1/posts/validate", headers=H, json=post).json()  # 3. check
if not check["valid"]:
    for p in check["problems"]:
        print(p["path"], p["code"], p.get("message"))  # fix these and retry
else:
    print(
        requests.post(f"{API}/v1/posts", headers=H, json=post).json()["summary"]
    )  # 4. awaiting_approval
```

JavaScript (Node 18+)

```
const API = "https://publish.dhakakacchi.com";
const H = { Authorization: `Bearer ${process.env.DK_KEY}`, "Content-Type": "application/json"
};

const post = {
  post_key: "eid-2026-text-1",
  variants: [{ platform: "threads", format: "text", caption: "Biryani o'clock.", slot: "2026-
12-20T19:30:00+01:00" }],
};
const check = await (await fetch(`${API}/v1/posts/validate`, { method: "POST", headers: H,
body: JSON.stringify(post) })).json();
if (!check.valid) console.log(check.problems);
else console.log(await (await fetch(`${API}/v1/posts`, { method: "POST", headers: H, body:
JSON.stringify(post) })).json());
```

9. Notes for an AI agent builder

1. Give the agent **only** a `draft` key, and tell it: *a human approves in the Google Sheet's Calendar tab; never ask for approval rights*.
2. First action every session: `GET /v1/spec` (or `GET /v1/platforms`). Never hard-code limits, they change; keep `spec_version` and send it back as `If-None-Match` to learn cheaply whether anything did.
3. Always call **validate before create**, and apply `problems[].path` fixes. A model can fix its own mistakes from the error text alone.
4. Put platform-specific fields in `options`. Always send `slot` with an offset. Use a stable, unique `post_key`.
5. Never publish "now": the earliest slot is a minute ahead, and drafts need a human anyway.
6. On any network error: resend the **same** request (it is safe), do not invent a new `post_key`.
7. Report back to the human: `post_key`, each platform's `state`, and `live_url` when published.

10. Good to know

- Times: you send any offset; the Sheet and Telegram messages show Berlin time. Times are stored in UTC.
- Posts made here need **connected accounts** (`GET /v1/platforms` lists them). Only the owner can connect accounts.
- Not built yet: editing a post in place (cancel and resend), per-key rate limits on the HTTP API (MCP has its own).
- Questions about a failed post: ask the owner; they see it in Telegram and the Calendar tab.